COMPARATIVE PERFORMANCE ANALYSIS OF ARITHMETIC OPTIMIZATION ALGORITHM FOR COVID-19 CT SCAN IMAGE SEGMENTATION


Author - KAREN INFANTA ROZARIO

1. SUMMARY

Medical image segmentation is an important technique in medical image processing that enables the identification and isolation of specific anatomical structures and abnormal regions in medical images. During the COVID-19 pandemic, computed tomography (CT) scans became an important imaging modality for examining lung abnormalities associated with the infection. Accurate segmentation of infected lung regions can assist healthcare professionals in evaluating the extent and distribution of pulmonary abnormalities.

This project investigates the performance of the Arithmetic Optimization Algorithm (AOA) for multilevel threshold-based segmentation of COVID-19 CT scan images. The study compares AOA with four alternative optimization algorithms: Clouded Leopard Optimization (CLO), Dung Beetle Optimization (DBO), Dwarf Mango Optimization (DMO), and Electric Fish Optimization (EFO).

The comparative results presented in the research poster demonstrate that AOA achieves higher reported segmentation accuracy than all four competing algorithms. AOA obtained an accuracy of 90.3% compared with 58.8% for CLO, 94.9% compared with 87.5% for DBO, 97% compared with 82.4% for DMO, and 94.6% compared with 64.1% for EFO. These findings indicate that AOA is a promising optimization technique for multilevel thresholding and medical image segmentation. Its mathematical operators and exploration–exploitation mechanisms may contribute to effective threshold selection and the identification of infected regions in complex CT images.



The project highlights the potential of optimization-based image segmentation in medical image analysis. However, further validation using standardized datasets, clearly defined evaluation metrics, and statistical testing is necessary before drawing conclusions about its clinical reliability or suitability for routine diagnostic applications.

2. INTRODUCTION

2.1 Background

Medical imaging technologies play a significant role in the detection, assessment, and monitoring of diseases. Computed tomography provides detailed cross-sectional images of internal organs, making it particularly useful for examining lung abnormalities.

COVID-19 can cause pulmonary abnormalities that appear in chest CT scans. Identifying these abnormalities accurately is important for assessing the distribution and extent of lung involvement. However, manual identification and segmentation of infected regions can be time-consuming and may be affected by variations in image quality and interpretation.

Image segmentation addresses this challenge by dividing an image into meaningful regions based on characteristics such as intensity, texture, and spatial information.

Multilevel thresholding is a segmentation technique that classifies image pixels into different groups using multiple intensity thresholds. The selection of appropriate thresholds is important because it directly influences the quality of the resulting segmentation.

Optimization algorithms can be used to determine suitable threshold values by searching for solutions that maximize or minimize a specified objective function. This approach can reduce the need for manually selecting thresholds and provide a systematic method for segmenting complex medical images.

2.2 Problem Statement

Accurate segmentation of COVID-19-related lung abnormalities in CT scans remains a challenging image-processing task because medical images may contain complex intensity patterns, variations in tissue appearance, and regions with similar pixel values.

Traditional threshold-selection methods may not always identify optimal thresholds for complex images. Metaheuristic optimization algorithms offer an alternative approach, but their performance can differ depending on their search mechanisms, convergence behavior, and ability to avoid local optima.

Therefore, a comparative evaluation is required to determine whether the Arithmetic Optimization Algorithm can achieve better segmentation accuracy than alternative optimization methods.

This project addresses the problem by comparing AOA with CLO, DBO, DMO, and EFO using the accuracy values reported in the accompanying research poster.

2.3 Motivation

The motivation for this project is to investigate an optimization-based approach to improving the segmentation of infected lung regions in COVID-19 CT scans.

The study focuses on AOA because it uses mathematical operators to guide the optimization process. These operators support the exploration of different candidate solutions and the exploitation of promising solutions.

By comparing AOA with four alternative algorithms, the project seeks to identify an optimization approach that demonstrates strong reported segmentation performance and may warrant further investigation for medical image-processing applications.

2.4 Significance of the Study

This research contributes to the study of automated medical image segmentation by examining the relative performance of different optimization algorithms.

The potential significance of the project includes:

- Supporting the development of optimization-based medical image-processing techniques.
- Investigating multilevel thresholding for the identification of abnormal lung regions.
- Comparing mathematical and bio-inspired optimization strategies.
- Identifying promising algorithms for further evaluation in medical image analysis.
- Providing a foundation for future research into automated segmentation systems.

The findings should be interpreted as an algorithmic comparison rather than evidence that the method independently diagnoses COVID-19 or improves clinical outcomes.

3. AIM AND OBJECTIVES

3.1 Aim

To evaluate the performance of the Arithmetic Optimization Algorithm for multilevel threshold-based segmentation of COVID-19 CT scan images and compare its reported accuracy with Clouded Leopard Optimization, Dung Beetle Optimization, Dwarf Mango Optimization, and Electric Fish Optimization.

3.2 Objectives

The main objectives of the project are:

1. To investigate the role of image segmentation in identifying COVID-19-related abnormalities in lung CT scans.
2. To examine multilevel thresholding as a method for segmenting medical images.
3. To study the application of the Arithmetic Optimization Algorithm to threshold selection.
4. To compare AOA with CLO, DBO, DMO, and EFO using the results presented in the research poster.
5. To evaluate the relative segmentation accuracy reported for each algorithm.
6. To identify the potential advantages and limitations of AOA in medical image segmentation.
7. To recommend directions for further research and validation.

4. LITERATURE BACKGROUND

4.1 Medical Image Segmentation

Medical image segmentation is the process of dividing an image into regions corresponding to different anatomical structures or abnormalities.

In lung CT analysis, segmentation can help separate lung tissue, infected regions, and surrounding structures. The quality of segmentation depends on the image characteristics, segmentation method, parameter selection, and evaluation procedure.

Accurate segmentation can support subsequent image analysis, including the measurement of abnormal regions and the extraction of quantitative imaging features.

4.2 Multilevel Thresholding

Thresholding is a segmentation technique that classifies pixels according to their intensity values.

In binary thresholding, a single threshold separates pixels into two classes. Multilevel thresholding uses multiple thresholds to divide an image into several intensity-based classes.

If an image has intensity values represented by (I(x,y)), a threshold-based segmentation procedure assigns pixels to different classes according to their positions relative to the selected threshold values.

For multiple thresholds, the problem involves finding a suitable set of threshold values that produces meaningful segmentation.

Selecting these thresholds becomes more challenging as the number of thresholds increases. Optimization algorithms can be used to search for threshold combinations that provide favorable segmentation results.

4.3 Arithmetic Optimization Algorithm

The Arithmetic Optimization Algorithm is a metaheuristic optimization method that uses arithmetic operators to guide the search for suitable solutions.

Its optimization process incorporates exploration and exploitation.

Exploration: The algorithm investigates different regions of the search space to identify promising candidate solutions.

Exploitation: The algorithm refines promising solutions to improve the quality of the final result.

In image segmentation, the candidate solutions can represent possible threshold combinations. An objective function is used to assess the quality of these solutions.

The algorithm iteratively updates candidate solutions and seeks an appropriate threshold configuration.

The performance of AOA depends on factors such as the objective function, parameter settings, image characteristics, and stopping criteria. These implementation details are important for reproducing and validating the results.

4.4 Competing Optimization Algorithms

This project compares AOA with four alternative algorithms.

4.4.1 Clouded Leopard Optimization (CLO)

CLO is included as a competing optimization method. The poster compares its segmentation performance with AOA and discusses limitations associated with avoiding local optima.

4.4.2 Dung Beetle Optimization (DBO)

DBO is a bio-inspired optimization algorithm based on modeled dung beetle behaviors. The poster evaluates its segmentation accuracy against AOA and identifies convergence behavior as a potential limitation.

4.4.3 Dwarf Mango Optimization (DMO)

DMO is another optimization method considered in the comparative analysis. The poster reports that AOA achieves higher segmentation accuracy than DMO and attributes the difference to the optimization behavior of the respective algorithms.

4.4.4 Electric Fish Optimization (EFO)

EFO is included to evaluate the relative effectiveness of an alternative bio-inspired optimization approach. The poster reports lower segmentation accuracy for EFO than for AOA.

The available poster provides comparative results and general interpretations for these methods. It does not provide sufficient implementation details to establish that every algorithm was evaluated under identical experimental conditions.

5. MATERIALS AND METHODS

5.1 Overview of the Methodology

The project follows a comparative image-segmentation workflow based on the process diagram included in the research poster.

The main stages are:

1. CT image data collection.
2. Feature extraction and analysis.
3. Data preprocessing and preparation.
4. Application of optimization algorithms.
5. Threshold-based image segmentation.
6. Performance evaluation.
7. Comparison of algorithmic results.
8. Interpretation of segmentation performance.

The poster identifies the principal processing stages but does not specify the exact dataset, programming language, software environment, threshold objective function, or parameter settings. These details must be documented separately if the project is to be reproduced experimentally.

5.2 Data Collection

The study focuses on CT scan images associated with COVID-19 patients.

CT images provide intensity information that can be processed to identify and distinguish different lung regions. The images serve as the input to the segmentation workflow.

A reproducible experimental implementation should specify the dataset source, number of images, image dimensions, file formats, inclusion criteria, and any relevant preprocessing performed before segmentation.

The supplied poster does not identify these dataset details.

5.3 Feature Extraction and Image Analysis

Image analysis is used to identify characteristics relevant to segmentation.

In a threshold-based approach, pixel intensity is a central component of the segmentation process. Additional image characteristics may also be considered depending on the implementation.

The poster includes a feature-extraction and analysis stage in its workflow diagram. However, it does not identify the exact features extracted or the mathematical procedures used to obtain them.

Accordingly, the precise feature-extraction procedure cannot be established from the available project material.

5.4 Data Preprocessing

Preprocessing prepares the input images for segmentation.

Depending on the implementation, preprocessing may involve image-format conversion, intensity normalization, noise reduction, resizing, or the preparation of reference masks.

These are possible components of a medical image-processing pipeline, not confirmed procedures in the supplied poster.

The specific preprocessing operations used in the original experiment should be documented to ensure that the results can be reproduced.

5.5 Application of the Arithmetic Optimization Algorithm

AOA is used to search for suitable threshold values for segmenting CT images.

The general process can be described as follows:

1. Define the optimization problem and the candidate threshold values.
2. Initialize a population of candidate solutions.
3. Evaluate the quality of the candidate solutions using a predefined objective function.
4. Update candidate solutions using the algorithm's arithmetic optimization mechanisms.
5. Balance exploration and exploitation during the search.
6. Repeat the optimization process until the stopping criterion is reached.
7. Select the best-performing threshold solution.
8. Apply the selected thresholds to the input image to obtain the segmented output.

This describes the general application of AOA to multilevel thresholding. The poster does not provide the exact objective function, initialization strategy, population size, iteration count, or stopping criterion used in the reported experiments.

5.6 Comparative Evaluation

The poster evaluates AOA against four competing algorithms.

Comparison	Algorithm 1	Algorithm 2
Study 1	Arithmetic Optimization Algorithm (AOA)	Clouded Leopard Optimization (CLO)
Study 2	Arithmetic Optimization Algorithm (AOA)	Dung Beetle Optimization (DBO)
Study 3	Arithmetic Optimization Algorithm (AOA)	Dwarf Mango Optimization (DMO)

Study 4	Arithmetic Optimization Algorithm (AOA)	Electric Fish Optimization (EFO)

Each comparison examines the reported segmentation accuracy of the algorithms.

For a rigorous experimental comparison, the algorithms should be evaluated using the same dataset, consistent preprocessing, comparable threshold configurations, and clearly defined evaluation metrics.

Repeated runs and statistical analysis would also help determine whether the observed differences are consistent rather than the result of random variation.

The supplied poster does not provide enough information to verify these experimental conditions.

5.7 Performance Evaluation

Segmentation accuracy is the principal quantitative result reported in the poster.

The reported values are:

- AOA versus CLO: 90.3% versus 58.8%.
- AOA versus DBO: 94.9% versus 87.5%.
- AOA versus DMO: 97.0% versus 82.4%.
- AOA versus EFO: 94.6% versus 64.1%.

These values are presented as reported by the poster and have not been independently recalculated or verified.

The poster does not provide the formula used to calculate segmentation accuracy, the ground-truth annotations, or additional quantitative metrics. Therefore, the results should be interpreted within the limits of the available information.

6. RESULTS

6.1 Comparative Segmentation Accuracy

The comparative results reported in the poster are summarized below.

Comparison	AOA Accuracy	Competing Algorithm Accuracy	Absolute Difference
AOA vs. CLO	90.3%	58.8%	31.5 percentage points
AOA vs. DBO	94.9%	87.5%	7.4 percentage points
AOA vs. DMO	97.0%	82.4%	14.6 percentage points
AOA vs. EFO	94.6%	64.1%	30.5 percentage points

Note: Absolute differences are calculated by subtracting the competing algorithm's reported accuracy from AOA's reported accuracy.

6.2 Results of AOA Versus CLO

In the first comparison, AOA achieved a reported accuracy of 90.3%, whereas CLO achieved 58.8%.

The difference was 31.5 percentage points in favor of AOA.

The poster suggests that AOA's balance between exploration and exploitation may help it handle complex patterns in COVID-19 CT imagery more effectively. It also identifies limitations in CLO's ability to avoid local optima.

These findings favor AOA within the reported comparison, although the experimental conditions and accuracy calculation require further documentation.

6.3 Results of AOA Versus DBO

In the second comparison, AOA achieved a reported segmentation accuracy of 94.9%, while DBO achieved 87.5%.

The difference was 7.4 percentage points.

According to the poster, AOA's mathematical operators contribute to its performance. The discussion also identifies suboptimal convergence as a potential limitation of DBO.

Among the four comparisons, this represents the smallest reported accuracy difference between AOA and a competing algorithm.

6.4 Results of AOA Versus DMO

In the third comparison, AOA achieved a reported accuracy of 97.0%, while DMO achieved 82.4%.

The difference was 14.6 percentage points.

The poster indicates that AOA provides more consistent segmentation results and may capture fine boundaries in infected lung regions more effectively.

It also identifies premature convergence as a potential limitation of DMO.

AOA achieved its highest reported accuracy in this comparison, making the AOA–DMO comparison the strongest numerical result for AOA among the four studies presented.

6.5 Results of AOA Versus EFO

In the fourth comparison, AOA achieved a reported accuracy of 94.6%, whereas EFO achieved 64.1%.

The difference was 30.5 percentage points.

The poster attributes AOA's relative performance to its convergence mechanisms and its handling of multilevel thresholding challenges. It also identifies difficulties in complex feature spaces as a potential limitation of EFO.

The reported results favor AOA by a substantial margin in this comparison.

6.6 Overall Results

AOA achieved higher reported segmentation accuracy than all four competing algorithms.

The principal findings are:

- **Highest reported AOA accuracy:** 97.0% against DMO.
- **Lowest reported AOA accuracy:** 90.3% against CLO.
- **Largest accuracy difference:** 31.5 percentage points against CLO.

- **Smallest accuracy difference:** 7.4 percentage points against DBO.
- **Consistent direction of results:** AOA had higher reported accuracy in all four comparisons.

These findings suggest that AOA is a promising candidate for further investigation in optimization-based CT image segmentation.

However, the four comparisons should not be interpreted as a single controlled experiment unless it can be established that they used the same dataset, evaluation protocol, and accuracy definition.

7. DISCUSSION

7.1 Interpretation of the Findings

The results presented in the poster indicate that AOA outperformed CLO, DBO, DMO, and EFO in their respective reported comparisons.

Its highest reported accuracy was 97.0% in the comparison with DMO. Its reported accuracy also exceeded 90% in the comparisons with CLO, DBO, and EFO.

The consistency of these results supports further investigation of AOA for multilevel threshold-based medical image segmentation.

Nevertheless, the differences in reported accuracy do not independently establish why AOA performed better. A rigorous explanation would require access to the experimental implementation, objective functions, datasets, parameter configurations, and evaluation procedures.

7.2 Importance of Exploration and Exploitation

An important consideration in metaheuristic optimization is the balance between exploration and exploitation.

Exploration allows an algorithm to investigate different parts of the search space. Exploitation focuses on refining solutions that have already demonstrated promising performance.

In multilevel thresholding, an effective balance can help identify suitable threshold combinations without becoming prematurely trapped in an inferior solution.

The poster identifies this balance as one possible reason for AOA's reported performance. However, confirming this explanation would require additional experimental evidence, such as convergence curves and repeated-run comparisons.

7.3 Relevance to Medical Image Analysis

Accurate segmentation can support the quantitative examination of lung abnormalities in CT scans.

A reliable segmentation system may assist subsequent tasks such as estimating the size of abnormal regions, examining spatial distributions, and preparing images for further analysis.

AOA may be useful in this context because optimization can help automate the selection of segmentation thresholds.

However, high reported segmentation accuracy alone does not establish clinical validity. Clinical use would require appropriate validation against expert annotations, assessment on independent datasets, and evaluation of performance across different imaging conditions and patient populations.

7.4 Limitations of the Study

Several limitations should be considered when interpreting the results.

1. Limited experimental details

The poster does not specify the dataset source, sample size, image dimensions, or patient distribution.

2. Unspecified accuracy definition

The formula and reference annotations used to calculate segmentation accuracy are not provided.

3. Missing implementation parameters

The objective functions, optimization settings, stopping criteria, and threshold configurations are not documented in the supplied material.

4. Limited evaluation metrics

The poster primarily reports accuracy. Additional segmentation metrics, such as Dice similarity coefficient, intersection over union, sensitivity, and specificity, would provide a more comprehensive assessment where appropriate.

5. No reported statistical significance testing

The available material does not include confidence intervals, repeated-run variability, or statistical tests comparing the algorithms.

6. Limited evidence of generalizability

The available poster does not establish whether the results generalize across independent datasets, different CT scanners, or variations in image quality.

7. No reported computational-cost analysis

Runtime, memory requirements, and convergence speed are not provided. These factors would be important when assessing the practical efficiency of the algorithms.

8. No direct evidence of clinical effectiveness

The project evaluates reported segmentation performance rather than clinical diagnostic accuracy, patient outcomes, or improvements in medical decision-making.

These limitations do not invalidate the reported comparisons, but they restrict the strength of the conclusions that can be drawn.

8. CONCLUSION

This project examines the performance of the Arithmetic Optimization Algorithm for multilevel threshold-based segmentation of COVID-19 CT scan images.

The comparative results presented in the research poster indicate that AOA achieved higher reported segmentation accuracy than Clouded Leopard Optimization, Dung Beetle Optimization, Dwarf Mango Optimization, and Electric Fish Optimization.

The reported accuracy values were 90.3% for AOA against 58.8% for CLO, 94.9% against 87.5% for DBO, 97.0% against 82.4% for DMO, and 94.6% against 64.1% for EFO.

The findings identify AOA as a promising optimization approach for medical image segmentation. Its exploration–exploitation mechanisms and arithmetic optimization operators may contribute to its ability to identify suitable threshold values in complex images.

The study also highlights the importance of comparing optimization algorithms when developing image-processing techniques for healthcare applications.

However, the available results do not establish clinical reliability or demonstrate that AOA is universally superior to other segmentation methods. The absence of detailed experimental protocols and independently verifiable evaluation procedures limits the conclusions that can be drawn.

Future work should focus on implementing the algorithms under controlled conditions, evaluating them on publicly available and appropriately annotated CT datasets, incorporating additional segmentation metrics, analyzing computational efficiency, and conducting statistical validation.

Overall, the project provides a comparative foundation for further research into optimization-based medical image segmentation and the potential application of AOA to the analysis of COVID-19-related lung abnormalities.

9. FUTURE SCOPE

The following extensions could strengthen the project and improve its research value.

9.1 Validation Using Standardized Datasets

The algorithms could be evaluated on a documented COVID-19 CT dataset containing reference segmentation masks. This would support reproducibility and enable direct comparison of segmentation quality.

9.2 Evaluation Using Multiple Metrics

Future experiments should consider metrics such as:

- Dice similarity coefficient.
- Intersection over union (IoU).
- Sensitivity and specificity.
- Precision and recall.
- Computational execution time.

The selected metrics should be appropriate to the segmentation task and calculated using clearly defined reference annotations.

9.3 Statistical Analysis

Each optimization algorithm could be evaluated across multiple independent runs and images.

Mean performance, standard deviation, confidence intervals, and suitable statistical tests could help establish whether observed differences are consistent and statistically meaningful.

9.4 Optimization of Algorithm Parameters

The effects of population size, iteration count, threshold count, and other algorithm parameters could be investigated to determine their influence on segmentation quality and computational cost.

9.5 Comparison With Additional Segmentation Methods

AOA could be compared with conventional thresholding methods, other metaheuristic optimization techniques, and established medical image-segmentation approaches.

Such comparisons would help establish the circumstances in which AOA provides a practical advantage.

9.6 Development of an Automated Segmentation Application

A future implementation could provide an interface for uploading CT images, running segmentation, displaying the resulting masks, and calculating evaluation metrics.

Any such application should be designed as a research or decision-support tool unless appropriate clinical validation and regulatory requirements have been addressed.

10. REFERENCES

The following references are reproduced from the supplied research poster. Their bibliographic details have not been independently verified.

1. Rana, M., et al. (2023). “A Comparative Study of AOA and GWO.” *Pattern Recognition Letters*. https://doi.org/10.1016/j.patrec.2023.08.005
2. Salehnia, T., et al. (2023). “A multi-level thresholding image segmentation method using hybrid Arithmetic Optimization and Harris Hawks Optimizer algorithms.” *Expert Systems with Applications*, 218, 122316. https://doi.org/10.1016/j.eswa.2023.122316
3. Wang, L., Wang, J., Zhu, L., et al. (2023). “Dual Multi-scale Mean Teacher Network for Semi-supervised Infection Segmentation in Chest CT Volume for COVID-19.” *arXiv preprint*, arXiv:2211.05548. https://doi.org/10.48550/arXiv.2211.05548
4. Thilagavathi, P., Geetha, R., Jothi Shri, S., and Somasundaram, K. (2025). “An effective COVID-19 classification in X-ray images using a new deep learning framework.” *Digital Health*, 11, 20552076241290893. https://doi.org/10.1177/20552076241290893
5. Gupta, R., and Srivastava, R. (2023). “Dwarf Mango Optimization: A Novel Nature-Inspired Metaheuristic Algorithm for Optimization Problems.” *Multimedia Tools and Applications*, 82, 25789–25817. https://doi.org/10.1007/s11042-023-15044-2
6. Shan, D., Li, Z., Chen, W., Li, Q., Tian, J., and Hong, Q. (2023). “Coarse-to-Fine COVID-19 Segmentation via Vision-Language Alignment.” *arXiv preprint*, arXiv:2303.00279. https://doi.org/10.48550/arXiv.2303.00279
7. Yang, G., Yang, J., Fan, W., and Yang, D. (2025). “Neural Network for Underwater Fish Image Segmentation Using an Enhanced Feature Pyramid Convolutional Architecture.” *Journal of Marine Science and Engineering*, 13(2), 238. https://doi.org/10.3390/jmse13020238