HKUSTx: ELEC1200.1x A System View of Communications: From Signals to Packets (Part 1)

KarenWest (/dashboard)

Courseware (/courses/HKUSTx/ELEC1200.1x/3T2014/courseware)

Course Info (/courses/HKUSTx/ELEC1200.1x/3T2014/info)

Course Outline (/courses/HKUSTx/ELEC1200.1x/3T2014/05fb01b36df14eb99ab54545dabc47f6/)

Grading Scheme (/courses/HKUSTx/ELEC1200.1x/3T2014/6e2be4dac3e44b4d9f812e7b5a5d5a29/)

요 - 의 Instructors (/courses/HKUSTx/ELEC1200.1x/3T2014/674fdd6887fe4f4bb73b984df4a5675b/)

Resources (/courses/HKUSTx/ELEC1200.1x/3T2014/a6a8267fef364cccbccd0128d091f11c/)

Discussion (/courses/HKUSTx/ELEC1200.1x/3T2014/discussion/forum)

Progress (/courses/HKUSTx/ELEC1200.1x/3T2014/progress)

## 4.2 QUIZ QUESTION 1 (1 point possible)

Suppose the response of a communication channel to the training sequence can be given as

$$y(n) = 6 + 22u(n - 1500) - 22u(n - 2000).$$

If we received an output sample with value of 15, what would be our estimate of the corresponding input bit?

Please select the correct answer.







## **EXPLANATION**

The minimum value of the response to the training sequence is 6, and the maximum was 28. We can decide whether the input bit was 0 or 1 by comparing to a threshold of (6+28)/2 = 17.

Since the output has value 15, which is less than 17, we decode to a bit 0.

**Hide Answer** 

You have used 0 of 1 submissions

## **4.2 QUIZ QUESTION 2** (1 point possible)

Suppose that a discrete time LTI channel has a given step response:

$$s(n) = 0.9(1 - 0.8^{n+1})u(n)$$

Assume that we transmit, as a training sequence, a pulse with unit height and width W samples. Assume that the pulse starts at sample index 0. What is the minimum value of W so that the channel response at the sample index W is larger than 0.8?

1 of 3

Please key in the numerical value of your answer in the box provided below.

9.31885

Help

9.31885

**Answer:** 9.424

## **EXPLANATION**

A pulse of width W samples that starts at time 0, ends at time W-1. For the response of the channel, at the end of the pulse, to be greater than 0.8, we must have

$$s(W) = 0.9(1 - 0.8^{W-1+1}) > 0.8$$

Manipulating this inequality, we obtain

$$0.9(1-0.8^W) > 0.8$$
 
$$0.8^{W+1} < 1 - \frac{0.8}{0.9}$$
 
$$W > \frac{\ln 0.1111}{\ln 0.8} \approx 9.847$$

Thus, the minimum pulse length in samples should be 10.

**Hide Answer** 

You have used 0 of 3 submissions

About (https://www.edx.org/jobs)

Press (https://www.edx.org/press) FAQ (https://www.edx.org/student-faq)
Contact (https://www.edx.org/contact)

and artificial intelligence.

EdX is a non-profit created by founding partners Harvard and MIT whose

mission is to bring the best of higher education to students of all ages anywhere in the world, wherever there is Internet access. EdX's free online MOOCs are interactive and subjects include computer science, public health, (http://www.meetup.com/YourMeetup)

(http://www.facebook.com/EdxOnline)

(https://twitter.com /YourPlatformTwitterAccount)

https://courses.edx.org/courses/HKUSTx/EL...



(https://plus.google.com /YourGooglePlusAccount/)



(http://youtube.com/user/edxonline) © 2014 edX, some rights reserved.

Terms of Service and Honor Code -Privacy Policy (https://www.edx.org/edx-privacy-policy)



3 of 3 10/06/2014 12:22 PM