CONTROL STRUCTURES: IF

0:00 / 4:31 1.0x

Download transcript .txt

Show Discussion New Post

1. CHECK YOUR UNDERSTANDING (1/1 point)

Compare the following two pieces of C code:

```
z = 0;              z = 0;
if (x = y)          if (x == y)
  z = x++;            z = x++;
```

If x = 1 and y = 2, what would be the value of z after executing the code on the left versus on the right?

- Left: 0, Right: 0
- Left: 1, Right: 1
- Left: 2, Right: 0 ✔
- Left: 3, Right: 1

Help

Show Answer *You have used 2 of 2 submissions*

Show Discussion New Post

2. CHECK YOUR UNDERSTANDING (1/1 point)

Consider the following LC-3 code segment:

```
 LDR R0, R4, #0
 BRz SKIP
 STR R0, R4, #1
SKIP
```

Which one of the following C code segments is equivalent to the LC-3 code?

-
```
if (x)
    y = x;
```
✔
-
```
if (x == 0)
    y = x;
```
-
```
if (x)
    x = x + 1;
```
-
```
if (x == 0)
    x = x + 1;
```

Show Answer *You have used 2 of 2 submissions*

Show Discussion

New Post

Help

CONTROL STRUCTURES: IF-ELSE



Download transcript .txt

Show Discussion

New Post

At 3:20 and 5:31, the highlighted line should be ADD R0, R0, R2.

CONTROL STRUCTURES: FOR

Help

0:00 / 6:06 1.0x

Download transcript .txt

Show Discussion New Post

3. CHECK YOUR UNDERSTANDING (1/1 point)

Consider the following C code segment:

```
for (i = n; i >= 0; i--);
    n = n + i;
```

Notice that the programmer accidently put a semicolon after the `for` statement. That means that the next statement `(n = n + i)` is not part of the loop body, and will only execute after the `for` loop completes.

Which of the following LC-3 assembly language programs implements this C segment?

Help

```
        LDR R0, R4, #0
        ADD R1, R0, #0
        BRn END
LOOP    ADD R0, R0, #-1
        BRzp LOOP
END
        ADD R1, R1, R0
        STR R1, R4, #0
        STR R0, R4, #1
```

```
        LDR R0, R4, #0
        ADD R1, R0, #0
        BRz END
LOOP    ADD R0, R0, #-1
        BRp LOOP
END
        ADD R1, R1, R0
        STR R1, R4, #0
        STR R0, R4, #1
```

```
        LDR R0, R4, #0
LOOP    ADD R0, R0, #-1
        BRnzp LOOP
END     ADD R0, R0, R0
        STR R0, R4, #0
```

```
        LDR R0, R4, #0
LOOP    ADD R0, R0, #-1
        BRzp LOOP
END     ADD R0, R0, R0
        STR R0, R4, #0
```

EXPLANATION

The first code is correct. The LDR loads the value of n from memory into R0, which will be used for `i`. Since `n` needs to be retained for the last C statement, the ADD instruction transfers the data from R0 into R1. If that transfer results in the `n` bit being set, then `n` < 0 and the loop is skipped entirely. Otherwise, the next ADD instruction decrements `i`, and the BRzp instruction will cause another iteration to be executed so long as `i` >= 0. The first ADD after the loop performs the statement `n = n + i` using the value of `n` in R1 and the value of `i` in R0. The next two STR instructions store the updated values of n and i.

The second code segment has the wrong nzp designations for the BR instructions.

The last two code segments fail to retain `n` and instead perform `i = i + i` after the loop and overwrite `n` with `i`.

Final Check | **Save** | **Hide Answer** *You have used 1 of 2 submissions*

Show Discussion

New Post



Help

EdX offers interactive online classes and MOOCs from the world's best universities. Online courses from MITx, HarvardX, BerkeleyX, UTx and many other universities. Topics include biology, business, chemistry, computer science, economics, finance, electronics, engineering, food and nutrition, history, humanities, law, literature, math, medicine, music, philosophy, physics, science, statistics and more. EdX is a non-profit online initiative created by founding partners Harvard and MIT.

Terms of Service and Honor Code

Privacy Policy (Revised 10/22/2014)

POWERED BY OPENedX

About edX

About

News

Contact

FAQ

edX Blog

Donate to edX

Jobs at edX

Follow Us

Facebook

Twitter

LinkedIn

Google+

Tumblr

Meetup

Reddit

Youtube