



Relational Design Theory

Boyce-Codd Normal Form

Relational design by decomposition

- “Mega” relations + properties of the data
- System decomposes based on properties
- Final set of relations satisfies normal form
 - No anomalies, no lost information
- Functional dependencies \Rightarrow Boyce-Codd Normal Form
- Multivalued dependences \Rightarrow Fourth Normal Form

Decomposition of a relational schema

$$R(A_1, \dots, A_n) \quad \bar{A}$$

$$\hookrightarrow R_1(B_1, \dots, B_k) \quad \bar{B}$$


$$R_2(C_1, \dots, C_m) \quad \bar{C}$$

$$\bar{B} \cup \bar{C} = \bar{A} \quad \checkmark$$

$$\underline{R_1 \bowtie R_2 = R} \quad \checkmark$$

$$R_1 = \pi_{\bar{B}}(R) \quad \leftarrow$$

$$R_2 = \pi_{\bar{C}}(R)$$



Decomposition Example #1

Student(SSN, sName, address,
HScode, HSname, HScity, GPA, priority)

$S_1(SSN, sName, addr, \underline{HScode}, GPA, priority)$

$S_2(\underline{HScode}, HSname, HScity)$

$$\bar{A} \cup \bar{B} = \bar{C} \quad S_1 \bowtie S_2 = \text{Student}$$

Decomposition Example #2

Student(SSN, sName, address,
HScode, HSname, HScity, GPA, priority)

S_1 (SSN, sName, addr, HScode, HSname, HScity)

S_2 (sName, HSname, GPA, priority)

$$\overline{A} \cup \overline{B} = \overline{C}$$

$$S_1 \bowtie S_2 \stackrel{?}{=} \text{Student}$$

Relational design by decomposition

- “Mega” relations + properties of the data
- System decomposes based on properties

❖ “Good” decompositions only ← “reassembly”
❖ Into “good” relations ← produces orig.
BCNF Lossless join property

Boyce-Codd Normal Form

Relation R with FDs is in BCNF if:

For each $\bar{A} \rightarrow B$, \bar{A} is a key

BCNF violation

\bar{A}	B	rest
a	b	—
a	b	—
	⋮	

$$\bar{A} \rightarrow B$$

⌞ key

$\bar{A} C D$

"contains a key"
"is a superkey"

BCNF? Example #1

Student(SSN, sName, address, HScode, HSname, HScity, GPA, priority)

✓ SSN → sName, address, GPA } Keys:
 ✓ GPA → priority { ssN, HScode }
 ✓ HScode → HSname, HScity

~~Every~~ FD have a key on LHS? .

No! No

BCNF? Example #2

Apply(SSN, cName, state, date, major)

SSN, cName, state → date, major

key

In BCNF.

Relational design by decomposition

- “Mega” relations + properties of the data
- System decomposes based on properties
- ❖ “Good” decompositions only — *algorithm.*
- ❖ Into “good” relations ✓ *BCNF* ←

BCNF decomposition algorithm

Input: relation R + FDs for R

Output: decomposition of R into BCNF relations with “lossless join”

Compute keys for R using FDs


Repeat until all relations are in BCNF: ←

Pick any R' with $\bar{A} \rightarrow \bar{B}$ that violates BCNF

Decompose R' into $R_1(A, B)$ and $R_2(A, \text{rest})$

Compute FDs for R_1 and R_2 ←

Compute keys for R_1 and R_2 ←



BCNF Decomposition Example

Student(SSN, sName, address, HScode, HSname, HScity, GPA, priority)

✓ SSN → sName, address, GPA ✓ GPA → priority

★ HScode → HSname, HScity

Key: {SSN, HScode}

[S1] (HScode, HSname, HScity) ← ☺

→ ~~S2 (SSN, sName, addr, HScode, GPA, priority)~~

↘ [S3] (GPA, priority) ← ☺

~~S4 (SSN, sName, addr, HScode, GPA)~~

↘ [S5] (SSN, sName, addr, GPA) ☺

[S6] (SSN, HScode) ☺

BCNF decomposition algorithm

Input: relation R + FDs for R

Output: decomposition of R into BCNF relations with “lossless join”

Compute keys for R

Repeat until all relations are in BCNF:

Pick any R' with $A \rightarrow B$ that violates BCNF

Decompose R' into $R_1(A, B)$ and $R_2(A, \text{rest})$

Compute FDs for R_1 and R_2 Implied FDs Closure.

Compute keys for R_1 and R_2

different answer

“Extend”

$A \rightarrow B$

$A \rightarrow BA^+$

Does BCNF guarantee a good decomposition?

- Removes anomalies? ✓
- Can logically reconstruct original relation?

yes

Too few or too many tuples?

(Handwritten: R, A, B, C, 1, 2, 3, 4, 2, 5, and two purple X's with arrows pointing to the first two rows)

A	B	C
1	2	3
4	2	5

(Handwritten: R, R1, R2, and a red arrow from R to R1 and R2)

$$R \bowtie R_2 = \begin{matrix} 123 \\ 125 \\ 423 \\ 425 \end{matrix}$$

(Handwritten: R1, A, B, 1, 2, 4, 2, and a pink circle around B)

A	B
1	2
4	2

(Handwritten: R2, B, C, 2, 3, 2, 5, and a pink circle around B)

B	C
2	3
2	5

Does BCNF guarantee a good decomposition?

- Removes anomalies?
- Can logically reconstruct original relation?
 - Too few or too many tuples?
- Some shortcomings discussed in later video