


- Courseware (/courses/UTAustinX/UT.6.01x/1T2014/courseware)
- Course Info (/courses/UTAustinX/UT.6.01x/1T2014/info)
- Discussion (/courses/UTAustinX/UT.6.01x/1T2014/discussion/forum)
- Progress (/courses/UTAustinX/UT.6.01x/1T2014/progress)
- Questions (/courses/UTAustinX/UT.6.01x/1T2014/a3da417940af4ec49a9c02b3eae3460b/)
- Syllabus (/courses/UTAustinX/UT.6.01x/1T2014/a827a8b3cc204927b6efaa49580170d1/)

Time is an important factor for embedded systems. The SysTick timer is simple mechanism we can use to measure and control time.

VIDEO 9.1. WORKING OF THE SYSTICK TIMER

Help



JONATHAN VALVANO: The systick device has three device registers.

The first is the control register.

All the registers are 32 bits, and the control register

has three bits down at the bottom.

Bit 0 is the enable bit, which turns it on.

Bit 1 is the interrupt enable bit or arm bit, which enables interrupts.



System | 9.2 | SysTick timer | 601 | The Cores Ed

<https://courses.edx.org/courses/UTAustinX/UT...>
(<http://www.facebook.com/EdxOnline>)

(<https://twitter.com/edXOnline>)

(<https://plus.google.com/108235383044095082735/posts>)

(<http://youtube.com/user/edxonline>)
© 2014 edX, some rights reserved.

Terms of Service and Honor Code -
Privacy Policy (<https://www.edx.org/edx-privacy-policy>)

Help