

CS144

An Introduction to Computer Networks

What the Internet is

The TCP and UDP Service Models



Nick McKeown


Professor of Electrical Engineering
and Computer Science, Stanford University

Outline


TCP Service Model

UDP Service Model

Transmission Control Protocol (TCP)





Peer layers communicate





The TCP Service Model

Property	Behavior
<i>Stream of bytes</i>	Byte delivery service.
<i>Connection oriented</i>	3-way handshake for connection setup.
<i>Reliable delivery</i>	<ol style="list-style-type: none">1. Acknowledgments indicate delivery.2. Checksums detect corrupted data.3. Sequence numbers detect missing data.4. Flow-control prevents overrunning receiver.
<i>In-sequence</i>	Data delivered to application in sequence transmitted.
<i>(Congestion Control</i>	Controls network congestion.)



TCP “stream of bytes” service




...emulated using TCP “segments”




The TCP Segment Format



Connection oriented: 3-way handshake




Connection Setup
3-way handshake




Connection Close/Teardown
2 x 2-way handshake

TCP: Port Demultiplexing




Initial Sequence Numbers



Connection Setup
3-way handshake

Sequence Numbers



TCP Sliding Window

We will learn about several features of TCP in later lectures:

- Window-based flow control
- Congestion control
- Retransmission and timeouts

Outline


TCP Service Model

UDP Service Model


User Datagram Protocol (UDP)

Property	Behavior
<i>Connectionless Datagram Service</i>	No connection established. Packets may show up in any order.
<i>Self contained datagrams</i>	
<i>Unreliable delivery</i>	<ol style="list-style-type: none">1. No acknowledgments.2. Checksum covers header, not data.3. No mechanism to detect missing or mis-sequenced data.4. No flow control.

The UDP Datagram Format



UDP: Port Demultiplexing



Summary

TCP provides in-order, reliable delivery of a stream of bytes between application processes.

UDP provides a simpler, datagram delivery service between application processes.

<The End>