

Middleware

You can add middleware to **FastAPI** applications.

A "middleware" is a function that works with every **request** before it is processed by any specific *path operation*. And also with every **response** before returning it.

- It takes each **request** that comes to your application.
- It can then do something to that **request** or run any needed code.
- Then it passes the **request** to be processed by the rest of the application (by some *path operation*).
- It then takes the **response** generated by the application (by some *path operation*).
- It can do something to that **response** or run any needed code.
- Then it returns the **response**.



Technical Details

If you have dependencies with `yield`, the exit code will run *after* the middleware.

If there were any background tasks (covered in the [Background Tasks](#)  section, you will see it later), they will run *after* all the middleware.

Create a middleware

To create a middleware you use the decorator `@app.middleware("http")` on top of a function.

The middleware function receives:

- The `request`.
- A function `call_next` that will receive the `request` as a parameter.
 - This function will pass the `request` to the corresponding *path operation*.
 - Then it returns the `response` generated by the corresponding *path operation*.
- You can then further modify the `response` before returning it.

Python 3.10+

```
import time

from fastapi import FastAPI, Request

app = FastAPI()

@app.middleware("http")
async def add_process_time_header(request: Request, call_next):
    start_time = time.perf_counter()
    response = await call_next(request)
    process_time = time.perf_counter() - start_time
    response.headers["X-Process-Time"] = str(process_time)
    return response
```



Tip

Keep in mind that custom proprietary headers can be added [using the x- prefix](#).

But if you have custom headers that you want a client in a browser to be able to see, you need to add them to your CORS configurations ([CORS \(Cross-Origin Resource Sharing\)](#)) using the parameter `expose_headers` documented in [Starlette's CORS docs](#).



Technical Details

You could also use `from starlette.requests import Request`.

FastAPI provides it as a convenience for you, the developer. But it comes directly from Starlette.

Before and after the `response`

You can add code to be run with the `request`, before any *path operation* receives it.

And also after the `response` is generated, before returning it.

For example, you could add a custom header `X-Process-Time` containing the time in seconds that it took to process the request and generate a response:

Python 3.10+

```
import time

from fastapi import FastAPI, Request

app = FastAPI()
```

```
@app.middleware("http")
async def add_process_time_header(request: Request, call_next):
    start_time = time.perf_counter()
    response = await call_next(request)
    process_time = time.perf_counter() - start_time
    response.headers["X-Process-Time"] = str(process_time)
    return response
```



Tip

Here we use `time.perf_counter()` [↗](#) instead of `time.time()` because it can be more precise for these use cases. 😊

Multiple middleware execution order

When you add multiple middlewares using either `@app.middleware()` decorator or `app.add_middleware()` method, each new middleware wraps the application, forming a stack. The last middleware added is the *outermost*, and the first is the *innermost*.

On the request path, the *outermost* middleware runs first.

On the response path, it runs last.

For example:

```
app.add_middleware(MiddlewareA)
app.add_middleware(MiddlewareB)
```

This results in the following execution order:

- **Request:** MiddlewareB → MiddlewareA → route
- **Response:** route → MiddlewareA → MiddlewareB

This stacking behavior ensures that middlewares are executed in a predictable and controllable order.

Other middlewares

You can later read more about other middlewares in the [Advanced User Guide: Advanced Middleware](#) [↗](#).

You will read about how to handle `CORS` with a middleware in the next section.