


Buffer Overflows

Joseph Hallett



What is it?

What happens when you declare array?

- You get a region of memory

Pointers are used to address arrays

- Very easy to fall off the end of the region!

Have been known about since the dawn of computers, but earliest tutorial on how to exploit them in *Phrack magazine*

<http://phrack.org/issues/49/14.html>

bristol.ac.uk




How do functions work?

example1.c:

```
void function(int a, int b, int c) {  
    char buffer1[5];  
    char buffer2[10];  
}
```

```
void main() {  
    function(1,2,3);  
}
```



What about something like...

example2.c

```
void function(char *str) {  
    char buffer[16];  
  
    strcpy(buffer, str);  
}
```

```
void main() {  
    char large_string[256];  
    int i;  
  
    for( i = 0; i < 255; i++)  
        large_string[i] = 'A';  
  
    function(large_string);  
}
```

bristol.ac.uk



example2.c

```
void function(char *str) {  
    char buffer[16];  
  
    strcpy(buffer, str);  
}
```

```
void main() {  
    char large_string[256];  
    int i;  
  
    for( i = 0; i < 255; i++)  
        large_string[i] = 'A';  
  
    function(large_string);  
}
```

bottom of
memory

top of
memory


<-----

buffer	sfp	ret	*str
[][][][

top of
stack

bottom of
stack

bristol.ac.uk



example2.c

```
void function(char *str) {  
    char buffer[16];  
  
    strcpy(buffer, str);  
}
```

```
void main() {  
    char large_string[256];  
    int i;  
  
    for( i = 0; i < 255; i++)  
        large_string[i] = 'A';  
  
    function(large_string);  
}
```

bottom of
memory

top of
memory


<-----

buffer	sfp	ret	*str
[AAAAAAAAAAAAAAAAAAAA]	[]	[]

top of
stack

bottom of
stack

bristol.ac.uk



example2.c

```
-----  
void function(char *str) {  
    char buffer[16];  
  
    strcpy(buffer,str);  
}
```

```
void main() {  
    char large_string[256];  
    int i;  
  
    for( i = 0; i < 255; i++)  
        large_string[i] = 'A';  
  
    function(large_string);  
}
```

bottom of
memory


top of
memory

<-----
buffer sfp ret *str
[AAAAAAAAAAAAAAAAAAAA] [AAAA] [AAAA] [AAAA] AAAAAAAAAAAAAAAAAAAAAA

top of
stack

bottom of
stack

bristol.ac.uk



example2.c

```
void function(char *str) {  
    char buffer[16];  
  
    strcpy(buffer, str);  
}
```

```
void main() {  
    char large_string[256];  
    int i;  
  
    for( i = 0; i < 255; i++)  
        large_string[i] = 'A';  
  
    function(large_string);  
}
```

bottom of
memory


top of
memory

<-----
buffer [AAAAAAAAAAAAAAAAAAAA] sfp [AAAA] ret [AAAA] *str [AAAA] AAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

top of
stack

bottom of
stack

bristol.ac.uk



Where shall we return?

Being able to overwrite stack data is bad...

But overwriting return addresses gives us arbitrary code execution...

Normally will just cause an access validation (non-executable memory)
...Or a bad instruction (something isn't valid machine code/aligned)

But *sometimes* you can take over the program...



Shellcode

Classic way of doing this is with buffer shellcode

- This rarely works now... (W^X memory breaks it)
- ...but in the labs we'll let you turn off these protections

Modern way is with *Return Oriented Programming* (ROP)

- We'll cover this later!

Some tricks to make it a bit easier...

- Alphabetic shellcode
- NOP-sleds



Shellcode

Classic way of doing this is with buffer shellcode

- This rarely works now... (W^X memory breaks it)
- ...but in the labs we'll let you turn off these protections

Modern way is with *Return Oriented Programming* (ROP)

- We'll cover this later!

Some tricks to make it a bit easier...

- Alphabetic shellcode
- NOP-sleds



Shellcode

bottom of
memory

top of
memory

<-----

top of
stack

buffer sfp ret *str
[?????NKsjalJvJKjv] [AAAA] [1234] [AAAA]AAAAAAAAAAAAAAAAAAAAA

bottom of
stack



How do we stop this?

- Stack canaries spot if buffers have been overrun!
- W^X makes shellcode harder (but not impossible)
- Use bounded data structures not the old C ones
- Use the bounded memory functions (strncpy)
- Use a modern compiler toolchain and turn on the security features
 - `-D_FORTIFY_SOURCE=2 -fstack-protector-all -fsanitize=address...`
- Avoid C?
- (or at least take care...)

