

Procedimientos SQL

```
DELIMITER $$
```

```
-- =====
```

```
-- 1. variable1
```

```
-- =====
```

```
DROP PROCEDURE IF EXISTS variable1 $$
```

```
CREATE PROCEDURE variable1 ()
```

```
BEGIN
```

```
    DECLARE v_entero1, v_entero2, v_entero3 INT;
```

```
    DECLARE v_entero4 INT DEFAULT -4000;
```

```
    DECLARE v_entero5 INT DEFAULT 400000000;
```

```
    DECLARE v_real1 FLOAT DEFAULT 344.67;
```

```
    DECLARE v_real2 FLOAT DEFAULT 1.5e14;
```

```
    DECLARE v_caracter1 NUMERIC(7,2) DEFAULT 4561.44;
```

```
    DECLARE v_caracter2 VARCHAR(20);
```

```
    DECLARE v_fecha1 DATE DEFAULT '1966-11-03';
```

```
    DECLARE v_fecha2 DATE DEFAULT CURRENT_DATE();
```

```
    SELECT v_entero1;
```

```
    SELECT real_3;
```

```
    SELECT v_fecha2;
```

```
END $$
```

```
-- =====
```

```
-- 2. variable2
```

```
-- =====
```

```
DROP PROCEDURE IF EXISTS variable2 $$
```

```
CREATE PROCEDURE variable2 ()
```

```
BEGIN
```

```
    DECLARE v_caracter1 CHAR(1);
```

```
    DECLARE v_forma_pago1 ENUM ('metalico', 'tarjeta', 'transferencia');
```

```
    SET v_forma_pago1 = 1;
```

```
    SET v_forma_pago1 = 'tarjeta';
```

```
    SET v_forma_pago1 = 'TARJETA';
```

```
END $$
```

```
-- =====
```

```
-- 3. asignal
-- =====
DROP PROCEDURE IF EXISTS asignal $$
CREATE PROCEDURE asignal ()
BEGIN
    DECLARE v_entero1, v_entero2, v_entero3 INT;
    DECLARE v_entero4 INT DEFAULT -4000;
    DECLARE v_real1 FLOAT DEFAULT 344.67;
    DECLARE v_real2 FLOAT DEFAULT 1.5e14;
    DECLARE v_real3 NUMERIC(7,2) DEFAULT 4561.44;
    DECLARE v_caracter1 CHAR(1) DEFAULT 'y';
    DECLARE v_fecha1 DATE DEFAULT '1966-11-03';
    DECLARE v_fecha2 DATE DEFAULT CURRENT_DATE();

    SET v_caracter1 = 'N';
    SET v_entero1 = v_entero4 + 10000;
    SET v_real2 = v_entero4 + v_real3;
    SET v_fecha1 = '2006/01/05', v_fecha2 = v_fecha2 + 1;

    SELECT v_caracter1;
    SELECT v_entero1;
    SELECT v_real2;
    SELECT v_fecha1;
    SELECT v_fecha2;
END $$
```

```
-- =====
-- 4. variable3
-- =====
DROP PROCEDURE IF EXISTS variable3 $$
CREATE PROCEDURE variable3 ()
BEGIN
    SET @v1 = @v1 * 2;
END $$
```

```
-- =====
-- 5. parametro3
-- =====
DROP PROCEDURE IF EXISTS parametro3 $$
CREATE PROCEDURE parametro3 (INOUT p_p1 DECIMAL(7,2))
BEGIN
    SET p_p1 = p_p1 / 166.386;
END $$
```

```

-- =====
-- 6. condicional3
-- =====
DROP PROCEDURE IF EXISTS condicional3 $$
CREATE PROCEDURE condicional3 ()
BEGIN
    DECLARE v_edad TINYINT UNSIGNED DEFAULT NULL;

    IF v_edad <= 30 THEN
        SELECT 'Joven';
    END IF;

    IF v_edad > 30 THEN
        SELECT 'Adulto';
    END IF;
END $$

```

```

-- =====
-- 7. condicional2
-- =====
DROP PROCEDURE IF EXISTS condicional2 $$
CREATE PROCEDURE condicional2 ()
BEGIN
    DECLARE v_edad TINYINT UNSIGNED DEFAULT NULL;

    IF v_edad <= 30 THEN
        SELECT 'Joven';
    ELSE
        SELECT 'Adulto';
    END IF;
END $$

```

```

-- =====
-- 8. condicional1
-- =====
DROP PROCEDURE IF EXISTS condicional1 $$
CREATE PROCEDURE condicional1 ()
BEGIN
    DECLARE v_edad TINYINT UNSIGNED DEFAULT 27;

    IF v_edad <= 12 THEN
        SELECT 'Niño';
    END IF;
END $$

```

```

ELSEIF v_edad <= 30 THEN
    SELECT 'Joven';
ELSE
    SELECT 'Adulto';
END IF;
END $$

-- =====
-- 9. when1
-- =====

DROP PROCEDURE IF EXISTS when1 $$
CREATE PROCEDURE when1 ()
BEGIN
    DECLARE v_forma_pago ENUM ('metalico','tarjeta','transferencia');

    SET v_forma_pago = 'metalico';

    CASE v_forma_pago
        WHEN 'metalico' THEN
            SELECT 'Forma de pago elegida: Metalico';
        WHEN 'tarjeta' THEN
            SELECT 'Forma de pago elegida: Tarjeta';
        ELSE
            SELECT 'Forma de pago elegida: Transferencia';
    END CASE;
END $$

DELIMITER ;

```