



First Session

- Dart basics
- **Data Types**
- if else
- loops

by karim toson

Section 1: Data Types _ Variables

its like boxs

Built-in (Primitive) Types

storing direct values single peace of data .

- **int**: For whole numbers (e.g., 42, -100).
- **double**: For decimal numbers (e.g., 3.14, 2.718).
- **bool**: For true/false values (e.g., true, false).
- **String** : for words ("names ").

complex (Non-Primitive) Types

Store complex data structures or references to objects. They can hold multiple values.

- List
- set
- map

Task

defining its data type and displaying the output

age = 30

job = 'software engineer'

male = True

score = 95.5

If-Else Statements in Dart

make decisions based on certain conditions.

Basic Syntax and Decision Making

At its core, an if statement checks a Boolean condition. If the condition is true, the code block immediately following it is executed. Otherwise, that block is skipped.

```
if (condition) {  
  // Code to execute if condition is true  
}
```

The else keyword can be added to specify a block of code to be executed when the if condition is false.

```
if (condition) {  
  // Code to execute if condition is true  
} else {  
  // Code to execute if condition is false  
}
```

Practical Examples in Dart

1. Simple if Statement

This example checks if a user's age is greater than or equal to 18 to grant access.

```
void main() {  
  int age = 20;  
  
  if (age >= 18) {  
    print('Access Granted: You are old enough to enter.');  }  
}  
  
// Expected Output: Access Granted: You are old enough to enter.
```

If-Else If Chain Example

This example demonstrates an if-else if chain to assign a performance message based on a numerical grade. The code checks conditions sequentially, executing the first block whose condition evaluates to true.

```
void main() {  
    int grade = 85;  
  
    if (grade >= 90) {  
        print("Excellent");  
    } else if (grade >= 75) {  
        print("Very Good");  
    } else if (grade >= 50) {  
        print("Pass");  
    } else {  
        print("Fail");  
    }  
}
```

Expected Output:

Very Good

Task

Write a Dart program that takes a temperature value and prints a message based on the weather condition

If the temperature is greater than 30 =====> print "It's Hot"

If the temperature is between 15 and 30 (inclusive) =====> print "Nice Weather"

If the temperature is less than 15 =====> print "It's Cold"

```
void main() {  
  
    int temp=30;  
  
    if(temp>30)  
    {  
        print('hot');  
  
    }  
    else if(temp>15&&temp<=30)  
    {  
        print('nice');  
    }  
    else  
    {  
        print('cold');  
    }  
  
}
```

`switch-case` Statements

```
switch (expression) {  
  case value1:  
    // Code to execute if expression equals value1  
    break;  
  case value2:  
    // Code to execute if expression equals value2  
    break;  
  case value3:  
  case value4: // Multiple cases can share the same block  
    // Code to execute if expression equals value3 or value4  
    break;  
  default:  
    // Code to execute if expression doesn't match any case  
    break;  
}
```


Task

Write a Dart program takes an operator ('-' , '+')

case 1 '+' print => "add operator "

case 2 '-' print => "subtract operator "

Understanding Loops in Dart

1. For Loop

The `for` loop is used when **you know exactly how many times** you want to iterate through a block of code.

Syntax

```
for (initialization; condition; increment/decrement) {  
  // code to be executed  
}
```

When to Use

Ideal for iterating over a fixed range, such as iterating through elements in a list, or performing a task a specific number of times.

2. While Loop

The `while` loop repeatedly executes a block of code as long as a specified condition is true. The condition is checked before each iteration.

Syntax

```
while (condition) {  
  // code to be executed  
}
```

When to Use

Use when the number of iterations is not known beforehand, and the loop needs to continue as long as a certain condition remains true (e.g., reading data until the end of a file).

Example

```
void main() {  
  int count = 0;  
  while (count < 3) {  
    print("While loop count: $count");  
    count++;  
  }  
}  
  
// Expected Output:  
// While loop count: 0  
// While loop count: 1  
// While loop count: 2
```

Task

Write a Dart program using a `for loop` to print only the **even numbers** between **1 and 20**

write a Dart program using a `while loop` to calculate the **sum of all numbers from 1 to 50** and print the result.

```
void main()
```

```
{
```

```
for (int i = 1; i <= 20; i++)
```

```
{
```

```
if (i % 2 == 0)
```

```
{
```

```
print(i); }
```

```
}
```

```
}
```

```
void main()
```

```
{
```

```
int sum = 0;
```

```
for (int i = 1; i <= 50; i++)
```

```
{
```

```
sum += i;
```

```
}
```

```
}
```

codewars



Achieve Mastery Through Challenge



Codewars



Reversed Strings

Complete the solution so that it reverses the string passed into it. 'world' => 'dlrow' 'word' => 'drow'

create a two number calculator where you can (+, -, /, *).

Assignment

<https://www.codewars.com/kata/5672a98bdbdd995fad00000f>