

Class 9 Lab

Karleen Guerrero (A16791042)

```
library(readr)
pdbdb <- read_csv("~/Downloads/pdb_stats (1).csv")
```

Rows: 6 Columns: 8

-- Column specification -----

Delimiter: ","

chr (1): Molecular Type

dbl (3): Multiple methods, Neutron, Other

num (4): X-ray, EM, NMR, Total

i Use `spec()` to retrieve the full column specification for this data.

i Specify the column types or set `show_col_types = FALSE` to quiet this message.

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
pdbdb <- read_csv('pdb_stats.csv', row.names = 1)
pdbdb
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	167,192	15,572	12,529	208	77	32
Protein/Oligosaccharide	9,639	2,635	34	8	2	0
Protein/NA	8,730	4,697	286	7	0	0
Nucleic acid (only)	2,869	137	1,507	14	3	1
Other	170	10	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	195,610					
Protein/Oligosaccharide	12,318					
Protein/NA	13,720					
Nucleic acid (only)	4,531					

Other	213
Oligosaccharide (only)	22

I need to remove the comma and convert to numeric to do math:

```
as.numeric( sub(",", "", pdbdb$Total) )
```

```
[1] 195610 12318 13720 4531 213 22
```

```
#as.numeric(pdbdb$Total)
```

I could turn this into a function to fix the whole table or any future table I read like this:

```
x <- pdbdb$Total
as.numeric( sub(",", "", x) )
```

```
[1] 195610 12318 13720 4531 213 22
```

```
comma2numeric <- function(x) {
  as.numeric( sub(",", "", x) )
}
```

Test it

```
comma2numeric(pdbdb$X.ray)
```

```
[1] 167192 9639 8730 2869 170 11
```

```
apply(pdbdb, 2, comma2numeric)
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other	Total
[1,]	167192	15572	12529	208	77	32	195610
[2,]	9639	2635	34	8	2	0	12318
[3,]	8730	4697	286	7	0	0	13720
[4,]	2869	137	1507	14	3	1	4531
[5,]	170	10	33	0	0	0	213
[6,]	11	0	6	1	0	4	22

Or try a different read/import function

```
library(readr)
pdbdb <- read_csv("pdb_stats.csv")
```

Rows: 6 Columns: 8

-- Column specification -----

Delimiter: ","

chr (1): Molecular Type

dbl (3): Multiple methods, Neutron, Other

num (4): X-ray, EM, NMR, Total

i Use `spec()` to retrieve the full column specification for this data.

i Specify the column types or set `show_col_types = FALSE` to quiet this message.

```
sum(pdbdb$Total)
```

```
[1] 226414
```

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
sum(pdbdb$'X-ray')/sum(pdbdb$Total) * 100
```

```
[1] 83.30359
```

```
sum(pdbdb$EM)/sum(pdbdb$Total)* 100
```

```
[1] 10.18091
```

Q2: What proportion of structures in the PDB are protein?

Mol*

Mol* (pronounced “molstar”) is a new web-based molecular viewer that we will need to learn the basics of here.

<https://molstar.org/viewer/>

We will use PDB code: 1HSG




Figure 1: A first image from molstar

Some more custom images:




Figure 2: The all important catalytic ASP25 amino acid




Figure 3: Surface display showing Merk compound in the peptide binding pocket




Figure 4: Ligand in pocket




Figure 5: Water molecule

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

5 structures

The Bio3D package

The bio3d package allows us to do all sorts of structural bioinformatics work in R.

Let's start with how it can read these PDB files:

```
library(bio3d)

pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```



```
Call: read.pdb(file = "1hsg")
```

```
Total Models#: 1
```

```
Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)
```

```
Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 172 (residues: 128)
```

```
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

```
Protein sequence:
```

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD  
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE  
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP  
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,  
      calpha, remark, call
```

```
attributes(pdb)
```

```
$names
```

```
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"
```

```
$class
```

```
[1] "pdb" "sse"
```

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40
	segid	elesy	charge										
1	<NA>	N	<NA>										
2	<NA>	C	<NA>										

```
3 <NA>      C  <NA>
4 <NA>      O  <NA>
5 <NA>      C  <NA>
6 <NA>      C  <NA>
```

```
pdbseq(pdb)
```

```
  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20
"P" "Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K"
21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40
"E" "A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G"
41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60
"R" "W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D"
61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80
"Q" "I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T"
81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99  1
"P" "V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F" "P"
  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21
"Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K" "E"
22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41
"A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G" "R"
42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61
"W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D" "Q"
62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81
"I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T" "P"
82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99
"V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F"
```

Q7: How many amino acid residues are there in this pdb object?

```
sum(pdb$calpha)
```

```
[1] 198
```

Q8: Name one of the two non-protein residues?

HOH and MK1

Q9: How many protein chains are in this structure?

```
2
```

```
unique(pdb$atom$chain)
```

```
[1] "A" "B"
```

Predicting functional motions of a single structure

Lets do bioinformatics prediction of functional motions- i.e the movements that one of these molecules needs to make to do its stuff.

```
adk <- read.pdb("6s36")
```

Note: Accessing on-line PDB file

PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
```

```
Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)
```

```
Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 244 (residues: 244)
```

```
Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]
```

```
Protein sequence:
```

```
MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV  
TDELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVDYVLEFDVPDELIVDKI  
VGRRVHAPSGRVYHVKFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM  
TAPLIG  
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
```

```
+ attr: atom, xyz, seqres, helix, sheet,  
      calpha, remark, call
```

```
# Perform flexibility prediction  
m <- nma(adk)
```

Building Hessian... Done in 0.044 seconds.
Diagonalizing Hessian... Done in 0.562 seconds.

```
plot(m)
```

