

Deep learning for medical image registration

Iris Kolenbrander

Outline for today:

- First hour:
 - Quick recap of medical image registration
 - Introduction non-parametric / deformable image registration
 - Deep learning for medical image registration:
 - Deep iterative registration
 - Supervised methods
 - Unsupervised (optimization-based) methods
- Second hour:
 - “Guest lecture”
 - Image registration for adaptive radiotherapy
 - Challenges in image registration, e.g., small open-source datasets

Learning outcomes

The student can:

- differentiate between parametric and non-parametric/deformable transformation models.
- explain what a displacement (vector) field is and calculate the corresponding number of free parameters, given a medical image pair to be registered.
- name the main advantages and disadvantages of using deep learning for medical image registration.
- categorize deep learning-based medical image registration methods into one of the three groups of methods based on how they deal with the ground truth displacement.
- For each category, give an example of a method that was proposed in recent literature.


Recap: medical image registration

Why important?


- Multi-modal registration (e.g. CT on MRI)
- Inter-subject (e.g. atlas registration)
- Longitudinal (e.g. treatment evaluation)

Remaining challenges:



- Large 3D volumes
- Accuracy vs. efficiency
- Intensity inhomogeneities and discontinuities
- Outlier rejection



Finding the optimal transformation




Transformation models




Rigid & Affine

- Point or feature-based (e.g. landmarks, fiducials)
- Intensity-based
- Gradient/edge-based



Non-linear


- Linear or higher order polynomials
- Spline-based




Non-parametric / deformable

- Allowing each image element to be displaced arbitrarily

Displacement (vector) field (DVF) = Dense set of vectors representing the displacement in a given spatial domain






Deformation: $\varphi = Id + u, \varphi: \Omega \rightarrow \mathbb{R}^d$
 or point-wise: $\varphi(x) = x + u(x)$


Displacement:

$$u: \Omega \rightarrow \mathbb{R}^d$$


e.g. u
 $= [u_x, u_y, u_z]$



Deformable image registration: how many free parameters (DOF) in 3D?



Typical spatial resolution of a
3D medical image
(MRI: e.g. $1.5 \times 1.5 \times 4 \text{ mm}^3$ voxels)




$$\text{DOF} = 3 \cdot N_x \cdot N_y \cdot N_z (!)$$

Deformable image registration is still a very active area of research, and many different deformable registration models exist:

- Free-form deformation model
- Optical flow
- Demons
- Fluid flow
- Diffeomorphisms
- ...

Note that the details of these models and their implementations are beyond the scope of this course.

Why focus on deep learning for medical image registration?



Real time
applications!

Learning image registration: how does it work?

Problem: how can we obtain the ground truth displacement ?

A. Deep iterative registration


- Learn a component of a classical registration method

B. Supervised transformation estimation


- Obtain using classical registration method
- or make synthetic ground truth

C. Unsupervised transformation estimation

- Use similarity metric to judge




Publications on deep learning for medical image registration




A. Deep iterative registration


Use a classical registration method and learn one component




Example 1: *Learning multimodal feature extraction (Haskins et al., 2019)*



Example 2: Reinforcement learning for image registration




(a) Training Data Generation: **Synthetic deformations** (blue arrows) and inter-subject GT deformations (black) are used for intra- (green) and inter-subject (red) image pairs for training. (b) Dual-stream network used for Q-value prediction including complete single-stage Markov Decision Process for testing (blue background).




B. Supervised transformation estimation


Requires many known transformations for training, use ground truth labels to calculate the loss



Example 1: “On-the-fly” simulation of displacement fields: T_{augm} (Eppenhof & Pluim, 2018)




Example 2: Weakly-supervised CNN for MR-US registration




C. Unsupervised transformation estimation

No ground truth needed, requires a differentiable similarity metric and a spatial transformer layer (STL).




Example 1: the *VoxelMorph* framework (Balakrishnan et al., 2018)



Spatial transformer networks (Jaderberg et al., NIPS 2015)

Spatial transformer = a learnable module that explicitly allows the spatial manipulation of data within the network

- *Differentiable*
- Can be inserted into existing convolutional neural networks
- Actively transforms feature maps (conditional on the feature map itself)



Example $T_\theta(G)$ for an affine transformation:

$$\begin{pmatrix} x_i^s \\ y_i^s \end{pmatrix} = T_\theta(G_i) = A_\theta \begin{pmatrix} x_i^t \\ y_i^t \\ 1 \end{pmatrix} = \begin{bmatrix} \theta_{11} & \theta_{12} & \theta_{13} \\ \theta_{21} & \theta_{22} & \theta_{23} \end{bmatrix} \begin{pmatrix} x_i^t \\ y_i^t \\ 1 \end{pmatrix}$$

Summary

- Parametric vs. non-parametric/deformable image registration
 - Displacement vector fields
- Different ways to use deep learning for image registration
 - Deep iterative registration
 - Supervised learning
 - Unsupervised learning
- Disadvantages of deep learning for image registration
(performance, # of training data, ground truth, ...)

