

Hands-on training session 3

Hui-Walter models with more than two diagnostic tests

Matt Denwood Giles Innocent Sonja Hartnack

2020-02-12

Introduction

Overview

Date/time:

- 20th February 2020
- 14.00 - 15.30

Teachers:

- Matt Denwood (presenter)
- Giles Innocent
- Sonja Hartnack

Recap

Important points from sessions 1 and 2

Session 3a: Hui-Walter models for multiple tests with conditional independence

What exactly is our latent class?

What do we mean by “conditionally independent?”

Example: three antibody tests

Rabbits and hats 2

Extreme care with multinomial tabulation

Use autohwiwaller!

Missing data in test results

Use autohwiwalter!

Combining Hui-Walter part with template.jags

Will likely be included in template.jags in future

Exercise

Simulate data from 3 or 4 tests and analyse

Optional Exercise

What happens if some data is missing for 1 (or more) tests?

Session 3b: Hui-Walter models for multiple tests with conditional dependence

Branching of processes leading to test results

Example: two antibody tests and one antigen test

Or three antibody tests where one has a different target to the others

Use autohwiwalter!

Exercise

Simulate data with a dependence between 2 tests

Model assuming conditional independence biases the estimates

Model with conditional dependence has bigger CI but unbiased

Session 3c: Model selection

Methods of selecting models

DIC works fine for hierarchical normal models

Bayes factors work well if you can count them

WAIC works better for a wide range of models

- 1 * Probably won't work for Hui-Walter though due to lack of
↪ independent data
- 2 * Could be useful if using the GLM version (untested!)

Models tend to be sensitive to priors

Simulating data and testing that your model recovers the parameters is a good idea

Discussion and free practical time