

EXCEPTIONS, ASSERTIONS

EXCEPTIONS AND ASSERTIONS

- what happens when procedure execution hits an **unexpected condition**?
something happens I didn't expect
-> It's an exception to what we plan for,
what we wanted to have happen
- get an **exception**... to what was expected
lead typically to a message from Python
 - trying to access beyond list limits

```
test = [1, 7, 4]  
test[4]
```

→ **IndexError**
 - trying to convert an inappropriate type

```
int(test)
```

→ **TypeError**
 - referencing a non-existing variable

```
a
```

→ **NameError**
 - mixing data types without coercion

```
'a' / 4
```

→ **TypeError**

OTHER TYPES OF EXCEPTIONS

- already seen common error types:
 - `SyntaxError`: Python can't parse program
 - `NameError`: local or global name not found
 - `AttributeError`: attribute reference fails
 - `TypeError`: operand doesn't have correct type
 - `ValueError`: operand type okay, but value is illegal
 - `IOError`: IO system reports malfunction (e.g. file not found)

WHAT TO DO WITH EXCEPTIONS?

- what to do when encounter an error?
- **fail silently**:
 - substitute default values or just continue
 - bad idea! user gets no warning
- return an **“error” value**
 - what value to choose?
 - complicates code having to check for a special value
- stop execution, **signal error** condition
 - in Python: **raise an exception**
`raise Exception("descriptive string")`

DEALING WITH EXCEPTIONS

- Python code can provide **handlers** for exceptions

-> able to control: What do I do when I see an exception

```
try:
    a = int(input("Tell me one number:"))
    b = int(input("Tell me another number:"))
    print(a/b)
    print("Okay")
except:
    print("Bug in user input.")
print("Outside")
```

Try says try to execute each of these instructions in turn. But if an exception is raised, stop that processing, jump to the except clause, and execute those statements. And then, carry on outside of the entire loop. If no exception is raised, ignore the except block

- exceptions **raised** by any statement in body of **try** are **handled** by the **except** statement and execution continues after the body of the except statement

HANDLING SPECIFIC EXCEPTIONS

- have **separate except clauses** to deal with a particular type of exception

```
try:
```

```
    a = int(input("Tell me one number: "))
    b = int(input("Tell me another number: "))
    print("a/b = ", a/b)
    print("a+b = ", a+b)
```

```
except ValueError:
```

```
    print("Could not convert to a number.")
```

```
except ZeroDivisionError:
```

```
    print("Can't divide by zero")
```

```
except:
```

```
    print("Something went very wrong.")
```

only execute
if these errors
come up

for all
other
errors

OTHER EXCEPTIONS

- `else:`
 - `body` of this is **executed** when **execution of associated `try` body **completes with no exceptions****
- `finally:`
 - `body` of this is **always executed** after `try`, `else` and `except` clauses, **even if they raised another error or executed a `break`, `continue` or `return`**
 - useful for **clean-up code** that should be **run no matter what else happened** (e.g. close a file)

pull things outside of the `try` body to isolate them as being things I always want to do if it runs correctly.

EXAMPLE EXCEPTION USAGE

```
while True:
    try:
        n = input("Please enter an integer")
        n = int(n)
        break
    except ValueError:
        print("Input not an integer; try again")
print("Correct input of an integer!")
```

(-> "do while" loop)

way to control ensuring that the input comes in the right way

only handles ValueError!
other errors will stop execution

Loop only exits when correct type of input provided

Only prints message if exception raised

EXAMPLE: CONTROL INPUT

```
data = []  
file_name = input("Provide a name of a file of data ")
```

get a file name by asking for input from the user

```
try:                                try to open the file  
    fh = open(file_name, 'r')  
except IOError:  
    print('cannot open', file_name)  
else:  
    for new in fh:  
        if new != '\n':  
            addIt = new[:-1].split(',') #remove trailing  
            data.append(addIt)  
finally:  
    fh.close() # close file even if fail
```

Jump out if no file of
that name

if that works well, I'm going to open up the file
and I'm going to be able to execute out.

Close file in either case

* reading in a new line. As long as it isn't just a carriage return, I'm going to take the line, split it by the commas to separate out the pieces to create a list, and then remove using this little thing of taking everything but the last element, removing the trailing carriage return, and add it into the file

EXAMPLE: CONTROL INPUT

- appears to correct read in data, and convert to a list of lists
- now suppose we want to restructure this into a list of names and a list of grades for each entry in the overall list

EXAMPLE: CONTROL INPUT

```
data = []
file_name = input("Provide a name of a file of data ")

try:
    fh = open(file_name, 'r')
except IOError:
    print('cannot open', file_name)
else:
    for new in fh:
        if new != '\n':
            addIt = new[:-1].split(',') #remove trailing \n
            data.append(addIt)
finally:
    fh.close() # close file even if fail

gradesData = []
if data:
    for student in data:
        try:
            gradesData.append([student[0:2], [student[2]]])
        except IndexError:
            gradesData.append([student[0:2], []])
```

data = []

data = [[student0 name, student0 name, grade0],
[student1 name, student1 name, grade1], ...]

as long as I've got some data
because I read that in appropriately,
which I wanted to check-- then I could loop through it

no grade for student substitute missing data,
the grade, with empty list

Handle case of no grade;
But assumes two names!

take out the first two elements-- the student's first and last name-- and the grades and convert
that into two lists, a list of the students' name and a list of the actual grades

EXAMPLE: CONTROL INPUT

- works okay if have standard form, including case of no grade
- but fails if names are not two parts long

EXAMPLE: CONTROL INPUT

```
data = []
file_name = input("Provide a name of a file of data ")

try:
    fh = open(file_name, 'r')
except IOError:
    print('cannot open', file_name)
else:
    for new in fh:
        if new != '\n':
            addIt = new[:-1].split(',') #remove trailing \n
            data.append(addIt)
finally:
    fh.close() # close file even if fail

gradesData = []
if data:
    for student in data:
        try:
            name = student[0:-1]
            grades = int(student[-1])
            gradesData.append([name, [grades]])
        except ValueError:
            gradesData.append([student[:], []])
```

pull out the name for the student, and I'm going to treat it as everything but the grade-- so everything but the last element. grades be that last element, and I'm going to try and convert it into an integer.

in the case that it can't-- because I don't have something there-- I'm going to catch the value error and simply insert an empty list in that case together with all of the elements of the student

Handle case of no grade;
Now allows for multiple names!

let the exception handle the special case

exception:

- how to handle exception when I get there
- control of deciding when to raise an exception
- > (and how to handle that exception when I get there)

EXCEPTIONS AS CONTROL FLOW

- don't return special values when an error occurred and then check whether 'error value' was returned
- instead, **raise an exception** when **unable to produce a result consistent with function's specification**

```
raise <exceptionName>(<arguments>)
```

```
raise ValueError("something is wrong")
```

keyword

*name of error
you want to raise*

*existing error exception (more
common) or created by ourselves*

typically a string with a message

EXAMPLE: RAISING AN EXCEPTION

```
def get_ratios(L1, L2):  
    """ Assumes: L1 and L2 are lists of equal length of numbers  
        Returns: a list containing L1[i]/L2[i] """  
    ratios = []  
    for index in range(len(L1)):  
        try:  
            ratios.append(L1[index]/float(L2[index]))  
        except ZeroDivisionError:  
            ratios.append(float('NaN')) #NaN = Not a Number  
        except:  
            if I try to index out of range when  
            lists are not of equal length  
                raise ValueError('get_ratios called with bad arg')  
    return ratios
```

manage flow of
program by raising
own error

EXAMPLE OF EXCEPTIONS

- assume we are **given a class list** for a **subject**: **each entry** is a **list of two parts**
 - a **list** of **first and last name** for a student
 - a **list** of **grades on assignments**

```
test_grades = [[['peter', 'parker'], [80.0, 70.0, 85.0]],  
               [['bruce', 'wayne'], [100.0, 80.0, 74.0]]]
```

- create a **new class list**, with **name, grades, and an average**

```
[[['peter', 'parker'], [80.0, 70.0, 85.0], 78.33333],  
 [['bruce', 'wayne'], [100.0, 80.0, 74.0], 84.666667]]]
```

EXAMPLE CODE

assuming I'm inputting things
that have a list of names and a list of grades.

```
[(['peter', 'parker'], [80.0, 70.0, 85.0]),  
(['bruce', 'wayne'], [100.0, 80.0, 74.0])]
```

```
def get_stats(class_list):  
    new_stats = []  
    for elt in class_list:  
        new_stats.append([elt[0], elt[1], avg(elt[1])])  
    return new_stats  
  
def avg(grades):  
    return sum(grades)/len(grades)
```

ERROR IF NO GRADE FOR A STUDENT

- if one or more students **don't have any grades**, get an error

```
test_grades = [[['peter', 'parker'], [10.0, 5.0, 85.0]],  
               [['bruce', 'wayne'], [10.0, 8.0, 74.0]],  
               [['captain', 'america'], [8.0, 10.0, 96.0]],  
               [['deadpool'], []]]
```

- get **ZeroDivisionError**: float division by zero because try to

```
return sum(grades) / len(grades)
```

length is 0

OPTION 1: FLAG THE ERROR BY PRINTING A MESSAGE

- decide to **notify** that something went wrong with a msg

```
def avg(grades):
```

```
    try:
```

```
        return sum(grades)/len(grades)
```

```
    except ZeroDivisionError:
```

```
        print('no grades data')
```

None returned if
exception raised

- running on some test data gives

```
no grades data
```

flagged the error

```
[[['peter', 'parker'], [10.0, 5.0, 85.0], 15.416666666666666],
```

```
 [['bruce', 'wayne'], [10.0, 8.0, 74.0], 13.833333333333334],
```

```
 [['captain', 'america'], [8.0, 10.0, 96.0], 17.5],
```

```
 [['deadpool'], [], None]]
```

because avg did
not return anything

OPTION 2: CHANGE THE POLICY

- decide that a student with no grades gets a **zero**

```
def avg(grades):  
    try:  
        return sum(grades)/len(grades)  
    except ZeroDivisionError:  
        print('no grades data')  
        return 0.0 explicit return
```

- running on some test data gives

no grades data


```
[[['peter', 'parker'], [10.0, 5.0, 85.0], 15.416666666666666],  
 [['bruce', 'wayne'], [10.0, 8.0, 74.0], 13.833333333333334],  
 [['captain', 'america'], [8.0, 10.0, 96.0], 17.5],  
 [['deadpool'], [], 0.0]]
```

still flag the error

now avg returns 0

Program flow for try (except else finally) statement

docs.python.org/3/reference/compound_stmts.html#the-try-statement
docs.python.org/3/tutorial/errors.html



ASSERTIONS

- want to be sure that **assumptions** on state of computation are as expected
- use an **assert statement** to raise an `AssertionError` exception if assumptions not met
- an example of good **defensive programming**

EXAMPLE

```
def avg(grades):
```

```
    assert not len(grades) == 0, 'no grades data'
```

```
    return sum(grades)/len(grades)
```

*function ends
immediately if
assertion not met*

- raises an `AssertionError` if it is given an empty list for grades
- otherwise runs ok

ASSERTIONS AS DEFENSIVE PROGRAMMING

- assertions don't allow a programmer to control response to unexpected conditions
- ensure that **execution halts** whenever an expected condition is not met
- typically used to **check inputs** to functions procedures, but can be used anywhere
- can be used to **check outputs** of a function to avoid propagating bad values
- can make it easier to locate a source of a bug

WHERE TO USE ASSERTIONS?

- goal is to spot bugs as soon as introduced and make clear where they happened
- use as a **supplement** to testing
- raise **exceptions** if users supplies **bad data input**
- use **assertions** to
 - check **types** of arguments or values
 - check that **invariants** on data structures are met
 - check **constraints** on return values
 - check for **violations** of constraints on procedure (e.g. no duplicates in a list)