



# Test Report

**Manufacturer:** DK-Technologies A/S

**Product:** PT5300

**Standard:** EN 60950-1:2006

**Report no:** B2013030

**Date and Signatur:** 2013-05-15

A handwritten signature in black ink, appearing to read "Aini Bolls", is written over the date.

## Bolls ApS

---

Ved Gadekæret 11F  
DK-3660 Stenløse  
Denmark

Tlf.: +45 48 18 35 66

Fax: +45 48 18 35 30

E-mail: [info@bolls.dk](mailto:info@bolls.dk)

web: [www.bolls.dk](http://www.bolls.dk)

# TEST REPORT

**EN 60950-1:2006**

## Information technology equipment – Safety – Part 1: General requirements

Report reference No .....: B2013030

Tested by Søren Carlsen

Approved by: Kim Boll Jensen

Date of issue .....: 15.05.2013

**Testing Laboratory Name** .....: Bolls ApS

Address .....: Ved Gadekæret 11F

DK – 3660 Stenløse

Denmark

**Applicant's Name** .....: DK-Technologies A/S

Address .....: Marielundvej 37D

2730 Herlev

## Test specification

Standard.....: EN 60950-1: 2006 (2. edition) + EN 60950-1 A1:2010 + EN 60950-1 A11:2009 + EN 60950-1 A12:2011

CAN/CSA C22.2 No. 60950/UL60950, Third Edition, based on IEC 60950, Third Edition

**Test Report Form No.....: IECEN60950 1B**

TRF originator .....: SGS Fimko Ltd

Master TRF .....: Dated 2003-03

Copyright © 2003 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Bolls ApS have no responsibility for products produced and sold under names mentioned in this report, and can not be held responsible for any mistakes which could lead to non-compliance according to this report.**

**Test item description .....**

Trademark .....: DK-Technologies A/S

Manufacturer .....: DK-Technologies A/S

Model and/or type reference .....: PT5300

Serial number .....: KU031256

Rating(s).....: 100-240 VAC, 50/60 Hz, 90 VA

**Equipment under test (EUT):**

**Marking plate:**

NP  
Voltage range to be updated with 100-240V  
Frequency range to be updated with 50/60 Hz

|   |                     |
|---|---------------------|
| <b>Particulars: test item vs. test requirements</b>   |                     |
| Equipment mobility .....  | stationary or fixed |
| Operating condition.....  | Continuous          |
| Mains supply tolerance (%).....   | +6 % and -10%       |
| Tested for IT power systems .....   | No                  |
| IT testing, phase-phase voltage (V) .....   | -                   |
| Class of equipment .....  | Class I             |
| Mass of equipment (kg).....   | 5                   |
| Protection against ingress of water .....   | IPX                 |
| <b>Test case verdicts</b>   |                     |
| Test case does not apply to the test object .:  | N/A                 |
| Test item does meet the requirement .....   | P(ass)              |
| Test item does not meet the requirement ...:  | F(ail)              |
| <b>Testing</b>  |                     |
| Date of receipt of test item .....  |                     |
| Date(s) of performance of test .....  | 19.04 – 03.05.2013  |
| General remarks   |                     |
| <p><b>"This report is not valid as a CB Test Report unless appended by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IEC 60335-1".</b></p> <p>The test result presented in this report relate only to the object(s) tested.<br/>         This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p> <p>"(see Enclosure #)" refers to additional information appended to the report.<br/>         "(see appended table)" refers to a table appended to the report.</p> <p>Throughout this report a comma (point) is used as the decimal separator.</p> |                     |
| National deviations:  |                     |
| USA,<br>Canada  |                     |
| See appended pages at end of report   |                     |

**General product information:**

The PT5300 HD-SD Varitime™ Sync Generator is specially designed to fit into HD as well as SD digital and mixed digital/analogue video installations, and it provides signals for synchronization, fault finding and checking of the entire digital chain. Because of its many parallel outputs, the PT5300 is ideal for supplying the video switcher with all commonly used test signals for alignment, but also as a stand-by pattern source.

Several generators can be added to the basic unit, making up to 4 different HD or SD SDI signals available at a time. Instead of SDI generators, one or two analogue test pattern generator modules can be added. All HD-SD SDI generators are switchable between 625 and 525 lines and the various HD formats, but differ in the number of signals, embedded audio, and other features.

The analogue composite generator is a dual standard, PAL and NTSC, and provides test signals and the PTV pattern.

| IEC 60950-1 / EN 60950-1 |   |                          |         |
|--------------------------|---|--------------------------|---------|
| Clause                   | Requirement – Test  | Result – Remark          | Verdict |
| 1                        | GENERAL   |                          | P       |
| 1.5                      | Components  |                          | P       |
| 1.5.1                    | General   | See appended table 1.5.1 | P       |
|                          | Comply with IEC 60950 or relevant component standard  |                          | P       |
| 1.5.2                    | Evaluation and testing of components  |                          | P       |
| 1.5.3                    | Thermal controls  |                          | P       |
| 1.5.4                    | Transformers  |                          | P       |
| 1.5.5                    | Interconnecting cables  |                          | P       |
| 1.5.6                    | Capacitors bridging insulation  |                          | P       |
| 1.5.7                    | Resistors bridging insulation   | See appended table 1.5.1 | P       |
| 1.5.7.1                  | Resistors bridging functional insulation, basic insulation or supplementary insulation  |                          | P       |
| 1.5.7.2                  | Resistors bridging double insulation or reinforced insulation between the a.c. mains supply and other circuits                                    |                          | P       |
| 1.5.7.3                  | Resistors bridging double insulation or reinforced insulation between the a.c. mains supply and circuits connected to an antenna or coaxial cable |                          | P       |
| 1.5.8                    | Components in equipment for IT power systems  | See appended table 1.5.1 | P       |
| 1.5.9                    | Surge suppressors   | See appended table 1.5.1 | P       |
| 1.5.9.1                  | General   |                          | P       |
| 1.5.9.2                  | Protection of VDRs  |                          | P       |
| 1.5.9.3                  | Bridging of functional insulation by a VDR  |                          | P       |
| 1.5.9.4                  | Bridging of basic insulation by a VDR   |                          | P       |
| 1.5.9.5                  | Bridging of supplementary, double or reinforced insulation by a VDR   |                          | P       |
| 1.6                      | Power interface   |                          | P       |
| 1.6.1                    | AC power distribution systems   |                          | P       |
| 1.6.2                    | Input current   | See appended table 1.6.2 | P       |
| 1.6.3                    | Voltage limit of hand-held equipment  |                          | NA      |
| 1.6.4                    | Neutral conductor   |                          | P       |
| 1.7                      | Marking and instructions  |                          | P       |



| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test  | Result – Remark  | Verdict |
| 1.7.1                    | Power rating and identification markings  |  | P       |
| 1.7.1.1                  | Power rating markings   |  | P       |
|                          | If EUT has multiple mains supply connections, each individual mains supply electrical rating must be marked |  | NA      |
|                          | Identification markings readily visible   |  | P       |
|                          | Rated voltage(s) or voltage range(s) (V) .....  | 100-240V   | P       |
|                          | Symbol for nature of supply, for d.c. only.....   |  | NA      |
|                          | Rated frequency or rated frequency range (Hz) .....   | 50-60Hz  | P       |
|                          | Rated current (mA or A) .....   | 90VA   | P       |
| 1.7.1.2                  | Identification markings   | Identification marking on front, rear and side of EUT  | P       |
|                          | Manufacturer's name or trademark or identification mark .....   |  | P       |
|                          | Type/model or type reference.....   |  | P       |
|                          | Symbol for Class II equipment only .....  |  | NA      |
|                          | Other markings and symbols .....  | CE-marking, WEEE-marking   | P       |
|                          | Identification markings readily visible   | Identification marking on front, rear and side of EUT  | P       |
| 1.7.2                    | Safety instructions and markings  |  | P       |
| 1.7.2.1                  | General   |  | P       |
| 1.7.2.2                  | Disconnect devices  |  |         |
| 1.7.2.3                  | Overcurrent protective device   | 1.6 A fuse placed in line in the power supply module, as first component after the mains connector | P       |
| 1.7.2.4                  | IT power distribution systems   |  | NA      |
| 1.7.2.5                  | Operator access with a tool   |  | NA      |
| 1.7.2.6                  | Ozone   |  | NA      |
| 1.7.3                    | Short duty cycles   |  | NA      |
| 1.7.4                    | Supply voltage adjustment .....   |  | NA      |
|                          | Methods and means of adjustment; reference to installation instructions .....                               |  | NA      |
| 1.7.5                    | Power outlets on the equipment .....  |  | NA      |
| 1.7.6                    | Fuse identification (marking, special fusing characteristics, cross-reference) .....                        | T1,6 AL/250VAC   | P       |
| 1.7.7                    | Wiring terminals  |  | P       |
| 1.7.7.1                  | Protective earthing and bonding terminals .....   | Protective earthing terminal and symbol on the rear of the chassis                                 | P       |



| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test                         | Result – Remark   | Verdict |
| 1.7.7.2                  | Terminal for a.c. mains supply conductors  | Terminals for line and neutral respectively                 | P       |
| 1.7.7.3                  | Terminals for d.c. mains supply conductors |   | NA      |
| 1.7.8                    | Controls and indicators                    |   | P       |
| 1.7.8.1                  | Identification, location and marking ..... |   | P       |
| 1.7.8.2                  | Colours .....                              | Red colour used for alarm                                   | P       |
| 1.7.8.3                  | Symbols according to IEC 60417.....        | Protective earthing conductor, protective bonding conductor | P       |
| 1.7.8.4                  | Markings using figures .....               | No marking using figures                                    | NA      |
| 1.7.9                    | Isolation of multiple power sources .....  |   | NA      |
| 1.7.10                   | Thermostats and other regulating devices   |   | NA      |
| 1.7.11                   | Durability                                 | See table 1.7.11  | P       |
| 1.7.12                   | Removable parts                            | No marking on removable parts                               | P       |
| 1.7.13                   | Replaceable batteries                      |   | NA      |
|                          | Language(s)                                |   | —       |
| 1.7.14                   | Equipment for restricted access locations  |   | NA      |

|         |  |   |    |
|---------|--|---|----|
| 2       | PROTECTION FROM HAZARDS  |   | P  |
| 2.1     | Protection from electric shock and energy hazards  |   | P  |
| 2.1.1   | Protection in operator access areas  | Operator access areas are the outer parts of EUT. Access to inner parts of EUT only for service persons | P  |
| 2.1.1.1 | Access to energized parts  | Operators have no access to inner parts of EUT.   | P  |
|         | Test by inspection .....   |   | P  |
|         | Test with test finger .....  |   | NA |
|         | Test with test pin .....   |   | NA |
|         | Test with test probe .....   |   | NA |
| 2.1.1.2 | Battery compartments .....   |   | NA |
| 2.1.1.3 | Access to ELV wiring   | No operator access to the inside of EUT   | NA |
|         | Working voltage (V <sub>peak</sub> or V <sub>rms</sub> ); minimum distance (mm) through insulation |   | —  |
| 2.1.1.4 | Access to hazardous voltage circuit wiring   | Hazardous voltage circuit wiring on mains power cable only.   | P  |
| 2.1.1.5 | Energy hazards .....   | No energy hazards in operator access area   | NA |
| 2.1.1.6 | Manual controls  | No energy hazards in operator access area   | NA |

| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test                                     | Result – Remark   | Verdict |
| 2.1.1.7                  | Discharge of capacitors in equipment                   |   | P       |
|                          | Time-constant (s); measured voltage (V).....:          | 0 Vp after 100 ms   | —       |
| 2.1.1.8                  | Energy hazards – d.c. mains supply                     | EUT not supplied from d.c. mains supply   | NA      |
|                          | a) Capacitor connected to the d.c. mains supply :      |   | NA      |
|                          | b) Internal battery connected to the d.c. mains supply |   | NA      |
| 2.1.1.9                  | Audio amplifiers in information technology equipment   |   | NA      |
| 2.1.2                    | Protection in service access areas                     | EUT to be disconnected before service and incorporates no bare parts at hazardous voltages in service access areas.<br><br>Unintentional bridging by conductive materials considered unlikely during service operations | P       |
| 2.1.3                    | Protection in restricted access locations              | EUT not to be installed in restricted access locations  | NA      |

|       |   |                                    |   |
|-------|---|------------------------------------|---|
| 2.2   | SELV circuits                                       |                                    | P |
| 2.2.1 | General requirements                                | Separate approved. See table 1.5.1 | P |
| 2.2.2 | Voltages under normal conditions (V).....:          |                                    | P |
| 2.2.3 | Voltages under fault conditions (V).....:           |                                    | P |
| 2.2.4 | Connection of SELV circuits to other circuits.....: |                                    | P |

|         |  |                     |    |
|---------|--|---------------------|----|
| 2.3     | TNV circuits   |                     | NA |
| 2.3.1   | Limits   | No TNV circuit used | NA |
|         | Type of TNV circuits.....:                               |                     | —  |
| 2.3.2   | Separation from other circuits and from accessible parts |                     | NA |
| 2.3.2.1 | General requirement                                      |                     | NA |
| 2.3.2.2 | Protection by basic insulation                           |                     | NA |
| 2.3.2.3 | Protection by earthing                                   |                     | NA |
| 2.3.2.4 | Protection by other constructions                        |                     | NA |
| 2.3.3   | Separation from hazardous voltages                       |                     | NA |
|         | Insulation employed.....:                                |                     | —  |
| 2.3.4   | Connection of TNV circuits to other circuits             |                     | NA |
|         | Insulation employed.....:                                |                     | —  |

| IEC 60950-1 / EN 60950-1 |  |                 |         |
|--------------------------|--|-----------------|---------|
| Clause                   | Requirement – Test                               | Result – Remark | Verdict |
| 2.3.5                    | Test for operating voltages generated externally |                 | NA      |

|       |  |                                  |    |
|-------|--|----------------------------------|----|
| 2.4   | Limited current circuits                                 |                                  | NA |
| 2.4.1 | General requirements                                     | No limited current circuits used | NA |
| 2.4.2 | Limit values   |                                  | NA |
|       | Frequency (Hz).....:                                     |                                  | —  |
|       | Measured current (mA).....:                              |                                  | —  |
|       | Measured voltage (V).....:                               |                                  | —  |
|       | Measured circuit capacitance (nF or $\mu$ F).....:       |                                  | —  |
| 2.4.3 | Connection of limited current circuits to other circuits |                                  | NA |

|     |  |                               |    |
|-----|--|-------------------------------|----|
| 2.5 | Limited power sources  |                               | NA |
|     | a) Inherently limited output   | No limited power sources used | NA |
|     | b) Impedance limited output  |                               | NA |
|     | c) Regulating network limited output under normal operating and single fault condition |                               | NA |
|     | d) Overcurrent protective device limited output  |                               | NA |
|     | Max. output voltage (V), max. output current (A), max. apparent power (VA)             |                               | —  |
|     | Current rating of overcurrent protective device (A)                                    |                               | —  |

|         |  |   |    |
|---------|--|---|----|
| 2.6     | Provisions for earthing and bonding                            |   | P  |
| 2.6.1   | Protective earthing  | EUT chassis connected to protective earth   | P  |
| 2.6.2   | Functional earthing  |   | NA |
| 2.6.3   | Protective earthing and protective bonding conductors          | Protective earthing conductor from EUT to protective earth has same current-carrying capacity as the line and neutral wires | P  |
| 2.6.3.1 | General  |   | P  |
| 2.6.3.2 | Size of protective earthing conductors                         |   | P  |
|         | Rated current (A), cross-sectional area ( $\text{mm}^2$ ), AWG | EUT rated 90 VA. Requirement according to table 3B: $0.75 \text{ mm}^2$   | —  |
| 2.6.3.3 | Size of protective bonding conductors                          |   | P  |
|         | Rated current (A), cross-sectional area ( $\text{mm}^2$ ), AWG | EUT rated 90 VA. Requirement according to table 3B: $0.75 \text{ mm}^2$   | —  |

| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test   | Result – Remark   | Verdict |
|                          | Protective current rating (A), cross-sectional area (mm <sup>2</sup> ), AWG  |   | -       |
| 2.6.3.4                  | Resistance of earthing conductors and their terminations, resistance (Ω), voltage drop (V), test current (A), duration (min) | Chassis: 25mohm @ 25A, 1 min<br>PE-connection:<br>21mohm @ 25A, 1 min<br>Power supply chassis: 22mohm @25A, 1 min | P       |
| 2.6.3.5                  | Colour of insulation   | Green/Yellow  | P       |
| 2.6.4                    | Terminals  |   | P       |
| 2.6.4.1                  | General  |   | P       |
| 2.6.4.2                  | Protective earthing and bonding terminals  | EUT incorporates both earthing and bonding terminals  | P       |
|                          | Rated current (A), type, nominal thread diameter (mm)  | EUT rated 90 VA. Requirement according to table 3B: 0.75 mm <sup>2</sup>  | —       |
| 2.6.4.3                  | Separation of the protective earthing conductor from protective bonding conductors   |   | P       |
| 2.6.5                    | Integrity of protective earthing   |   | P       |
| 2.6.5.1                  | Interconnection of equipment   | No power output provided  | NA      |
| 2.6.5.2                  | Components in protective earthing conductors and protective bonding conductors   | No components in protective earthing conductor  | P       |
| 2.6.5.3                  | Disconnection of protective earth  |   | P       |
| 2.6.5.4                  | Parts that can be removed by an operator   |   | P       |
| 2.6.5.5                  | Parts removed during servicing   |   | P       |
| 2.6.5.6                  | Corrosion resistance   |   | P       |
| 2.6.5.7                  | Screws for protective bonding  | 4 mm screw used   | P       |
| 2.6.5.8                  | Reliance on telecommunication network or cable distribution system   | Protective earthing of EUT not relying on telecommunication network or cable distribution system                  | NA      |

|       |  |   |    |
|-------|--|---|----|
| 2.7   | Overcurrent and earth fault protection in primary circuits   |   | P  |
| 2.7.1 | Basic requirements   | EUT is provided with a fuse in the input on the power inlet.<br>Fuse placed in the line | P  |
|       | Instructions when protection relies on building installation | Protection does not rely on building installation                                       | NA |
| 2.7.2 | Faults not simulated in 5.3.7                                | See table 1.5.1 and fire enclosure used   | P  |
| 2.7.3 | Short-circuit backup protection                              | Backup protection in building installation.<br>Fuse has high-breaking capacity          | P  |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test                              | Result – Remark  | Verdict |
| 2.7.4                    | Number and location of protective devices ..... | A fuse, in the line conductor.<br>Line and neutral reliably identified when EUT is installed | P       |
| 2.7.5                    | Protection by several devices                   |  | NA      |
| 2.7.6                    | Warning to service personnel.....               |  | NA      |

|         |   |                         |     |
|---------|---|-------------------------|-----|
| 2.8     | Safety interlocks   |                         | NA  |
| 2.8.1   | General principles  | Interlocks not required | NA  |
| 2.8.2   | Protection requirements   |                         | NA  |
| 2.8.3   | Inadvertent reactivation  |                         | NA  |
| 2.8.4   | Fail-safe operation   |                         | NA  |
| 2.8.5   | Moving parts  |                         | NA  |
| 2.8.6   | Overriding  |                         | NA  |
| 2.8.7   | Switches, relays and their related circuits                       |                         | NA  |
| 2.8.7.1 | Separation distances for contact gaps and their related circuits: |                         | NA  |
| 2.8.7.2 | Overload test   |                         | NA  |
| 2.8.7.3 | Endurance test  |                         | NA  |
| 2.8.7.4 | Electric strength test  |                         | NA  |
| 2.8.8   | Mechanical actuators  |                         | N/A |

|       |                                    |   |    |
|-------|------------------------------------|---|----|
| 2.9   | Electrical insulation              |   | P  |
| 2.9.1 | Properties of insulating materials |   | P  |
| 2.9.2 | Humidity conditioning              |   | NA |
|       | Humidity (%), Temperature (°C)     |   | —  |
| 2.9.3 | Grade of insulation                | Reinforced or double insulation between primary and secondary.<br>Basic insulation between primary and protective earth | P  |
| 2.9.4 | Separation from hazardous voltages |   | P  |
|       | Method(s) used                     | Method 1 a)   | —  |

|          |   |                         |   |
|----------|---|-------------------------|---|
| 2.10     | Clearances, creepage distances and distances through insulation |                         | P |
| 2.10.1   | General   |                         | P |
| 2.10.1.1 | Frequency   |                         | P |
| 2.10.1.2 | Pollution degrees   | Pollution degree 2 used | P |
| 2.10.1.3 | Reduced values for functional insulation                        |                         | P |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test                                | Result – Remark  | Verdict |
| 2.10.1.4                 | Intervening unconnected conductive parts          | Insulation of transformers separate approved. See table 1.5.1  | P       |
| 2.10.1.5                 | Insulation with varying dimensions                |  | NA      |
| 2.10.1.6                 | Special separation requirements                   | Relevant only for products with TNV  | NA      |
| 2.10.1.7                 | Insulation in circuits generating starting pulses |  | NA      |
| 2.10.2                   | Determination of working voltage                  | See table 1.5.1. Secondary voltage is SELV   | P       |
| 2.10.2.1                 | General   |  | P       |
| 2.10.2.2                 | RMS working voltage                               | See table 1.5.1. Secondary voltage is SELV   | P       |
| 2.10.2.3                 | Peak working voltage                              | See table 1.5.1. Secondary voltage is SELV   | P       |
| 2.10.3                   | Clearances  |  | P       |
| 2.10.3.1                 | General   | EUT to be used up to 2000 m above sea level.<br>EUT to be used in Overvoltage Category II  | P       |
| 2.10.3.2                 | Mains transient voltages                          |  | P       |
|                          | a) AC mains supply .....                          | EUT to be used in Overvoltage Category II  | P       |
|                          | b) Earthed d.c. mains supplies .....              |  | NA      |
|                          | c) Unearthed d.c. mains supplies .....            |  | NA      |
|                          | d) Battery operation .....                        | Applicable only to products being supplied from a dedicated battery that has no provision for charging from an external mains supply   | NA      |
| 2.10.3.3                 | Clearances in primary circuits                    | See table 1.5.1.   | P       |
| 2.10.3.4                 | Clearances in secondary circuits                  | Requirements deemed to be fulfilled without measurement.<br>Max voltage in secondary circuit: < 71 V <sub>peak</sub>   | P       |
| 2.10.3.5                 | Clearances in circuits having starting pulses     |  | NA      |
| 2.10.3.6                 | Transients from a.c. mains supply .....           | EUT deemed to fulfill the requirements without test.<br>Transients on AC mains deemed to be suppressed in the primary circuit of EUT and not be transmitted to the secondary | P       |
| 2.10.3.7                 | Transients from d.c. mains supply .....           |  | NA      |

| IEC 60950-1 / EN 60950-1 |   |   |         |
|--------------------------|---|---|---------|
| Clause                   | Requirement – Test  | Result – Remark   | Verdict |
| 2.10.3.8                 | Transients from telecommunication networks and cable distribution systems ..... |   | NA      |
| 2.10.3.9                 | Measurement of transient voltage levels   |   | NA      |
|                          | a) Transients from a mains supply   |   | NA      |
|                          | For an a.c. mains supply .....  |   | NA      |
|                          | For a d.c. mains supply .....   |   | NA      |
|                          | b) Transients from a telecommunication network :                                |   | NA      |
| 2.10.4                   | Creepage distances  |   | P       |
| 2.10.4.1                 | General   |   | P       |
| 2.10.4.2                 | Material group and comparative tracking index                                   |   | P       |
|                          | CTI tests.....  | Material group IIIb is assumed to be used   | —       |
| 2.10.4.3                 | Minimum creepage distances  | Only applicable to main power supply. See table 1.5.1   | —       |
| 2.10.5                   | Solid insulation  | Printed circuit boards are solid insulation.<br><br>Solid insulation on wires and in transformers and in plastic spacer between screws and PCB in power supply module | P       |
| 2.10.5.1                 | General   |   | P       |
| 2.10.5.2                 | Distances through insulation  | No requirements for functional and basic insulation.<br>See appended table 1.5.1  | P       |
| 2.10.5.3                 | Insulating compound as solid insulation   | Insulating compound used as solid insulation in previously approved components only.<br>See appended table 1.5.1  | P       |
| 2.10.5.4                 | Semiconductor devices   | Optocouplers are previously approved components.<br>See appended table 1.5.1  | P       |
| 2.10.5.5                 | Cemented joints   | EUT incorporates no cemented joints   | NA      |
| 2.10.5.6                 | Thin sheet material – General   | Thin sheet material used on wires in transformers.<br>See appended table 1.5.1.<br><br>The thin sheet material used to fulfills the requirements                      | P       |
| 2.10.5.7                 | Separable thin sheet material   | No separable thin sheet materials used in EUT   | NA      |
|                          | Number of layers (pcs).....   |   | —       |
| 2.10.5.8                 | Non-separable thin sheet material   | See appended table 1.5.1  | P       |



| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test   | Result – Remark   | Verdict |
| 2.10.5.9                 | Thin sheet material – standard test procedure                                |   | P       |
|                          | Electric strength test   |   | —       |
| 2.10.5.10                | Thin sheet material – alternative test procedure                             |   | P       |
|                          | Electric strength test   |   | —       |
| 2.10.5.11                | Insulation in wound components   | See appended table 1.5.1  | P       |
| 2.10.5.12                | Wire in wound components   | See appended table 1.5.1  | P       |
|                          | Working voltage .....  | Working voltage exceed 71 V   | P       |
|                          | a) Basic insulation not under stress .....                                   | See appended table 1.5.1  | P       |
|                          | b) Basic, supplementary, reinforced insulation :                             | See appended table 1.5.1  | P       |
|                          | c) Compliance with Annex U .....   |   | P       |
|                          | Two wires in contact inside wound component; angle between 45° and 90° ..... |   | P       |
| 2.10.5.13                | Wire with solvent-based enamel in wound components                           | Applicable only to TNV circuits   | NA      |
|                          | Electric strength test   |   | —       |
|                          | Routine test   |   | NA      |
| 2.10.5.14                | Additional insulation in wound components                                    | See appended table 1.5.1  | P       |
|                          | Working voltage .....  | Working voltage exceeds 71 V  | P       |
|                          | - Basic insulation not under stress .....                                    | See appended table 1.5.1  | P       |
|                          | - Supplementary, reinforced insulation .....                                 | See appended table 1.5.1  | P       |
| 2.10.6                   | Construction of printed boards   |   | P       |
| 2.10.6.1                 | Uncoated printed boards  | See appended table 1.5.1  | P       |
| 2.10.6.2                 | Coated printed boards  | EUT incorporates no printed boards that are coated in the standard's meaning of “coated”          | NA      |
| 2.10.6.3                 | Insulation between conductors on the same inner surface of a printed board   | PCB in power supply having hazardous voltage only.<br>PCB is not multi-layer but single layer PCB | NA      |
| 2.10.6.4                 | Insulation between conductors on different layers of a printed board         | PCB in power supply having hazardous voltage only.<br>PCB is not multi-layer but single layer PCB | NA      |
|                          | Distance through insulation  |   | NA      |
|                          | Number of insulation layers (pcs).....                                       |   | NA      |
| 2.10.7                   | Component external terminations  | Coating not used to increase clearances and creepage distances                                    | NA      |
| 2.10.8                   | Tests on coated printed boards and coated components                         |   | NA      |

| IEC 60950-1 / EN 60950-1 |   |   |         |
|--------------------------|---|---|---------|
| Clause                   | Requirement – Test  | Result – Remark                                     | Verdict |
| 2.10.8.1                 | Sample preparation and preliminary inspection                   |   | NA      |
| 2.10.8.2                 | Thermal conditioning  |   | NA      |
| 2.10.8.3                 | Electric strength test  |   | NA      |
| 2.10.8.4                 | Abrasion resistance test  |   | NA      |
| 2.10.9                   | Thermal cycling   |   | NA      |
| 2.10.10                  | Test for Pollution Degree 1 environment and insulating compound | EUT designed for pollution degree 2 environment     | NA      |
| 2.10.11                  | Tests for semiconductor devices and cemented joints             | See appended table 1.5.1                            | P       |
| 2.10.12                  | Enclosed and sealed parts                                       | Hermetic sealed components are previously certified | P       |

|        |  |  |   |
|--------|--|--|---|
| 3      | WIRING, CONNECTIONS AND SUPPLY                 |  |   |
| 3.1    | General  |  | P |
| 3.1.1  | Current rating and overcurrent protection      |  | P |
| 3.1.2  | Protection against mechanical damage           | Wireways are smooth and free from sharp edges  | P |
| 3.1.3  | Securing of internal wiring                    | Inside EUT the wiring are run smoothly   | P |
| 3.1.4  | Insulation of conductors                       |  | P |
| 3.1.5  | Beads and ceramic insulators                   | See appended table 1.5.1   | P |
| 3.1.6  | Screws for electrical contact pressure         | Screws engage min. two threads into a metal part   | P |
| 3.1.7  | Insulating materials in electrical connections | Connection to protective earth by means of a nut engaged with more than two threads.       | P |
| 3.1.8  | Self-tapping and spaced thread screws          | Self-tapping screws not used   | P |
| 3.1.9  | Termination of conductors                      |  | P |
|        | 10 N pull test                                 | 230 VAC conductors and PE-conductor subjected to 10 N pull test                            | P |
| 3.1.10 | Sleeving on wiring                             | Sleeving on wires in transformers, retained in position by other means (tape, or the like) | P |

|         |                                    |                                   |    |
|---------|------------------------------------|-----------------------------------|----|
| 3.2     | Connection to a mains supply       |                                   | P  |
| 3.2.1   | Means of connection .....          |                                   | P  |
| 3.2.1.1 | Connection to an a.c. mains supply | EUT equipped with appliance inlet | P  |
| 3.2.1.2 | Connection to a d.c. mains supply  |                                   | NA |

| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test   | Result – Remark   | Verdict |
| 3.2.2                    | Multiple supply connections  |   | NA      |
| 3.2.3                    | Permanently connected equipment                                      |   | NA      |
|                          | Number of conductors, diameter (mm) of cable and conduits .....      | Mains cable having three conductors.  | —       |
| 3.2.4                    | Appliance inlets   | See appended table 1.5.1  | P       |
| 3.2.5                    | Power supply cords   | Power supply cord specified in installation manual  | P       |
| 3.2.5.1                  | AC power supply cords  | Power supply cord specified in installation manual  | P       |
|                          | Type.....  |   | —       |
|                          | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG..... |   | —       |
| 3.2.5.2                  | DC power supply cords  |   | NA      |
| 3.2.6                    | Cord anchorages and strain relief                                    | EUT not provided with a non-detachable power supply cord.   | NA      |
|                          | Mass of equipment (kg), pull (N) .....                               |   | —       |
|                          | Longitudinal displacement (mm) .....                                 |   | —       |
| 3.2.7                    | Protection against mechanical damage                                 | Power cord not subjected to sharp points or cutting edges   | P       |
| 3.2.8                    | Cord guards  | Requirements applicable only to products having a non-detachable power supply cord and being hand-held or intended to be moved while in operation | NA      |
|                          | Diameter or minor dimension D (mm); test mass (g) .....              |   | —       |
|                          | Radius of curvature of cord (mm).....                                |   | —       |
| 3.2.9                    | Supply wiring space  | Mains supply conductors easily introduced and connected.<br><br>Conductors unlikely to become free from their terminals.                          | P       |

|       |  |   |    |
|-------|--|---|----|
| 3.3   | Wiring terminals for connection of external conductors |   | P  |
| 3.3.1 | Wiring terminals                                       | EUT provided with terminals in which connection is made by effective devices                          | P  |
| 3.3.2 | Connection of non-detachable power supply cords        | Requirements applicable only to products having special non-detachable power supply                   | NA |
| 3.3.3 | Screw terminals  | Protective earth is clamped by means of a nut.<br>Other screw terminals refer to appended table 1.5.1 | P  |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test  | Result – Remark  | Verdict |
| 3.3.4                    | Conductor sizes to be connected   | AC mains input wires used:<br>0.75 mm <sup>2</sup>   | P       |
|                          | Rated current (A), cord/cable type, cross-sectional area (mm <sup>2</sup> ).....: | Mains input cables:<br>Up to 1.6 A   | —       |
| 3.3.5                    | Wiring terminal sizes   | Protective earth and mains supply conductors clamped by means of a nut on a stud with a diameter > 3 mm  | P       |
|                          | Rated current (A), type and nominal thread diameter (mm) .....                    |  | —       |
| 3.3.6                    | Wiring terminals design   | Wiring terminals for mains cables previously certified terminals. See appended table 1.5.1   | P       |
| 3.3.7                    | Grouping of wiring terminals  | AC mains supply terminals located close to each other. Protective earthing terminal at the rear of the enclosure.  | P       |
| 3.3.8                    | Stranded wire   | Terminals located so that an escaping strand of a flexible conductor is unlikely to make accidental contact to accessible conductive parts.<br><br>No soldering at places where the conductor is subjected to contact pressure | P       |

|       |   |  |    |
|-------|---|--|----|
| 3.4   | Disconnection from the mains supply               |  | P  |
| 3.4.1 | General requirement                               |  | P  |
| 3.4.2 | Disconnect devices                                | EUT disconnect at the main supply plug   | P  |
| 3.4.3 | Permanently connected equipment                   | External disconnect device prescribed in installation instructions                 | NA |
| 3.4.4 | Parts which remain energized                      |  | NA |
| 3.4.5 | Switches in flexible cords                        | No switch in flexible cords  | P  |
| 3.4.6 | Number of poles - single-phase and d.c. equipment | Applicable only to products with a disconnect device provided as a part of the EUT | NA |
| 3.4.7 | Number of poles - three-phase equipment           |  | NA |
| 3.4.8 | Switches as disconnect devices                    | Applicable only to products with a disconnect device provided as a part of the EUT | NA |

| IEC 60950-1 / EN 60950-1 |                             |   |         |
|--------------------------|-----------------------------|---|---------|
| Clause                   | Requirement – Test          | Result – Remark   | Verdict |
| 3.4.9                    | Plugs as disconnect devices | Description for safe operation included in the instruction manual | P       |
| 3.4.10                   | Interconnected equipment    | EUT not part of interconnected equipment                          | NA      |
| 3.4.11                   | Multiple power sources      |   | NA      |

|       |  |   |    |
|-------|--|---|----|
| 3.5   | Interconnection of equipment             |   | P  |
| 3.5.1 | General requirements                     | EUT intended to be connected to other equipment | P  |
| 3.5.2 | Types of interconnection circuits.....:  | Power supply is considered SELV circuit         | P  |
| 3.5.3 | ELV circuits as interconnection circuits |   | NA |
| 3.5.4 | Data ports for additional equipment      | Max. power supply output is 8 A                 | P  |

|     |                       |                   |    |
|-----|-----------------------|-------------------|----|
| 4   | PHYSICAL REQUIREMENTS |                   | P  |
| 4.1 | Stability             |                   | P  |
|     | Angle of 10°          | Tested            | P  |
|     | Test: force (N).....: | Not floorstanding | NA |

|       |                          |  |    |
|-------|--------------------------|--|----|
| 4.2   | Mechanical strength      |  | P  |
| 4.2.1 | General                  |  | P  |
| 4.2.2 | Steady force test, 10 N  | Tested by inspection. Metal enclosure  | P  |
| 4.2.3 | Steady force test, 30 N  | Applicable only to parts of an enclosure located in an operator access area protected by a cover or door   | NA |
| 4.2.4 | Steady force test, 250 N | Fan not withstanding 250 N – giving test finger access to internal parts. Min. 4 mm distance is worst case measured from test finger to live parts at power inlet filter | P  |
| 4.2.5 | Impact test              | EUT checked by inspection<br>Enclosure made of 2 mm aluminium  | P  |
|       | Fall test                | EUT checked by inspection<br>Enclosure made of 2 mm aluminium  | P  |

| IEC 60950-1 / EN 60950-1 |  |  |         |
|--------------------------|--|--|---------|
| Clause                   | Requirement – Test                               | Result – Remark  | Verdict |
|                          | Swing test                                       | EUT checked by inspection<br>Enclosure made of 2 mm aluminium  | P       |
| 4.2.6                    | Drop test; height (mm) .....                     |  | NA      |
| 4.2.7                    | Stress relief test                               |  | NA      |
| 4.2.8                    | Cathode ray tubes                                |  | NA      |
|                          | Picture tube separately certified.....           |  | NA      |
| 4.2.9                    | High pressure lamps                              |  | NA      |
| 4.2.10                   | Wall or ceiling mounted equipment; force (N) . : | EUT checked by inspection.<br>Enclosure made of 2 mm aluminium | P       |
| 4.2.11                   | Rotating solid media                             |  | NA      |

|       |  |   |    |
|-------|--|---|----|
| 4.3   | Design and construction                                |   | P  |
| 4.3.1 | Edges and corners                                      |   | P  |
| 4.3.2 | Handles and manual controls; force (N).....            | EUT checked by inspection.<br>Rack handles subjected to 50 N testing  | P  |
| 4.3.3 | Adjustable controls                                    | Change in settings only by service personnel.<br>Settings only accessible by opening the box with a tool                | P  |
| 4.3.4 | Securing of parts                                      |   | P  |
| 4.3.5 | Connection by plugs and sockets                        | Plugs and sockets employed only in a manner unlikely to create a hazard   | P  |
| 4.3.6 | Direct plug-in equipment                               |   | NA |
|       | Torque .....   |   | -  |
|       | Compliance with the relevant mains plug standard ..... |   | NA |
| 4.3.7 | Heating elements in earthed equipment                  |   | NA |
| 4.3.8 | Batteries  | Batteries not operator-replaceable  | P  |
|       | - Overcharging of a rechargeable battery               | Any leaks, explosion or emission of flames from a battery will be completely contained in the cabinet. No test required | NA |
|       | - Unintentional charging of a non-rechargeable battery | do.   | NA |
|       | - Reverse charging of a rechargeable battery           | do.   | NA |
|       | - Excessive discharging rate for any battery           | do.   | NA |
| 4.3.9 | Oil and grease   |   | NA |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test  | Result – Remark  | Verdict |
| 4.3.10                   | Dust, powders, liquids and gases  |  | NA      |
| 4.3.11                   | Containers for liquids or gases   |  | NA      |
| 4.3.12                   | Flammable liquids.....:   |  | NA      |
|                          | Quantity of liquid (l).....:  |  | NA      |
|                          | Flash point (°C).....:  |  | NA      |
| 4.3.13                   | Radiation   | EUT so designed that there is no risk of harmful effects of radiation  | P       |
| 4.3.13.1                 | General   | EUT not generating ionizing radiation  | NA      |
| 4.3.13.2                 | Ionizing radiation  |  | NA      |
|                          | Measured radiation (pA/kg) .....  |  | —       |
|                          | Measured high-voltage (kV) .....  |  | —       |
|                          | Measured focus voltage (kV) .....                                       |  | —       |
|                          | CRT markings .....  |  | —       |
| 4.3.13.3                 | Effect of ultraviolet (UV) radiation on materials                       |  | NA      |
|                          | Part, property, retention after test, flammability classification ..... |  | NA      |
| 4.3.13.4                 | Human exposure to ultraviolet (UV) radiation . :                        |  | NA      |
| 4.3.13.5                 | Lasers (including laser diodes) and LEDs                                | All diodes are inherently Class I laser products.<br>Laser labelling not required  | P       |
| 4.3.13.5.1               | Lasers (including laser diodes)   | EUT not incorporating lasers or laser diodes   | NA      |
|                          | Laser class .....   |  | —       |
| 4.3.13.5.2               | Light emitting diodes (LEDs)  | EUT not incorporating LEDs that produce optical radiation in excess of the limits specified in IEC 62471 in the wavelength range 200 to 3000 nm. | —       |
| 4.3.13.6                 | Other types .....   |  | NA      |

|         |   |   |    |
|---------|---|---|----|
| 4.4     | Protection against hazardous moving parts |   | P  |
| 4.4.1   | General                                   | EUT incorporating a low-voltage fan         | P  |
| 4.4.2   | Protection in operator access areas       | No access to moving parts using test finger | P  |
| 4.4.3   | Protection in restricted access locations |   | NA |
| 4.4.4   | Protection in service access areas        |   | NA |
| 4.4.5   | Protection against moving fan blades      | Test finger can't touch fan blade           | NA |
| 4.4.5.1 | General                                   |   | NA |



| IEC 60950-1 / EN 60950-1 |                                |                 |         |
|--------------------------|--------------------------------|-----------------|---------|
| Clause                   | Requirement – Test             | Result – Remark | Verdict |
| 4.4.5.2                  | Protection for users           |                 | NA      |
| 4.4.5.3                  | Protection for service persons |                 | NA      |

|       |   |   |   |
|-------|---|---|---|
| 4.5   | Thermal requirements                    |   | P |
| 4.5.1 | General                                 |   | P |
| 4.5.2 | Temperature tests                       |   | P |
|       | Normal load condition per Annex L ..... |   | — |
| 4.5.3 | Temperature limits for materials        | See appended table 4.5  | P |
| 4.5.4 | Touch temperature limits                | See appended table 4.5  | P |
| 4.5.5 | Resistance to abnormal heat .....       | Parts at hazardous voltage mounted on thermoplastic parts. See appended table 1.5.1 | P |

|         |  |   |    |
|---------|--|---|----|
| 4.6     | Openings in enclosures                         |   | P  |
| 4.6.1   | Top and side openings                          | Opening unlikely to create hazard                           | P  |
|         | Dimensions (mm) .....                          |   | —  |
| 4.6.2   | Bottoms of fire enclosures                     | Openings in bottom <40mm <sup>2</sup> under V-1 materials   | P  |
|         | Construction of the bottom, dimensions (mm)... |   | —  |
| 4.6.3   | Doors or covers in fire enclosures             | EUT incorporates no door leading to an operator access area | NA |
| 4.6.4   | Openings in transportable equipment            |   | NA |
| 4.6.4.1 | Constructional design measures                 |   | NA |
|         | Dimensions (mm) .....                          |   | —  |
| 4.6.4.2 | Evaluation measures for larger openings        |   | NA |
| 4.6.4.3 | Use of metallized parts                        | No metallized parts   | NA |
| 4.6.5   | Adhesives for constructional purposes          | No adhesives used for constructional purposes               | NA |
|         | Conditioning temperature (°C)/time (weeks).... |   | —  |

|       |  |  |    |
|-------|--|--|----|
| 4.7   | Resistance to fire   |  | P  |
| 4.7.1 | Reducing the risk of ignition and spread of flame                      | Aluminium enclosure used and no flammability test required | P  |
|       | Method 1, selection and application of components wiring and materials | See appended table 4.7                                     | P  |
|       | Method 2, application of all of simulated fault condition tests        |  | NA |

| IEC 60950-1 / EN 60950-1 |  |   |         |
|--------------------------|--|---|---------|
| Clause                   | Requirement – Test   | Result – Remark   | Verdict |
| 4.7.2                    | Conditions for a fire enclosure                                  | A fire enclosure is required  | P       |
| 4.7.2.1                  | Parts requiring a fire enclosure                                 |   | P       |
| 4.7.2.2                  | Parts not requiring a fire enclosure                             |   | NA      |
| 4.7.3                    | Materials  |   | P       |
| 4.7.3.1                  | General  |   | P       |
| 4.7.3.2                  | Materials for fire enclosures                                    | Fire enclosure made of aluminium  | P       |
| 4.7.3.3                  | Materials for components and other parts outside fire enclosures | Decorative parts made of HB75 materials   | P       |
| 4.7.3.4                  | Materials for components and other parts inside fire enclosures  | Power supply connectors (230V, 5 & 12 V) are made of material with 94V-2 flammability rating.<br>See appended table 1.5.1 | P       |
| 4.7.3.5                  | Materials for air filter assemblies                              |   | NA      |
| 4.7.3.6                  | Materials used in high-voltage components                        |   | NA      |

|         |   |   |    |
|---------|---|---|----|
| 5       | ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS |   |    |
| 5.1     | Touch current and protective conductor current            |   |    |
| 5.1.1   | General   |   | P  |
| 5.1.2   | Configuration of equipment under test (EUT)               |   | P  |
| 5.1.2.1 | Single connection to an a.c. mains supply                 |   | P  |
| 5.1.2.2 | Redundant multiple connections to an a.c. mains supply    |   | NA |
| 5.1.2.3 | Simultaneous multiple connections to an a.c. mains supply |   | NA |
| 5.1.3   | Test circuit  |   | P  |
| 5.1.4   | Application of measuring instrument                       | Measuring instrument according to annex D.1 | P  |
| 5.1.5   | Test procedure  |   | P  |
| 5.1.6   | Test measurements   |   | P  |
|         | Test voltage (V) .....                                    | 450 mV                                      | —  |
|         | Measured touch current (mA) .....                         | 0.9   | —  |
|         | Max. allowed touch current (mA) .....                     | 3.5   | —  |
|         | Measured protective conductor current (mA) . . .          |   | —  |
|         | Max. allowed protective conductor current (mA).....       |   | —  |
| 5.1.7   | Equipment with touch current exceeding 3.5 mA .....       |   | NA |
| 5.1.7.1 | General .....   |   | NA |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test  | Result – Remark  | Verdict |
| 5.1.7.2                  | Simultaneous multiple connections to the supply   |  | NA      |
| 5.1.8                    | Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks | No telecommunication networks and cable distribution systems | NA      |
| 5.1.8.1                  | Limitation of the touch current to a telecommunication network and a cable distribution system                  |  | NA      |
|                          | Test voltage (V) .....  |  | —       |
|                          | Measured touch current (mA) .....   |  | —       |
|                          | Max. allowed touch current (mA) .....   |  | —       |
| 5.1.8.2                  | Summation of touch currents from telecommunication networks.....  |  | NA      |
|                          | a) EUT with earthed telecommunication ports ..  |  | NA      |
|                          | b) EUT whose telecommunication ports have no reference to protective earth                                      |  | NA      |

|       |                   |  |   |
|-------|-------------------|--|---|
| 5.2   | Electric strength |  | P |
| 5.2.1 | General           | See appended table 5.2   | P |
| 5.2.2 | Test procedure    | Test voltages according to table 5B.<br>See appended table 1.5.1 for power supply<br>Test performed with at voltage of 1500 VACrms on power supply inlet | P |

|       |  |  |    |
|-------|--|--|----|
| 5.3   | Abnormal operating and fault conditions            |  | P  |
| 5.3.1 | Protection against overload and abnormal operation | See appended table 5.3   | P  |
| 5.3.2 | Motors   | (see appended Annex B)   | P  |
| 5.3.3 | Transformers                                       | (see appended Annex C)   | P  |
| 5.3.4 | Functional insulation.....                         | Functional insulation on electronic modules except for the power supply module. Considered to fulfil the requirements without test | P  |
| 5.3.5 | Electromechanical components                       |  | NA |
| 5.3.6 | Audio amplifiers in ITE .....                      |  | NA |
| 5.3.7 | Simulation of faults                               | See table 1.5.1 and fire enclosure used  | P  |

| IEC 60950-1 / EN 60950-1 |   |  |         |
|--------------------------|---|--|---------|
| Clause                   | Requirement – Test  | Result – Remark  | Verdict |
| 5.3.8                    | Unattended equipment  | Applicable for products having thermostats, temperature limiters or thermal cut-outs | NA      |
| 5.3.9                    | Compliance criteria for abnormal operating and fault conditions | See table 1.5.1 and fire enclosure used  | P       |
| 5.3.9.1                  | During the tests  |  | P       |
| 5.3.9.2                  | After the tests   |  | P       |

|         |   |                               |    |
|---------|---|-------------------------------|----|
| 6       | CONNECTION TO TELECOMMUNICATION NETWORKS  |                               | P  |
| 6.1     | Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment |                               | NA |
| 6.1.1   | Protection from hazardous voltages  | No connection to TNV-circuits | NA |
| 6.1.2   | Separation of the telecommunication network from earth  |                               | NA |
| 6.1.2.1 | Requirements  |                               | NA |
|         | Test voltage (V) .....  |                               | —  |
|         | Current in the test circuit (mA) .....  |                               | —  |
| 6.1.2.2 | Exclusions.....   |                               | NA |

|         |   |  |    |
|---------|---|--|----|
| 6.2     | Protection of equipment users from overvoltages on telecommunication networks |  | NA |
| 6.2.1   | Separation requirements   |  | NA |
| 6.2.2   | Electric strength test procedure  |  | NA |
| 6.2.2.1 | Impulse test  |  | NA |
| 6.2.2.2 | Steady-state test   |  | NA |
| 6.2.2.3 | Compliance criteria   |  | NA |

|     |  |                   |    |
|-----|--|-------------------|----|
| 6.3 | Protection of the telecommunication wiring system from overheating |                   | NA |
|     | Max. output current (A).....                                       | No power provided | —  |
|     | Current limiting method.....                                       |                   | —  |

|     |   |   |   |
|-----|---|---|---|
| 7   | CONNECTION TO CABLE DISTRIBUTION SYSTEMS  |   | P |
| 7.1 | General   |   | P |
| 7.2 | Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment | Manual states protective earth conductor must be used | P |
| 7.3 | Protection of equipment users from overvoltages on the cable distribution system  | SELV circuit used                                     | P |
| 7.4 | Insulation between primary circuits and cable distribution systems  | SELV circuit used                                     | P |

| IEC 60950-1 / EN 60950-1 |                    |  |         |
|--------------------------|--------------------|--|---------|
| Clause                   | Requirement – Test | Result – Remark  | Verdict |
| 7.4.1                    | General            | Manual states protective earth conductor must be used                      | P       |
| 7.4.2                    | Voltage surge test | No test performed as manual states protective earth conductor must be used | NA      |
| 7.4.3                    | Impulse test       | No test performed as manual states protective earth conductor must be used | NA      |

|       |  |   |    |
|-------|--|---|----|
| A     | ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE   |   | P  |
| A.1   | Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)  |   | NA |
| A.1.1 | Samples.....:  |   | —  |
|       | Wall thickness (mm).....:  |   | —  |
| A.1.2 | Conditioning of samples; temperature (°C).....:  |   | NA |
| A.1.3 | Mounting of samples.....:  |   | NA |
| A.1.4 | Test flame (see IEC 60695-11-3)  |   | NA |
|       | Flame A, B, C or D .....   |   | —  |
| A.1.5 | Test procedure   |   | NA |
| A.1.6 | Compliance criteria  |   | NA |
|       | Sample 1 burning time (s)  |   | —  |
|       | Sample 2 burning time (s)  |   | —  |
|       | Sample 3 burning time (s)  |   | —  |
| A.2   | Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4) |   | P  |
| A.2.1 | Samples, material.....:  | Aluminium, therefore no flammability test performed | —  |
|       | Wall thickness (mm).....:  | 2 mm  | —  |
| A.2.2 | Conditioning of samples  |   | NA |
| A.2.3 | Mounting of samples .....  |   | NA |
| A.2.4 | Test flame (see IEC 60695-11-4)  |   | NA |
|       | Flame A, B or C .....  |   | —  |
| A.2.5 | Test procedure   |   | NA |
| A.2.6 | Compliance criteria  |   | NA |
|       | Sample 1 burning time (s)  |   | —  |
|       | Sample 2 burning time (s)  |   | —  |
|       | Sample 3 burning time (s)  |   | —  |
| A.2.7 | Alternative test acc. to IEC 60695-2-2, cl. 4 and 8  |   | NA |

| IEC 60950-1 / EN 60950-1 |                                  |                 |         |
|--------------------------|----------------------------------|-----------------|---------|
| Clause                   | Requirement – Test               | Result – Remark | Verdict |
|                          | Sample 1 burning time (s)        |                 | —       |
|                          | Sample 2 burning time (s)        |                 | —       |
|                          | Sample 3 burning time (s)        |                 | —       |
| A.3                      | Hot flaming oil test (see 4.6.2) |                 | NA      |
| A.3.1                    | Mounting of samples              |                 | NA      |
| A.3.2                    | Test procedure                   |                 | NA      |
| A.3.3                    | Compliance criterion             |                 | NA      |

|       |  |   |    |
|-------|--|---|----|
| B     | ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2) |   | NA |
| B.1   | General requirements   | Fan separate approved, See appended table 1.5 | NA |
|       | Position .....   |   | —  |
|       | Manufacturer .....   |   | —  |
|       | Type .....   |   | —  |
|       | Rated values .....   |   | —  |
| B.2   | Test conditions  |   | NA |
| B.3   | Maximum temperatures   |   | NA |
| B.4   | Running overload test  |   | NA |
| B.5   | Locked-rotor overload test   |   | NA |
|       | Test duration (days) .....   |   | —  |
|       | Electric strength test: test voltage (V) .....                         |   | —  |
| B.6   | Running overload test for d.c. motors in secondary circuits            |   | NA |
| B.6.1 | General  |   | NA |
| B.6.2 | Test procedure   |   | NA |
| B.6.3 | Alternative test procedure   |   | NA |
| B.6.4 | Electric strength test; test voltage (V) :                             |   | NA |
| B.7   | Locked-rotor overload test for d.c. motors in secondary circuits       |   | NA |
| B.7.1 | Test procedure   |   | NA |
| B.7.2 | Alternative test procedure; test time (h).....:                        |   | NA |
| B.7.3 | Electric strength test   |   | NA |
| B.7.4 | Electric strength test; test voltage (V) .....                         |   | NA |
| B.8   | Test for motors with capacitors  |   | NA |
| B.9   | Test for three-phase motors  |   | NA |
| B.10  | Test for series motors   |   | NA |
|       | Operating voltage (V) .....  |   | —  |

| IEC 60950-1 / EN 60950-1 |   |   |         |
|--------------------------|---|---|---------|
| Clause                   | Requirement – Test  | Result – Remark   | Verdict |
| C                        | ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)                           |   | P       |
|                          | Position .....  | Transformer in power supply separate approved. See appended table 1.5 | —       |
|                          | Manufacturer .....  |   | —       |
|                          | Type .....  |   | —       |
|                          | Rated values .....  |   | —       |
|                          | Method of protection.....   |   | —       |
| C.1                      | Overload test   | See appended table 1.5  | P       |
| C.2                      | Insulation  | See appended table 1.5  | P       |
|                          | Protection from displacement of windings.....                         | See appended table 1.5  | P       |
| D                        | ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)    |   | P       |
| D.1                      | Measuring instrument  | P   | —       |
| D.2                      | Alternative measuring instrument                                      | NA  | —       |
| E                        | ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)                   |   | NA      |
| F                        | ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10)  |   | P       |
| G                        | ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES        |   | NA      |
| G.1                      | Clearances  |   | NA      |
| G.1.1                    | General   |   | NA      |
| G.1.2                    | Summary of the procedure for determining minimum clearances           |   | NA      |
| G.2                      | Determination of mains transient voltage (V)...                       |   | NA      |
| G.2.1                    | AC mains supply .....   |   | NA      |
| G.2.2                    | Earthed d.c. mains supplies .....                                     |   | NA      |
| G.2.3                    | Unearthed d.c. mains supplies .....                                   |   | NA      |
| G.2.4                    | Battery operation .....   |   | NA      |
| G.3                      | Determination of telecommunication network transient voltage (V)..... |   | NA      |
| G.4                      | Determination of required withstand voltage (V).....                  |   | NA      |



| IEC 60950-1 / EN 60950-1 |  |                 |         |
|--------------------------|--|-----------------|---------|
| Clause                   | Requirement – Test                               | Result – Remark | Verdict |
| G.4.1                    | Mains transients and internal repetitive peaks : |                 | NA      |
| G.4.2                    | Transients from telecommunication networks .:    |                 | NA      |
| G.4.3                    | Combination of transients                        |                 | NA      |
| G.4.4                    | Transients from cable distribution systems       |                 | NA      |
| G.5                      | Measurement of transient levels (V).....:        |                 | NA      |
|                          | a) Transients from a mains supply                |                 | NA      |
|                          | For an a.c. mains supply                         |                 | NA      |
|                          | For a d.c. mains supply                          |                 | NA      |
|                          | b) Transients from a telecommunication network   |                 | NA      |
| G.6                      | Determination of minimum clearances.....:        |                 | NA      |

|   |  |    |
|---|--|----|
| H | ANNEX H, IONIZING RADIATION (see 4.3.13) | NA |
|---|--|----|

|   |  |   |
|---|--|---|
| J | ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6) | P |
|   | Metal used .....: Aluminium (Al) and chrome (Cr) used      | — |

|     |   |   |    |
|-----|---|---|----|
| K   | ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.7)             |   | P  |
| K.1 | Making and breaking capacity                                | EUT incorporates no thermostats or temperature limiters                                     | NA |
| K.2 | Thermostat reliability; operating voltage (V).....:         |   | NA |
| K.3 | Thermostat endurance test; operating voltage (V) .....:     |   | NA |
| K.4 | Temperature limiter endurance; operating voltage (V) .....: |   | NA |
| K.5 | Thermal cut-out reliability                                 | Thermal cut-out deemed to fulfil the requirements without test.<br>See appended table 1.5.1 | P  |
| K.6 | Stability of operation                                      | EUT deemed to fulfil the requirements without test  | P  |

|     |   |  |    |
|-----|---|--|----|
| L   | ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.1) |  | P  |
| L.1 | Typewriters   |  | NA |
| L.2 | Adding machines and cash registers  |  | NA |
| L.3 | Erasers   |  | NA |
| L.4 | Pencil sharpeners   |  | NA |
| L.5 | Duplicators and copy machines   |  | NA |

| IEC 60950-1 / EN 60950-1 |                          |                 |         |
|--------------------------|--------------------------|-----------------|---------|
| Clause                   | Requirement – Test       | Result – Remark | Verdict |
| L.6                      | Motor-operated files     |                 | NA      |
| L.7                      | Other business equipment |                 | P       |

|         |   |  |    |
|---------|---|--|----|
| M       | ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)     |  | NA |
| M.1     | Introduction  |  | NA |
| M.2     | Method A  |  | NA |
| M.3     | Method B  |  | NA |
| M.3.1   | Ringing signal  |  | NA |
| M.3.1.1 | Frequency (Hz) .....  |  | —  |
| M.3.1.2 | Voltage (V) .....   |  | —  |
| M.3.1.3 | Cadence; time (s), voltage (V) .....                            |  | —  |
| M.3.1.4 | Single fault current (mA).....                                  |  | —  |
| M.3.2   | Tripping device and monitoring voltage.....                     |  | NA |
| M.3.2.1 | Conditions for use of a tripping device or a monitoring voltage |  | NA |
| M.3.2.2 | Tripping device   |  | NA |
| M.3.2.3 | Monitoring voltage (V).....                                     |  | NA |

|     |  |  |    |
|-----|--|--|----|
| N   | ANNEX N, IMPULSE TEST GENERATORS (see 2.10.3.4, 6.2.2.1, 7.3.2 and clause G.5) |  | NA |
| N.1 | ITU-T impulse test generators  |  | NA |
| N.2 | IEC 60065 impulse test generator   |  | NA |

|   |                               |  |   |
|---|-------------------------------|--|---|
| P | ANNEX P, NORMATIVE REFERENCES |  | P |
|---|-------------------------------|--|---|

|   |   |                 |   |
|---|---|-----------------|---|
| Q | ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1) |                 | P |
|   | a) Preferred climatic categories :                        | See table 1.5.1 | P |
|   | b) Maximum continuous voltage :                           |                 | P |
|   | c) Pulse current :  |                 | P |

|     |   |  |    |
|-----|---|--|----|
| R   | ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES                |  | NA |
| R.1 | Minimum separation distances for unpopulated coated printed boards (see 2.10.6) |  | NA |
| R.2 | Reduced clearances (see 2.10.3)   |  | NA |

|     |  |  |    |
|-----|--|--|----|
| S   | ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3) |  | NA |
| S.1 | Test equipment                                       |  | NA |

| IEC 60950-1 / EN 60950-1 |  |                    |         |
|--------------------------|--|--------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark    | Verdict |
| S.2                      | Test procedure   |                    | NA      |
| S.3                      | Examples of waveforms during impulse testing   |                    | NA      |
| H                        |  |                    |         |
| T                        | ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)                   |                    | NA      |
|                          |  |                    | —       |
| U                        | ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4) |                    | P       |
|                          |  | See table 1.5.1    | —       |
| V                        | ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)                                     |                    | P       |
| V.1                      | Introduction   |                    | P       |
| V.2                      | TN power distribution systems  |                    | P       |
| W                        | ANNEX W, SUMMATION OF TOUCH CURRENTS   |                    | P       |
| W.1                      | Touch current from electronic circuits   |                    | P       |
| W.1.2                    | Earthed circuits   |                    | P       |
| W.2                      | Interconnection of several equipments  |                    | NA      |
| W.2.1                    | Isolation  |                    | NA      |
| W.2.2                    | Common return, isolated from earth   |                    | NA      |
| W.2.3                    | Common return, connected to protective earth   | Common return used | P       |
| X                        | ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)                  |                    | P       |
| X.1                      | Determination of maximum input current   |                    | P       |
| X.2                      | Overload test procedure  |                    | P       |
| Y                        | ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)                            |                    | NA      |
| Y.1                      | Test apparatus .....   |                    | NA      |
| Y.2                      | Mounting of test samples .....   |                    | NA      |
| Y.3                      | Carbon-arc light-exposure apparatus .....  |                    | NA      |
| Y.4                      | Xenon-arc light exposure apparatus .....   |                    | NA      |
| Z                        | Annex Z, Overvoltage categories (see 2.10.3.2 and Clause G.2)                          |                    | P       |

| IEC 60950-1 / EN 60950-1                       |   |                 |         |
|--|---|-----------------|---------|
| Clause   | Requirement – Test  | Result – Remark | Verdict |
| AA   | Annex AA, Mandrel test (see 2.10.5.8)                         |                 | NA      |
| BB   | Annex BB, Changes in the second edition                       |                 | -       |
| CC   | Evaluation of integrated circuit (IC) current limiters        |                 |         |
| CC.1   | Integrated circuit (IC) current limiters                      |                 |         |
| CC.2   | Test program 1  |                 |         |
| CC.3   | Test program 2  |                 |         |
| DD   | Requirements for the mounting means of rack-mounted equipment |                 |         |
| DD.1   | General   |                 |         |
| DD.2   | Mechanical strength test, variable N                          |                 |         |
| DD.3   | Mechanical strength test, 250 N, including end stops          |                 |         |
| DD.4   | Compliance  |                 |         |
| EE   | Household and home/office document/media shredders            |                 |         |
| EE.1   | General   |                 |         |
| EE.2   | Markings and instructions                                     |                 |         |
| EE.3   | Inadvertent reactivation                                      |                 |         |
| EE.4   | Disconnection of power to hazardous moving parts              |                 |         |
| EE.5   | Protection against hazardous moving parts                     |                 |         |
| EN 60950-1:2006 – CENELEC COMMON MODIFICATIONS |   |                 | P       |

| IEC 60950-1 / EN 60950-1 |   |          |            |                 |               |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
|--------------------------|---|----------|------------|-----------------|---------------|---------|--------|-------|------------|---------|------|-------|--------|---------|------|---------|---------------|-------|------|-------|------|-------|------|---------|--------|-------|--------|---------|------------|-------|------|----------|--------|-----------|--------|---------|------|-------|---------|-------|--------|-------|------------|-----|--------|---------|------|---------|--------|---------|------------|-------|--------|---|------------|---------|--------|---------|------|-------|---------|-------|--------|---------|------|-----|--------|-----|------|-----|------------|-------|--------|---------|--------|--|--|---|
| Clause                   | Requirement – Test  |          |            | Result – Remark |               | Verdict |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| CONTENTS                 | ADD THE FOLLOWING ANNEXES:<br>Annex ZA (normative) Normative references to international publications with their corresponding European publications<br>Annex ZB (normative) Special national conditions<br>Annex ZC (informative) A-deviations   |          |            |                 |               | P       |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| General                  | Delete all the “country” notes in the reference document according to the following list:<br><table><tr><td>1.4.8</td><td>Note 2</td><td>1.5.1</td><td>Note 2 &amp; 3</td><td>1.5.7.1</td><td>Note</td></tr><tr><td>1.5.8</td><td>Note 2</td><td>1.5.9.4</td><td>Note</td><td>1.7.2.1</td><td>Note 4, 5 &amp; 6</td></tr><tr><td>2.2.3</td><td>Note</td><td>2.2.4</td><td>Note</td><td>2.3.2</td><td>Note</td></tr><tr><td>2.3.2.1</td><td>Note 2</td><td>2.3.4</td><td>Note 2</td><td>2.6.3.3</td><td>Note 2 &amp; 3</td></tr><tr><td>2.7.1</td><td>Note</td><td>2.10.3.2</td><td>Note 2</td><td>2.10.5.13</td><td>Note 3</td></tr><tr><td>3.2.1.1</td><td>Note</td><td>3.2.4</td><td>Note 3.</td><td>2.5.1</td><td>Note 2</td></tr><tr><td>4.3.6</td><td>Note 1 &amp; 2</td><td>4.7</td><td>Note 4</td><td>4.7.2.2</td><td>Note</td></tr><tr><td>4.7.3.1</td><td>Note 2</td><td>5.1.7.1</td><td>Note 3 &amp; 4</td><td>5.3.7</td><td>Note 1</td></tr><tr><td>6</td><td>Note 2 &amp; 5</td><td>6.1.2.1</td><td>Note 2</td><td>6.1.2.2</td><td>Note</td></tr><tr><td>6.2.2</td><td>Note 6.</td><td>2.2.1</td><td>Note 2</td><td>6.2.2.2</td><td>Note</td></tr><tr><td>7.1</td><td>Note 3</td><td>7.2</td><td>Note</td><td>7.3</td><td>Note 1 &amp; 2</td></tr><tr><td>G.2.1</td><td>Note 2</td><td>Annex H</td><td>Note 2</td><td></td><td></td></tr></table> |          |            |                 |               | 1.4.8   | Note 2 | 1.5.1 | Note 2 & 3 | 1.5.7.1 | Note | 1.5.8 | Note 2 | 1.5.9.4 | Note | 1.7.2.1 | Note 4, 5 & 6 | 2.2.3 | Note | 2.2.4 | Note | 2.3.2 | Note | 2.3.2.1 | Note 2 | 2.3.4 | Note 2 | 2.6.3.3 | Note 2 & 3 | 2.7.1 | Note | 2.10.3.2 | Note 2 | 2.10.5.13 | Note 3 | 3.2.1.1 | Note | 3.2.4 | Note 3. | 2.5.1 | Note 2 | 4.3.6 | Note 1 & 2 | 4.7 | Note 4 | 4.7.2.2 | Note | 4.7.3.1 | Note 2 | 5.1.7.1 | Note 3 & 4 | 5.3.7 | Note 1 | 6 | Note 2 & 5 | 6.1.2.1 | Note 2 | 6.1.2.2 | Note | 6.2.2 | Note 6. | 2.2.1 | Note 2 | 6.2.2.2 | Note | 7.1 | Note 3 | 7.2 | Note | 7.3 | Note 1 & 2 | G.2.1 | Note 2 | Annex H | Note 2 |  |  | P |
| 1.4.8                    | Note 2  | 1.5.1    | Note 2 & 3 | 1.5.7.1         | Note          |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 1.5.8                    | Note 2  | 1.5.9.4  | Note       | 1.7.2.1         | Note 4, 5 & 6 |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 2.2.3                    | Note  | 2.2.4    | Note       | 2.3.2           | Note          |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 2.3.2.1                  | Note 2  | 2.3.4    | Note 2     | 2.6.3.3         | Note 2 & 3    |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 2.7.1                    | Note  | 2.10.3.2 | Note 2     | 2.10.5.13       | Note 3        |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 3.2.1.1                  | Note  | 3.2.4    | Note 3.    | 2.5.1           | Note 2        |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 4.3.6                    | Note 1 & 2  | 4.7      | Note 4     | 4.7.2.2         | Note          |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 4.7.3.1                  | Note 2  | 5.1.7.1  | Note 3 & 4 | 5.3.7           | Note 1        |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 6                        | Note 2 & 5  | 6.1.2.1  | Note 2     | 6.1.2.2         | Note          |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 6.2.2                    | Note 6.   | 2.2.1    | Note 2     | 6.2.2.2         | Note          |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 7.1                      | Note 3  | 7.2      | Note       | 7.3             | Note 1 & 2    |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| G.2.1                    | Note 2  | Annex H  | Note 2     |                 |               |         |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 1.5.1                    | Add the following NOTE:<br>NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC   |          |            |                 |               | P       |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |
| 2.7.1                    | <i>Replace the subclause as follows:</i><br>Basic requirements<br>To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c):<br><br>a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment;<br><br>b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;<br><br>c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the  |          |            |                 |               | P       |        |       |            |         |      |       |        |         |      |         |               |       |      |       |      |       |      |         |        |       |        |         |            |       |      |          |        |           |        |         |      |       |         |       |        |       |            |     |        |         |      |         |        |         |            |       |        |   |            |         |        |         |      |       |         |       |        |         |      |     |        |     |      |     |            |       |        |         |        |  |  |   |

| IEC 60950-1 / EN 60950-1 |   |                 |         |
|--------------------------|---|-----------------|---------|
| Clause                   | Requirement – Test  | Result – Remark | Verdict |
|                          | installation instructions.<br>If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.   |                 |         |
|                          | S (GB): To protect against excessive currents and short-circuits in the PRIMARY CIRCUIT OF DIRECT PLUG-IN EQUIPMENT, protective device shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT.   |                 | NA      |
| 2.7.2                    | Void.   |                 | P       |
| 3.2.3                    | Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.  |                 | P       |
| 3.2.5.1                  | Replace “60245 IEC 53” by “H05 RR-F”;<br>“60227 IEC 52” by “H03 VV-F or H03 VVH2-F”;<br>“60227 IEC 53” by “H05 VV-F or H05 VVH2-F2”.<br><br>In Table 3B, replace the first four lines by the following:<br><br>  Up to and including 6  <br>0,75 a)  <br>  Over 6 up to and including 10   (0,75) b)<br>1,0  <br>  Over 10 up to and including 16   (1,0) c)<br>1,5  <br><br>In the conditions applicable to Table 3B delete the words “in some countries” in condition a).<br>In NOTE 1, applicable to Table 3B, delete the second sentence. |                 | P       |
| 3.3.4                    | C: In table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following:<br><br>"Over 10 up to and including 16   1,5 to 2,5   1,5 to 4"<br><br>Delete the fifth line: conductor sizes for 13 to 16 A.   |                 | NA      |
| 4.3.13.6                 | Add the following note:<br><br>NOTE Z1 Attention is drawn to 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz. Standards taking into account this Recommendation which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.  |                 | P       |
| Zx (Amd 12:2011)         | Protection against excessive sound pressure from personal music players   |                 | NA      |

| IEC 60950-1 / EN 60950-1 |  |                               |         |
|--------------------------|--|-------------------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark               | Verdict |
| Zx.1                     | General  |                               | NA      |
| Zx.2                     | Equipment requirements   |                               | NA      |
| Zx.3                     | Warning  |                               | NA      |
| Zx.4                     | Requirements for listening devices (headphones and earphones)  |                               | NA      |
| Zx.4.1                   | Wired listening devices with analogue input  |                               | NA      |
| Zx.4.2                   | Wired listening devices with digital input   |                               | NA      |
| Zx.4.3                   | Wireless listening devices   |                               | NA      |
| Zx.5                     | Measurement methods  |                               | NA      |
| Annex H                  | <p>C: Replace the last paragraph of this annex by:</p> <p>At any point 10 cm from the surface of the operator access area, the dose rate shall not exceed 1 <math>\mu</math>Sv/h (0,1 mR/h) (see note). Account is taken of the background level.</p> <p>Replace the notes as follows:</p> <p>NOTE These values appear in Directive 96/29/Euratom.</p> <p>Delete Note 2.</p> |                               | NA      |
| Annex Zx                 | Significance of $L_{Aeq, T}$ in EN 50332-1 and additional information  |                               | -       |
| Bibliography             | Additional EN standards  |                               | -       |
|                          |  |                               |         |
| ZA                       | NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS  |                               | -       |
|                          |  |                               |         |
| ZB                       | SPECIAL NATIONAL CONDITIONS  |                               | P       |
|                          |  |                               |         |
| 1.2.4.1                  | In <b>Denmark</b> , certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.   | Both national and Schuko plug | P       |
| 1.2.13.14                | In <b>Norway</b> and <b>Sweden</b> , for requirements see 1.7.2.1 and 7.3 of this annex  |                               | P       |
| 1.5.7.1                  | In Finland, Norway and Sweden, resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.   | See table 1.5.1               | NA      |



| IEC 60950-1 / EN 60950-1 |   |                           |         |
|--------------------------|---|---------------------------|---------|
| Clause                   | Requirement – Test  | Result – Remark           | Verdict |
| 1.5.8                    | In <b>Norway</b> , due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).  | See table 1.5.1           | P       |
| 1.5.9.4                  | In <b>Finland, Norway and Sweden</b> , the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.   |                           | NA      |
| 1.7.2.1                  | <p>In <b>Finland, Norway and Sweden</b>, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet.</p> <p>The marking text in the applicable countries shall be as follows:</p> <p>In Finland: "Laite on liitettävä suojamaadoituskoskettimilla varustettuun pistorasiaan"</p> <p>In Norway: "Apparatet må tilkoples jordet stikkontakt"</p> <p>In Sweden: "Apparaten skall anslutas till jordat uttag"</p> | No surge suppressors used | NA      |

| IEC 60950-1 / EN 60950-1 |  |                                   |         |
|--------------------------|--|-----------------------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark                   | Verdict |
| 1.7.2.1                  | <p>In Norway and Sweden, the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system.</p> <p>It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in:</p> <p>“Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11).”</p> <p>NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min.</p> <p>Translation to Norwegian (the Swedish text will also be accepted in Norway):<br/> “Utstyr som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel- TV nettet.”</p> <p>Translation to Swedish:<br/> ”Utrustning som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av utrustningen till kabel-TV nät galvanisk isolator finnas mellan utrustningen och kabel-TV nätet.”</p> | No such cable distribution system | NA      |

| IEC 60950-1 / EN 60950-1 |   |   |         |
|--------------------------|---|---|---------|
| Clause                   | Requirement – Test  | Result – Remark                               | Verdict |
| 1.7.5                    | In <b>Denmark</b> , socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1-1b or DK 1-5a.<br><br>For CLASS II EQUIPMENT the socket outlet shall be in accordance with Standard Sheet DKA 1-4a. | No socket-outlet                              | NA      |
| 2.2.4                    | In <b>Norway</b> , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.   |   | NA      |
| 2.3.2                    | In <b>Finland, Norway and Sweden</b> there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.   | Applicable only to products with TNV circuits | NA      |
| 2.3.4                    | In <b>Norway</b> , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.   | Applicable only to products with TNV circuits | NA      |
| 2.6.3.3                  | In the <b>United Kingdom</b> , the current rating of the circuit shall be taken as 13 A, not 16 A.  | Current <1A                                   | P       |
| 2.7.1                    | In the <b>United Kingdom</b> , to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.                                     | Current <1A                                   | NA      |
| 2.10.5.13                | In <b>Finland, Norway and Sweden</b> , there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.   | Applicable only to products with TNV circuits | NA      |

| IEC 60950-1 / EN 60950-1 |  |                        |         |
|--------------------------|--|------------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark        | Verdict |
| 3.2.1.1                  | <p>In <b>Switzerland</b>, supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets:</p> <p>SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A<br/> SEV 6533-2.1991 Plug Type 11 L+N 250 V, 10 A<br/> SEV 6534-2.1991 Plug Type 12 L+N+PE 250 V, 10 A</p> <p>In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16 A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998:</p> <p>SEV 5932-2.1998 Plug Type 25 3L+N+PE 230/400 V, 16 A<br/> SEV 5933-2.1998 Plug Type 21 L+N 250 V, 16 A<br/> SEV 5934-2.1998 Plug Type 23 L+N+PE 250 V, 16 A</p> | Relevant plug not used | NA      |
| 3.2.1.1                  | <p>In <b>Denmark</b>, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to the Heavy Current Regulations, Section 107-2-D1.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.</p> <p>If poly-phase equipment and single-phase equipment having a RATED CURRENT exceeding 13 A is provided with a supply cord with a plug, this plug shall be in accordance with the Heavy Current Regulations, Section 107-2-D1 or EN 60309-2.</p>  |                        | P       |

| IEC 60950-1 / EN 60950-1 |  |                         |         |
|--------------------------|--|-------------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark         | Verdict |
| 3.2.1.1                  | <p>In <b>Spain</b>, supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994.</p> <p>Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994.</p> <p>If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.</p> | Schuko plug accepted    | P       |
| 3.2.1.1                  | <p>In the <b>United Kingdom</b>, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations.</p> <p>NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.</p>  | National plug available | P       |
| 3.2.1.1                  | <p>In <b>Ireland</b>, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997</p>   | National plug available | P       |
| 3.2.4                    | In <b>Switzerland</b> , for requirements see 3.2.1.1 of this annex.  |                         | P       |
| 3.2.5.1                  | In the <b>United Kingdom</b> , a power supply cord with conductor of 1,25 mm <sup>2</sup> is allowed for equipment with a rated current over 10 A and up to and including 13 A.  | Current <1A             | NA      |

| IEC 60950-1 / EN 60950-1 |  |                            |         |
|--------------------------|--|----------------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark            | Verdict |
| 3.3.4                    | In the <b>United Kingdom</b> , the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is:<br><br>• 1,25 mm <sup>2</sup> to 1,5 mm <sup>2</sup> nominal cross-sectional area.  | Current <1A                | NA      |
| 4.3.6                    | In the <b>United Kingdom</b> , the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.   | Direct plug equipment only | NA      |
| 4.3.6                    | In <b>Ireland</b> , DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.  | Direct plug equipment only | NA      |
| 5.1.7.1                  | In <b>Finland, Norway and Sweden</b> TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment:<br><br>• STATIONARY PLUGGABLE EQUIPMENT TYPE A that<br>◦ is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and<br>◦ has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and<br>◦ is provided with instructions for the installation of that conductor by a SERVICE PERSON;<br><br>• STATIONARY PLUGGABLE EQUIPMENT TYPE B;<br><br>• STATIONARY PERMANENTLY CONNECTED EQUIPMENT. | Current < 3,5 mA           | P       |

| IEC 60950-1 / EN 60950-1 |  |                   |         |
|--------------------------|--|-------------------|---------|
| Clause                   | Requirement – Test   | Result – Remark   | Verdict |
| 6.1.2.1                  | <p>In <b>Finland, Norway and Sweden</b>, add the following text between the first and second paragraph of the compliance clause:</p> <p>If this insulation is solid, including insulation forming part of a component, it shall at least consist of either</p> <ul style="list-style-type: none"> <li>- two layers of thin sheet material, each of which shall pass the electric strength test below, or</li> <li>- one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below.</li> </ul> <p>Alternatively for components, there is no distance through insulation requirement for the insulation consisting of an insulating compound completely filling the casing, so that clearance and creepage distances do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition.</p> <ul style="list-style-type: none"> <li>- passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and</li> <li>- is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.</li> </ul> <p>It is permitted to bridge this insulation with a capacitor complying with EN 60384-14, subclass Y2.</p> <p>A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:</p> <ul style="list-style-type: none"> <li>- the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1;</li> <li>- the additional testing shall be performed on all the test specimens as described in EN 60384-14;</li> <li>- the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.</li> </ul> | SELV circuit used | NA      |

| IEC 60950-1 / EN 60950-1 |   |                   |         |
|--------------------------|---|-------------------|---------|
| Clause                   | Requirement – Test  | Result – Remark   | Verdict |
| 6.1.2.2                  | In <b>Finland, Norway and Sweden</b> , the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.  | SELV circuit used | NA      |
| 7.2                      | In <b>Finland, Norway and Sweden</b> , for requirements see 6.1.2.1 and 6.1.2.2 of this annex.<br>The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.   |                   | NA      |
| 7.3                      | In <b>Norway and Sweden</b> , for requirements see 1.2.13.14 and 1.7.2.1 of this annex.   |                   | NA      |
| 7.3                      | In <b>Norway</b> , for installation conditions see EN 60728-11:2005.  |                   | NA      |
|                          |   |                   |         |
| ZC                       | A-DEVIATIONS (INFORMATIVE)  |                   | P       |
| 1.5.1                    | <b>Switzerland</b> (Ordinance on environmentally hazardous substances SR 814.081, Annex 1.7, Mercury - Annex 1.7 of SR 814.81 applies for mercury.)<br><br>Add the following:<br><br>NOTE In Switzerland, switches containing mercury such as thermostats, relays and level controllers are not allowed.  |                   | P       |
| 1.7.2.1                  | <b>Germany</b> (Gesetz über technische Arbeitsmittel und Verbraucherprodukte (Geräte- und Produktsicherheitsgesetz – GPSG) [Law on technical labour equipment and consumer products], of 6th January 2004, Section 2, Article 4, Clause (4), Item 2).<br><br>If for the assurance of safety and health certain rules during use, amending or maintenance of a technical labour equipment or readymade consumer product are to be followed, a manual in German language has to be delivered when placing the product on the market.<br><br>Of this requirement, rules for use even only by SERVICE PERSONS are not exempted. |                   | P       |



| IEC 60950-1 / EN 60950-1 |   |                 |         |
|--------------------------|---|-----------------|---------|
| Clause                   | Requirement – Test  | Result – Remark | Verdict |
| 1.7.13                   | <b>Switzerland</b> (Ordinance on chemical hazardous risk reduction SR 814.81, Annex 2.15 Batteries)<br>Annex 2.15 of SR 814.81 applies for batteries. |                 | P       |

| 1.5.1   | TABLE: list of critical components |               |  |   | P                                      |
|---|------------------------------------|---------------|--|---|--|
| object/part No.   | manufacturer/<br>trademark         | type/model    | technical data                           | standard  | mark(s) of<br>conformity <sup>1)</sup> |
| Main cord with<br>plug  | Various                            | Various       | National                                 | National  | VDE, S, UL,<br>CSA or<br>equivalent    |
| Appliance plug  | Schurter                           | KFA 4301.5012 | 250VAC, 50/60Hz, 2A                      | EN<br>133200:199<br>9,<br>UL 1283               | VDE,S,UL,CSA                           |
| Fuse  | Any                                | 5x20          | T1,6 AL/250VAC                           | IEC60127  | UL, CSA, VDE                           |
| Power supply  | Sunpower                           | SPS-060P-T1   | 88-264VAC                                | EN/IEC/UL<br>60950-1<br>CSA 22.2<br>no. 60950-1 | TÜV, UL                                |
| Internal wire   | Various                            | 1015          | 105 deg C<br>0.75mm <sup>2</sup><br>600V | STYLE 1015                                      | UL                                     |
| Crimps fork-<br>shape   | Various                            | 6.3mm         | -  | ANSI/UL 486                                     | UL                                     |
| Crimps female   | Various                            | 6.3mm         | -  | ANSI/UL 486                                     | UL                                     |
| Crimps circular   | Various                            | 4mm           | -  | ANSI/UL 486                                     | UL                                     |
| Fan   | Sunon                              | KDE1204PKV2   | 12VDC, 0,6W                              | ANSI/UL 507                                     | UL E77551                              |
| Terminal block  | Various                            | -             | -  | 94V-2   | UL                                     |
| PCB   | Various                            | -             | -  | 94V-1   | UL                                     |
| <sup>1)</sup> an asterisk indicates a mark which assures the agreed level of surveillance |                                    |               |  |   |  |

| 1.6.2  | TABLE: electrical data (in normal conditions) |       |       |        |             | P                |
|--------|---|-------|-------|--------|-------------|------------------|
| fuse # | I rated (A)                                   | U (V) | P (W) | I (mA) | I fuse (mA) | condition/status |
| 1      | 1.6   | 100   | 44    | 575    |             | Normal operation |
| 1      | 1.6   | 230   | 38    | 262    |             | Normal operation |

|   |                               |                            |                        |                            |                    |   |
|---|-------------------------------|----------------------------|------------------------|----------------------------|--------------------|---|
| 1.7.11  | TABLE: Durability of markings |                            |                        |                            |                    | P |
| Marking method (see NOTE)   |                               |                            |                        |                            | Agent              |   |
| 1) Printing   |                               |                            |                        |                            | A Water            |   |
| 2) Label  |                               |                            |                        |                            | B Petroleum spirit |   |
| 3)  |                               |                            |                        |                            | C                  |   |
| NOTE – Where applicable include print method, label material, ink or paint type, fixing method, adhesive and surface to which marking is fixed. |                               |                            |                        |                            |                    |   |
| Marking location  |                               |                            |                        | Marking method (see above) |                    |   |
| Side marking  |                               |                            |                        | Label                      |                    |   |
| Rear position   |                               |                            |                        | Printing                   |                    |   |
|   |                               |                            |                        |                            |                    |   |
|   |                               |                            |                        |                            |                    |   |
| Method  | Test agent                    | Remains legible<br>Verdict | Label loose<br>Verdict | Curled edges<br>Verdict    | Comments           |   |
| Label   | A,B                           | Yes                        | No                     | No                         | Test passed        |   |
| Printing  | A,B                           | Yes                        | No                     | No                         | Test passed        |   |

|   |   |              |                  |         |                   |          |
|---|---|--------------|------------------|---------|-------------------|----------|
| 2.10.3 and 2.10.4   | TABLE: clearance and creepage distance measurements |              |                  |         |                   | NA       |
| clearance cl and creepage distance dcr at/of:                   | Up (V)  | U r.m.s. (V) | required cl (mm) | cl (mm) | required dcr (mm) | dcr (mm) |
|   |   |              |                  |         |                   |          |
|   |   |              |                  |         |                   |          |
|   |   |              |                  |         |                   |          |
|   |   |              |                  |         |                   |          |
|   |   |              |                  |         |                   |          |
|   |   |              |                  |         |                   |          |
| *1: power supply previously approved component, see table 1.5.1 |   |              |                  |         |                   |          |

|                                       |   |           |                     |                     |            |
|---------------------------------------|---|-----------|---------------------|---------------------|------------|
| 2.10.5                                | TABLE: distance through insulation measurements |           |                     |                     | NA         |
| distance through insulation di at/of: |   | Up<br>(V) | test voltage<br>(V) | required di<br>(mm) | di<br>(mm) |
|                                       |   |           |                     |                     |            |
|                                       |   |           |                     |                     |            |
|                                       |   |           |                     |                     |            |
|                                       |   |           |                     |                     |            |
|                                       |   |           |                     |                     |            |

|   |                            |               |                         |                        |                                  |               |               |                   |               |               |
|---|----------------------------|---------------|-------------------------|------------------------|----------------------------------|---------------|---------------|-------------------|---------------|---------------|
| 4.3.8   | TABLE: Batteries           |               |                         |                        |                                  |               |               |                   | P             |               |
| The tests of 4.3.8 are applicable only when appropriate battery data is not available   |                            |               |                         |                        | Data available, no test required |               |               |                   | P             |               |
| Is it possible to install the battery in a reverse polarity position?   |                            |               |                         |                        | No                               |               |               |                   | P             |               |
|   | Non-rechargeable batteries |               |                         | Rechargeable batteries |                                  |               |               |                   |               |               |
|   | Discharging                |               | Un-intentional charging | Charging               |                                  | Discharging   |               | Reversed charging |               |               |
|   | Meas. current              | Manuf. Specs. |                         |                        | Meas. current                    | Manuf. Specs. | Meas. current | Manuf. Specs.     | Meas. current | Manuf. Specs. |
| Max. current during normal condition  |                            |               |                         |                        |                                  |               |               |                   |               |               |
| Max. current during fault condition   |                            |               |                         |                        |                                  |               |               |                   |               |               |
|   |                            |               |                         |                        |                                  |               |               |                   |               |               |
| Test results:   |                            |               |                         |                        |                                  |               |               |                   |               | Verdict       |
| - Chemical leaks  |                            |               |                         |                        |                                  |               |               |                   |               |               |
| - Explosion of the battery  |                            |               |                         |                        |                                  |               |               |                   |               |               |
| - Emission of flame or expulsion of molten metal  |                            |               |                         |                        |                                  |               |               |                   |               |               |
| - Electric strength tests of equipment after completion of tests  |                            |               |                         |                        |                                  |               |               |                   |               |               |
| Supplementary information:<br>Any leaks, explosion or emission of flames from a battery will be completely contained in the cabinet. No test required |                            |               |                         |                        |                                  |               |               |                   |               |               |

|  |                              |                    |                     |                    |                                       |                               |                  |
|--|------------------------------|--------------------|---------------------|--------------------|---------------------------------------|-------------------------------|------------------|
| 4.5  | TABLE: thermal requirements  |                    |                     |                    | P                                     |                               |                  |
|  | Supply voltage (V) .....     | 230 VAC            |                     |                    | —                                     |                               |                  |
|  | t <sub>amb1</sub> (°C) ..... | 23                 |                     |                    | —                                     |                               |                  |
|  | t <sub>amb2</sub> (°C) ..... | 23                 |                     |                    | —                                     |                               |                  |
| maximum temperature T of part/at::   |                              | T (°C)             |                     |                    | allowed T <sub>max</sub> (°C)<br>(*4) |                               |                  |
|  |                              | *1                 | *2                  | *3                 |                                       |                               |                  |
| Fan  |                              | 35                 | 36                  | 44                 | 48                                    |                               |                  |
| PCB near DC-converter  |                              | 30                 | 30                  | 40                 | 83                                    |                               |                  |
| DC-converter coil  |                              | 30                 | 31                  | 38                 | 83                                    |                               |                  |
| DC-converter   |                              | 29                 | 30                  | 40                 | 83                                    |                               |                  |
| Power inlet filter   |                              | 30                 | 31                  | 35                 | 62                                    |                               |                  |
| Power supply low-voltage capacitor   |                              | 43                 | 45                  | 56                 | 83                                    |                               |                  |
| Power supply switch transformer  |                              | 53                 | 54                  | 63                 | 83                                    |                               |                  |
| Power supply high-voltage capacitor  |                              | 39                 | 40                  | 48                 | 83                                    |                               |                  |
| Chassis cover bottom under power supply  |                              | 32                 | 33                  | 39                 | 47                                    |                               |                  |
| Chassis cover top over PCB equipped with BB-connection   |                              | 28                 | 29                  | 34                 | 47                                    |                               |                  |
| Chassis cover top over power supply  |                              | 29                 | 29                  | 34                 | 47                                    |                               |                  |
| Keypad “GENLOCK”   |                              | 25                 | 25                  | 32                 | 63                                    |                               |                  |
| Keypad “Compass”   |                              | 25                 | 25                  | 30                 | 63                                    |                               |                  |
| Display  |                              | 25                 | 25                  | 30                 | 73                                    |                               |                  |
| Supplementary information:   |                              |                    |                     |                    |                                       |                               |                  |
| *1: Normal operation   |                              |                    |                     |                    |                                       |                               |                  |
| *2: Abnormal - Air outlet holes blocked  |                              |                    |                     |                    |                                       |                               |                  |
| *3:Abnormal – Fan motor blocked  |                              |                    |                     |                    |                                       |                               |                  |
| *4: Allowed temperature corrected for allowed ambient temperature of 45°C. Correction means that the allowed temperature is lowered by 22°C (45 – 23 = 22°C) |                              |                    |                     |                    |                                       |                               |                  |
|  |                              |                    |                     |                    |                                       |                               |                  |
| Temperature T of winding:  | t <sub>1</sub> (°C)          | R <sub>1</sub> (Ω) | t <sub>2</sub> (°C) | R <sub>2</sub> (Ω) | T (°C)                                | Allowed T <sub>max</sub> (°C) | Insulation class |
|  |                              |                    |                     |                    |                                       |                               |                  |
|  |                              |                    |                     |                    |                                       |                               |                  |
| Supplementary information:   |                              |                    |                     |                    |                                       |                               |                  |

|       |  |        |  |  |    |
|-------|--|--------|--|--|----|
| 4.5.5 | TABLE: Ball pressure test of thermoplastic parts |        |  |  | NA |
|       | Allowed impression diameter (mm) .....           | ≤ 2 mm |  |  | —  |

| Part                       | Test temperature (°C) | Impression diameter (mm) |
|----------------------------|-----------------------|--------------------------|
|                            |                       |                          |
|                            |                       |                          |
| Supplementary information: |                       |                          |

|   |                           |                          |                  |                |                    |          |
|---|---------------------------|--------------------------|------------------|----------------|--------------------|----------|
| 4.7   | TABLE: Resistance to fire |                          |                  |                |                    | P        |
| Part  |                           | Manufacturer of material | Type of material | Thickness (mm) | Flammability class | Evidence |
| Enclosure                                   |                           | Any                      | Aluminium        | 2              |                    |          |
|   |                           |                          |                  |                |                    |          |
| Supplementary information: No test required |                           |                          |                  |                |                    |          |

|                               |   |  |                              |                    |
|-------------------------------|---|--|------------------------------|--------------------|
| 5.2                           | TABLE: electric strength tests, impulse tests and voltage surge tests |  |                              | P                  |
| test voltage applied between: |   | Voltage shape (AC, DC, impulse, surge) | test voltage (V) a.c. / d.c. | breakdown Yes / No |
| Functional:                   |   |  |                              |                    |
|                               |   |  |                              |                    |
|                               |   |  |                              |                    |
| Basic/supplementary:          |   |  |                              |                    |
| L/N – PE                      |   | AC                                     | 1500 Vrms                    | No                 |
|                               |   |  |                              |                    |
| Reinforced                    |   |  |                              |                    |
|                               |   |  |                              |                    |
|                               |   |  |                              |                    |
| Supplementary information     |   |  |                              |                    |

| 5.3           | TABLE: fault condition tests                                    |                    |           |          |                  | P                        |
|---------------|---|--------------------|-----------|----------|------------------|--------------------------|
|               | ambient temperature (°C) .....: 23                              |                    |           |          |                  | —                        |
|               | Power source for EUT: Manufacturer, model/type, output rating : |                    |           |          |                  | —                        |
| component No. | fault   | Supply voltage (V) | test time | fuse No. | fuse current (A) | Observation              |
| Fan           | Fan blocked   | 100                | >3 hours  | 1        | 0,575            | No hazard, see table 4.5 |
| Fan           | Fan blocked   | 230                | >3 hours  | 1        | 0,262            | No hazard, see table 4.5 |
| Enclosure     | Air inlet blocked   | 100                | >3 hours  | 1        | 0,575            | No hazard, see table 4.5 |

| component<br>No.          | fault                | Supply<br>voltage<br>(V) | test time | fuse<br>No. | fuse current<br>(A) | Observation              |
|---------------------------|----------------------|--------------------------|-----------|-------------|---------------------|--------------------------|
| Enclosure                 | Air inlet<br>blocked | 230                      | >3 hours  | 1           | 0,262               | No hazard, see table 4.5 |
| supplementary information |                      |                          |           |             |                     |                          |
|                           |                      |                          |           |             |                     |                          |

| EN / IEC60950-1   |  |                                     |         |
|---|--|-------------------------------------|---------|
| Clause  | Requirement - Test   | Result                              | Verdict |
| USA/Canada  |  |                                     |         |
| CAN/CSA C22.2 No. 60950/UL60950, Third Edition, based on IEC 60950, Third Edition |  |                                     |         |
|   | <p><i>"CEC" denotes Canadian Electrical Code</i></p> <p><i>"NEC" denotes US National Electrical Code.</i></p>  |                                     | -       |
|   | <p><b>SPECIAL NATIONAL CONDITIONS</b></p> <p>The following is a summary of the key national differences based on national regulatory requirements, such as the Canadian Electrical Code (CEC) Part I and the Canadian Building Code, which are referenced in legislation and which form the basis for the rules and practices followed in electrical and building installations</p>  |                                     | -       |
| 1.1.1   | All equipment is to be designed to allow installation in accordance with the National Electrical Code (NEC), ANSI/NFPA 70, the Canadian Electrical Code (CEC), Part I, CAN/CSA C22.1, and when applicable, the National Electrical Safety Code, IEEE C2. Also, unless marked or otherwise identified, installation is allowed per the Standard for the Protection of Electronic Computer/Data-Processing Equipment, ANSI/NFPA 75.  |                                     | P       |
| 1.4.14  | For Pluggable Equipment Type A, the protection in the installation is assumed to be 20A.   | Type B used                         | NA      |
| 1.5.5   | <p>For lengths exceeding 3.05 m, external interconnecting flexible cord and cable assemblies are required to be a suitable cable type (e.g., DP, CL2) specified in the CEC/NEC.</p> <p>For lengths 3.05 m or less, external interconnecting flexible cord and cable assemblies that are not types specified in the CEC are required to have special construction features and identification markings.</p>   | Interconnecting cables not supplied | NA      |
| 1.7.1   | <p>Equipment for use on a.c. mains supply systems with a neutral and more than one phase conductor (e.g. 120/240 V, 3-wire) require a special marking format for electrical ratings.</p> <p>A voltage rating that exceeds an attachment plug cap rating is only permitted if it does not exceed the extreme operating conditions in Table 2 of CAN/CSA C22.2 No. 235, and if it is part of a range that extends into the Table 2 "Normal Operating Conditions." Likewise, a voltage rating shall not be lower than the specified "Normal Operating Conditions," unless it is part of a range</p> | One phase used only                 | NA      |



| EN / IEC60950-1 |  |  |         |
|-----------------|--|--|---------|
| Clause          | Requirement - Test   | Result   | Verdict |
|                 | that extends into the "Normal Operating Conditions."   |  |         |
| 1.7.7           | Wiring terminals intended to supply Class 2 outputs in accordance with CEC Part 1 or NEC shall be marked with the voltage rating and "Class 2" or equivalent. Marking shall be located adjacent to the terminals and shall be visible during wiring.   |  | NA      |
| 2.5             | Where a fuse is used to provide Class 2, Limited Power Source, or TNV current limiting, it shall not be operator-accessible unless it is not interchangeable.  |  | NA      |
| 2.6.3.3         | The first column on Table 2D modified to require, "Smaller of the RATED CURRENT of the equipment or the PROTECTIVE CURRENT RATING of the circuit under consideration."   |  | P       |
| 2.7.1           | Suitable NEC/CEC branch circuit protection rated at the maximum circuit rating is required for all standard supply outlets and receptacles (such as supplied in power distribution units) if the supply branch circuit protection is not suitable.<br><br>Power distribution transformers distributing power at 100 volts or more, and rated 10 kVA or more, require special transformer overcurrent protection. | Not a distribution unit                            | NA      |
| 3.2             | Wiring methods (terminals, leads, etc.) used for the connection of the equipment to the mains shall be in accordance with the NEC/CEC.   | National plug used                                 | P       |
| 3.2.1           | Power supply cords are required to have attachment plugs rated not less than 125 percent of the rated current of the equipment.  | Supply cord rated >125% than rated current of 1.6A | P       |
| 3.2.1.2         | Equipment connected to a centralized d.c. power system, and having one pole of the DC mains input terminal connected to the main protective earthing terminal in the equipment, is required to comply with special earthing, wiring, marking and installation instruction requirements.  | No d.c. power used                                 | NA      |
| 3.2.3           | Permanent connection of equipment to the mains supply by a power supply cord is not permitted, except for certain equipment, such as ATMs.   |  | NA      |
| 3.2.5           | Power supply cords are required to be no longer than 4.5 m in length.<br><br>Minimum cord length is required to be 1.5 m, with certain constructions such as external power supplies allowed to consider both input and output cord lengths into the requirement.<br><br>Flexible power supply cords are required to be compatible with Article 400 of the NEC, and  | Power cord min. 1.5m and max. 4.5m                 | P       |

| EN / IEC60950-1 |   |  |         |
|-----------------|---|--|---------|
| Clause          | Requirement - Test  | Result   | Verdict |
|                 | Tables 11 and 12 of the CEC.  |  |         |
| 3.2.9           | Permanently connected equipment is required to have a suitable wiring compartment and wire bending space.   |  | NA      |
| 3.3             | Wiring terminals and associated spacings for field wiring connections shall comply with CSA C22.2 No. 0.  | No field wiring connection, appliance coupler used | NA      |
| 3.3.3           | Wire binding screws are not permitted to attach conductors larger than 10 AWG (5.3 mm <sup>2</sup> ). Wire binding screws are not permitted to attach conductors larger than 10 AWG (5.3 mm <sup>2</sup> ).   |  | NA      |
| 3.3.4           | Terminals for permanent wiring, including protective earthing terminals, are required to be suitable for Canadian/US wire gauge sizes, rated 125 percent of the equipment rating, and be specially marked when specified (1.7.7).   |  | NA      |
| 3.3.5           | First column of Table 3E revised to require "Smaller of the RATED CURRENT of the equipment or the PROTECTIVE CURRENT RATING of the circuit under consideration."  |  | NA      |
| 3.4.2           | Motor control devices are required for cord-connected equipment with a motor if the equipment is rated more than 12 A, or if the motor has a nominal voltage rating greater than 120 V, or is rated more than 1/3 hp (locked rotor current over 43 A).                                      | No motor control device                            | NA      |
| 3.4.8           | Vertically-mounted disconnect switches and circuit breakers are required to have the "on" position indicated by the handle in the up position.  | No switch used                                     | NA      |
| 3.4.11          | For computer room applications, equipment with battery systems capable of supplying 750 VA for five minutes are required to have a battery disconnect means that may be connected to the computer room remote power-off circuit.  | No d.c. supply used                                | NA      |
| 4.3.12          | The maximum quantity of flammable liquid stored in equipment is required to comply with NFPA 30.  | No liquid store                                    | NA      |
| 4.3.13.5        | Equipment with lasers is required to meet the Canadian Radiation Emitting Devices Act, REDR C1370 and/or Code of Federal Regulations 21 CFR 1040, as applicable.  | No laser used                                      | NA      |
| 4.7             | For computer room applications, automated information storage systems with combustible media greater than 0.76 m <sup>3</sup> (27 cu ft) are required to have a provision for connection of either automatic sprinklers or a gaseous agent extinguishing system with an extended discharge. | No combustible media used                          | NA      |
| 4.7.3.1         | For computer room applications, enclosures with   |  | NA      |

| EN / IEC60950-1 |   |  |         |
|-----------------|---|--|---------|
| Clause          | Requirement - Test  | Result   | Verdict |
|                 | combustible material measuring greater than 0.9 m <sup>2</sup> (10 sq ft) or a single dimension greater than 1.8 m (6 ft) are required to have a flame spread rating of 50 or less. For other applications, enclosures with the same dimensions require a flame spread rating of 200 or less.   |  |         |
|                 |   |  |         |
| Annex H         | Equipment that produces ionizing radiation is required to comply with the Canadian Radiation Emitting Devices Act, REDR C1370 and/or Code of Federal Regulations, 21 CFR 1020, as applicable.   | No ionizing radiation  | NA      |
|                 |   |  |         |
|                 | OTHER DIFFERENCES   |  |         |
| 1.5.1           | Some components and materials associated with the risk of fire, electric shock, or personal injury are required to have component or material ratings in accordance with the applicable national (Canadian and/or U.S.) component or material standard requirements. These components include:<br><br>attachment plugs, battery packs (rechargeable type, used with transportable equipment), cathode ray tubes, circuit breakers, communication circuit accessories, connectors (used for current interruption of non-LPS circuits), cord sets and power supply cords, direct plug-in equipment, enclosures (outdoor), flexible cords and cables, fuses (branch circuit), fuseholders, ground-fault current interrupters, industrial control equipment, insulating tape, interconnecting cables, lampholders, limit controls, printed wiring, protectors for communications circuits, receptacles, solid state controls, supplementary protectors, switches (including interlock switches), thermal cutoffs, thermostats, (multi-layer) transformer winding wire, transient voltage surge suppressors, tubing, wire connectors, and wire and cables. | Flexible cord, fuse, interconnecting cables, PCB, transformer winding wire, wire and wire connectors are rated ref. relevant requirements. See table 1.5.1 | P       |
| 1.6.1.2         | A circuit for connection to the DC Mains Supply is classified as either a SELV Circuit, TNV-2 Circuit or Hazardous Voltage Circuit depending on the maximum operating voltage of the supply. This maximum operating voltage shall include consideration of the battery charging "float voltage" associated with the intended supply system, regardless of the marked power rating of the equipment.   | No DC Mains used   | NA      |
| 2.3.1           | For TNV-2 and TNV-3 circuits with other than ringing signals and with voltages exceeding 42.4   | No TNV-2 or TNV-3 circuits   | NA      |

| EN / IEC60950-1 |  |  |         |
|-----------------|--|--|---------|
| Clause          | Requirement - Test   | Result                                 | Verdict |
|                 | Vpeak or 60 Vd.c., the maximum acceptable current through a 2000 ohm resistor (or greater) connected across the voltage source with other loads disconnected is 7.1 mA peak or 30 mA d.c. under normal operating conditions.   | used                                   |         |
| 2.3.2.1         | In the event of a single fault between TNV and SELV circuits, the limits of 2.2.3 apply to SELV Circuits and accessible conductive parts.  | Only SELV circuit used                 | NA      |
| 4.2.8.1         | Enclosures around CRTs with a face diameter of 160 mm or more are required to reduce the risk of injury due to the implosion of the CRT.   | No CRT used                            | NA      |
| 4.3.2           | Equipment with handles is required to comply with special loading tests.   | Rack handles subjected to 50 N testing | P       |
| 5.1.8.3         | Equipment intended to receive telecommunication ringing signals is required to comply with a special touch current measurement tests.  | No telecommunication                   | NA      |
| 5.3.7           | Internal (e.g., card cage) SELV circuit connectors and printed wiring board connectors that are accessible to the operator and that deliver power are to be overloaded.<br><br>During abnormal operating testing, if a circuit is interrupted by the opening of a component, the test shall be repeated twice (three tests total) using new components as necessary. | No power output                        | NA      |
| 6.4             | Equipment intended for connection to telecommunication network outside plant cable is required to be protected against overvoltage from power line crosses in accordance with 6.4 and Annex NAC.   | No telecommunication                   | NA      |
|                 |  |  |         |
| Annex EE        | Articulated accessibility probe (Fig EE.3) required for assessing accessibility to document/media shredders instead of the Figure 2A test finger.  | No shredder                            | NA      |
|                 |  |  |         |
| M.2             | Continuous ringing signals up to 16 mA only are permitted if the equipment is subjected to special installation and performance restrictions.  | No telecommunication                   | NA      |
|                 |  |  |         |
| Annex NAD       | Equipment connected to a telecommunication and cable distribution networks and supplied with an earphone intended to be held against, or in the ear is required to comply with special acoustic pressure requirements.   | No earphone                            | NA      |

**List of test equipment used:**

(Note: This is an example of the required attachment. Other forms with a different layout but containing similar information are also acceptable.)

| Clause  | Measurement / testing   | Testing / measuring equipment / material used   | Range used  | Calibration date |
|---------|-------------------------|---|---|------------------|
| 1.6.2   | Input                   | Wattmeter Chroma 66202<br>A81                   | 300 V<br>2 A / 0.1 A                                    | 11.03.2014       |
| 2.1.1.7 | Residual voltage        | Oscilloscope Tektronix TDS 2022B<br>A44         | Channel 1, 100<br>V/50 ms<br>Storage single<br>sequence | 29.04.2015       |
|         |                         | Test box Bl. A96                                |   |                  |
| 2.6.3.4 | Earth bond              | HP 6032A DC-power supply<br>A43                 | 11V/25A   | 25.04.2015       |
|         |                         | Multimeter Fluke 189<br>A38                     | mVDC  | 04.06.2014       |
| 4.3.2   | Design and construction | SHIMPO FGE-100X pull meter                      | 100N  | 08.03.2015       |
| 4.5     | Temperature             | Thermo coupler connecting box<br>Pico XFY16/513 | 8 channels  | -                |
|         |                         | Thermo coupler connecting box<br>Pico HJL29/188 | 8 channels  | -                |
| 5.1     | Touch current           | Multimeter Fluke 189<br>A38                     | VAC   | 04.06.2014       |
|         |                         | Test box Bl. A111                               |   | 02.01.2014       |
| 5.2     | High voltage            | HV generator GW Instek GPT-715A<br>A120         | AC  | 22.02.2015       |