

BEM?RK! Kabelenderne skal afsk?res s? t?t p? connectoren som muligt

	/	UN - D 28	TOLERANCES UNLE TOLERANCE HVOR II	SS OTHERWIS	SE STATED ER ANGIVET	A	Ш	UN - D 60 ISO 1101					
_A R II	N MICROMETER	25	DIMENSION M?L	ANGLE VINKEL		<u> </u>	ПА	UN — D 160 ISO 5459	ITEM POS	ASSEMBLY NO	D.	SAMLINGS NR	QUANT. ANTAL
ROUGHNESS RUHED	UNIT ENHED	₹₫ ΔMP 2-215083-6 20P : 2422 025 07156								TERN NO.	MODEL	NR.	
	mm mm	로 AMP 2-215083-6 20P : 2422 025 07156 물론 20×AWG28 modul 1,27 : 4008 105 04010											
SCALE SKALA	LE PROJ. LA EUROP. 52							ORDER NO.		ORDRE NR.	QUANT. ANTAL		
		TREATMENT BEHANDLING											
CLASS NO. KLASSE NR.												1	
		RIB, CABLE											
		W/MICRO M. 20P				=11	0 '	4008	105	5 0487 - -			
	.K.		SUPERS. ERST.			1	SH SI BL B	t 110-1			116	KU	FORM △4
DDC CHECK CONTROL DAT 98-04-02 PROTELEVISION TECHNOLOGIES A/S								/S – Ko	Kornmarksvej 21 — DK—2605 Br?ndby				