

# Compact VariTime™ Sync Generator, PT 5202



- Varitime™, 8 fields for PAL
- Varitime™, 4 fields for NTSC
- Slave applications, genlocking to PAL, NTSC or 10 MHz clock
- Stand-alone SPG with internal TCXO master reference
- Multistandard: 525/60, 625/50 and dual standard operation
- Outputs:
  - 3 Black Burst
  - 1 SDI Test Signal Generator (incl. SDI Black)
  - 1 Analog video generator
  - 1 AES/EBU or Analog Audio
  - 1 Word Clock at 44.1 or 48 kHz
- Source identification programmable into colourbar on SDI and analog Video
- Source identification, fixed or scrolling up/down
- Easy operation via menu or serial control via RS232 interface
- Windows user interface application included
- Four programmable presets directly selectable
- 1U, half 19" wide and rack-mountable

## Application

The new digital studios need cost effective and reliable synchronisation for the main equipment to work reliably. For this purpose PTV offers a fully integrated solution eliminating any costs associated with modular structures, support of many different signal types and fancy operating features.

All solutions have been carefully designed to meet all requirements for the modern studio and editing.

PTV/DK-Audio introduces the next generation of the Compact VariTime Sync Generator.

The PT 5202 includes all basic features for professional sync, timing and test signals in one half-sized box. New is a user friendly frontplate control and moving text on the colourbar pattern.

## Ease of Operation

A clearly labelled frontplate with separate pushbutton for quick access to main functions, allows intuitive selection of main functions.

When a main function is selected, the detailed menu structure is opened on the LCD screen. In the menus all programmable parameters can be managed, e.g. timing, testsignals and audio parameters.

Also the frontplate gives instant access to 4 presets.

In addition to the frontplate control, all configurations can be set via an RS232 interface.

To facilitate the remote control without having to make a software code, a Windows application program is included with the instrument.

The Windows interface makes it easy to manage all timing, test signals and audio features in one screen. Modification from factory preset can be saved as a file on the PC harddisk or uploaded to the PT 5202 as a setup. The setup are uploaded to PT 5202 in an instant mode or stored as a preset in the instrument. Communication between PT 5202 and PC via standard RS-232 protocol, makes it possible to use any kind of PC.



## Master/Genlock Applications

The PT 5202 is designed to manage slave as well as master operations, as a stand alone unit.

In systems where PT 5202 operates as a master unit it locks to an internal TCXO reference oscillator.

For use in applications where the PT 5202 operates as a slave the genlock function is used.

The genlock function features genlock to NTSC and PAL video signals, Black Burst, composite or a 10 MHz reference clock, e.g. from a GPS receiver. Further more the genlock function features timing and active loop-through of the genlock signal.

## Analog Black Burst Outputs

The sync generator is equipped with three VariTime™ analog Black Burst outputs. Each of these Black Burst outputs is individually fully timeable and can be configured as NTSC or PAL-generator, in any combination.

## SDI Output

A SDI Test Signal generator, fully configurable in system and timing, is also included. This Test Signal Generator provides standard colourbars and test-patterns, according to SMPTE and EBU. For diagnostics in studio setups a list of simple test signals is available. The SDI output includes codes for embedded audio, featuring data for 1kHz Stereo and silence

The SDI signals are in general generated as 10 bit signals, except one of the EBU 75% Colourbar signals which is generated with 8 bit according to ITU 801

## Analog Video Output

The analog video generator is based on the same digitally signal definitions as the SDI Test Signal Generator. It outputs the same test pattern in the same system and with the same sync timing.

This output is primarily for testing purposes and is not usable as a timing reference as the output is not consistently locked to the BB's. The colour-frame (ScH phasing) of this output may randomly be one of four at power-up.

## Source Identification

One line of 16 characters can be programmed into the EBU Colourbar and the SMPTE bar. The text is fixed positioned or can be made scrolling up/down to reveal if a digital transmission link is a "freeze" condition.

## Audio Generators

PT 5201 contains an Analog Audio Generator or an AES/EBU Serial Digital generator. One format at the time as both signals are available on the same XLR connectors.

## Analog Audio Outputs

The Analog Audio generator provides three different test tones in a number of levels. The output is available in stereo, mono and includes click markers for identification of left channel. The click interval is selectable.

## AES/EBU Serial Digital Audio Outputs

The Serial Digital Audio generator provides three different test tones in a number of levels. The output is available in stereo, mono and includes click markers for identification of left channel. The click interval and samplings frequency for the AES/EBU output is selectable. The generator also features system lock and timing facilities for elimination of Lip Sync problems.

## WordClock Output

The WordClock signal is a continuous reference clock operating at HC-MOS level, used for synchronising audio equipment. The sampling frequency of 44.1 or 48 kHz is selectable. The 48kHz is phaselocked to video, while the 44.1kHz is frequency locked only.

## Presets

Four complete instrument presets have been included to make it simple to change the configuration for different studio setups. Changes between the presets are available from the frontpanel. The number of presets stored in the configuration PC is unlimited.

# Product Data

## Master oscillator

Master Frequency Reference TCXO:

- Temperature drift: 0-50°:  $\pm 2,5$  ppm
- Ageing: (1 ppm/year; first year, then better

## Remote Control

- Input interface: RS-232 port, 9 pole D-sub, male
- Protocol: SCPI based
- Baud rate: 9600 Kbit

## Genlock

- Input: 75 Ohm looped through Connector: BNC
- Return loss: >36dB to 6 MHz
- Genlock Signal:  
Video: PAL, NTSC  
Continuous freq.: 10 MHz

Genlock Video requirements:

- Amplitude: nominal  $\pm 3$  dB
- S/N ratio: >26 dB
- Input Sc-H phase: Nominally  $\pm 45^\circ$
- Genlock Continuous freq.:  
Amplitude: 1 V  $\pm 3$  dB
- Pull-in range for fsc.:  $\pm 50$  Hz
- Jitter when locked to burst: < 0,5°
- Jitter when locked to sync: < 5 ns

Timing facilities

- Range:  
PAL:  $\pm 4$  fields  
NTSC:  $\pm 2$  fields
- Resolution:  
Analog Black Burst < 0.5 ns  
SDI and Analog Video: 37ns

## Analog Black Burst Outputs

- Output interface: BNC, 75 Ohm
- Return loss: >36 dB, to 5 MHz
- Sync amplitude:  
PAL: -300mV  $\pm 2\%$   
NTSC: -286mV  $\pm 2\%$
- Burst amplitude:  
PAL: 300mV  $\pm 2\%$   
NTSC: 286mV  $\pm 2\%$
- Timing range:  
PAL:  $\pm 4$  fields  
NTSC:  $\pm 2$  fields
- Timing resolution: 0.15 ns
- Sc-H phase: Default 0°, adjustment  $\pm 180^\circ$ , resolution < 1°
- S/N ratio: 60 dB unweighted to 5 MHz
- Jitter on burst: < 0.5 °

### SDI Test Signal Output

- Output Interface: BNC, 75 Ohm
- Format:  
270 Mb/s serial, complies with ITU-R BT 656 and SMPTE 259 M
- Return loss: >15 dB, 5 - 270MHz
- Timing range:  
PAL:  $\pm 1$  field  
NTSC:  $\pm 1$  field
- Timing resolution: 37 ns
- Jitter: < 0.20 UI
- Rise and fall time: 0.75 - 1.50 ns
- Embedded Audio: 1kHz stereo, levels: -20dB<sub>FS</sub> for 525 lines  
-18 dB<sub>FS</sub> for 625 lines  
Silence and Off

### Analog Video Output

- Output interface: BNC, 75 Ohm
- Return loss: >36 dB to 5 MHz
- Timing resolution: 37 ns
- Sc-H phase:  
Default 0°, adjustment  $\pm 180^\circ$ , resolution  $\pm 1^\circ$
- S/N ratio:  
60 dB unweighted to 5 MHz
- Colourframing compared to BB's is not consistent, may be either 0°, 90°, 180° or 270° at power-up.

### Common test signals, SDI and analog generator:

#### Specific 525-lines patterns

- SMPTE Color Bar
- FCC
- 75% Color Bar, ITU-R BT.801 (timing and level acc. To ITU 801)
- 100% Color Bar
- 75% Red

#### Specific 625-lines patterns:

- EBU Color Bar
- 75% Color Bar, ITU-R BT.801 (timing and levels acc. To ITU801)
- 100% Color Bar
- 75% Color Bar with Red
- 75% Red
- CCIR 18

#### Common Test patterns 525 and 625:

- 10% window
- 15% Window
- 20% Window
- 100% Window
- 15 kHz BI/Wh
- White 100%
- Black
- SDI Check Field
- Digital Grey
- Staircase, 5 Step
- Staircase, 10 Step
- Crosshatch
- PLUGE

### Source Identification on SDI and Video

- Text on EBU colourbar and on SMPTE colourbar
- 1 line of text with up 16 characters
- Text position: fixed or scrolling up/down

### Analog Audio Output

- Output Interface:
- Balanced XLR, 30 Ohm
- Amplitude: 0 dBu, 775 mV
- Distortion: < 0.1%
- Output signals:  
Stereo 500 Hz, no click  
Stereo 1 KHz, no click  
Stereo 8 KHz, no click  
Stereo EBU, 1 KHz, single click in ch A

- Click rate: 1 or 3 sec.
- Levels: From +10 to -36 dBu in steps and Silence

### AES/EBU Audio Output

- Output Interface: Balanced XLR, 110 Ohm  $\pm 20\%$  (According to AES3 1992)
- Amplitude: Typically 3 Vpp
- Rise and fall time: 10 - 30 ns
- Jitter: <20 ns
- Timing range:  $\pm 10 \mu\text{s}$  in 0.8  $\mu\text{s}$  step
- Data rate: 3.072 Mbit/s
- Sampling frequency: 44,1 kHz or 48 kHz
- Coding: Linear PCM, 20-bits two complement binary, Bi-phase mark
- Output signals:  
Stereo 500 Hz, no click  
Stereo 1 kHz, no click  
Stereo 8 kHz, no click  
Stereo EBU, 1 kHz, single click in ch. A
- Click rate: 1 or 3 sec
- Levels: Silence, 0 -9, -12, -15, -16, -18, -20 dB<sub>FS</sub>
- Pre-emphasis: None

### WordClock Output

- Output Interface: BNC, 75 Ohm
- Reference output: 44.1 or 48 KHz HC-MOS level 0-5V unterminated

## General Specifications

### Power Supply

- Mains supply voltage: 100-240V
- Frequency: 47-63 Hz
- Power consumption: 22W

### Mechanical data

19" rackmountable cabinet

- Height: 42 mm (1.73")
- Width: 217mm (8.54")
- Depth: 400 mm (17.3")
- Weight: 2 kg (4.4lbs)

### Environmental data

- Operational temperatures:  
+5°C to +45°C (41°F to 113°F)
- Storage temperatures:  
-30°C to 70°C (-22° to +158°)

### Electromagnetic compatibility


- Complies with requirements for immunity and emission in EN555103-1 and EN55103-2

### Safety

- Safety: complies with IEC/ EN61010-1

### Rackmount

- Rackmount kit included



Rearpanel PT5202

## Ordering Information

PT 5202

Compact VariTime™ Sync Generator

9449 052 02001

## FOR FURTHER INFORMATION

*Contact the PTV sales office in your area, or contact us directly:*



**International: DK-AUDIO A/S** • Marielundvej 37D • DK-2730 Herlev • Denmark

Tel: +45 44 85 02 55 • Fax: +45 44 85 02 50 • [e-mail: info@dk-audio.com](mailto:info@dk-audio.com)

**UK: DK-AUDIO (UK) Ltd** • 72, New Bond Street • London W1S 1RR • England

Tel: +44 870 2414 118 • Fax: +44 870 2414 119 • [e-mail: apa@dk-audio.com](mailto:apa@dk-audio.com)

**Germany: DK-AUDIO Germany** • Ziegeleiweg 16 • D-31832 Springe • Germany

Tel: +49 (0) 5041 80 29 80 • Fax: +49 (0) 5041 80 29 99 • [e-mail: info.de@dk-audio.com](mailto:info.de@dk-audio.com)

**USA: DK-AUDIO America Inc.** • 4417 East Villa Rita Drive, Phoenix, AZ 85032, USA

Tel: +1 602 765 0532 • Fax: +1 602 765 1473 • [e-mail: jdt@dk-audio.com](mailto:jdt@dk-audio.com)