Users' Guide for the code RADAR5 - Version 2

Nicola Guglielmi *
Gran Sasso Science Institute,
Formerly at Dip. di Matematica Pura e Applicata, Università dell'Aquila,
via Crispi 7, I-67010 L'Aquila, Italy,
e-mail: nicola.guglielmi@gssi.it, guglielm@univaq.it
and
Ernst Hairer
Section de Mathématiques, Université de Genève,
CH-1211 Genève 4, Switzerland,
e-mail: Ernst.Hairer@math.unige.ch

December 2004
©2000-2004–present N. Guglielmi, E. Hairer

Technical Report

Versions 2.1 and 2.2

These two versions are distributed on the websites of the authors. With respect to Version 2.1 (Dec '04), Version 2.2 (Jan. '24) fixes a few bugs, and makes other little changes with respect to previous version 2.1. All changes have minimal impact, if any, on backward compatibility with version 2.1. basic differences from version 2.1: concern the call to radar5, which now includes a few further parameters concerning vector dimensions. The subroutine contr5 - which was given as an external files - is now included in this file. the algorithm implementing the numerical integrator has not changed with respect to version 2.1.

A Copyright Notice is given in Section 9.

1   The problem

We consider initial value problems for delay differential equations

$$
\begin{aligned}
M\,y'(t) &= f\Big(t, y(t), y(\alpha_1(t, y(t))), \ldots, y(\alpha_m(t, y(t)))\Big), \\
y(t_0) &= y_0, \qquad y(t) = g(t) \quad \text{for} \ \ t < t_0,
\end{aligned}
\tag{1}
$$

where M is a constant $d \times d$ matrix and $\alpha_i(t, y(t)) \le t$ for all $t \ge t_0$ and for all i. The value $g(t_0)$ may be different from y_0, allowing for a discontinuity at t_0.

The presence of the matrix M in the problem formulation has several reasons. If a partial delay differential equation is discretized in space by finite elements, we obtain an equation of the form (1) where M is the mass matrix. A multiplication of the equation by M^{-1} would destroy the sparsity pattern of the problem and is not recommended.

Since we allow the matrix M to be singular, the above formulation includes all kinds of differential-algebraic delay equations. For $M = \text{diag}(I, \varepsilon I)$ with a very small $\varepsilon > 0$, we get singularly perturbed problems, which form an important class of stiff problems. Moreover, neutral problems

$$y'(t) = f\Big(t, y(t), y(\alpha(t, y(t))), y'(t), y'(\alpha(t, y(t)))\Big) \tag{2}$$

can be written in the form (1), if we introduce a new variable $z(t) = y'(t)$ for the derivative. In fact, this problem becomes equivalent to

$$\begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix} \begin{pmatrix} y'(t) \\ z'(t) \end{pmatrix} = \begin{pmatrix} z(t) \\ -z(t) + f\Big(t, y(t), y(\alpha(t, y(t))), z(t), z(\alpha(t, y(t)))\Big) \end{pmatrix}. \tag{3}$$

In this implementation, the special structure of the right-hand side is exploited on the linear algebra level during the solution of arising nonlinear systems.

We assume throughout that a solution exists on the considered interval of integration (possibly with discontinuities).

The aim of next section is to show how implicit Runge-Kutta methods, in particular collocation methods based on Radau nodes, can be applied to solve problems of type (1). Many aspects of the implementation are a straightforward extension of ideas implemented in the code RADAU5 for ordinary differential equations, and described in Hairer & Wanner [13, Sect. IV.8].

Here we restrict our discussion to new difficulties that are due to the presence of small delays, and to large elements in the derivative of f with repect to the retarded arguments. Some example problems with their drivers for RADAR5 are provided at the end of the report.

2   Numerical Method

Our main interest is the numerical solution of stiff delay differential equations. Since collocation methods based on Radau nodes have been successfully applied to stiff ordinary differential equations (see the code RADAU5 of [13]), and since these methods have excellent stability properties also for delay equations (see for example Zennaro [20] and Guglielmi & Hairer [9]), it is quite natural to take them as a basis for a code solving stiff problems of the type (1).

For ease of presentation, we assume that only one lag term is present ($m = 1$) and that the problem is autonomous:

$$M y'(t) = f\Big(y(t), y(\alpha(t, y(t)))\Big), \tag{4}$$

where $\alpha(t, y(t)) \leq t$, $y(t_0) = y_0$, and $y(t) = g(t)$ for $t < t_0$. Needless to say that the presented code is written for the general situation.

Radau IIA methods are implicit Runge-Kutta methods, whose coefficient matrix $A = (a_{ij})$ is invertible, and whose weights satisfy $b_i = a_{si}$ ("stiff accuracy"). We denote $c_i = \sum_j a_{ij}$ (see [13] for more information on these methods). For an implementation we consider a grid $t_0 < t_1 < t_2 < \ldots$, and we denote the stepsize by $h_n = t_{n+1} - t_n$.

An application of the Radau IIA methods to the problem (4) yields approximations $y_n \approx y(t_n)$ by solving the nonlinear system

$$M\left(Y_i^{(n)} - y_n\right) = h_n \sum_{j=1}^{s} a_{ij} f\left(Y_j^{(n)}, Z_j^{(n)}\right), \qquad y_{n+1} = Y_s^{(n)}, \tag{5}$$

where $Z_i^{(n)}$ is a suitable approximation to $y(\alpha_i^{(n)})$ with

$$\alpha_i^{(n)} = \alpha(t_n + c_i h_n, Y_i^{(n)})$$

.

We put

$$Z_i^{(n)} = \begin{cases} g(\alpha_i^{(n)}) & \text{if } \alpha_i^{(n)} < t_0 \\ u_m(\alpha_i^{(n)}) & \text{if } \alpha_i^{(n)} \in [t_m, t_{m+1}], \end{cases} \tag{6}$$

where $u_m(t)$ is a polynomial approximation of the solution $y(t)$ on the interval $[t_m, t_{m+1}]$. A natural choice for u_m is the collocation polynomial, which is of degree s and passes through the values y_m, and $Y_i^{(m)}$ for $i = 1, \dots, s$. Using the Lagrange interpolation formula it is seen to be of the form

$$u_m(t_m + \tau h_m) = \ell_0(\tau) y_m + \sum_{i=1}^{s} \ell_i(\tau) Y_i^{(m)}, \tag{7}$$

where $\ell_i(\tau)$ is the polynomial of degree s satisfying $\ell_i(c_i) = 1$ and $\ell_i(c_j) = 0$ for $j \neq i$ (here we add $c_0 = 0$ to the nodes $c_1, \dots, c_s$ of the method).

Order of Convergence. If the matrix M is invertible, and if the delay is larger than the step size (i.e., $t - \alpha(t, y(t)) \geq h$), it follows from the standard theory for ordinary differential equations that the local error at grid points is $\mathcal{O}(h^{2s})$, and that the internal stages $Y_i^{(n)}$ approximate the local solution at $t_n + c_i h_n$ with an error of size $\mathcal{O}(h^{s+1})$. In the case of a state-dependent delay this gives an additional $\mathcal{O}(h^{s+2})$ contribution to the local error (due to the multiplication by h_n in (5)). Therefore, on bounded intervals, the global error is of size $\mathcal{O}(h^{s+1})$. For stiff problems, a further order reduction to $\mathcal{O}(h^s)$ is possible, which is in complete analogy to stiff ordinary differential equations (see e.g., [13, Chap. VI]).

If the delay is smaller than the step size, the theory for ordinary differential equations can no longer be applied, and a more involved analysis is necessary. Such a study is beyond the scope of this report. However, we want to emphasize that a general purpose code for stiff delay equations should be able to allow for step sizes larger than the delay, because it is known that stiff solvers are efficient only if 'large' step sizes can be used. Difficulties in an implementation that arise due to the presence of large step sizes, are discussed in [10].

2.1   Solving the Nonlinear Equations

An efficient solution of the nonlinear equations (5) is the most demanding part of an implementation of implicit Runge-Kutta methods. For stiff problems (or when M is singular), this system cannot be solved by fixed point iteration, and one is obliged to use some kind of simplified Newton iterations.

As common in the implementation of implicit Runge-Kutta methods, we pre-multiply the system (5) by $A^{-1} = (\omega_{ij})$ and so obtain the nonlinear system $F(Y) = 0$, where $Y = (Y_1, \ldots, Y_s)^T$ and the ith component of $F(Y)$ is

$$F_i(Y) = \sum_{j=1}^{s} \omega_{ij} M(Y_j - y_n) - h f(Y_i, Z_i) \tag{8}$$

(here, we suppress the subscript n when it does not give rise to confusion). In view of an application of simplified Newton iterations we compute (denoting as δ_{ij} the Kronecker symbol

$$\frac{\partial F_i}{\partial Y_j} = \omega_{ij} M - h\delta_{ij}\Big(f_y(Y_i, Z_i) + f_z(Y_i, Z_i)u'_m(\alpha_i)\alpha_y(t_n + c_i h, Y_i)\Big), \tag{9}$$

where we have to add the term

$$-h f_z(Y_i, Z_i)\ell_j(\sigma_i) \qquad \text{if} \quad \sigma_i := (\alpha(t_n + c_i h, Y_i) - t_n)/h > 0. \tag{10}$$

For an efficient implementation, we replace the exact Jacobian of the nonlinear system with an approximation which, written in tensor notation, is given by

$$A^{-1} \otimes M - hI \otimes \Big(f_y + f_z u'_m(\alpha)\alpha_y\Big) - hL \otimes f_z. \tag{11}$$

The arguments of f_y, f_z, α, and α_y are choson independent of i. The $s \times s$ matrix L has elements given by

$$l_{ij} = \begin{cases} \ell_j(\sigma_i) & \text{if } \alpha(t_n + c_i h, Y_i) > t_n \\ 0 & \text{else.} \end{cases}$$

For an implementation we distinguish the two situations:

Step size is smaller than the delay or, more precisely, if $\sigma_i \leq 0$ for $i = 1, \ldots, s$. For a constant delay (i.e., $\alpha(t, y) = t - \tau$), this happens if and only if $h \leq \tau$ (because $c_i \leq c_s = 1$). In this situation, the matrix L vanishes identically, and the matrix (11) has exactly the same structure as for ordinary differential equations $My' = f(y)$. Transforming the matrix A^{-1} to diagonal form, the linear system with matrix (11) can be solved efficiently as described in [13, Sect. IV.8]. The user of our code can either provide a subroutine with the analytic expression of $f_y(y, z) + f_z(y, z)y'(\alpha(t, y))\alpha_y(t, y)$ (where $z \approx y(\alpha(t, y(t)))$), or he can choose the option of computing it internally by numerical differentiation. Observe that the nasty second term of this matrix is only present for state-dependent delays.

Step size is larger than the delay. In this case, the matrix L in (11) is non-zero. Since, in general, the matrices A^{-1} and L are not simultaneously diagonalizable, the tensor product structure cannot easily be exploited for an efficient solution of the linear systems with matrix (11). However, when the delay is very small compared to the step size (i.e., $\alpha(t_n + c_i h, Y_i) \approx t_n + c_i h$), we get $\sigma_i \approx c_i$, and the matrix L becomes close to the identity. Consequently, the second and third terms in (11) can be considered together, and the idea of diagonalizing the matrix A^{-1} can again be applied.

In conclusion, we adopt the following strategy for approximating the Jacobian of the nonlinear Runge-Kutta equations: if $\alpha(t_n + c_i h, Y_i) \leq t_n$ for at least one i, we let $L = 0$, otherwise we put

4

$L = I$ (identity) in the Jacobian approximation of (11). In both cases standard techniques for stiff ordinary differential equations can be applied, and the tensor product structure of the linear system can be exploited. In case of difficulties in the convergence of the simplified Newton iterations we use the correct L. This, however, requires the LR decomposition of the full matrix (11), which is about 5 times as expensive for the 3-stage method ($s = 3$).

2.2   Error estimation

In the case of a state-dependent delay or of a variable stepsize integration, the $\mathcal{O}(h^{s+2})$ contribution to the local error, due to the approximation of delayed variables, determines a global error $\mathcal{O}(h^{s+1})$. Hence the 3-stage Radau IIA method has classical order $p = 4$ (when applied to (1)).

Now we briefly outline the stepsize control mechanism implemented by the code RADAR5 (this means that we restrict our attention to the case $s = 3$). In ordinary differential equations the stepsize is chosen accordingly to a suitable error estimation at grid points. However, for problems of the form (1), the control of the only local error at grid points could be very misleading and in many problems it turns out to be fundamental to estimate the error in the continuous numerical approximation to the solution.

A classical error estimation at mesh points is obtained, as in the standard ODE framework, by embedding a method of lower order into the Radau method. We call σ_n the estimated local error at grid points.

In the general case, the local order of the error-estimating method turns out to be 4, that is

$$\sigma_n = \mathcal{O}(h_n^4).$$

As we have mentioned, for delay equations, where the uniform accuracy of the numerical solution has also influence on the local error, it is necessary to control the error uniformly in time.

To do this we may consider in general also the polynomial

$$v_m(t_m + \vartheta h_m) = \sum_{i=1}^{s} \ell_i(\vartheta) Y_i^{(m)}, \qquad \vartheta \in [0, 1], \tag{12}$$

of degree $s-1$, which interpolates the values $Y_i^{(m)}$ but not y_m (compare with (7)). In the considered case, that is $s = 3$, v_m is a parabola. It turns out that

$$\eta_n = \max_{\vartheta \in [0,1]} \|u_n(t_n + h_n\vartheta) - v_n(t_n + h_n\vartheta)\| = \|u_n(t_n) - v_n(t_n)\| = \mathcal{O}(h_n^3).$$

We use this quantity as an indicator for the uniform error and denote it as *continuous* component of the local error.

The estimate used for the stepsize control is finally given by

$$\mathrm{err}_n = \gamma_1 \sigma_n + \gamma_2 \, (\eta_n)^{4/3} = \mathcal{O}(h_n^4), \tag{13}$$

with the parameters $\gamma_1, \gamma_2 \geq 0$ possibly tuned by the user. This choice is the fruit of both theoretical and empirical analyses. The order of the estimation is 4 when the solution is smooth, and is obtained quite cheaply.

For the details of this technique we refer the reader to [10].

2.3 Breaking points

Discontinuities may occur in various orders of the derivative of the solution, independently of the regularity of the right hand side. In fact, if either $y_0 \neq g(t_0)$ or some right-hand derivative of the solution at t_0 is different from the corresponding left-hand derivative (which means that the solution is not smooth at t_0) the discontinuity at t_0 may propagate along the integration interval by means of the deviating argument $\alpha(t, y(t))$. Evidently, as soon as $\alpha(\xi, y(\xi)) = t_0$ for some $\xi \geq t_0$, due to the fact that y is not regular at t_0, $f(t, y(t), y(\alpha(t, y(t))))$ is not smooth at ξ. Such discontinuity points are referred in the literature as *breaking points* (see for example [2]). If the deviating arguments do not depend on the solution itself, that is $\alpha = \alpha(t)$, such points may be computed and possibly inserted in advance into a mesh of integration. This allows for decomposing the Cauchy problem (1) into a finite (if the number of breaking points is finite) sequence of regular problems. But in the general case (so-called state-dependent) this computation is not possible and one has to deal with a truly non-smooth problem.

   If the breaking points are not included in the mesh and a variable stepsize integration is used, the stepsize may be severely restricted near the low order jump discontinuities. In the sequel the *order* of a breaking point ξ means that of the highest continuous derivative of the solution at ξ.

Detection of the breaking point

In order to discover the presence of a breaking point we have to detect the presence of a zero of the function $d(t) = \alpha(t, u(t)) - \zeta$ where ζ is a previous breaking point and $u(\cdot)$ a suitable continuous approximation (e.g. (7) to the solution. We monitor the function $d(t)$ only in three cases:

  (i)   if the Newton process does not converge;

  (ii) if the estimated error is not under the given required tolerance;

  (iii) if the error increases (from a step to the subsequent) over a prescribed threshold.

The search hence activates only in case of a stepsize rejection or of an excessive change of the estimated error, and proceeds through the following phases (we focus attention on the n-th time step, where we assume a stepsize rejection).

Algorithm 1

  1). Assume that the step $[t_n, t_n + \bar{h}_n]$ is not accepted;

  2). Look for zeros of the functions

$$d_i(s) = \alpha\Big(s, u_{n-1}(s)\Big) - \zeta_i$$

   for $s \in [t_n, t_n + \bar{h}_n]$ and for all previously computed breaking points ζ_i $(i = 1, 2, \ldots)$;

  3). Let $\hat{\imath}$ such that $d_{\hat{\imath}}(t_n) \cdot d_{\hat{\imath}}(t_n + \bar{h}_n) < 0$;

The breaking point will then be close to a zero of $d_{\hat{\imath}}(s)$. We indicate it by $\hat{\xi}$, that is

$$\alpha\Big(\hat{\xi}, u_{n-1}(\hat{\xi})\Big) - \zeta_{\hat{\imath}} = 0.$$

Computation of the breaking point

Once a breaking point is detected the second phase of the algorithm activates with the goal to compute it to the desired accuracy. Let us denote by $\mathbf{Y} = (Y_1^{(n)}, \cdots, Y_s^{(n)})^{\mathrm{T}}$ the vectors of unknown stage values.

Algorithm 2

4). Solve equations (5) in tandem with

$$\alpha\Big(t_n + h, u_n(t_n + h)\Big) - \hat{\zeta} = 0 \tag{14}$$

with respect to the unknowns $\mathbf{Y}$ and h.

5a). **If** the step is accepted (that is that the estimated local error is below the required error tolerance) the point $\xi = t_n + h$ is inserted into the set of computed breaking points;

5b). **Otherwise** the stepsize is reduced according to the classical stepsize selection strategy.

Other authors considered techniques for approximating the breaking points (see e.g. [14] and [8]). In contrast to our approach, they do not use the continuous output of the actually computed step, but some approximation whose error is difficult to control.

The new basic idea presented here is related to the fact that in the algorithm which computes the RK-step, the stepsize is not fixed but is variable; this allows for an accurate computation of the breaking point to the discrete order p of the method ($\hat{\xi}$ may instead be a quite inaccurate approximation of it and is in any case related to the uniform order q of the method).

3 The code

The code RADAR5 is written in ANSI Fortran-90 and is made of the following routines, which constitute the kernel of the program.

3.1 Main differences with respect to Version 1

The new version 2 of the code RADAR5 implements a new strategy - peculiar to implicit schemes - allowing to detect automatically and then to compute very accurately those breaking points which have to be inserted into the mesh to guarantee the required accuracy. In particular for state-dependent delays, where breaking points are not known in advance, this treatment leads to a significant improvement in accuracy. As a by-product we design strategies that are able to detect points of non-uniqueness or non-existence of the solution so that the code can terminate when such a situation occurs.

The Newton process for solving the Runge–Kutta equations has been also modified.

3.2 The main routine RADAR5

The typical CALL to the main subroutine is as follows.

```
RADAR5(N,FCN,PHI,ARGLAG,X,Y,XEND,H,
     &                    RTOL,ATOL,ITOL,
     &                    JAC,IJAC,MLJAC,MUJAC,
     &                    JACLAG,NLAGS,NJACL,
     &                    MAS,IMAS,MLMAS,MUMAS,SOLOUT,IOUT,
     &                    WORK,LWORK,IWORK,LIWORK,RPAR,IPAR,IDID,
     &                    GRID,LGRID,IPAST,NRDENS)
```

In version 2.1 the call was slightly different

```
        CALL RADAR5(N,FCN,PHI,ARGLAG,X,Y,XEND,H,
     &              RTOL,ATOL,ITOL,
     &              JAC,IJAC,MLJAC,MUJAC,
     &              JACLAG,NLAGS,NJACL,
     &              IMAS,SOLOUT,IOUT,
     &              WORK,IWORK,RPAR,IPAR,IDID,
     &              GRID,IPAST,MAS,MLMAS,MUMAS)
```

List of arguments

N Denotes the dimension of the system.

FCN Name (external) of the subroutine computing the right hand-side of the system of delay differential equations. This has to be provided by the user. For a description see Sect. 5.1 and for examples see Sect. 8.

PHI Name (external) of the function providing the initial functions for the dependent variables of the system of delay differential equations. This has to be provided by the user. For a description see Sect. 5.2 and for examples see Sect. 8.

ARGLAG Name (external) of the function providing the deviating arguments. This has to be provided by the user. For a description see Sect. 5.3 and for examples see Sect. 8.

X At the input denotes the initial value of the independent variable. At the output denotes the last value for which the solution has been computed.

Y At the input denotes the initial values for the vector of dependent variables (it may be different from the value of PHI at X; in this case it is highly recommended to set IWORK(13) and GRID(1) (see below). At the output denotes the numerical solution at X.

XEND Final value of X (XEND-X has to be positive).

H Initial guess for the stepsize; for stiff equations with initial transient, H=1.D0/(norm of F'); usually 1.D-3 or 1.D-5 is good. If H=0, the code puts H=$1.D-6$. At output denotes the predicted stepsize of the last accepted step.

RTOL Relative tolerance; can be both a scalar or a vector.

ATOL Absolute tolerance; can be both a scalar or a vector.

ITOL Switch for RTOL and ATOL. If ITOL=0 both RTOL and ATOL are scalars. The code keeps (roughly) the local error as

$$RTOL * ABS(Y(I)) + ATOL.$$

If ITOL=1 both RTOL and ATOL are vectors. The code keeps (roughly) the local error as

$$RTOL(I) * ABS(Y(I)) + ATOL(I).$$

JAC Name (external) of the subroutine which computes the partial derivatives of F(X,Y,Z) (where Z denotes the retarded variables) with respect to Y. This routine is only called if IJAC=1; otherwise (if IJAC=0) a numerical approximation is provided by the code. In the case IJAC=0 the user has to supply a dummy subroutine For a description see Sect. 5.4 and for examples see Sect. 8.

IJAC Switch for the computation of the Jacobian. If IJAC=0 the Jacobian is computed internally by finite differences; the subroutine JAC is not necessary. If IJAC=1 the Jacobian is supplied by the subroutine JAC.

MLJAC Switch for the banded structure of the Jacobian: If $MLJAC = N$ the Jacobian is a full matrix. If $0 <= MLJAC < N$ MLJAC is the lower bandwith of the Jacobian matrix.

MUJAC The upper bandwith of the Jacobian matrix. Does not need to be set if $MLJAC = N$.

JACLAG Name (external) of the subroutine which computes the partial derivatives of F(X,Y,Z) with respect to Z (where Z denote the delayed variables). This has to be provided by the user only if he sets NLAGS > 0 (in such case the user has to provide the derivative entries with respect to the NLAGS deviating arguments). In the case NLAGS = 0 the user has to supply a dummy subroutine. For a description see Sect. 5.5 and for examples see Sect. 8.

NLAGS Denotes the number of delay arguments which the user wants to take into account when computing the partial derivatives of F(X,Y,Z) with respect to Z (see (10)). It is of interest for the computation of the Jacobian of the nonlinear Runge–Kutta iteration. If it is set to 0 no derivatives with respect to delayed variables are considered; if set to P (> 0), NJACL derivative entries with respect to P delayed variables are computed. For a detailed explanation see Sect. 5.5 and for examples see Sect. 8.

NJACL Total number of derivative entries with respect to delayed variables which are intended to be computed by the routine JACLAG.

MAS Name (external) of the subroutine computing the mass matrix M. If IMAS=0 the subroutine is not needed and the mass matrix is assumed to be the identity; in such a case a dummy routine has to be provided by the user. If IMAS=1 the matrix has to be provided. For a description see Sect. 5.7 and for examples see Sect. 8. Finally if IMAS=2 this addresses neutral problems where the matrix has a special structure.

IMAS Gives information on the mass matrix. If IMAS=0 then M is taken as the identity matrix. If IMAS=1,2 the mass matrix is supplied by the user through the subroutime MAS.

`MLMAS` Switch for the banded structure of the mass matrix. If MLMAS=N, M is a full matrix; if $0 <=$ MLMAS $< N$, MLMAS is the lower bandwidth of the matrix M.

Constraint: MLMAS <= MLJAC.

`MUMAS` Upper bandwith of the mass matrix. Does not need to be set if MLMAS = N.

Constraint: MUMAS <= MUJAC.

`SOLOUT` Name (external) of the subroutine providing the numerical solutions during the integration. If IOUT=1 it is called after every succeful step; if IOUT=0 it is never called; in such a case the user should provide a dummy routine. It has also access to the continuous output of the approximate solutions. For a description see Sect. 5.6 and for examples see Sect. 8.

`IOUT` Flag for calling the subroutine SOLOUT. If IOUT=1 it is called after every accepted step. If IOUT=0 it is never called. This option is recommended when doing tests on performances.

`WORK` Array of state parameters of real kind for controlling and tuning the execution. WORK(1), WORK(2),.., WORK(20) serve as parameters for the code; for a standard use of the code (default values) they can be set to 0 by the user before calling RADAR5. For a description see Sect. 3.3.2 and for examples see Sect. 8.

`LWORK` Dimension of the array WORK.

`IWORK` Array of state parameters of integer kind for controlling and tuning the execution. IWORK(1), IWORK(2),.., IWORK(20) serve as parameters for the code; for a standard use of the code (default values) they can be set to 0 by the user before calling RADAR5. For a description see Sect. 3.3.1 and for examples see Sect. 8.

`LIWORK` Dimension of the array IWORK.

`RPAR` Array of real parameters which can be used for communication between your calling program and the routines/functions FCN, JAC, MAS, SOLOUT, ARGLAG, PHI, JACLAG. It is useful to pass the variables which parametrize the differential system. For further details see the examples in Sect. 8.

`IPAR` Array of integer parameters which can be used for communication between your calling program and the routines/functions FCN, JAC, MAS, SOLOUT, ARGLAG, PHI, JACLAG.

`IDID` Reports on succesfullness of the integration upon return:

IDID= 1: Succesful computation;,

IDID= 2: Succesful computation interrupted by routine SOLOUT;

IDID=-1: Non-consistent input values;

IDID=-2: Too many stepsizes required ($>$ NMAX)

IDID=-3: Stepssize becomes too small;

IDID=-4: Jacobian matrix repeteadly singular;

IDID=-5: Computation interrupted by routine YLAGR5;

IDID=-6: The equation makes use of advanced arguments.

`GRID` Array of length LGRID (which must be at least IWORK(13)+1). Contains prescribed mesh points, which the integration method has to take as grid points. For a correct use it is necessary that $X <$ GRID(1) $<$ GRID(2) $< \ldots <$ GRID(NGRID) $<=$ XEND.

`LGRID` Dimension of the array GRID.

`IPAST` Integer array of dimension IWORK(15) (number of components for which dense output is required). For $0 <$ IWORK(15) $< N$ the components for which dense output is required have to be specified in IPAST(1),...,IPAST(IWORK(15)) (for NRDENS=N this is done automatically).

`NRDENS` Number of components for which is required to store dense output (this is the number of components which appear as delayed in the right-hand-side of the system to be solved.

3.3 Input work parameters to be specified by the user

Several parameters of the code are tuned to make it work well. They may be defined by setting WORK(1),...,WORK(10) as well as IWORK(1),...,IWORK(15) different from zero. For zero input the code automatically choses default values.

3.3.1 The `IWORK` array (integer parameters)

`IWORK(1)` If IWORK(1) $\neq 0$, the code transfoms the Jacobian matrix to Hessenberg form. This is particularly advantageous for large systems with full Jacobian.

It does not work for banded Jacobian and for implicit systems (IMAS=1).

`IWORK(2)` This is the maximal number of allowed steps. The default value is 100000.

`IWORK(3)` This is the maximum number of Newton iterations for the solution of the algebraic system of equations in each step. The default value is 7.

`IWORK(4)` If IWORK(4) $= 0$ the extrapolated collocation polynomial is taken to provide starting values for Newton itaration. If IWORK(4) $\neq 0$ no extrapolation is done but the initial solution value is used. The latter is recommended if Newton's method has difficulties with convergence. The default value is 0.

`IWORK(5)`, `IWORK(6)`, `IWORK(7)` Are relevant to delay differential algebraic systems of index > 1 (see explanations inside the code).

`IWORK(8)` Switch for stepsize strategy If IWORK(8) $= 1$ the modified predictive control (developed by Gustaffson) is used. If IWORK(8) $= 2$ the classical stepsize control is used (for a detailed description see [13]) The first choice often produce safer results while the second is generally faster. The default value is 1.

`IWORK(9)`, `IWORK(10)` Parameters relevant to systems with special structure; see the explanation inside the code.

IWORK(11) Step size selection strategies for stiff ordinary differential equations are usually based on error estimations at grid points. For delay equations, where the accuracy of the dense output strongly influences the performance, such an approach often is not sufficient (see [10]). For this reason the code also controls the error in the dense output.

IWORK(11) switches to different types of error controls.

-1: pure control of the dense output (makes use of a quadratic and a linear polynomials interpolating the stage values);

0: mixed control of dense output and discrete output;

1: simpler mixed control;

2: pure control of the discrete output (is provided by the routine ESTRAD).

Default value is 0. When the solution is definitely smooth 2 is recommended.

IWORK(12) Maximum number of steps stored in the dense output array (PAST). It has to be declared in the calling driver program. Has to be sufficiently large if the delays can be large so that many back steps has to be stored.

IWORK(13) Number of prescribed grid points in the integration mesh. In the integration, typically, at these points the solution or one of its derivative may have a discontinuity. These points have to be set by the user as GRID(1),...,GRID(NGRID). Default value is 0.

IWORK(14) An efficient solution of the nonlinear equations (5) is the most demanding part of an implementation of implicit Runge-Kutta methods. We consider two possible iterations (see [10] for a detailed explanation).

IWORK(14) is the selector for the iteration. If is set to 1 it forces the code to a simplified iteration (always preserving the block tensor structure of the Jacobian). If set to 2 it possibly executes a full iteration (when the selected stepsize is larger than some delays and the simplified iteration does not converge). Default value is 1.

IWORK(15) Number of solution components for which the dense output is required in the computation of the right-hand side (often denoted as NRDENS).

IWORK(16) it gives the integer NDIMN Option valid for neutral problems. Number of derivative components (Z variables) of the neutral problem excluded true solution components.

3.3.2 The WORK array (real parameters)

WORK(1) The rounding unit. Default value is 10^{-16}.

WORK(2) The safety factor in stepsize prediction. Default value is 0.9.

WORK(3) Determines whether the Jacobian should be recomputed. If negative forces the code to compute the Jacobian after every accepted step. Suggested values: 0.1 if Jacobian evaluations are expensive, 0.001 if Jacobian evaluations are not expensive. Default value is 0.001.

WORK(4) Stopping criterion for Newton iteration (usually chosen < 1). Smaller values make the code solower but safer. Default value: $\min\left(0.03, \sqrt{\mathrm{RTOL}(1)}\right)$.

WORK(5), WORK(6) If WORK(5) < HNEW/HOLD < WORK(6), then the stepsize is not changed. This saves LU-decompositions and computing time for large systems. Suugested values: WORK(5)=1.0, WORK(6)=1.2 for small systems, WORK(5)=0.99, WORK(6)=2.0 for large full systems. Default values: WORK(5)=1.0, WORK(6)=1.2.

WORK(7) Maximal allowed stepsize. Default value: XEND-X.

WORK(8), WORK(9) Parameters controlling the stepsize selection. The new stepsize is chosen subject to the restriction:

$$\text{WORK(8)} \leq \text{HNEW/HOLD} \leq \text{WORK(9)}$$

Default values: WORK(8)=0.2, WORK(9)=8.0.

WORK(10) Parameter for tuning the error control of dense output (it is active if IWORK(11) = 0). Range of admissible values $0 \leq \text{WORK(10)} \leq 1$. For smaller values the control is stronger. Suggested values: 0.0 for problems with almost discontinuous solutions (like shocks), 1.0 for problems with fairly smooth solutions, intermediate values for intermediate problems. Default value: 0.D0.

WORK(11) Parameter for controlling the search of breaking points: if the error increases of a factor larger than WORK(11) (from a step to the following), the routine searching breaking points activates. Default value: 5.D0

3.4 Output parameters for statistics

IWORK(13) Number of full Newton iterations.

IWORK(14) Number of function evaluations (those for numerical evaluation ot the Jacobian are not taken into account).

IWORK(15) Number of Jacobian evaluations (either analytically or numerically).

IWORK(16) Total number of computed steps.

IWORK(17) Total number of accepted steps.

IWORK(18) Total number of rejected steps due to error test (step rejections in the first step are not taken into account).

IWORK(19) Number of LU-decompositions.

IWORK(20) Number of forward-backward substitutions of both systems; the NSTEP forward backward substitutions needed for stepsize selection are not taken into account.

3.5 The routine LAGR5

It provides the position in the dense output array (PAST) for every delayed component which is present in the problem.

The typical call is as follows.

```
CALL LAGR5(IL,X,N,Y,ARGLAG,PAST,THETA,IPOS,RPAR,IPAR,PHI,IPAST,NRDS)
```

Note the the last three arguments were not present in Version 1.

List of arguments

IL The index addressing the required delayed argument.

X,Y The argument for the delay term α_{IL}.

N Denotes the dimension of Y.

ARGLAG The name of the function computing the deviating arguments.

PAST The array storing the dense output.

IPOS Captures the position (in the dense output array) of the interval where the deviating arguments falls.

THETA Relative position (its value is between 0 and 1) of the deviating argument within the interval addressed by IPOS.

RPAR,IPAR User-defined arrays containing optional parameters for the delay equation.

PHI The initial function.

IPAST Integer vector which identifies delayed variables.

NRDS Number of delayed components.

3.6   The routine YLAGR5

It provides an approximation to the IC-th component of the solution at any abscissa of the integration interval. Such an approximation is determined by means of the computed piecewise polynomial continuous extension of the discrete numerical solution. Its call has to be preceeded by a call of LAGR5.

   The typical call is as follows.

```
CALL YLAGR5(IC,THETA,IPOS,PHI,RPAR,IPAR,PAST,IPAST,NRDS)
```

List of arguments

IC The index addressing the required component.

THETA,IPOS As in LAGR5. The required component (addressed by IC) has to be approximated at the abscissa addressed by means of IPOS and THETA.

PHI The initial function.

PAST The array storing the dense output.

IPAST Integer array specifying the indexes of the components whose continuous approximation are stored into PAST during integration.

NRDS Total number of components for which dense output is required.

RPAR,IPAR As in RADAR5.

3.7 The new routines BPDTCT and BPACC

Provide the detection and the computation of possible breaking points (not described here for sake of conciseness).

4 Modules common to all the routines

Version 2.2 does not use modules. Version 2.1 uses a module.

The module IP_ARRAY at the beginning of the main file **radar5.f** makes common (to all routines which declare it) the vector IPOSV which is a useful multiple pointer to the dense output for different delays. Its dimension is set to 10. If the equation to be solved makes use of more than 10 delays, the user has to modify the dimension of the vector IPOSV and set it to the desired value and finally has to recompile (or to remake if using the make command).

4.1 Workspace

The module in version 2.1 has to be as follows:

```
MODULE IP_ARRAY
    INTEGER, dimension(#NL) :: IPOSV
END MODULE IP_ARRAY
```

where #NL is larger than the number of considered (different) delays.

5 Routines to be provided by the user

Each user-defined subroutine is described in this section. The argument lists of each subroutine contain arguments in one of three classifications:

Input The argument is read, but not written to.

Modified The argument is both read and written.

Output The argument is only written.

5.1 Subroutine FCN

The FCN subroutine computes the right hand side of the considered system. It has to be declared external in the calling program and its name may be chosen by the user.

5.1.1 Argument list

```
SUBROUTINE FCN(N,X,Y,F,ARGLAG,PHI,RPAR,IPAR,PAST,IPAST,NRDS)

IMPLICIT REAL*8 (A-H,K,O-Z)
INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), dimension(N) :: Y
REAL(kind=DP), dimension(N) :: F
REAL(kind=DP), dimension(1) :: PAST
INTEGER, dimension(1) :: IPAST
REAL(kind=DP), dimension(1) :: RPAR
EXTERNAL PHI
```

5.1.2 Input

`N,ARGLAG,PHI,RPAR,IPAR,IPAST` As in the main routine `RADAR5`

`X,Y` Values of the independent and dependent variables at which the function has to be evaluated.

`PAST` Array containing the required dense output.

`NRDS` Number of components for which dense output is required.

5.1.3 Output

`F` Vector of values assumed by the right hand side.

5.2 Function `PHI`

The `PHI` function provides initial functions for the components which appear in the system with delays. It has to be declared external in the calling program and its name may be chosen by the user.

5.2.1 Argument list

```
FUNCTION PHI(I,X,RPAR,IPAR)
IMPLICIT REAL*8 (A-H,O-Z)
INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), dimension(1) :: RPAR
```

5.2.2 Input

`I` Index of the component.

`X` Value of the independent variable at which the function has to be evaluated.

`RPAR, IPAR` As in the main routine `RADAR5`

5.2.3 Output

`PHI` Required value of the initial function.

5.3 Subroutine `ARGLAG`

The `ARGLAG` function provides the deviating arguments $\alpha_i(t, y(t)), i = 1, 2, \ldots,$ in the system. It has to be declared external in the calling program and its name may be chosen by the user.

5.3.1 Argument list

```
FUNCTION ARGLAG(IL,X,N,Y,RPAR,IPAR,PHI,PAST,IPAST,NRDS)
IMPLICIT REAL*8 (A-H,O-Z)
INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), dimension(1) :: Y
REAL(kind=DP), dimension(1) :: PAST
INTEGER, dimension(1) :: IPAST
INTEGER, dimension(1) :: IPAR
REAL(kind=DP), dimension(1) :: RPAR
```

Note the the last four arguments were not present in Version 1.

5.3.2 Input

`IL` Index of the deviating argument.

`X,Y` Values of the independent and dependent variables at which the function has to be evaluated.

`N` Denotes the dimension of the system.

`RPAR, IPAR` As in the main routine `RADAR5`

`PHI`   The initial function.

`PAST` The memory array.

`IPAST` Integer vector which identifies delayed variables.

`NRDS` Number of delayed components.

5.3.3 Output

`ARGLAG` Required value of the deviating argument.

5.4 Subroutine `JAC`

The `JAC` subroutine provides the Jacobian of the function $f\big(t, y(t), y(\alpha_1(t, y(t))), \ldots, y(\alpha_m(t, y(t)))\big)$ (FCN) with respect to $y(t)$ (Y variables). It is optional (it is activated if IJAC=1). If used, it has to be declared external in the calling program and its name may be chosen by the user. If not provided set IJAC=0 and put a dummy name in the call statement to the main routine RADAR5.

5.4.1 Argument list

```
SUBROUTINE JAC(N,X,Y,DFY,LDFY,ARGLAG,PHI,RPAR,IPAR,PAST,IPAST,NRDS)
IMPLICIT REAL*8 (A-H,K,O-Z)
INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), dimension(N) :: Y
REAL(kind=DP), dimension(LDFY,N) :: DFY
REAL(kind=DP), dimension(1) :: PAST
```

```
      INTEGER, dimension(1) :: IPAST
      REAL(kind=DP), dimension(1) :: RPAR
      EXTERNAL PHI
```

5.4.2 Input

`N,ARGLAG,PHI,RPAR,IPAR,IPAST` As in the main routine `RADAR5`

`X,Y` Values of the dependent and independent variable at which the function has to be evaluated.

`RPAR, IPAR` As in the main routine `RADAR5`

`PAST, NRDS` As in the routine `FCN`

`LDFY` Leading dimension of the Jacobian.

5.4.3 Output

`DFY` Matrix containing the standard Jacobian evaluated at X,Y.

5.5 Subroutine `JACLAG`

The `JACLAG` subroutine provides the derivatives of $f\Big(t, y(t), y(\alpha_1(t, y(t))), \ldots, y(\alpha_m(t, y(t)))\Big)$ (FCN) with respect to $y(\alpha_1(t, y(t))), \ldots, y(\alpha_m(t, y(t)))$ (delayed variables). It may be very important when the code uses stepsizes larger than delays and aims to perform *exact* Newton iterations. It is suggested but optional (if the user does not want to use this option he has to set IWORK(14)=1 and NLAGS=0). If used, it has to be declared external in the calling program and its name may be chosen by the user. If not provided set NLAGS=0 and put a dummy name in the call statement to RADAR5.

5.5.1 Argument list

```
      SUBROUTINE JACLAG(N,X,Y,DFYL,ARGLAG,PHI,IVE,IVC,IVL,
     &                  RPAR,IPAR,PAST,IPAST,NRDS)

      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(1) :: DFYL
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST
      REAL(kind=DP), dimension(1) :: RPAR
      INTEGER, dimension(1) :: IVE,IVC,IVL
      EXTERNAL PHI
```

5.5.2 Input

N,ARGLAG,PHI,RPAR,IPAR,IPAST As in the main routine `RADAR5`

X,Y Values of the dependent and independent variable at which the function has to be evaluated.

RPAR, IPAR As in the main routine `RADAR5`

PAST, NRDS As in the routine `FCN`

5.5.3 Output

IVE,IVC,IVL Vector of indeces which address the derivative entries with respect to delayed terms in the right hand side.

For the K-th entry,

IVE(K) has to indicate the number of the relevant equation;

IVC(K) has to indicate the number of the relevant component;

IVL(K) has to indicate the number of the relevant delay.

DFYL Array containing the values of the derivative entries with respect to delayed components. For the K-th entry,

DFYL(K) has to store the value of the derivative.

This array will be used by the code – when required – to construct the full Jacobian matrix.

5.6 Subroutine `SOLOUT`

The `SOLOUT` subroutine provides the numerical approximation of the solution during the integration.

5.6.1 Argument list

```
SUBROUTINE SOLOUT (NR,XOLD,X,HSOL,Y,CONT,LRC,N,RPAR,IPAR,IRTRN)

IMPLICIT REAL*8 (A-H,O-Z)
INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), PARAMETER :: XSTEP=0.01D0
REAL(kind=DP), dimension(N) :: Y
REAL(kind=DP), dimension(LRC) :: CONT
REAL(kind=DP), dimension(1) :: RPAR
EXTERNAL PHI
```

5.6.2 Input

X,Y Values of the dependent and independent variable at which the function has to be evaluated.

N,RPAR,IPAR As in the main routine `RADAR5`

LRC Dimension of the array `CONT`.

Table 1: Source files in the RADAR5 package

files	description
`radar5.f`	main routines implementing the integration scheme
`dc_decdel.f`	routines involving error estimation
`decsol.f`	rotines providing the necessary linear algebra
`contr5.f`	(only in version 2.1) routine providing continuous output

5.6.3 Modified

`CONT` Vector of dense output for the current stepsize and for all components (used for output aims).

5.6.4 Output

`NR` Number of the mesh point at which the solution is furnished.

`XOLD` The preceeding mesh point.

`HSOL` The value of the stepsize for the current step.

`IRTRN` If set < 0, serves to interrupt the integration.

5.7 Subroutine `MAS`

The `MAS` subroutine computes the mass matrix M of the implicit system. It has to be declared external in the calling program and its name may be chosen by the user. If is not provided the system is considered explicit, that is M is taken as the identity matrix.

5.7.1 Argument list

```
SUBROUTINE MAS(N,Q,LQ,RPAR,IPAR)

INTEGER, PARAMETER :: DP=kind(1D0)
REAL(kind=DP), dimension(1) :: RPAR
REAL(kind=DP), dimension(LQ,N) :: Q
```

5.7.2 Input

`N,RPAR,IPAR` As in the main routine `RADAR5`

`LQ` Leading dimension of the mass matrix.

5.7.3 Output

`Q` The N × N mass matrix of the system.

5.8 Neutral problems

When dealing with neutral problems (2)–(3), the structure requires to insert first the delayed components and then the delayed derivative components in the vector IPAST (see for example the driver of the problem NEUTLOG).

In this case the user should add in the driver the following instructions (where `NRDENS` addresses the number of components of the solution - the delayed ones - for which it is required to store the dense output). If

```
 I1,...,IM
```

are the indices of the variables $z = \dot{y}$ which appear with delays they have to be stored in the vector IPAST as follows.

```
C --- NEUTRAL PROBLEMS, TAKING INTO ACCOUNT OF DERIVATIVE COMPONENTS
      IWORK(16)=1
      IPAST(NRDENS+1)=I1
      ....
      IPAST(NRDENS+M)=IM
```

As an example consider the neutral problem (which is coded in the example NEUTLOG, which is distributed with Radar5):

$$
\begin{aligned}
y_1'(t) &= f_1(t, y(t)) = y_1(t)\left(1 - y_1(t - \tau) - \rho z_1(t - \tau)\right) - \frac{y_2(t)y_1(t)^2}{1 + y_1(t)^2} \\
y_2'(t) &= y_2(t)\left(\frac{y_1(t)^2}{1 + y_1(t)^2} - \alpha\right) \\
0 &= f_1(t, y(t)) - z_1(t)
\end{aligned}
\tag{15}
$$

with constant delay τ and parameteres ρ and α. The state vector Y has the 3 components (in ascending order) $Y(1) = y_1, Y(2) = y_2$ and $Y(3) = z_1 = y_1'$.

In the driver program the user should include the following

```
      INTEGER, PARAMETER :: NRDENS=2
      ...

C     SELECT IMPLICIT FORM ASSOCIATED TO NEUTRAL PROBLEMS
      IMAS=2

C     THE COMPONENTS WHICH REQUIRE DENSE OUTPUT, Y(1) AND
C     Y(3), WHICH REPRESENTS FIRST DERIVATIVE OF Y(1)
      IPAST(1)=1
      IPAST(2)=3

C --- DERIVATIVE COMPONENTS
      IWORK(16)=1
      IPAST(NRDENS+1)=1
```

so that the third state variable is $z_1 = y_1'$ (as appears clear from the statement `IPAST(NRDENS+1)` = 1 being NRDENS+1=3).

6 How to install RADAR5

This section describes how to obtain and install RADAR5.

6.1 Getting the files and installing the code

The code, together with nine driver programs, is available at the addresses
'`http://www.unige.ch/h̃airer`' under item 'software', as well as at the address
'`https://www.gssi.it/people/professors/lectures-maths/item/545-guglielmi-nicola`'
and is mirrored at the address
'`http://univaq.it/~guglielm`' .

   The user can download the tar-file archive and generate the directory of the program and the directories including the examples in its own computer by making use of the Unix command
`tar -xvf radar5.f`

   People who do not use UNIX operative systems may either use standard routines to extract files from compressed archives or may contact directly the authors and will be provided of the package in the desired format.

   RADAR5 Version 2.1 consists of 4 ANSI Fortran-90 files, while RADAR5 Version 2.2 consists of 3 ANSI Fortran-90 files. Both versions are given plus the present documentation/installation pdf file (manrad5-v2). Also included in the distribution are eleven drivers for the test programs. Makefiles for automatic compilation are also provided.

7 Examples provided

RADAR5 comes with 11 examples:

a) ENZYME, kinetics with an inhibitor molecule, dimension 4, one constant delay;

b) HAYASHI, an almost singular state dependent neutral problem, dimension 2 as differential-algebraic problem, one vanishing delay;

c) HEPATITIS, acute hepatitis B virus infection, dimension 10, 5 constant delays;

d) OREGONATOR, chemical kinetics, dimension 2, one constant delay;

e) ROBERTSON, chemical reaction with steady state solution, dimension 3, one constant delay, very large time interval (step sizes larger than the delay);

f) SDISC, non smooth artificial problem, dimension 1, 1 constant delay;

g) WALTMAN, threshold model for antibody production, dimension 6, 2 state-dependent delays tending to zero, discontinuities in the right-hand side of the equations,

h) PAUL, state-dependent artificial problem, various order discontinuities,

i) ELSNOR, problem with solution termination (see [5]).

j) MODCEG, neutral problem with state dependent delays, modification of Castletone and Grimme model.

k) NEUTLOG, artificial neutral problem.

Remarks

An improvement in the accuracy and computational cost with respect to Version 1 has been observed in problems b), c), g), h), i). In the other examples the performances essentially coincide.

8 Example of use

8.1 The Oregonator model.

This problem, taken from [7], consists of two equations and one constant delay. They are given by

$$
\begin{aligned}
y_1'(t) &= kM1\,A\,y_2(t) - kM2\,y_1(t)\,y_2(t-\tau) + kM3\,B\,y_1(t) - 2\,kM4\,y_1(t)^2 \\
y_2'(t) &= -kM1\,A\,y_2(t) - kM2\,y_1(t)\,y_2(t-\tau) + fr\,kM3\,By_1(t)
\end{aligned}
$$

with

$$
\begin{aligned}
kM1 &= 1.34 \\
kM2 &= 1.6 \cdot 10^9 \\
kM3 &= 8.0 \cdot 10^3 \\
kM4 &= 4.0 \cdot 10^7 \\
kM5 &= 1.0 \\
fr &= 1.0 \\
A &= 6.0 \cdot 10^{-2} \\
B &= 6.0 \cdot 10^{-2} \\
\tau &= 0.15
\end{aligned}
$$

Initial values and functions are $y_1(t) = 10^{-10}$ and $y(t) = 10^{-5}$ for $t \le 0$. We consider the integration interval $[0, 100.5]$ and $Atol = 10^{-9} \cdot Rtol$.

The driver program

```
      IMPLICIT REAL*8 (A-H,O-Z)

      REAL*4 start,finish
      INTEGER, PARAMETER :: DP=kind(1D0)
C --->  PARAMETERS FOR RADAR5 (FULL JACOBIAN) <---
      INTEGER, PARAMETER :: ND=2
      INTEGER, PARAMETER :: NRDENS=1
      INTEGER, PARAMETER :: NGRID=1
      INTEGER, PARAMETER :: NLAGS=1
      INTEGER, PARAMETER :: NJACL=2
      INTEGER, PARAMETER :: MXST=4000
      INTEGER, PARAMETER :: LWORK=30
      INTEGER, PARAMETER :: LIWORK=30
      REAL(kind=DP), dimension(ND) :: Y
      REAL(kind=DP), dimension(NGRID+1) :: GRID
      REAL(kind=DP), dimension(LWORK) :: WORK
      INTEGER, dimension(LIWORK) :: IWORK
      INTEGER, dimension(NRDENS+2*ND) :: IPAST
      DIMENSION IPAR(1),RPAR(10)
      DIMENSION ATOL(1),RTOL(1)
```

```
        INTEGER, dimension(23) :: ISTAT
        EXTERNAL  FCN,PHI,ARGLAG,JFCN,JACLAG,SOLOUT


C ------ FILE TO OPEN ----------
        OPEN(9,FILE='sol.out')
        OPEN(10,FILE='cont.out')
        REWIND 9
        REWIND 10


C       PARAMETERS IN THE DIFFERENTIAL EQUATION
C ---   kM1
        RPAR(1)=1.34
C ---   kM2
        RPAR(2)=1.6D9
C ---   kM3
        RPAR(3)=8.0D3
C ---   kM4
        RPAR(4)=4.0D7
C ---   kM5
        RPAR(5)=1.D0
C ---   fr
        RPAR(6)=1.D0
C ---   A
        RPAR(7)=6.D-2
C ---   B
        RPAR(8)=6.D-2
C ---   Tau
        RPAR(9)=15.D-2


C ------------------------------------------------------------------------
C
C --- DIMENSION OF THE SYSTEM
        N=ND
C --- COMPUTE THE JACOBIAN ANALYTICALLY
        IJAC=1
C --- JACOBIAN IS A FULL MATRIX
        MLJAC=N
C --- DIFFERENTIAL EQUATION IS IN EXPLICIT FORM
        IMAS=0
C --- OUTPUT ROUTINE IS USED DURING INTEGRATION
        IOUT=1
C --- INITIAL VALUES
        X=0.0D0
        Y(1)= 1.D-10
        Y(2)= 1.D-5
C       Consistent with initial function
C --- DELAY
        TAU=RPAR(9)
C --- ENDPOINT OF INTEGRATION
        XEND=100.5D0
C --- REQUIRED (RELATIVE AND ABSOLUTE) TOLERANCE
```

```
          ITOL=0
          RTOL=1.D-9
          ATOL=RTOL*1.D-9
C --- INITIAL STEP SIZE
          H=1.0D-6
C --- DEFAULT VALUES FOR PARAMETERS
          IWORK=0
          WORK=0.0D0
C --- MAX NUMBER OF STEPS
          IWORK(2)=100000
C --- WORKSPACE FOR PAST
          IWORK(12)=MXST
C --- THE SECOND COMPONENT USES RETARDED ARGUMENT
          IWORK(15)=NRDENS
          IPAST(1)=2
C --- SET THE PRESCRIBED GRID-POINTS
         DO I=1,NGRID
          GRID(I)=I*TAU
         END DO
         LGRID = NGRID+1
C --- WORKSPACE FOR GRID
         IWORK(13)=NGRID
C --- CONTROL OF NEWTON ITERATION
         IWORK(14)=1
C _____
C --- CALL OF THE SUBROUTINE RADAR5
          CALL cpu_time(start)
          CALL RADAR5(N,FCN,PHI,ARGLAG,X,Y,XEND,H,
     &                RTOL,ATOL,ITOL,
     &                JFCN,IJAC,MLJAC,MUJAC,
     &                JACLAG,NLAGS,NJACL,
     &                FCN,IMAS,MLMAS,MUMAS,SOLOUT,IOUT,
     &                WORK,LWORK,IWORK,LIWORK,RPAR,IPAR,IDID,
     &                GRID,LGRID,IPAST,NRDENS)
          CALL cpu_time(finish)
C --- PRINT FINAL SOLUTION SOLUTION
          WRITE (6,90) X,Y(1),Y(2)
C --- PRINT STATISTICS
           DO J=14,20
              ISTAT(J)=IWORK(J)
           END DO
          WRITE(6,*)' *** TOL=',RTOL,'  TIME=',finish-start,' ***'
          WRITE (6,91) (ISTAT(J),J=14,20)
          WRITE (6,92) ISTAT(23)
 90       FORMAT(1X,'X =',F8.2,'    Y =',2E18.10)
 91       FORMAT(' fcn=',I7,' jac=',I6,' step=',I6,
     &           ' accpt=',I6,' rejct=',I6,' dec=',I6,
     &           ' sol=',I7)
 92       FORMAT(' full Newt. its =',I7)
          WRITE(6,*) 'SOLUTION IS TABULATED IN FILES: sol.out & cont.out'
          STOP
```

```
          END
```

The subroutine SOLOUT

Determines the updating of the files `sol.out` and `cont.out` where the solution is stored. The format of such files has to be chosen according to the graphics packages one intends to use for drawing the solution. The file sol.out contains the values of the approximate solution components at the (adaptively) computed mesh-points. The file cont.out contains the values of the approximate solution components at points prescribed by the user (in the present case a uniform grid has been chosen for the output representation).

```
        SUBROUTINE SOLOUT (NR,XOLD,X,HSOL,Y,CONT,LRC,N,
     &                     RPAR,IPAR,IRTRN)
C ----- PRINTS THE DISCRETE OUTPUT AND THE CONTINUOUS OUTPUT
C       AT EQUIDISTANT OUTPUT-POINTS
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), PARAMETER :: XSTEP=0.01D0
        REAL(kind=DP), dimension(N) :: Y
        REAL(kind=DP), dimension(LRC) :: CONT
        DIMENSION IPAR(1),RPAR(10)
C       XOUT IS USED FOR THE DENSE OUTPUT
        COMMON /INTERN/XOUT

        WRITE (9,99) X,Y(1),Y(2)
C
        IF (NR.EQ.1) THEN
           WRITE (10,99) X,Y(1),Y(2)
           XOUT=XSTEP
        ELSE
 10        CONTINUE
           IF (X.GE.XOUT) THEN
              WRITE (10,99) XOUT,CONTR5(1,N,XOUT,CONT,X,HSOL),
     &                           CONTR5(2,N,XOUT,CONT,X,HSOL)
              XOUT=XOUT+XSTEP
              GOTO 10
           END IF
        END IF
 99     FORMAT(1X,'X =',F12.8,'    Y =',2E18.10)
        RETURN
        END
```

The function ARGLAG

Provides the deviating argument α_1.

```
        FUNCTION ARGLAG(IL,X,N,Y,RPAR,IPAR,PHI,PAST,IPAST,NRDS)
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(1) :: PAST
```

```
      INTEGER, dimension(1) :: IPAST
      DIMENSION IPAR(1),RPAR(10)

      ARGLAG=X-RPAR(9)

      RETURN
      END
```

The subroutine FCN

Provides the right hand side of the differential system, that is

$$
\begin{aligned}
f_1 &= kM1\,A\,y_2 - kM2\,y_1\,z_2 + kM3\,B\,y_1 - 2\,kM4\,y_1^2 \\
f_2 &= -kM1\,A\,y_2 - kM2\,y_1\,z_2 + fr\,kM3\,B y_1
\end{aligned}
$$

where $z_2 := y_2(\alpha_1(t))$ and $\alpha_1(t)$ denotes the deviating argument ($\alpha_1(t) = t - \tau$ in the present case).

```
      SUBROUTINE FCN(N,X,Y,F,ARGLAG,PHI,RPAR,IPAR,
     &                PAST,IPAST,NRDS)
      IMPLICIT REAL*8 (A-H,K,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(N) :: F
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST
      DIMENSION IPAR(1),RPAR(10)
      EXTERNAL PHI,ARGLAG

      kM1=RPAR(1)
      kM2=RPAR(2)
      kM3=RPAR(3)
      kM4=RPAR(4)
      kM5=RPAR(5)
      fr =RPAR(6)
      A  =RPAR(7)
      B  =RPAR(8)



      F(1)=  kM1*A*Y(2) - kM2*Y(1)*Y2L1 + kM3*B*Y(1)-2.D0*kM4*Y(1)**2
      F(2)= -kM1*A*Y(2) - kM2*Y(1)*Y2L1 + fr*kM3*B*Y(1)
      RETURN
      END

C     Evaluates the unique deviating arguments (IL=1) and sets
C     its value into THETA1 and the position of the relative interval
C     into IPOS1
      CALL LAGR5(1,X,N,Y,ARGLAG,PAST,THETA1,IPOS1,RPAR,IPAR,
     &          PHI,IPAST,NRDS)

C     Evaluates the (only) component requiring dense output (which is Y(2))
```

```
C        and puts the result into Z2
         Z2=YLAGR5(2,THETA1,IPOS1,PHI,RPAR,IPAR,
     &               PAST,IPAST,NRDS)
C        Computes F
         F(1)=  kM1*A*Y(2) - kM2*Y(1)*Z2 + kM3*B*Y(1)-2.D0*kM4*Y(1)**2
         F(2)= -kM1*A*Y(2) - kM2*Y(1)*Z2 + fr*kM3*B*Y(1)
         RETURN
         END
```

The subroutine JFCN

Provides the Jacobian (with respect to the variables y_1 and y_2) of the right hand side analytically. We remark that this function could be provided numerically. In this case we have

$$\frac{\partial f}{\partial y} = \begin{pmatrix} -kM2\,z_2 + kM3\,B - 4\,kM4\,y_1 & kM1\,A \\ -kM2\,z_2 + fr\,kM3\,B & -kM1\,A \end{pmatrix}$$

where $\alpha_1(t) = t - \tau$ and $z_2 = y_2(\alpha_1(t))$. Hence the routine is written as follows.

```
         SUBROUTINE JFCN(N,X,Y,DFY,LDFY,ARGLAG,PHI,RPAR,IPAR,
     &                   PAST,IPAST,NRDS)
C ----- STANDARD JACOBIAN OF THE EQUATION
         IMPLICIT REAL*8 (A-H,K,O-Z)
         INTEGER, PARAMETER :: DP=kind(1D0)
         REAL(kind=DP), dimension(N) :: Y
         REAL(kind=DP), dimension(LDFY,N) :: DFY
         REAL(kind=DP), dimension(1) :: PAST
         INTEGER, dimension(1) :: IPAST
         DIMENSION IPAR(1),RPAR(10)
         EXTERNAL PHI,ARGLAG

         kM1=RPAR(1)
         kM2=RPAR(2)
         kM3=RPAR(3)
         kM4=RPAR(4)
         kM5=RPAR(5)
         fr =RPAR(6)
         A  =RPAR(7)
         B  =RPAR(8)

         CALL LAGR5(1,X,N,Y,ARGLAG,PAST,THETA1,IPOS1,RPAR,IPAR,
     &             PHI,IPAST,NRDS)
         Z2=YLAGR5(2,THETA1,IPOS1,PHI,RPAR,IPAR,
     &               PAST,IPAST,NRDS)
C        Jacobian matrix (2x2) with respect to Y(1) and Y(2)
         DFY(1,1)= -kM2*Z2 + kM3*B - 4.D0*kM4*Y(1)
         DFY(1,2)=  kM1*A
         DFY(2,1)= -kM2*Z2 + fr*kM3*B
         DFY(2,2)= -kM1*A
         RETURN
         END
```

The subroutine JACLAG

Provides the Jacobian (with respect to the retarded variablexs $z_2(t) = y_2(\alpha_1(t))$) of the right hand side analytically. This is stored in a one dimensional array as described in Sect. 5.5. We remark that this function could not be provided numerically (at present time). In this case we have

$$\frac{\partial f}{\partial z} = \begin{pmatrix} 0 & -kM2\,y_1 \\ 0 & -kM2\,y_1 \end{pmatrix}$$

where $\alpha_1(t) = t - \tau$ and $z_i(t) = y_i(\alpha_1(t)), i = 1, 2$. Since we store such matrix in a vector (because we assume it is sparse), the routine is written as follows.

```
      SUBROUTINE JACLAG(N,X,Y,DFYL,ARGLAG,PHI,IVE,IVC,IVL,
     &                  RPAR,IPAR,PAST,IPAST,NRDS)
C ----- JACOBIAN OF DELAY TERMS IN THE EQUATION
      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(2) :: DFYL
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST
      DIMENSION IPAR(1),RPAR(10)
      INTEGER, dimension(2) :: IVE,IVC,IVL
      EXTERNAL PHI,ARGLAG

      kM1=RPAR(1)
      kM2=RPAR(2)
      A  =RPAR(7)
      B  =RPAR(8)
C ---  The Jacobian has two entries;
C      the first entry ((1)) is relevant to
C     - the first (and only) delay, whose index is hence equal to 1 (IVL(1)=1)
C     - the first equation (IVE(1)=1)
C     - the second component of the solution (IVC(1)=2)
      IVL(1)=1
      IVE(1)=1
      IVC(1)=2
C      The value of the derivative with respect to the delayed second
C      component in the first equation is finally given by
      DFYL(1)=-kM2*Y(1)

C      the second entry ((2)) is relevant to
C     - the first (and only) delay, whose index is hence equal to 1 (IVL(2)=1)
C     - the second equation (IVE(2)=2)
C     - the second component of the solution (IVC(2)=2)
      IVL(2)=1
      IVE(2)=2
      IVC(2)=2
C      The value of the derivative with respect to the delayed second
C      component in the second equation is finally given by
      DFYL(2)=-kM2*Y(1)
      RETURN
```

```
      END
```

The initial function PHI

Provides the initial functions.

```
      FUNCTION PHI(I,X,RPAR,IPAR)
      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      DIMENSION IPAR(1),RPAR(10)
      SELECT CASE (I)
      CASE (2)
          PHI= 1.D-5
      END SELECT
      RETURN
      END
```

Compilation

We create a file, called "dr-oregon.f", including all previous routines, and put it in a subdirectory (called OREGON) of the main directory RADAR5, where the source and the object files of the main routines of the code are installed. The following makefile is also created in the directory OREGON,

```
FC = f90
FCFLAGS = -c
DEBUGFLAGS = -g
LIB = /lib /usr/lib
.f.o:
      $(FC) $(FCFLAGS) $(DEBUGFLAGS) $*.f

OBJ2 =    ../radar5.o ../dc_ladel.o ../lapack.o ../lapackc.o
OBJ1 =    dr-oregon.o
prog :  $(OBJ1)
      $(FC) $(DEBUGFLAGS) -o driver $(OBJ1) $(OBJ2)
```

The simple use of the Unix command **make** generates the compilation and the linking phase for the program. The executable file is called "driver". In case of troubles check whether the fortran libraries are stored in the directories `/lib` and `/usr/lib`.

Execution

Executing the program driver generates the following output.

```
 STARTING INTEGRATION...
 NUMBER OF PRESCRIBED GRID POINTS:           1
 NUMBER OF DELAYED COMPONENTS:          1
 INTEGRATION...
         42  COMPUTED BREAKING POINTS:
 X =  100.50    Y =  0.2749861728E-09  0.3559046560E-06
```

```
   *** TOL=  1.000000000000001E-009   TIME=  0.2812500      ***
 fcn=  71367 jac=  5140 step=  9391 accpt=  9132 rejct=   233 dec=  7710 sol=  20743
 full Newt. its =      0
 SOLUTION IS TABULATED IN FILES: sol.out & cont.out
```

The program also generates two output files, sol.out and cont.out, which contain - respectively - the discrete computed solution and an approximation of the solution on a uniform mesh with density chosen by the user.

8.2 Artificial neutral problem.

Our second example, which is a modification by Enright & Hayashi [6] of a problem considered originally by Castleton & Grimm [4], is

$$
\begin{aligned}
v'(t) \;=\; & \cos{(t)}\Big(1 + v(t\,v^2(t))\Big) + c\,v(t)\,v'(tv^2(t)) \\
& + (1-c)\,\sin t\,\cos{(t\,\sin^2 t)} - \sin{(t + t\,\sin^2 t)}
\end{aligned}
\tag{16}
$$

with initial value $v(0) = 0$. For every choice of the parameter c, it has $v(t) = \sin t$ as exact solution. It has a vanishing delay at $t = 0, \pi/2, 3\pi/2, \ldots$, and for $c = 1$ it has a singularity at $t = \pi/2$ (i.e., $y'(\pi/2)$ is not well defined by the equation (16). For this problem, the numerical solution of the nonlinear Runge-Kutta equations causes some difficulties.

We have rewritten the neutral equation (16) in the form (1) by setting $y_1(t) = v(t)$ and introducing the new variable $y_2(t) = v'(t)$ and $z_1(t) = y_1(\alpha_1(t, y))$, $z_2(t) = y_2(\alpha_1(t, y))$, with $\alpha_1(t, y) = ty_1^2(t)$, as explained in the first section,

$$
\begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}
\begin{pmatrix} y_1'(t) \\ y_2'(t) \end{pmatrix}
=
\begin{pmatrix} f_1(t, y, z) \\ f_2(t, y, z) \end{pmatrix}.
\tag{17}
$$

with

$$
f_1(t, y_1, y_2, z_1, z_2) \;=\; y_2(t)
$$

$$
\begin{aligned}
f_2(t, y_1, y_2, z_1, z_2) \;=\; & -y_2(t) + \cos{(t)}(1 + z_1(t)) + c\,y_1(t)\,z_2(t) + \\
& (1-c)\,\sin t\,\cos{(t\,\sin^2 t)} - \sin{(t + t\,\sin^2 t)}.
\end{aligned}
$$

Then we have applied our code RADAR5 with $Rtol = Atol = 10^{-8}$. We display the total number of steps (accepted and rejected), the number of steps where difficulties appeared in solving the nonlinear system (so that the correct matrix L had to be used in (11)), and the global error at the endpoint of integration. We observe that such difficulties appear only for values close to ± 1. It is somewhat surprising that our code solves the problem correctly even for $c = 1$ (the singular case).

For conciseness we do not report the driver program and present only part of the user-defined routines.

Table 2: Statistics for the problem (16) with $Rtol = Atol = 10^{-8}$

c	nr. of steps	nr. of full Jac	error at $t = \pi$
-1.0	55	2	$0.20 \cdot 10^{-7}$
-0.7	54	0	$0.50 \cdot 10^{-8}$
-0.3	44	0	$0.59 \cdot 10^{-8}$
0.0	41	0	$0.46 \cdot 10^{-8}$
0.3	42	1	$0.22 \cdot 10^{-9}$
0.7	56	4	$0.56 \cdot 10^{-8}$
1.0	83	9	$0.36 \cdot 10^{-8}$

The function ARGLAG

Provides the deviating argument, $\alpha_1(t, y) = t\, y_1^2$.

```
        FUNCTION ARGLAG(IL,X,N,Y,RPAR,IPAR,PHI,PAST,IPAST,NRDS)
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(1) :: PAST
        INTEGER, dimension(1) :: IPAST
        DIMENSION IPAR(1),RPAR(2)
C       ARGLAG=MIN(X,X*Y(1)**2)
        ARGLAG=X*Y(1)*Y(1)
        RETURN
        END
```

The subroutine FCN

Provides the right hand side of the differential system (17).

```
        SUBROUTINE FCN(N,X,Y,F,ARGLAG,PHI,RPAR,IPAR,
     &                 PAST,IPAST,NRDS)
        IMPLICIT REAL*8 (A-H,K,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), dimension(N) :: Y
        REAL(kind=DP), dimension(N) :: F
        REAL(kind=DP), dimension(1) :: PAST
        INTEGER, dimension(1) :: IPAST
        DIMENSION IPAR(1),RPAR(2)
        EXTERNAL PHI,ARGLAG
C       Contains the parameter in the equation
        P=RPAR(1)

        CALL LAGR5(1,X,N,Y,ARGLAG,PAST,THETA,IPOS,RPAR,IPAR,
     &             PHI,IPAST,NRDS)

        Y1L1=YLAGR5(1,THETA,IPOS,PHI,RPAR,IPAR,
```

32

```
      &              PAST,IPAST,NRDS)
        Y2L1=YLAGR5(2,THETA,IPOS,PHI,RPAR,IPAR,
      &              PAST,IPAST,NRDS)

        RPAR(2)=COS(X)*(1.D0+Y1L1)+ P*Y(1)*Y2L1
C     &       +(1.D0-P)*SIN(X)*COS(X*SIN(X)*SIN(X)) -
C     &        SIN(X+X*SIN(X)*SIN(X))

        F(1)= RPAR(2)
        F(2)=-Y(2)+RPAR(2)

        RETURN
        END
```

The subroutine JACLAG

Provides the Jacobian (with respect to the variables z_1 and z_2) of the right hand side analytically. In this case we have

$$\frac{\partial f}{\partial z} = \begin{pmatrix} 0 & 0 \\ \cos t & c\, y_1 \end{pmatrix}$$

Hence both entries are relevant to the second equation and the routine is written as follows.

```
        SUBROUTINE JACLAG(N,X,Y,DFYL,ARGLAG,PHI,IVE,IVC,IVL,
      &                   RPAR,IPAR,PAST,IPAST,NRDS)
C ----- JACOBIAN OF DELAY TERMS IN THE EQUATION
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), dimension(N) :: Y
        REAL(kind=DP), dimension(4) :: DFYL
        REAL(kind=DP), dimension(1) :: PAST
        INTEGER, dimension(1) :: IPAST
        DIMENSION IPAR(1),RPAR(2)
        INTEGER, dimension(4) :: IVE,IVC,IVL
        EXTERNAL PHI,ARGLAG

        P=RPAR(1)

C       the first entry ((1)) is relevant to
C     - the first (and only) delay, whose index is hence equal to 1 (IVL(1)=1)
C     - the second equation (IVE(1)=2)
C     - the first component of the solution (IVC(1)=1)
        IVL(1)=1
        IVE(1)=2
        IVC(1)=1
C       The value of the derivative with respect to the delayed second
C       component in the first equation is finally given by
        DFYL(1)=COS(X)

C       the second entry ((2)) is relevant to
C     - the first (and only) delay, whose index is hence equal to 1 (IVL(2)=1)
C     - the second equation (IVE(2)=1)
```

```
C      - the second component of the solution (IVC(2)=2)
       IVL(2)=1
       IVE(2)=2
       IVC(2)=2
       DFYL(2)=P*Y(1)

       RETURN
       END
```

The subroutine JAC

Is not provided. In this case the standard Jacobian is approximated numerically (see the released driver program).

The initial function PHI

Provides the necessary initial functions, if required.

```
       FUNCTION PHI(I,X,RPAR,IPAR)
       IMPLICIT REAL*8 (A-H,O-Z)
       INTEGER, PARAMETER :: DP=kind(1D0)
       REAL(kind=DP), dimension(1) :: RPAR
       SELECT CASE (I)
       CASE (1)
           PHI=SIN(X)
       CASE (2)
           PHI=COS(X)
       END SELECT
       RETURN
       END
```

The mass matrix subroutine

Provides the mass matrix for the implicit DDE.

```
       SUBROUTINE QFUN(N,Q,LQ,RPAR,IPAR)
C ----  MATRIX "M" FOR THE NEUTRAL PROBLEM
       INTEGER, PARAMETER :: DP=kind(1D0)
       REAL(kind=DP), dimension(1) :: RPAR
       REAL(kind=DP), dimension(LQ,N) :: Q
       Q(1,1)=1.D0
       Q(1,2)=0.D0
       Q(2,1)=0.D0
       Q(2,2)=0.D0
       RETURN
       END
```

8.3 State dependent scalar problem.

We consider Problem 1.3.10 of [17]. It is a state dependent scalar problem with known solution on the considered interval. The equation is

$$y'(t) = y(y(t)) \qquad \text{for} \qquad t \geq 2 \qquad (18)$$

with initial condition $y(t) = 0.5$ for $t < 2$, and $y(2) = 1$. The discontinuity of the solution at $\xi_0 = 2$ creates breaking points at $\xi_1 = 4$ and $\xi_2 = 4 + 2\ln 2 \approx 5.386$. The exact solution is $y(t) = t/2$ for $\xi_0 \leq t \leq \xi_1$, $y(t) = 2\exp(t/2 - 2)$ for $\xi_1 \leq t \leq \xi_2$, and $y(t) = 4 - 2\ln(1 + \xi_2 - t)$ for $\xi_2 \leq t \leq 5.5$.

To get the same accuracy of about five digits, we applied the version 1 of the code [10] with tolerance RTOL $= 10^{-7}$, and the actual version 2 with RTOL $= 10^{-4}$. As initial step size we take $h = 0.01$. A large number of steps are needed with version 1-code to overcome breaking points, whereas with the version 2-code the breaking points are hit exactly. For the integration over the interval $[2, 5.5]$, the version 1-code requires 31 accepted and has 20 step rejections (15 to step over the first breaking point); the version 2-code gives the same accuracy with 11 accepted and 3 rejected steps. Two of them are necessary to detect the breaking points, and the other is due to error estimation. It is interesting to mention that for tolerances RTOL $> 10^{-3}$ only the first breaking point ξ_1 is computed, and for more stringent tolerances both of them are computed with high accuracy. We consider the integration interval $[2, 5.5]$ and $Atol = Rtol$.

The driver program

```
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
C --->   PARAMETERS FOR RADAR5 (FULL JACOBIAN) <---
        INTEGER, PARAMETER :: ND=1
        INTEGER, PARAMETER :: NRDENS=1
        INTEGER, PARAMETER :: NGRID=0
        INTEGER, PARAMETER :: NLAGS=1
        INTEGER, PARAMETER :: NJACL=1
        INTEGER, PARAMETER :: MXST=5000
        INTEGER, PARAMETER :: LWORK=30
        INTEGER, PARAMETER :: LIWORK=30
        REAL*4 start,finish
        REAL(kind=DP), dimension(ND) :: Y
        REAL(kind=DP), dimension(NGRID+1) :: GRID
        REAL(kind=DP), dimension(LWORK) :: WORK
        REAL(kind=DP), dimension(1) :: RTOL
        REAL(kind=DP), dimension(1) :: ATOL
        INTEGER, dimension(LIWORK) :: IWORK
        INTEGER, dimension(NRDENS+2*ND) :: IPAST
        INTEGER, dimension(22) :: ISTAT
        DIMENSION IPAR(1),RPAR(1)
        EXTERNAL  FCN,JFCN,PHI,ARGLAG,JACLAG,QFUN,SOLOUT

C ------ FILE TO OPEN ----------
        OPEN(10,FILE='cont.out')
        REWIND 10
        TOL =1.0D-6
```

```
C ----------------------------------------------------------------------
C
C --- DIMENSION OF THE SYSTEM
         N=ND
C --- COMPUTE THE STANDARD JACOBIAN ANALYTICALLY
         IJAC=0
C --- JACOBIAN IS A FULL MATRIX
         MLJAC=N
C --- DIFFERENTIAL EQUATION IS IN EXPLICIT FORM
         IMAS=0
         MLMAS=N
C --- OUTPUT ROUTINE IS USED DURING INTEGRATION
         IOUT=1
C --- INITIAL VALUES
         X=2.0D0
         Y(1)=1.0D0
C        Consistent with initial function
C --- ENDPOINT OF INTEGRATION
         XEND=5.5D0
C        XEND=2.D0
C --- REQUIRED (RELATIVE AND ABSOLUTE) TOLERANCE
         ITOL=0
         RTOL=TOL
         ATOL=RTOL
C --- INITIAL STEP SIZE
         H=1.0D-2
C --- DEFAULT VALUES FOR PARAMETERS
         IWORK=0
         WORK=0.0D0
C --- ERROR CONTROL
         IWORK(11)=1
C --- STEPSIZE RATIOS
C        WORK(8)=0.5D0
C        WORK(9)=2.0D0
C --- WORKSPACE FOR PAST
         IWORK(12)=MXST
C --- BOTH COMPONENTS USE RETARDED ARGUMENT
         IWORK(15)=NRDENS
         IPAST(1)=1
C --- CONTROL OF NEWTON ITERATION
         IWORK(3)=10
         IWORK(14)=1
C --- GRID
         IWORK(13)=NGRID
         LGRID=NGRID+1


C ----------------------------------------------------------------------
C --- CALL OF THE SUBROUTINE RADAR5
         CALL cpu_time(start)
         CALL RADAR5(N,FCN,PHI,ARGLAG,X,Y,XEND,H,
     &                    RTOL,ATOL,ITOL,
```

```
     &                      JFCN,IJAC,MLJAC,MUJAC,
     &                      JACLAG,NLAGS,NJACL,
     &                      QFUN,IMAS,MLMAS,MUMAS,SOLOUT,IOUT,
     &                      WORK,LWORK,IWORK,LIWORK,RPAR,IPAR,IDID,
     &                      GRID,LGRID,IPAST,NRDENS)
        CALL cpu_time(finish)
C ---
        WRITE (6,*) 'Time = ',finish-start
        YT=-2.D0*LOG(EXP(-2.D0)*(1.D0-XEND+LOG(4.D0*EXP(4.D0))))
C --- PRINT FINAL SOLUTION SOLUTION
        WRITE (6,90) X,Y(1),ABS(Y(1)-YT)
C --- PRINT STATISTICS
         DO J=13,20
            ISTAT(J)=IWORK(J)
         END DO
        WRITE(6,*)' ***** TOL=',RTOL,' ****'
        WRITE (6,91) (ISTAT(J),J=14,20)
        WRITE (6,92) ISTAT(13)
 90     FORMAT(1X,'X =',F8.2,'    Y =',2E23.15)
 91     FORMAT(' fcn=',I7,' jac=',I6,' step=',I6,
     &         ' accpt=',I6,' rejct=',I6,' dec=',I6,
     &         ' sol=',I7)
 92     FORMAT(' full Newt. its =',I7)
        WRITE(6,*) 'SOLUTION IS TABULATED IN FILES: sol.out & cont.out'

        CLOSE(10)
        STOP
        END
C
```

The subroutine SOLOUT

Determines the updating of the files `sol.out` and `cont.out` where the solution is stored.

```
        SUBROUTINE SOLOUT (NR,XOLD,X,HSOL,Y,CONT,LRC,N,
     &                      RPAR,IPAR,IRTRN)
C ----- PRINTS THE DISCRETE OUTPUT AND THE CONTINUOUS OUTPUT
C       AT EQUIDISTANT OUTPUT-POINTS
        IMPLICIT REAL*8 (A-H,O-Z)
        INTEGER, PARAMETER :: DP=kind(1D0)
        REAL(kind=DP), PARAMETER :: XSTEP=0.002D0
        REAL(kind=DP), dimension(N) :: Y
        REAL(kind=DP), dimension(LRC) :: CONT
        REAL(kind=DP), dimension(1) :: RPAR
C       EXTERNAL PHI
C       XOUT IS USED FOR THE DENSE OUTPUT
        COMMON /INTERN/XOUT
        IF (NR.EQ.1) THEN
           WRITE (10,99) X,Y(1)
           XOUT=XSTEP
        ELSE
```

```
10        CONTINUE
          IF (X.GE.XOUT) THEN
              WRITE (10,99) XOUT,CONTR5(1,N,XOUT,CONT,X,HSOL)
              XOUT=XOUT+XSTEP
              GOTO 10
          END IF
      END IF
99    FORMAT(1X,'X =',F12.8,'   Y =',2E18.10)
      RETURN
      END
```

The function ARGLAG

Provides the deviating argument.

```
      DOUBLE PRECISION FUNCTION ARGLAG(IL,X,N,Y,RPAR,IPAR,
     &                                 PHI,PAST,IPAST,NRDS)
      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST
      INTEGER, dimension(1) :: IPAR
      REAL(kind=DP), dimension(1) :: RPAR

      ARGLAG=Y(1)

      RETURN
      END
```

The subroutine FCN

Provides the right hand side of the differential system.

```
      SUBROUTINE FCN(N,X,Y,F,ARGLAG,PHI,RPAR,IPAR,
     &               PAST,IPAST,NRDS)
      IMPLICIT REAL*8 (A-H,K,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(N) :: F
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST,IPAR(1)
      REAL(kind=DP), dimension(1) :: RPAR
      REAL RN
      EXTERNAL PHI,ARGLAG

      CALL LAGR5(1,X,N,Y,ARGLAG,PAST,THETA,IPOS,RPAR,IPAR,
     &           PHI,IPAST,NRDS)
      Y1L1=YLAGR5(1,THETA,IPOS,PHI,RPAR,IPAR,
     &            PAST,IPAST,NRDS)
```

```
      F(1)= Y1L1
      RETURN
      END
```

The subroutine JFCN

Could provide the Jacobian (with respect to the variable y) of the right hand side analytically. In this case (IJAC=0) an approximation of the Jacobian is obtained numerically.

The subroutine JACLAG

Provides the Jacobian (with respect to the retarded variablexs $z(t) = y(\alpha(t, y))))$ of the right hand side analytically. This is stored in a one dimensional array as described in Sect. 5.5. We remark that this function could not be provided numerically (at present time). In this case we have

$$\frac{\partial f}{\partial z} = 1$$

where $\alpha(t, y) = y(t)$. Since we store such matrix in a vector (because we assume it is sparse), the routine is written as follows.

```
      SUBROUTINE JACLAG(N,X,Y,DFYL,ARGLAG,PHI,IVE,IVC,IVL,
     &                   RPAR,IPAR,PAST,IPAST,NRDS)
C ----- JACOBIAN OF DELAY TERMS IN THE EQUATION
      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(N) :: Y
      REAL(kind=DP), dimension(1) :: DFYL
      REAL(kind=DP), dimension(1) :: PAST
      INTEGER, dimension(1) :: IPAST
      REAL(kind=DP), dimension(1) :: RPAR
      INTEGER, dimension(1) :: IVE,IVC,IVL
      EXTERNAL PHI,ARGLAG
      IVL(1)=1
      IVE(1)=1
      IVC(1)=1
      DFYL(1)=1.D0
      RETURN
      END
```

The initial function PHI

Provides the initial functions.

```
      DOUBLE PRECISION FUNCTION PHI(I,X,RPAR,IPAR)
      IMPLICIT REAL*8 (A-H,O-Z)
      INTEGER, PARAMETER :: DP=kind(1D0)
      REAL(kind=DP), dimension(1) :: RPAR
      PHI=0.5D0
      RETURN
      END
```

Compilation

We create a file, called "dr-paul.f", including all previous routines, and put it in a subdirectory (called PAUL) of the main directory RADAR5, where the source and the object files of the main routines of the code are installed. The following makefile is also created in the directory PAUL,

```
FC = f90 FCFLAGS = -c DEBUGFLAGS = -g LIB = /lib /usr/lib .f.o:
        $(FC) $(FCFLAGS) $(DEBUGFLAGS) $*.f

OBJ2 =    ../radar5.o ../dc_decdel.o ../decsol.o OBJ1 = dr-paul.o
prog : $(OBJ1)
        $(FC) $(DEBUGFLAGS) -o driver $(OBJ1) $(OBJ2)
```

The simple use of the Unix command **make** generates the compilation and the linking phase for the program. The executable file is called "driver". In case of troubles check whether the fortran libraries are stored in the directories `/lib` and `/usr/lib`.

Execution

Executing with $Rtol = 10^{-4}$ the program driver generates the following output.

```
STARTING INTEGRATION...
NUMBER OF PRESCRIBED GRID POINTS:          0
NUMBER OF DELAYED COMPONENTS:          1
INTEGRATION...
        3  COMPUTED BREAKING POINTS:
Time =   0.0000000E+00
X =    5.50    Y = 0.424141226333301E+01  0.317235091529255E-07
 ***** TOL= 1.000000000000001E-006  ****
fcn=    120 jac=      6 step=    17 accpt=    13 rejct=     2 dec=    16 sol=    35
full Newt. its =      0
SOLUTION IS TABULATED IN FILES: sol.out & cont.out
```

The program also generates two output files, sol.out and cont.out, which contain - respectively - the discrete computed solution and an approximation of the solution on a uniform mesh with density chosen by the user.

Table 1 illustrates the global number of steps (accepted and rejected) and the obtained accuracy by the two different versions of the code (V1 and V2) for different tolerances (and an initial stepsize $h = 10^{-6}$). The gain obtained by the automatic computation of breaking point is quite evident.

9   Copyright Notice

Table 3: Statistics for the problem (18) with different tolerances.

TOL	steps-V1	accuracy	steps-V2	accuracy
$1e-4$	35	$0.14 \cdot 10^{-3}$	16	$0.20 \cdot 10^{-5}$
$1e-7$	53	$0.27 \cdot 10^{-5}$	21	$0.12 \cdot 10^{-7}$
$1e-10$	89	$0.20 \cdot 10^{-6}$	39	$0.17 \cdot 10^{-9}$
$1e-12$	127	$0.16 \cdot 10^{-7}$	68	$0.33 \cdot 10^{-10}$

1. RADAR5 may only be used for educational and research purposes by the person or organization to whom they are supplied (the "User").

2. Code that uses RADAR5 (a code that calls subroutines in RADAR5) does not fall under this Copyright Notice. However, code derived from RADAR5 does fall under this Copyright Notice.

3. RADAR5 is provided without warranty of any kind, either expressed or implied. Neither the University of Geneva nor the Authors shall be liable for any direct or consequential loss or damage whatsoever arising out of the use of RADAR5 by the User.

4. Any use of RADAR5 in any commercial application shall be subject to prior written agreement between the Authors and the User on suitable terms and conditions.

10   Final comments

As soon as you download a copy of RADAR5, please send email to us at `nicola.guglielmi@gssi.it` `(guglielm@univaq.it) or Ernst.Hairer@math.unige.ch`, so that we can put you on a mailing list for news and updates. Please include your postal address as well.

While we would appreciate hearing any bug reports and comments, we cannot promise that we can fix any specific bugs. We would also appreciate receiving copies of publications that refer to the package.

If you find this software to have a different performance than the software you were previously using, we would be very interested in getting copies of your delay equations. Of particular interest are large stiff problems coming from real-life applications.

Acknowledgments

References

[1] C.T.H. Baker, J.C. Butcher, C.A.H. Paul, *Experience of STRIDE applied to delay differential equations*, Technical Report 208, Univ. Manchester, 1992.

[2] A. Bellen, M. Zennaro, *Numerical Methods for Delay Differential Equations*, Numerical Mathematics and Scientific Computation Series, Oxford University Press, 2003.

[3] G.A. Bocharov, G.I. Marchuk, A.A. Romanyukha, *Numerical solution by LMMs of stiff delay differential systems modelling an immune response*, Numer. Math. 73, 131–148 (1996).

[4] R.N. Castleton, L.J. Grimm, *A first order method for differential equations of neutral type*, Math. Comp. 27, 571–577 (1973).

[5] L.E. El'sgol'ts, S.B. Norkin: *Introduction to the theory and application of differential equations with deviating arguments*, Academic Press, New York, 1973.

[6] W.H. Enright, H. Hayashi, *A delay differential equation solver based on a continuous Runge-Kutta method with defect control*, Numer. Algorithms 16, 349–364 (1998).

[7] I. Epstein, Y. Luo, *Differential delay equations in chemical kinetics. Nonlinear models: the cross-shaped phase diagram and the Oregonator*, J. Chemical Physics 95, 244–254 (1991).

[8] A. Feldstein and K.W. Neves, *High order methods for state-dependent delay differential equations with nonsmooth solutions*, SIAM J. Numer. Anal. 21, 844–863 (1984).

[9] N. Guglielmi, E. Hairer, *Order stars and stability for delay differential equations*, Numer. Math. 83, 371–383 (1999).

[10] N. Guglielmi and E. Hairer, *Implementing Radau II-A methods for stiff delay differential equations*, Computing 67, 1–12 (2001).

[11] N. Guglielmi and E. Hairer, *Computing breaking points in implicit delay differential equations*, Advances in Computational Mathematics , (2008).

[12] E. Hairer, S.P. Nørsett, G. Wanner, *Solving Ordinary Differential Equations I. Nonstiff Problems, 2nd edition*, Springer Series in Computational Mathematics **8**, Springer-Verlag Berlin, 1993.

[13] E. Hairer, G. Wanner, *Solving Ordinary Differential Equations II. Stiff and Differential-Algebraic Problems, 2nd edition*, Springer Series in Computational Mathematics **14**, Springer-Verlag Berlin, 1996.

[14] R. Hauber, *Numerical treatment of retarded differential-algebraic equations by collocation methods*, Adv. Comput. Math. 7, 573–592 (1997).

[15] Z. Jackiewicz, E. Lo, *The numerical solution of neutral functional-differential equations by Adams predictor-corrector methods*, Appl. Numer. Math. 8, 477–491 (1991).

[16] M. Okamoto, K. Hayashi, *Frequency conversion mechanism in enzymatic feedback systems*, J. Theor. Biol. 108, 529–537 (1984).

[17] C.A.H Paul, *A test set of functional differential equations*, Technical Report 243, Univ. Manchester (1994).

[18] P. Waltman, *A threshold model of antigen–stimulated antibody production*, Theoretical Immunology (Immunology Ser. 8), Dekker, New York, 437–453 (1978).

[19] R. Weiner, K. Strehmel, *A type insensitive code for delay differential equations basing on adaptive and explicit Runge-Kutta interpolation methods*, Computing 40, 255–265 (1988).

[20] M. Zennaro, *P-stability properties of Runge-Kutta methods for delay differential equations*, Numer. Math. 49, 305–318 (1986).