vobiz endpoints 6

Created	@March 17, 2026 2:08 AM
Class	vobiz

IP Access Control Lists

Manage IP-based authentication for your SIP trunks using IP whitelisting.

Introduction

IP Access Control Lists (IP ACLs) provide IP-based authentication for your SIP trunks. By whitelisting specific IPv4 addresses, you can allow calls from trusted sources without requiring username/password authentication. This is ideal for scenarios with static IP addresses such as PBX systems, SIP gateways, or carrier connections.

Multiple IP addresses can be whitelisted for a single trunk, allowing connections from different locations or devices. Each IP ACL entry can be individually enabled or disabled, providing flexible control over which sources can authenticate to your trunk.

IPv4 Only: Currently, IP ACL only supports IPv4 addresses. IPv6 support is not available at this time.

Static IPs Required: IP-based authentication works best with static IP addresses. If your IP address changes frequently, consider using credential-based authentication instead.

Use Cases

Office PBX Systems

Perfect for on-premises PBX systems with static public IP addresses. Simplifies configuration by eliminating the need to manage credentials on the PBX.

SIP Gateway Integration

Ideal for SIP gateways and Session Border Controllers (SBCs) that operate from known, fixed IP addresses. Provides faster authentication without credential exchange.

Carrier Interconnections

Commonly used for trunk connections with telecom carriers who provide calls from specific IP addresses. Standard practice in carrier-to-carrier peering.

Data Center Deployments

Excellent for cloud or data center deployments where your infrastructure has dedicated static IPs. Reduces authentication overhead and improves performance.

IP ACL vs Credentials

Feature	IP ACL	Credentials
Best For	Static IP addresses	Dynamic IP addresses
Setup Complexity	Simple (no client config)	Moderate (configure username/password)
Security Level	Good (IP-based)	Better (cryptographic)
Performance	Faster (no auth exchange)	Slightly slower (auth required)
NAT Compatibility	Limited (public IP only)	Excellent (works anywhere)
Combined Use	Both can be used together for maximum security	

Maximum Security:
For production environments, consider using both IP ACL and credentials together. This requires authentication from both a whitelisted IP address AND valid credentials, providing defense in depth.

Available Operations

1

The IP ACL Object

Learn about the structure and attributes of IP ACL objects

2

Create IP ACL

Whitelist a new IPv4 address for trunk authentication

3

Retrieve All IP ACLs

List all IP ACL entries for a trunk with pagination support

4

Update IP ACL

Modify existing IP ACL properties like IP address, status, or description

5

Delete IP ACL

Permanently remove an IP address from the whitelist

NAT Considerations:
If your SIP client is behind NAT, the source IP address will be the public IP of your router/firewall, not the private IP of the device.

You can find your public IP by visiting services like `https://api.ipify.org`

The IP ACL Object

Complete structure and attributes of an IP Access Control List object.

The
IP ACL object represents a whitelisted IPv4 address that can authenticate to a specific trunk without requiring credentials. Each IP ACL entry is associated with a trunk and contains the IP address along with optional metadata like description and enabled status.

IPv4 Only: The `ip_address`
field only accepts IPv4 addresses in standard dotted-decimal notation (e.g., 192.168.1.1). IPv6 addresses are not currently supported.

Public IPs:
Ensure you whitelist the public IP address, not private/internal IPs. For devices behind NAT, use the router's public IP address.

Attributes

IP ACL Attributes

Parameter	Type	Description
`id` optional	string (UUID)	Unique identifier for the IP ACL entry. Automatically generated upon creation.
`trunk_id` optional	string (UUID)	The ID of the trunk this IP ACL entry belongs to.
`ip_address` optional	string	IPv4 address in dotted-decimal notation (e.g., 203.0.113.50). Required field. Must be a valid IPv4 address.
`description` optional	string	Optional description providing context about the IP address, such as "Office static IP" or "PBX server".
`enabled` optional	boolean	Whether the IP ACL entry is active and can be used for authentication. Default: true.
`created_at` optional	string (ISO 8601)	Timestamp when the IP ACL entry was created. Format: YYYY-MM-DDTHH:mm:ssZ (UTC timezone).
`updated_at` optional	string (ISO 8601)	Timestamp of the last update to the IP ACL entry. Format: YYYY-MM-DDTHH:mm:ssZ (UTC timezone).

Example

IP ACL Object Response

A typical IP ACL object as returned by the API:

IP ACL Object

```
{
  "id": "c1d2e3f4-a5b6-7890-cdef-1234567890ab",
  "trunk_id": "bfab10fb-cb97-488b-9c63-989c32980b0f",
  "ip_address": "203.0.113.50",
  "description": "Office static IP",
  "enabled": true,
  "created_at": "2025-01-15T10:40:15Z",
  "updated_at": "2025-01-15T10:40:15Z"
}
```

Best Practices:

- Only whitelist IP addresses you control and trust
- Use descriptive descriptions to identify each IP's purpose
- Regularly audit your IP ACL list and remove unused entries
- For dynamic IPs, consider using credential authentication instead
- Test connectivity after adding new IP addresses
- Disable rather than delete entries when temporarily blocking access

Finding Your Public IP: If you're unsure of your public IP address, you can check it by running `curl https://api.ipify.org` from your command line or visiting the URL in your browser.

Create IP ACL

Whitelist a new IPv4 address for IP-based trunk authentication.

This
 API creates a new IP ACL entry to whitelist an IPv4 address for authentication on the account. Once added, calls originating from the whitelisted IP address will be allowed without requiring credential authentication (unless both authentication methods are required).

Public IP Required:
Make sure to whitelist your public IP address, not a private/internal IP. If you're behind NAT, use your router's public IP address.

IPv4 Only: Only IPv4 addresses are supported. IPv6 addresses will be rejected with a validation error.

HTTP Request

POST `https://api.vobiz.ai/api/v1/account/{account_id}/ip-acl`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request Parameters

Request Parameters

Parameter	Type	Description
`ip_address` required	string	IPv4 address in dotted-decimal notation (e.g., 203.0.113.50 or 192.168.1.100). Must be a valid IPv4 format.
`enabled` optional	boolean	Whether the IP ACL entry is active and can be used for authentication. Default: true. Set to false to create a disabled entry.
`description` optional	string	Optional description providing context about the IP address, such as "Office static IP", "PBX server", or "Carrier connection".

Response

Returns the complete IP ACL object including the auto-generated `id` UUID and timestamps.

Response - 201 Created

```
{
  "id": "c1d2e3f4-a5b6-7890-cdef-1234567890ab",
```

```
  "ip_address": "192.168.1.100",
  "description": "Office IP address",
  "enabled": true,
  "created_at": "2025-01-22T11:20:30Z",
  "updated_at": "2025-01-22T11:20:30Z"
}
```

Examples

cURL - Basic IP ACL

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "ip_address": "203.0.113.50",
    "description": "Office static IP",
    "enabled": true
  }'
```

cURL - PBX Server IP

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "ip_address": "198.51.100.42",
    "description": "FreePBX server in data center",
    "enabled": true
  }'
```

Error Response (400 Bad Request): If the IP address format is invalid:

Error Response - 400 Bad Request

```
{
  "error": "Invalid IP address format",
  "code": 400
}
```

Next Steps:

- Save the IP ACL `id` for future operations
- Verify the IP address is correct before testing
- Test connectivity by making a call from the whitelisted IP
- Monitor authentication logs to confirm IP-based auth is working

NAT Tip: If you're behind NAT or a firewall, determine your public IP with: `curl https://api.ipify.org`

Retrieve All IP ACLs

List all IP ACL entries for a trunk with pagination support.

This API retrieves a paginated list of all IP ACL entries associated with the account. Use this endpoint to view all whitelisted IP addresses, audit your IP access configuration, and manage multiple IP ACL entries.

Security Audit: Regularly review this list to ensure only authorized IP addresses are whitelisted. Remove any entries that are no longer needed.

HTTP Request

GET `https://api.vobiz.ai/api/v1/account/{account_id}/trunks/ip-acl`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

Request Parameters

Parameter	Type	Description
`limit` optional	integer	Number of results per page. Default: 20. Maximum:

Parameter	Type	Description
		100.
`offset` optional	integer	Number of results to skip for pagination. Default: 0. Use with limit for page navigation.

Response

Returns a paginated list of IP ACL objects with metadata about pagination state.

Response - 200 OK


```
{
  "meta": {
    "limit": 20,
    "offset": 0,
    "total_count": 5
  },
  "objects": [
    {
      "id": "c1d2e3f4-a5b6-7890-cdef-1234567890ab",

      "ip_address": "203.0.113.50",
      "description": "Office static IP",
      "enabled": true,
      "created_at": "2025-01-15T10:40:15Z",
      "updated_at": "2025-01-15T10:40:15Z"
    },
    {
      "id": "d2e3f4a5-b6c7-8901-def1-234567890abc",

      "ip_address": "198.51.100.42",
      "description": "PBX server in data center",
      "enabled": true,
      "created_at": "2025-01-16T09:20:30Z",
      "updated_at": "2025-01-16T09:20:30Z"
    },
    {
      "id": "e3f4a5b6-c7d8-9012-ef12-34567890abcd",

      "ip_address": "192.0.2.100",
      "description": "Backup office IP",
      "enabled": false,
      "created_at": "2025-01-17T14:15:45Z",
      "updated_at": "2025-01-20T11:30:00Z"
    }
  ]
}
```

Examples

cURL - Default Pagination

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{Auth_ID}/trunks/ip-acl" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

cURL - Custom Pagination

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{Auth_ID}/trunks/ip-acl?limit=50&offset=0" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Pagination Tip: Use `total_count` from the meta object to calculate total pages. For page 2 with limit 20, use offset=20.

Monitoring: Review the `enabled` field for each entry. Disabled entries appear in the list but won't allow authentication. Check `updated_at` to see when entries were last modified.

Update IP ACL

Modify an existing IP ACL entry's properties.

This API updates an existing IP ACL entry. You can change the whitelisted IP address, modify the description, or enable/disable the entry. All fields are optional - only include the fields you want to update.

Partial Updates: You can update any combination of fields. Fields not included in the request will retain their current values.

Disable vs Delete: To temporarily block an IP without losing the configuration, set `enabled: false` instead of deleting the entry.

HTTP Request

PUT `https://api.vobiz.ai/api/v1/account/{account_id}/ip-acl/{ip_acl_id}`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request Parameters

All parameters are optional. Only include the fields you want to update.

Request Parameters

Parameter	Type	Description
`ip_address` optional	string	New IPv4 address in dotted-decimal notation. Must be a valid IPv4 format if provided.
`enabled` optional	boolean	Whether the IP ACL entry is active. Set to false to disable without deleting.
`description` optional	string	Updated description for the IP ACL entry.

Response

Returns the complete updated IP ACL object with the new values and an updated `updated_at` timestamp.

Response - 200 OK

```
{
  "id": "c1d2e3f4-a5b6-7890-cdef-1234567890ab",

  "ip_address": "192.168.1.200",
  "description": "Updated office IP address",
  "enabled": false,
  "created_at": "2025-01-15T10:40:15Z",
  "updated_at": "2025-01-22T11:45:20Z"
}
```

Examples

cURL - Update IP Address

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl/c1d2e3f4-a5b6-7890-cdef-1234567890ab \
```

```
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "ip_address": "192.168.1.200",
    "description": "Updated office IP after ISP change"
  }'
```

cURL - Disable IP ACL Entry

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl/c1d2e3f4-a5b6-7890-cdef-1234567890ab \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "enabled": false
  }'
```

cURL - Update Description Only

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl/c1d2e3f4-a5b6-7890-cdef-1234567890ab \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "description": "Main office - Building A"
  }'
```

IP Address Changes:
If you update the IP address, existing authenticated connections may be disconnected. Plan IP changes during maintenance windows.

Error Response (400 Bad Request): If the new IP address format is invalid:

Error Response - 400 Bad Request

```
{
  "error": "Invalid IP address format",
  "code": 400
}
```

Best Practice:
When changing IP addresses, add the new IP first, test connectivity, then disable or delete the old IP entry to avoid service interruption.

Delete IP ACL

Permanently remove an IP address from the trunk whitelist.

This API permanently deletes an IP ACL entry from a trunk. Once deleted, the IP address will no longer be whitelisted for authentication, and calls from this IP will be rejected unless other authentication methods (like credentials) are configured and valid.

Warning: This action is permanent and cannot be undone. Active connections from this IP address may be immediately disconnected.

Alternative: Consider disabling the IP ACL entry instead of deleting it by setting `enabled: false`. This preserves the configuration for future use.

HTTP Request

DELETE `https://api.vobiz.ai/api/v1/account/{account_id}/ip-acl/{ip_acl_id}`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Response

Returns HTTP 204 No Content on successful deletion. No response body is returned.

Response - 204 No Content

`No Content`

Examples

cURL - Delete IP ACL

cURL Request

```
curl -X DELETE https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl/c1d2e3f4-a5b6-7890-cdef-1234567890ab \
```

```
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Error Response (404 Not Found): If the IP ACL ID doesn't exist or was already deleted:

Error Response - 404 Not Found

```
{
  "error": "IP ACL not found",
  "code": 404
}
```

Before Deleting:

- Verify you have the correct IP ACL ID
- Ensure you have alternative authentication methods configured (if needed)
- Check if there are active connections from this IP
- Consider temporarily disabling instead of deleting

After Deletion:

- The IP address is immediately removed from the whitelist
- New authentication attempts from this IP will fail
- Active calls may be terminated depending on trunk configuration
- The IP ACL entry cannot be recovered - create a new one if needed

Alternative - Disable Instead: To temporarily block an IP without losing the configuration:

Alternative - Disable IP ACL

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/ip-acl/IP_ACL_ID \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{"enabled": false}'
```

Origination URIs

Configure outbound SIP routing destinations for your trunk calls.

Introduction

Origination URIs define the SIP endpoints where outbound calls from your trunk will be routed. Each URI represents a destination carrier, SIP provider, PBX system, or other SIP-capable endpoint that will receive your outbound traffic.

You can configure multiple origination URIs per trunk to implement load balancing and failover strategies. The system uses priority and weight values to intelligently distribute traffic across your configured destinations, ensuring high availability and optimal resource utilization.

Priority: Lower numbers indicate higher priority. URIs with priority 1 are tried first, then priority 2 as failover, and so on.

Weight: Used for load balancing among URIs with the same priority. Higher weight values receive proportionally more traffic. For example, a URI with weight 20 receives twice the traffic of one with weight 10.

Use Cases

Carrier Interconnection

Route outbound calls to your upstream carrier or SIP provider. Configure primary and backup carriers with different priorities to ensure uninterrupted service if your primary carrier experiences issues.

PBX Integration

Connect your trunk to an on-premises or cloud PBX system. Route calls to your FreeSWITCH, Asterisk, or other SIP-capable PBX for call processing, IVR, call routing, and other telephony features.

Load Balancing

Distribute call traffic across multiple SIP servers using weight-based load

balancing. Configure multiple URIs with the same priority but different weights to control traffic distribution ratios.

Geographic Redundancy

Configure origination URIs pointing to SIP servers in different geographic regions. If one region becomes unavailable, calls automatically fail over to servers in other regions based on priority settings.

Available Operations

1

The Origination URI Object

Learn about the structure and attributes of origination URI objects

2

Create Origination URI

Add new SIP destination endpoints for outbound call routing

3

Retrieve All Origination URIs

List all origination URIs associated with a trunk with pagination support

4

Update Origination URI

Modify URI, priority, weight, or status of existing origination URIs

5

Delete Origination URI

Permanently remove an origination URI from a trunk

Quick Start: Begin by reviewing the origination URI object structure, then create your first URI to start routing outbound calls. Configure multiple URIs with different priorities for failover.

The Origination URI Object

Complete structure and attributes of an Origination URI object.

The
Origination URI object represents a SIP endpoint destination for outbound calls. Each URI specifies where your trunk should route outbound traffic, along with priority and weight settings that control failover behavior and load distribution.

SIP URI Format: Origination URIs must follow the standard SIP URI format: `sip:user@host:port` or `sip:host:port`

Examples: `sip:provider@sip.example.com:5060`, `sip:192.168.1.100:5060`

Attributes

Origination URI Attributes

Parameter	Type	Description
`id` optional	string (UUID)	Unique identifier for the origination URI. Automatically generated upon creation.
`trunk_id` optional	string (UUID)	The trunk identifier that owns this origination URI.
`uri` optional	string	The SIP URI destination. Required field. Must follow format: sip:user@host:port or sip:host:port. Examples: sip:provider@sip.example.com:5060, sip:10.0.0.1:5060
`priority` optional	integer	Routing priority (lower = higher priority). URIs with priority 1 are tried first, then priority 2 as failover. Default: 1.
`weight` optional	integer	Load balancing weight. Used to distribute traffic among URIs with the same priority. Higher values receive more traffic. Default: 10.

Parameter	Type	Description
`enabled` optional	boolean	Whether the URI is active and can be used for routing calls. Default: true.
`created_at` optional	string (ISO 8601)	Timestamp when the origination URI was created. Format: YYYY-MM-DDTHH:mm:ssZ (UTC timezone).
`updated_at` optional	string (ISO 8601)	Timestamp of the last update to the origination URI. Format: YYYY-MM-DDTHH:mm:ssZ (UTC timezone).

Example

Origination URI Object Response

A typical origination URI object as returned by the API:

Origination URI Object

```
{
  "id": "e1f2a3b4-c5d6-7890-efab-567890123456",
  "trunk_id": "bfab10fb-cb97-488b-9c63-989c32980b0f",
  "uri": "sip:provider@sip.example.com:5060",
  "priority": 1,
  "weight": 10,
  "enabled": true,
  "created_at": "2025-01-15T10:45:30Z",
  "updated_at": "2025-01-15T10:45:30Z"
}
```

Priority-Based Routing:
The system tries URIs in order of priority (lowest number first). If all priority 1 URIs fail, it attempts priority 2, and so on.

Weight-Based Load Balancing:
Among URIs with the same priority, traffic is distributed proportionally based on weight. A URI with weight 20 receives twice the traffic of one with weight 10.

Example: With two URIs at priority 1 (weights 10 and 20), the first receives ~33% of traffic and the second receives ~67%.

Create Origination URI

Add a new SIP destination endpoint for outbound call routing.

This API creates a new origination URI (SIP destination) for routing outbound calls from your trunk. The URI must be a valid SIP endpoint in the format `sip:user@host:port` or `sip:host:port`.

Valid SIP URI Formats:

- `sip:provider@sip.example.com:5060` - Domain with user
- `sip:192.168.1.100:5060` - IP address
- `sip:trunk@sip.carrier.net:5061` - Custom port

Invalid Formats:

- `http://sip.example.com` - Wrong protocol
- `provider@sip.example.com:5060` - Missing sip: prefix
- `sip:example.com` - Missing port number

HTTP Request

POST `https://api.vobiz.ai/api/v1/account/{account_id}/origination-uris`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request Parameters

Request Parameters

Parameter	Type	Description
`uri` required	string	SIP URI destination in format sip:user@host:port or sip:host:port. Must be a valid, reachable SIP endpoint. Examples:

Parameter	Type	Description
		sip:provider@sip.example.com:5060, sip:192.168.1.100:5060
`priority` optional	integer	Routing priority (lower = higher priority). Default: 1. Use priority 1 for primary routes, priority 2 for backup/failover routes.
`weight` optional	integer	Load balancing weight. Default: 10. Higher values receive proportionally more traffic among URIs with the same priority. Example: weight 20 gets 2x traffic vs weight 10.
`enabled` optional	boolean	Whether the URI is active for routing. Default: true. Set to false to temporarily disable without deleting.

Response

Returns the complete origination URI object including the auto-generated `id` UUID and timestamps.

Response - 201 Created

```
{
  "id": "e1f2a3b4-c5d6-7890-efab-567890123456",
```

```
  "uri": "sip:provider@sip.example.com:5060",
  "priority": 1,
  "weight": 10,
  "enabled": true,
  "created_at": "2025-01-22T12:00:15Z",
  "updated_at": "2025-01-22T12:00:15Z"
}
```

Examples

cURL - Primary Origination URI

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
```

```
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:provider@sip.example.com:5060",
    "priority": 1,
    "weight": 10,
    "enabled": true
  }'
```

cURL - Failover URI with Lower Priority

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:backup@sip-backup.example.com:5060",
    "priority": 2,
    "weight": 10,
    "enabled": true
  }'
```

cURL - Load Balancing Configuration

Create two URIs with the same priority but different weights for 70/30 traffic split:

cURL Request - Primary (70% traffic)

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:server1@sip.example.com:5060",
    "priority": 1,
    "weight": 70
  }'
```

cURL Request - Secondary (30% traffic)

```
curl -X POST https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:server2@sip.example.com:5060",
    "priority": 1,
    "weight": 30
  }'
```

Error Response (400 Bad Request): If SIP URI format is invalid:

Error Response - 400 Bad Request

```
{
  "error": "Invalid SIP URI format. Expected: sip:user@host:port",
  "code": 400
}
```

Best Practices:

- Configure at least 2 origination URIs for redundancy (one primary, one failover)
- Use priority 1 for primary destinations, priority 2 for backup/failover
- Adjust weights to distribute load across multiple carriers or servers
- Test connectivity to each URI before enabling in production

Retrieve All Origination URIs

List all origination URIs associated with a trunk.

This API retrieves all origination URIs configured for a specific trunk. The response includes routing configuration such as priority, weight, and enabled status for each URI. Use pagination parameters to control the number of results returned.

Use Case:
List all routing destinations to audit your trunk's outbound call routing configuration, verify failover setup, or analyze load balancing distribution across multiple carriers.

HTTP Request

GET `https://api.vobiz.ai/api/v1/account/{account_id}/trunks/origination-uris`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

Request Parameters

Parameter	Type	Description
`limit` optional	integer	Maximum number of URIs to return per page. Default: 20. Range: 1-100.
`offset` optional	integer	Number of URIs to skip before starting to return results. Default: 0. Used for pagination.

Response

Returns a paginated list of origination URI objects with metadata about the result set.

Response - 200 OK


```
{
  "meta": {
    "limit": 20,
    "offset": 0,
    "total_count": 3
  },
  "objects": [
    {
      "id": "e1f2a3b4-c5d6-7890-efab-567890123456",

      "uri": "sip:provider@sip.example.com:5060",
      "priority": 1,
      "weight": 10,
      "enabled": true,
      "created_at": "2025-01-15T10:45:30Z",
      "updated_at": "2025-01-15T10:45:30Z"
    },
    {
      "id": "f2g3h4i5-j6k7-8901-lmno-678901234567",

      "uri": "sip:backup@sip-backup.example.com:5060",
      "priority": 2,
      "weight": 10,
      "enabled": true,
      "created_at": "2025-01-15T11:00:00Z",
      "updated_at": "2025-01-15T11:00:00Z"
    },
    {
      "id": "g3h4i5j6-k7l8-9012-mnop-789012345678",
```

```
      "uri": "sip:secondary@sip.example.com:5060",
      "priority": 1,
      "weight": 20,
      "enabled": true,
      "created_at": "2025-01-15T11:15:00Z",
      "updated_at": "2025-01-15T11:15:00Z"
    }
  ]
}
```

Example Routing Logic:

- Priority 1 URIs (first and third) handle primary traffic
- Among priority 1, traffic is split 33% to first URI (weight 10) and 67% to third URI (weight 20)
- Priority 2 URI (second) serves as failover if all priority 1 URIs fail

Examples

cURL - List All URIs

cURL Request

```
curl -X GET https://api.vobiz.ai/api/v1/account/{Auth_ID}/trunks/origination-uris \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

cURL - Paginated Results

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{Auth_ID}/trunks/origination-uris?
limit=10&offset=0" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Pagination:

- Use `limit` to control page size
- Use `offset` to skip to a specific page
- Check `total_count` in meta to determine total URIs
- Calculate total pages: `Math.ceil(total_count / limit)`

Update Origination URI

Modify an existing origination URI's configuration.

This
 API updates an existing origination URI. You can modify the SIP destination, adjust priority and weight for routing optimization, or enable/disable the URI without deleting it. All fields are optional - only include the fields you want to change.

Common Use Cases:

- Change URI priority to implement failover strategies or promote a backup URI to primary
- Adjust weights to rebalance traffic distribution across multiple carriers
- Update the SIP destination when switching carriers or changing server addresses
- Temporarily disable a URI (enabled: false) without deleting it for maintenance windows

HTTP Request

PUT `https://api.vobiz.ai/api/v1/account/{account_id}/origination-uris/{uri_id}`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request Parameters

All parameters are optional. Only include fields you want to update.

Request Parameters

Parameter	Type	Description
`uri` optional	string	Updated SIP URI destination in format sip:user@host:port or sip:host:port. Must be a valid, reachable SIP endpoint.
`priority` optional	integer	Updated routing priority (lower = higher priority). Change to promote/demote URIs in failover hierarchy.
`weight` optional	integer	Updated load balancing weight. Adjust to rebalance traffic distribution among same-priority URIs.
`enabled` optional	boolean	Updated active status. Set to false to temporarily disable without deleting.

Response

Returns the complete updated origination URI object with the new values and an updated timestamp.

Response - 200 OK

```
{
  "id": "e1f2a3b4-c5d6-7890-efab-567890123456",

  "uri": "sip:updated@sip.example.com:5060",
  "priority": 2,
  "weight": 20,
  "enabled": false,
  "created_at": "2025-01-15T10:45:30Z",
  "updated_at": "2025-01-22T12:30:45Z"
}
```

Examples

cURL - Change Priority for Failover

Promote a backup URI (priority 2) to primary (priority 1):

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
```

```
    "priority": 1
  }'
```

cURL - Adjust Load Balancing Weight

Increase weight to shift more traffic to this URI:

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "weight": 50
  }'
```

cURL - Update SIP Destination

Change the URI to point to a different carrier or server:

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:newcarrier@sip.newprovider.com:5060"
  }'
```

cURL - Temporarily Disable URI

Disable URI for maintenance without deleting it:

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "enabled": false
  }'
```

cURL - Multiple Updates

Update multiple fields in a single request:

cURL Request

```
curl -X PUT https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "uri": "sip:updated@sip.example.com:5060",
    "priority": 1,
    "weight": 30,
    "enabled": true
  }'
```

Failover Strategy Example:

- If primary carrier fails, update priority from 2 to 1 to promote backup to primary
- After carrier maintenance, restore original priority settings
- Use enabled: false during planned maintenance instead of changing priorities
- Test connectivity before re-enabling URIs after maintenance

Delete Origination URI

Permanently remove an origination URI from a trunk.

This API permanently deletes an origination URI from your trunk. Once deleted, the trunk will no longer route outbound calls to this destination. The operation cannot be undone - deleted URIs must be recreated if needed again.

Warning: Deleting an origination URI is permanent and cannot be reversed. Ensure you have at least one active URI remaining for outbound calls to continue functioning.

Important: If you delete all origination URIs, your trunk will not be able to route any outbound calls. Always maintain at least one active URI for production trunks.

Alternative: Instead of deleting, consider setting `enabled: false` to temporarily disable the URI without losing the configuration.

This allows you to re-enable the URI later without needing to reconfigure the SIP destination, priority, and weight.

HTTP Request

DELETE `https://api.vobiz.ai/api/v1/account/{account_id}/origination-uris/{uri_id}`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Response

Returns HTTP 204 No Content on successful deletion. No response body is returned.

Response - 204 No Content

```
No Content
```

Examples

cURL - Delete Origination URI

cURL Request

```
curl -X DELETE https://api.vobiz.ai/api/v1/account/{Auth_ID}/origination-uris/e1f2a3b4-c5d6-7890-efab-567890123456 \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Error Response (404 Not Found): If the origination URI does not exist:

Error Response - 404 Not Found

```
{
  "error": "Origination URI not found",
  "code": 404
}
```

Before Deleting:

- List all origination URIs to verify you're deleting the correct one
- Ensure at least one other active URI exists for outbound call routing
- Consider the impact on failover and load balancing configuration
- Save URI configuration details if you might need to recreate it later

Safe Deletion Workflow:

1. First, set `enabled: false` on the URI to disable it
2. Monitor outbound calls to ensure remaining URIs handle traffic correctly
3. Wait for a testing period (e.g., 24 hours) to confirm no issues
4. If no problems occur, proceed with permanent deletion
5. If issues arise, re-enable the URI before it's deleted

Production Best Practices:

- Never delete the last remaining active origination URI on a production trunk
- Always maintain at least 2 URIs (one primary, one backup) for redundancy
- Document the reason for deletion and the URI configuration in your change log
- Plan deletions during maintenance windows to minimize potential impact