vobiz endpoints 2

Created	@March 17, 2026 12:44 AM
Class	vobiz

Account

The Account object lets you perform actions on your Vobiz account.

Key Features

- View account type (standard or developer) and billing mode (prepaid or postpaid)
- Monitor account balance and credit information
- Access auth credentials and resource URIs for API integration

Base URI

Base URI

`https://api.vobiz.ai/api/v1/Account/`

Account Operations

The Account Object

View the structure and attributes of the Account object including account type, billing mode, credits, and timezone.

Retrieve Account Details

GET request to retrieve all details of your Vobiz account including balance, auth credentials, and settings.

The Account Object

The
 Account object contains all the information about your Vobiz account, including authentication credentials, pricing tier, verification status,
 and timestamps.

Attributes

Account Attributes

Parameter	Type	Description
`id` optional	string	Unique identifier for the account (e.g., "MA_XXXXXX").
`api_id` optional	string	Internal API reference identifier.
`name` optional	string	Name of the account or company.
`email` optional	string	Email address associated with the account.
`phone` optional	string	Primary phone number for the account.
`type` optional	string	Account type (e.g., "MASTER", "SUB_ACCOUNT").
`auth_id` optional	string	Authentication ID used for API requests.
`auth_secret` optional	string	Secret key for authentication (only shown in secure contexts).
`auth_token_expire_time` optional	string	ISO 8601 timestamp when the current auth token expires.
`description` optional	string | null	Optional description or notes for the account.
`company` optional	string	Full legal name of the company.
`address | city | state | zip_code` optional	string	Physical location details for the account.
`country` optional	string | null	Country code or name for the

Parameter	Type	Description
		account location.
`timezone` optional	string	Local timezone of the account (e.g., "America/Los_Angeles").
`account_type` optional	string	Billing model (e.g., "PREPAID", "POSTPAID").
`postpaid` optional	boolean	Indicates if the account is on a postpaid billing plan.
`auto_recharge` optional	boolean	Whether auto-recharge is enabled for prepaid accounts.
`enabled` optional	boolean	Whether the account is generally enabled for service.
`is_active` optional	boolean	Whether the account is currently active.
`is_verified` optional	boolean	Whether the account identity has been verified.
`is_trial_account` optional	boolean	Indicates if the account is a trial account.
`role` optional	string	Role of the user associated with the account (e.g., "ADMIN", "USER").
`carrier_type` optional	string	Type of carrier service (e.g., "VOIP", "PSTN").
`customer_type` optional	string	Type of customer (e.g., "ENTERPRISE", "SMB").
`credit_limit` optional	string	Maximum credit allowed for postpaid accounts.
`cps_limit` optional	number	Current calls per second limit for the account.
`concurrent_calls_limit` optional	number	Current concurrent calls limit for the account.
`base_cps_limit` optional	number	Base calls per second limit before any purchased add-ons.

Parameter	Type	Description
`base_concurrent_calls_limit` optional	number	Base concurrent calls limit before any purchased add-ons.
`purchased_cps` optional	number	Additional CPS purchased by the account.
`purchased_concurrent_calls` optional	number	Additional concurrent calls purchased by the account.
`risk_rating` optional	string	Risk assessment rating for the account (e.g., "LOW", "MEDIUM").
`risk_status` optional	string	Current risk status (e.g., "NORMAL", "FLAGGED").
`ip_auth_enabled` optional	boolean	Whether IP authentication is enabled for API access.
`ip_whitelist_rules` optional	array	List of IP addresses or CIDR blocks allowed for API access.
`allow_aws_ips` optional	boolean	Whether to allow AWS IP ranges for API access.
`features` optional	object	Map of enabled features like call_queue and transcription_enabled.
`limits` optional	object	Includes cps_limit, concurrent_calls_limit, and base limits.
`pricing_tier_id` optional	string	Unique identifier of the pricing tier assigned to this account.
`pricing_tier` optional	object	Complete pricing tier object with billing rates and descriptions.
`created_at` optional	string	ISO 8601 timestamp when the account was created.
`updated_at` optional	string	ISO 8601 timestamp when the account was last updated.
`last_login` optional	string	ISO 8601 timestamp of the most recent login.

Example Account Object

JSON


```
{
  "id": "MA_XXXXXX",
  "api_id": "api_v1_XXXXXX",
  "name": "Acme Corporation",
  "email": "admin@company.com",
  "phone": "+1234567890",
  "type": "MASTER",
  "auth_id": "YOUR_AUTH_ID",
  "auth_secret": "sk_live_XXXXXXXXXXXXXXXXXXXX",
  "auth_token_expire_time": "2025-11-22T03:16:12Z",
  "description": null,
  "company": "Acme Corp LLC",
  "address": "123 Tech Lane",
  "city": "Innovation City",
  "state": "California",
  "zip_code": "90001",
  "country": "US",
  "timezone": "America/Los_Angeles",
  "account_type": "PREPAID",
  "postpaid": false,
  "auto_recharge": true,
  "enabled": true,
  "is_active": true,
  "is_verified": true,
  "is_trial_account": false,
  "role": "ADMIN",
  "carrier_type": "VOIP",
  "customer_type": "ENTERPRISE",
  "credit_limit": "100.00",
  "cps_limit": 10,
  "concurrent_calls_limit": 50,
  "base_cps_limit": 5,
  "base_concurrent_calls_limit": 25,
  "purchased_cps": 5,
  "purchased_concurrent_calls": 25,
  "risk_rating": "LOW",
  "risk_status": "NORMAL",
  "ip_auth_enabled": false,
  "ip_whitelist_rules": [],
  "allow_aws_ips": true,
  "features": {
    "call_queue": true,
    "transcription_enabled": true
  },
  "pricing_tier_id": "1fa3db95-526a-4b5e-86a6-4bcd62ef31fa",
  "pricing_tier": {
    "id": "1fa3db95-526a-4b5e-86a6-4bcd62ef31fa",
    "name": "baseTier",
```

```
    "description": "Standard enterprise pricing plan",
    "currency": "INR",
    "rate_per_minute": "0.4500",
    "billing_increment_seconds": 60,
    "minimum_duration_seconds": 0,
    "is_active": true,
    "is_default": true
  },
  "created_at": "2025-10-17T08:51:00.552579Z",
  "updated_at": "2025-10-22T03:16:11.815251Z",
  "last_login": "2025-10-22T03:16:12.901344Z"
}
```


Pricing Tier Object

Each account includes a nested `pricing_tier` object that defines billing rates:

- **name**: Name of the pricing tier (e.g., "baseTier")
- **description**: A brief description of the pricing plan
- **rate_per_minute**: Cost per minute of call time in the specified currency
- **billing_increment_seconds**: Granularity of billing (e.g., 60 = billed by full minutes)
- **minimum_duration_seconds**: Minimum billable duration for calls
- **currency**: Currency code (USD, INR, EUR, etc.)

Retrieve Account Details

GET `https://api.vobiz.ai/api/v1/auth/me`

Retrieves the complete account details including pricing tier information and authentication credentials.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request

cURL

```
curl -X GET https://api.vobiz.ai/api/v1/auth/me \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Arguments

No arguments need to be passed.

Response Example

Success Response (200 OK)


```
{
  "id": "MA_XXXXXX",
  "api_id": "api_v1_XXXXXX",
  "name": "Acme Corporation",
  "email": "admin@company.com",
  "phone": "+1234567890",
  "type": "MASTER",
  "auth_id": "YOUR_AUTH_ID",
  "auth_secret": "sk_live_XXXXXXXXXXXXXXXXXXXX",
  "auth_token_expire_time": "2025-11-22T03:16:12Z",
  "description": null,
  "company": "Acme Corp LLC",
  "address": "123 Tech Lane",
  "city": "Innovation City",
  "state": "California",
  "zip_code": "90001",
  "country": "US",
  "timezone": "America/Los_Angeles",
  "account_type": "PREPAID",
  "postpaid": false,
  "auto_recharge": true,
  "enabled": true,
  "is_active": true,
  "is_verified": true,
  "is_trial_account": false,
  "role": "ADMIN",
  "carrier_type": "VOIP",
  "customer_type": "ENTERPRISE",
  "credit_limit": "100.00",
  "cps_limit": 10,
  "concurrent_calls_limit": 50,
  "base_cps_limit": 5,
  "base_concurrent_calls_limit": 25,
  "purchased_cps": 5,
  "purchased_concurrent_calls": 25,
  "risk_rating": "LOW",
```

```
  "risk_status": "NORMAL",
  "ip_auth_enabled": false,
  "ip_whitelist_rules": [],
  "allow_aws_ips": true,
  "features": {
    "call_queue": true,
    "transcription_enabled": true
  },
  "pricing_tier_id": "1fa3db95-526a-4b5e-86a6-4bcd62ef31fa",
  "pricing_tier": {
    "id": "1fa3db95-526a-4b5e-86a6-4bcd62ef31fa",
    "name": "baseTier",
    "description": "Standard enterprise pricing plan",
    "currency": "INR",
    "rate_per_minute": "0.4500",
    "billing_increment_seconds": 60,
    "minimum_duration_seconds": 0,
    "is_active": true,
    "is_default": true
  },
  "created_at": "2025-10-17T08:51:00.552579Z",
  "updated_at": "2025-10-22T03:16:11.815251Z",
  "last_login": "2025-10-22T03:16:12.901344Z"
}
```


Pricing Tier: Each account is associated with a pricing tier that determines the per-minute call rate and billing increments. The `pricing_tier` object provides complete details about your account's billing configuration.

Balance & Transactions

Retrieve account balance details and transaction history.

Get Transactions

GET `https://api.vobiz.ai/api/v1/account/{account_id}/transactions`

Retrieve a list of transactions for a specific account.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request

cURL

```
curl --location 'https://api.vobiz.ai/api/v1/account/YOUR_AUTH_ID/transactions?limit=50&offset=0' \
--header 'X-Auth-ID: YOUR_AUTH_ID' \
--header 'X-Auth-Token: YOUR_AUTH_TOKEN' \
--header 'Accept: application/json'
```

Response

JSON Reponse


```
{
    "account_id": "MA_XXXXXX",
    "total": 125,
    "page": 1,
    "per_page": 50,
    "total_pages": 3,
    "transactions": [
        {
            "id": "txn_6883ee37-4085-465f-97c2-e1c67c50aab9",
            "account_id": "MA_XXXXXX",
            "balance_id": "bal_a84cd3a6-21f4-4b4c-99f2-3d069cb65459",
            "type": "debit",
            "amount": 0.9,
            "currency": "INR",
            "description": "Stream session (70s)",
            "reference": "cdr_e565c2de-975c-4ba5-b115-44b1042cd397",
            "reference_type": "cdr",
            "status": "completed",
            "processed_at": "2025-12-08T09:38:06.923988Z",
            "created_at": "2025-12-08T09:38:06.923988Z",
            "updated_at": "2025-12-08T09:38:06.923988Z"
        },
        {
            "id": "txn_6aa3bf01-9158-4f1a-9980-8b3416b57e5a",
            "account_id": "MA_XXXXXX",
            "balance_id": "bal_a84cd3a6-21f4-4b4c-99f2-3d069cb65459",
            "type": "debit",
            "amount": 0.45,
            "currency": "INR",
            "description": "Stream session (30s)",
            "reference": "cdr_f876d3ef-1234-5678-90ab-cdef12345678",
            "reference_type": "cdr",
            "status": "completed",
            "processed_at": "2025-12-08T09:40:15.123456Z",
            "created_at": "2025-12-08T09:40:15.123456Z",
            "updated_at": "2025-12-08T09:40:15.123456Z"
        }
    ],
```

```
    "summary": {
        "total_transactions": 125,
        "total_debit": 150.75,
        "total_credit": 500.00,
        "net_amount": 349.25,
        "by_reference_type": [
            {
                "reference_type": "cdr",
                "total_debit": 140.25,
                "total_credit": 0.00,
                "count": 110
            },
            {
                "reference_type": "payment",
                "total_debit": 0.00,
                "total_credit": 500.00,
                "count": 1
            },
            {
                "reference_type": "refund",
                "total_debit": 10.50,
                "total_credit": 0.00,
                "count": 14
            }
        ]
    }
}
```

Get Balance

GET `https://api.vobiz.ai/api/v1/account/{account_id}/balance/{currency}`

Retrieve the balance for a specific account and currency.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request

cURL

```
curl --location 'https://api.vobiz.ai/api/v1/account/YOUR_AUTH_ID/balance/INR' \
--header 'X-Auth-ID: YOUR_AUTH_ID' \
--header 'X-Auth-Token: YOUR_AUTH_TOKEN' \
--header 'Accept: application/json'
```

Response

JSON Response

```
{
    "id": "bal_a84cd3a6-21f4-4b4c-99f2-3d069cb65459",
    "account_id": "MA_XXXXXX",
    "currency": "INR",
    "balance": 3082.65,
    "reserved_funds": 0,
    "promotional_balance": 100.50,
    "promotional_reserved_balance": 0,
    "promo_credits": 25.00,
    "available_balance": 3183.15,
    "credit_limit": 0,
    "low_balance_threshold": 50,
    "status": "active",
    "created_at": "2025-10-17T08:51:01.646973Z",
    "updated_at": "2025-12-08T09:38:06.921968Z"
}
```

Concurrency

Monitor and manage the number of concurrent lines being used in your account.

Overview

The
 Concurrency API allows you to retrieve real-time data about how many concurrent lines are active for your account. This is essential for monitoring line utilization and ensuring you have sufficient capacity for your communication needs.

Get Concurrency

GET `https://api.vobiz.ai/api/v1/account/{auth_id}/concurrency`

Retrieve the current number of concurrent lines active for a specific account.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request

cURL

```
curl -X GET "https://api.vobiz.ai/api/v1/account/YOUR_AUTH_ID/concurrency" \
--header 'X-Auth-ID: YOUR_AUTH_ID' \
--header 'X-Auth-Token: YOUR_AUTH_TOKEN' \
--header 'Accept: application/json'
```

Response

JSON Response

```
{
    "account_id": "MA_XXXXXX",
    "concurrent_calls": 5,
    "max_concurrent": 100,
    "utilization_pct": 5.0,
    "timestamp": "2024-03-21T10:30:00Z",
    "request_id": "req_883ee377-4085-465f-97c2-e1c67c50aab9"
}
```

Subaccounts

You
 can manage multiple customer accounts using Subaccounts. Subaccounts are owned by a parent Account and can be used to segment, manage, and keep track of the account usage of each user independently.

Base URI

Base URI

```
https://api.vobiz.ai/api/v1/Account/{auth_id}/Subaccount/
```

Key Features

- Complete resource isolation with dedicated auth credentials for secure multi-tenancy
- Independent management of trunks, numbers, CDRs, and balances per subaccount
- Parent account retains full administrative control over all subaccount operations

- Each subaccount receives unique auth_id and auth_token for API access

Subaccount Operations

The Subaccount Object

View the structure and attributes of the Subaccount object including auth credentials, enabled status, and resource URI.

Create a Subaccount

POST request to create a new subaccount with a name and enabled status. Returns unique auth credentials.

Retrieve a Subaccount

GET request to retrieve details of a specific subaccount including auth credentials and settings.

Update a Subaccount

POST request to update subaccount name or enabled status. Disabling blocks all API calls and trunk usage.

Delete a Subaccount

DELETE request to permanently remove a subaccount. Optionally cascade delete or reassociate resources.

List All Subaccounts

GET request to retrieve all subaccounts with pagination support. Sorted by creation date.

Subaccount Use Cases

Multi-Tenant SaaS

Create
 a subaccount for each customer. Each customer gets isolated resources
and their own API credentials for programmatic access.

Department Isolation

Create subaccounts for different departments (Sales, Support, Operations). Each department gets their own trunks and phone numbers.

Reseller Model

Create subaccounts for resellers who manage their own customers. Track usage and billing separately per subaccount.

Development/Staging

Create subaccounts for dev, staging, and production environments. Test changes in isolation without affecting production.

The Subaccount Object

The Subaccount object represents an isolated account under your main Vobiz account, with its own authentication credentials, permissions, and rate limiting capabilities.

Attributes

Subaccount Attributes

Parameter	Type	Description
`id` optional	string	Unique identifier for the sub-account (e.g., "SA_67401KW8").
`name` optional	string	Name of the sub-account.
`description` optional	string | null	Description of the sub-account purpose or usage.
`permissions` optional	object	Permissions object defining what the sub-account can access. Contains boolean fields like "calls" and "cdr".
`rate_limit` optional	integer	API rate limit for this sub-account (requests

Parameter	Type	Description
		per time period).
`parent_account_id` optional	string	ID of the parent main account (e.g., " {Auth_ID}").
`auth_id` optional	string	Authentication ID used for API requests.
`is_active` optional	boolean	Whether the sub-account is currently active and can make API calls.
`created_at` optional	string	ISO 8601 timestamp when the sub-account was created.
`updated_at` optional	string	ISO 8601 timestamp when the sub-account was last updated.
`last_used` optional	string | null	ISO 8601 timestamp when the sub-account was last used for API calls. Null if never used.

Example Subaccount Object

JSON

```
{
  "name": "Support Team",
  "description": "Support-facing voice workload",
  "permissions": {
    "calls": true,
    "cdr": true
  },
  "rate_limit": 500,
  "id": "SA_67401KW8",
  "parent_account_id": "{Auth_ID}",
  "auth_id": "inG9oUky5uFjdUECaQNzeyVYD6ommaJd",
  "is_active": true,
  "created_at": "2025-10-22T03:57:35.997500Z",
  "updated_at": "2025-10-22T03:57:35.997500Z",
  "last_used": null
}
```

Permissions Object: The `permissions` object controls what resources the sub-account can access:

- **calls:** Whether the sub-account can make/receive calls
- **cdr:** Whether the sub-account can access Call Detail Records

Rate Limiting: The `rate_limit` field controls API request throttling for this sub-account. Set this based on expected usage patterns to prevent abuse.

Create a Subaccount

POST `https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/`

Creates
 a new Subaccount object. Provision isolated subaccounts under your main
 account for multi-tenant SaaS applications, reseller models, or
departmental resource segregation.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Parameters

Request Parameters

Parameter	Type	Description
`name` required	string	A human-readable name for the subaccount.
`email` required	string	Email address associated with the subaccount.
`phone` optional	string	Phone number associated with the subaccount.
`description` optional	string	Description of the sub-account purpose or usage.
`rate_limit` required	integer	API rate limit for this sub-account (requests per time period).
`permissions` required	object	Permissions object defining what the sub-account can access. Contains boolean fields like "calls" and "cdr".
`password` required	string	Password for the sub-account authentication.

Parameter	Type	Description
`enabled` optional	boolean	Whether the subaccount is active and enabled for use.

Request

cURL

```
curl -X POST 'https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/' \
--header 'X-Auth-ID: {auth_id}' \
--header 'X-Auth-Token: {auth_token}' \
--header 'Content-Type: application/json' \
--data-raw '{
  "name": "Support Team",
  "email": "support@example.com",
  "phone": "+1234567890",
  "description": "Support-facing voice workload",
  "rate_limit": 500,
  "permissions": {
    "calls": true,
    "cdr": true
  },
  "password": "S0pport123!",
  "enabled": true
}'
```

Request Body

JSON

```
{
  "name": "Support Team",
  "email": "support@example.com",
  "phone": "+1234567890",
  "description": "Support-facing voice workload",
  "rate_limit": 500,
  "permissions": {
    "calls": true,
    "cdr": true
  },
  "password": "S0pport123!",
  "enabled": true
}
```

Response Example

Success Response (201 Created)

```
{
  "message": "Sub-account created successfully",
  "sub_account": {
    "name": "Support Team",
    "email": "support@example.com",
    "phone": "+1234567890",
    "description": "Support-facing voice workload",
    "permissions": {
      "calls": true,
      "cdr": true
    },
    "rate_limit": 500,
    "id": "{sub_account_id}",
    "parent_account_id": "{auth_id}",
    "parent_auth_id": "{parent_auth_id}",
    "auth_id": "{auth_id}",
    "auth_token": "{auth_token}",
    "api_id": "{api_id}",
    "email_verified": true,
    "enabled": true,
    "is_active": true,
    "created": "2025-10-22T03:57:35.997500Z",
    "modified": "2025-10-22T03:57:35.997500Z",
    "created_at": "2025-10-22T03:57:35.997500Z",
    "updated_at": "2025-10-22T03:57:35.997500Z",
    "account": "/api/v1/accounts/{auth_id}/",
    "resource_uri": "/api/v1/accounts/{auth_id}/sub-accounts/{sub_account_id}/",
    "last_used": null
  },
  "auth_credentials": {
    "auth_id": "{auth_id}",
    "auth_token": "{auth_token}"
  },
  "tokens": {
    "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "refresh_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "token_type": "bearer",
    "expires_in": 1800
  }
}
```


Success! The response contains three important sections:

- **sub_account:** The created sub-account object with all details
- **auth_credentials:** The `auth_id` and `auth_token` for API authentication - save these securely!
- **tokens:** JWT access and refresh tokens for immediate API access

Security Note: The `auth_token` is only returned once during creation. Store it securely - you won't be able to retrieve it again. If lost, you'll need to regenerate credentials.

Retrieve a Subaccount

GET `https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}`

Retrieves the detail of a specific Subaccount by its ID.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request

cURL

```
curl -X GET 'https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}'
\
--header 'X-Auth-ID: {auth_id}' \
--header 'X-Auth-Token: {auth_token}'
```

Arguments

No arguments need to be passed.

Response Example

Success Response (200 OK)

```
{
  "name": "Support Team",
  "email": "support@example.com",
  "phone": "+1234567890",
  "description": "Support-facing voice workload",
  "permissions": {
    "calls": true,
    "cdr": true
  },
  "rate_limit": 500,
```

```
  "id": "{sub_account_id}",
  "parent_account_id": "{auth_id}",
  "parent_auth_id": "{parent_auth_id}",
  "auth_id": "{auth_id}",
  "auth_token": "{auth_token}",
  "api_id": "{api_id}",
  "email_verified": true,
  "enabled": true,
  "is_active": true,
  "created": "2025-10-22T03:57:35.997500Z",
  "modified": "2025-10-22T03:57:35.997500Z",
  "created_at": "2025-10-22T03:57:35.997500Z",
  "updated_at": "2025-10-22T03:57:35.997500Z",
  "account": "/api/v1/accounts/{auth_id}/",
  "resource_uri": "/api/v1/accounts/{auth_id}/sub-accounts/{sub_account_id}/",
  "last_used": null
}
```


Update a Subaccount

PUT `https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}`

Updates
 the sub-account object by setting the values to the parameters passed. Parameters that are not provided remain unchanged.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Note: Use this endpoint to update sub-account settings like description, rate limits, or permissions. Setting `is_active=false` would disable the sub-account if that field is supported.

Parameters

Request Parameters

Parameter	Type	Description
`name` optional	string	Name of the sub-account.

Parameter	Type	Description
`email` optional	string	Email address associated with the subaccount.
`phone` optional	string	Phone number associated with the subaccount.
`description` optional	string	Description of the sub-account purpose or usage.
`rate_limit` optional	integer	API rate limit for this sub-account (requests per time period).
`permissions` optional	object	Permissions object defining what the sub-account can access. Contains boolean fields like "calls" and "cdr".
`enabled` optional	boolean	Whether the subaccount is active and enabled for use.

Request

cURL

```
curl -X PUT 'https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}'
\
--header 'X-Auth-ID: {auth_id}' \
--header 'X-Auth-Token: {auth_token}' \
--header 'Content-Type: application/json' \
--data-raw '{
  "description": "Updated permissions",
  "rate_limit": 750,
  "email": "updated@example.com",
  "enabled": true
}'
```

Request Body

JSON

```
{
  "description": "Updated permissions",
  "rate_limit": 750,
  "email": "updated@example.com",
  "enabled": true
}
```

Response Example

Success Response (200 OK)

```
{
  "name": "Support Team",
  "email": "updated@example.com",
  "phone": "+1234567890",
  "description": "Updated permissions",
  "permissions": {
    "calls": true,
    "cdr": true
  },
  "rate_limit": 750,
  "id": "{sub_account_id}",
  "parent_account_id": "{auth_id}",
  "parent_auth_id": "{parent_auth_id}",
  "auth_id": "{auth_id}",
  "auth_token": "{auth_token}",
  "api_id": "{api_id}",
  "email_verified": true,
  "enabled": true,
  "is_active": true,
  "created": "2025-10-22T03:57:35.997500Z",
  "modified": "2025-10-22T03:59:52.261439Z",
  "created_at": "2025-10-22T03:57:35.997500Z",
  "updated_at": "2025-10-22T03:59:52.261439Z",
  "account": "/api/v1/accounts/{auth_id}/",
  "resource_uri": "/api/v1/accounts/{auth_id}/sub-accounts/{sub_account_id}/",
  "last_used": null
}
```


Complete Object Returned: The response returns the full updated sub-account object, not just a success message. Notice the `updated_at` timestamp has changed to reflect the modification.

Delete a Subaccount

DELETE `https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}`

Permanently deletes a Subaccount. This action removes the sub-account and all its associated credentials.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Warning:
Deleting a subaccount is permanent. This action cannot be undone.
Ensure you have backed up any necessary data before proceeding.

Request

cURL

```
curl -X DELETE 'https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/{sub_account_id}' \
--header 'X-Auth-ID: {auth_id}' \
--header 'X-Auth-Token: {auth_token}'
```

Parameters

No request body or parameters required. The sub-account ID is specified in the URL path.

Response Example

Success Response (200 OK)

```
{
  "message": "Sub-account deleted successfully"
}
```

Success: The API returns a 200 OK status with a confirmation message when the sub-account is successfully deleted.

List All Subaccounts

GET `https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/`

Returns a paginated list of subaccounts sorted by creation date, with the most recently created subaccount appearing first.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Parameters

Request Parameters

Parameter	Type	Description
`page` optional	integer	Page number for pagination. Defaults to 1.
`size` optional	integer	Number of results per page. Defaults to 25.
`active_only` optional	boolean	Filter to return only active sub-accounts. Set to true to filter out inactive sub-accounts.

Request

cURL

```
curl -X GET 'https://api.vobiz.ai/api/v1/accounts/{account_id}/sub-accounts/?
page=1&size=25&active_only=true' \
--header 'X-Auth-ID: {auth_id}' \
--header 'X-Auth-Token: {auth_token}'
```

Response Example

Success Response (200 OK)

```
{
  "sub_accounts": [
    {
      "name": "Support Team",
      "email": "support@example.com",
      "phone": "+1234567890",
      "description": "Support-facing voice workload",
      "permissions": {
        "calls": true,
        "cdr": true
      },
      "rate_limit": 500,
      "id": "{sub_account_id}",
      "parent_account_id": "{auth_id}",
      "parent_auth_id": "{parent_auth_id}",
      "auth_id": "{auth_id}",
      "auth_token": "{auth_token}",
      "api_id": "{api_id}",
      "email_verified": true,
      "enabled": true,
      "is_active": true,
      "created": "2025-10-22T03:57:35.997500Z",
      "modified": "2025-10-22T03:57:35.997500Z",
```

```
      "created_at": "2025-10-22T03:57:35.997500Z",
      "updated_at": "2025-10-22T03:57:35.997500Z",
      "account": "/api/v1/accounts/{auth_id}/",
      "resource_uri": "/api/v1/accounts/{auth_id}/sub-accounts/{sub_account_id}/",
      "last_used": null
    }
  ],
  "total": 1,
  "page": 1,
  "size": 25
}
```


Pagination: The response includes pagination metadata at the root level:

- **total:** Total number of sub-accounts matching the filter
- **page:** Current page number
- **size:** Number of results per page