vobiz endpoints 4

Created	@March 17, 2026 1:33 AM
Class	vobiz

Phone Numbers

Manage
 phone numbers in your Vobiz account. List owned numbers, view inventory, purchase numbers, and release numbers back to inventory.

Key Features

- List all phone numbers owned by your account with pagination support
- Browse available phone numbers in inventory
- Purchase numbers from inventory and assign to your account
- Release numbers back to inventory when no longer needed
- Master accounts (MA_) can include numbers from sub-accounts
- View detailed number information including capabilities, pricing, and status

Base URL

Base URL

`https://api.vobiz.ai/api`

Authentication

All Phone Number API endpoints require authentication via `X-Auth-ID` and `X-Auth-Token` headers.

Required Headers:

- **X-Auth-ID:** Your Auth ID (e.g., {Auth_ID})

- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Available Operations

The PhoneNumber Object

View the complete structure and attributes of a PhoneNumber object including number details, capabilities, billing information, and provider settings.

List Account Phone Numbers

GET request to retrieve all phone numbers owned by your account with pagination support. Master accounts can include numbers from sub-accounts.

List Inventory Numbers

GET request to browse available phone numbers in inventory (not assigned to any account) that are available for purchase.

Purchase from Inventory

POST request to purchase a number from inventory and assign it to your account. Debits balance for setup and monthly fees.

Unrent a Number

DELETE request to release a phone number back to inventory. The number will be unassigned from your account and trunk group.

The PhoneNumber Object

The PhoneNumber object represents a phone number in the Vobiz system, including details about capabilities, billing, and status.

Attributes

PhoneNumber Attributes

Parameter	Type	Description
`id` optional	string	UUID identifier for the phone number.
`auth_id` optional	string	Auth ID (MA_xxx or SA_xxx) that owns this number. Null if number is in inventory and not assigned to any account.
`e164` optional	string	Phone number in E164 format (e.g., "+14155551234").
`country` optional	string	Country code (e.g., "US", "IN").
`region` optional	string	State/region code (e.g., "CA", "MH"). Optional.
`capabilities` optional	object	Object containing boolean flags for each capability: voice, sms, mms, fax.
`capabilities.voice` optional	boolean	Whether the number supports voice calling.
`capabilities.sms` optional	boolean	Whether the number supports SMS messaging.
`capabilities.mms` optional	boolean	Whether the number supports MMS messaging.
`capabilities.fax` optional	boolean	Whether the number supports fax.
`status` optional	string	Current status of the number. One of: "active", "pending_purchase", "pending_release", "released", "blocked".
`setup_fee` optional	number	One-time setup fee charged when purchasing the number.
`monthly_fee` optional	number	Monthly recurring fee for the number.
`currency` optional	string	Currency code for fees (e.g., "USD", "INR").
`trunk_group_id` optional	string	UUID of assigned trunk group. Null if not assigned to any trunk. Optional.

Parameter	Type	Description
`purchased_at` optional	string	ISO 8601 timestamp when the number was purchased. Optional.
`released_at` optional	string	ISO 8601 timestamp when the number was released. Optional.
`created_at` optional	string	ISO 8601 timestamp when the number record was created.
`updated_at` optional	string	ISO 8601 timestamp when the number record was last updated.

Number Status Values

Status	Description
active	Number is active and available
pending_purchase	Purchase in progress
pending_release	Release in progress
released	Number has been released
blocked	Number is blocked

Example PhoneNumber Object

JSON

```
{
  "id": "550e8400-e29b-41d4-a716-446655440000",
  "auth_id": "{Auth_ID}",
  "e164": "+14155551234",
  "country": "US",
  "region": "CA",
  "capabilities": {
    "voice": true,
    "sms": true,
    "mms": false,
    "fax": false
  },
  "status": "active",
  "setup_fee": 1.00,
  "monthly_fee": 1.00,
  "currency": "USD",
  "trunk_group_id": "660e8400-e29b-41d4-a716-446655440001",
  "purchased_at": "2025-01-15T10:00:00Z",
```

```
  "created_at": "2025-01-15T10:00:00Z",
  "updated_at": "2025-01-15T10:00:00Z"
}
```

List Account Phone Numbers

Returns a list of phone numbers that have been purchased and assigned to your account.

API Endpoint

GET `https://api.vobiz.ai/api/v1/account/{auth_id}/numbers`

Authentication Required:

- **X-Auth-ID:** Your Auth ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

Request Parameters

Parameter	Type	Description
`page` optional	integer	Page number for pagination. Default: 1.
`per_page` optional	integer	Items per page. Default: 25. Maximum: 100.
`include_subaccounts` optional	boolean	Include numbers from sub-accounts. Default: true for master accounts (MA_). When true, fetches numbers from all sub-accounts under the master account.

Master Accounts (MA_): For master accounts, setting `include_subaccounts=true` fetches the sub-account list from the Account Service and includes all numbers from SA_ accounts in a single query.

cURL - X-Auth-ID & X-Auth-Token

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{AUTH_ID}/numbers" \
  -H "X-Auth-ID: {AUTH_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}"
```

Response Example

Success Response (200 OK)


```
{
  "items": [
    {
      "id": "90be0b9e-521d-41da-aebd-aba05006272f",
      "auth_id": "{Auth_ID}",
      "e164": "+918071387149",
      "country": "IN",
      "region": "Karnataka",
      "capabilities": {
        "voice": false,
        "sms": false,
        "mms": false,
        "fax": false
      },
      "status": "active",
      "trunk_group_id": null,
      "setup_fee": 100,
      "monthly_fee": 500,
      "currency": "INR",
      "purchased_at": "2025-10-22T05:04:09.705084Z",
      "created_at": "2025-10-21T12:03:44.837733Z",
      "updated_at": "2025-10-22T05:04:09.705084Z"
    }
  ],
  "page": 1,
  "per_page": 25,
  "total": 1
}
```


Response Structure:

- **items:** Array of phone number objects purchased by your account
- **page:** Current page number
- **per_page:** Number of items per page
- **total:** Total count of purchased phone numbers

Note: Only phone numbers with a populated `auth_id` field are returned. Numbers in inventory (with empty auth_id) are not included.

List Inventory Numbers

Browse available phone numbers in inventory that are not assigned to any account.

This
 endpoint lists phone numbers in inventory (auth_id IS NULL) that are available for purchase. These are numbers that can be assigned to your account using the Purchase from Inventory endpoint.

Note:
 Only numbers with status='active' and auth_id=NULL are returned. These numbers are ready to be purchased and assigned to your account.

HTTP Request

GET `/v1/account/{auth_id}/inventory/numbers`

Authentication Required:

- **X-Auth-ID:** Your Auth ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

Request Parameters

Parameter	Type	Description
`country` optional	string	Filter by country code (e.g., "US", "IN"). Optional.
`page` optional	integer	Page number for pagination. Default: 1.
`per_page` optional	integer	Items per page. Default: 25. Maximum: 100.

Response

Returns a paginated list of phone numbers available in inventory.

Response - 200 OK

```
{
  "items": [
    {
      "id": "550e8400-e29b-41d4-a716-446655440000",
      "e164": "+14155551234",
      "country": "US",
      "region": "CA",
      "status": "active",
      "setup_fee": 0.0,
      "monthly_fee": 1.0,
      "currency": "INR",
      "created_at": "2025-01-15T10:00:00Z",
      "updated_at": "2025-01-15T10:00:00Z"
    }
  ],
  "page": 1,
  "per_page": 25,
  "total": 500
}
```

Examples

cURL - List All Inventory Numbers

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{AUTH_ID}/inventory/numbers?page=1&per_page=25" \
  -H "X-Auth-ID: {AUTH_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}"
```

cURL - Filter by Country

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{AUTH_ID}/inventory/numbers?country=US&page=1&per_page=25" \
  -H "X-Auth-ID: {AUTH_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}"
```

Use Cases:

- Browse available numbers before purchasing
- Check inventory for specific countries or regions
- View pricing information for available numbers
- Find numbers with specific capabilities (voice, SMS, MMS)

Next Step: Once you find a number you want, use the Purchase from Inventory endpoint to assign it to your account.

Purchase from Inventory

Purchase a phone number from inventory and assign it to your account.

This endpoint purchases a number from inventory and assigns it to your account. The operation debits your account balance for the setup fee and monthly fee.

Important: Purchase Process

1. Verifies number exists in inventory (auth_id IS NULL)
2. Determines billing account (parent MA_ for SA_ accounts)
3. Debits balance (setup_fee + monthly_fee)
4. Assigns auth_id to your account
5. Sets purchased_at timestamp
6. Returns updated number

Note: If you have insufficient balance, the purchase will fail and the number will remain in inventory. Balance Service is used to debit the amount.

HTTP Request

POST `/v1/account/{auth_id}/numbers/purchase-from-inventory`

Authentication Required:

- **X-Auth-ID:** Your Auth ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Request Body

Request Parameters

Parameter	Type	Description
`e164` required	string	Phone number to purchase in E164 format (e.g., "+919876543210").
`currency` optional	string	Currency for transaction. Defaults to the number's currency or "USD" if not specified.

Response

Returns a success message and the updated PhoneNumber object with auth_id assigned to your account.

Response - 200 OK

```
{
  "message": "purchased from inventory",
  "number": {
    "id": "550e8400-e29b-41d4-a716-446655440000",
    "auth_id": "{Auth_ID}",
    "e164": "+919876543210",
    "country": "IN",
    "region": "MH",
    "status": "active",
    "provider": "manual",
    "setup_fee": 0.0,
    "monthly_fee": 1.0,
    "currency": "USD",
    "purchased_at": "2025-01-15T10:00:00Z",
    "created_at": "2025-01-15T10:00:00Z",
    "updated_at": "2025-01-15T10:00:00Z"
  }
}
```

Examples

cURL - Purchase Number from Inventory

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/account/{AUTH_ID}/numbers/purchase-from-inventory \
  -H "X-Auth-ID: {AUTH_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}" \
  -H "Content-Type: application/json" \
  -d '{
    "e164": "+919876543210",
```

```
    "currency": "USD"
  }'
```

Error Response (404 Not Found): If number does not exist in inventory:

Error Response - 404 Not Found

```
{
  "error": "not found",
  "message": "number not found in inventory"
}
```

Error Response (500 Internal Server Error): If balance debit fails:

Error Response - 500 Internal Server Error

```
{
  "error": "internal server error",
  "message": "failed to purchase number from provider"
}
```

Best Practices:

- Always check inventory first to ensure the number is available
- Verify you have sufficient balance before purchasing
- Note that setup_fee + monthly_fee will be debited immediately
- For sub-accounts (SA_), the parent master account (MA_) will be charged

Release a Phone Number

Releases a phone number from your account back to inventory. This operation cannot be undone.

API Endpoint

DELETE `https://api.vobiz.ai/api/v1/account/{auth_id}/numbers/{e164_number}`

Authentication Required:

- **X-Auth-ID:** Your Auth ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Warning

Releasing
 a phone number is a permanent action that cannot be reversed. Once released, the number returns to inventory and you will lose access to it
 immediately. Any active calls or configurations using this number will be affected.

Path Parameters

e164_number: The phone number in E.164 format to release (e.g., "+918071387149"). This must be a number currently assigned to your account.

No request body is required for this endpoint.

cURL - X-Auth-ID & X-Auth-Token

cURL Request

```
curl -X DELETE "https://api.vobiz.ai/api/v1/account/{AUTH_ID}/numbers/{PHONE_NUMBER}" \
  -H "X-Auth-ID: {AUTH_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}"
```

Response Example

Success Response (200 OK)

```
{
  "message": "number returned to inventory"
}
```

Success: The phone number has been released from your account and returned to inventory.

Changes Made:

- `auth_id` set to NULL
- `trunk_group_id` set to NULL
- `released_at` timestamp set
- Number becomes available in inventory for purchase

Error Response (403 Forbidden): If account does not own this number:

Error Response - 403 Forbidden

```
{
  "error": "forbidden",
  "message": "account does not own this number"
}
```

Endpoint

Manage SIP endpoints for making and receiving calls from IP phones, mobile devices, and SIP clients.

The
 Endpoint API allows you to create and manage SIP endpoints that can be used to make and receive calls through various devices and applications.
 Endpoints are essential for building communication systems with IP phones, softphones, and SIP clients.

Note:
 Each endpoint is assigned a unique SIP URI that external users can use to establish calls. Endpoints can be registered on SIP clients for real-time communication.

What is an Endpoint?

A
 Vobiz endpoint, also known as a SIP endpoint, can be any device or application that uses the Session Initiation Protocol (SIP) to perform communications operations:

IP Phones

Hardware SIP phones that connect directly to your network.

Mobile Phones

Mobile apps using SIP softphone applications.

Desktop Applications

Web or desktop softphones using WebRTC or SIP clients.

Wireless Devices

Any wireless SIP-compatible device on your network.

Use Cases:
Endpoints are commonly used for call center agents taking calls, business phone systems, customer support hotlines, and building custom VoIP applications.

API Endpoint

Base URL

https://api.vobiz.ai/api/v1

Endpoint Base URI

https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token Header:** Your account Auth Token

Available Operations

OBJECT**The Endpoint object**
Complete structure and attributes of an Endpoint object.View Documentation →POST**Create an endpoint**
Create a new SIP endpoint for receiving and making calls.View Documentation →DELETE**Delete an endpoint**
Permanently delete an existing endpoint.View Documentation →GET**Retrieve an endpoint**
Get details of a specific endpoint including registration status.View Documentation →POST**Update an endpoint**
Update endpoint password, alias, or attached application.View Documentation →GET**List all endpoints**
Retrieve a list of all endpoints in your account.View Documentation →

SIP Configuration

After creating an endpoint, configure your SIP client with the following details to connect:

Server Settings

SIP Server: `sip.vobiz.ai`

Domain: `sip.vobiz.ai`

Transport:UDP/TCP/TLS

Port:5060 (UDP/TCP), 5061 (TLS)

Credentials

Username: `{endpoint_username}`

Password: `{endpoint_password}`

Display Name: `{alias}` (optional)

Example Configuration:

```
SIP URI: sip:john_doe@sip.vobiz.ai
Username: john_doe
Password: SecurePassword123!
Server: sip.vobiz.ai
Port: 5060
Transport: UDP
```

WebRTC Configuration: For WebRTC applications, use JWT token authentication. Connect to `wss://sip.vobiz.ai:7443` and authenticate using a JWT token obtained from the API.

Best Practices

Strong Passwords

Use complex passwords with minimum 8 characters, including mix of letters, numbers, and symbols.

Unique Usernames

Usernames must be unique within your account. Use descriptive names for easy identification.

Application Assignment

Assign applications to endpoints for automatic call routing and handling.

Permission Control

Only enable permissions (voice, video, messaging) that your endpoints actually need.

Monitor Registration

Check sip_registered field regularly to verify endpoint connectivity and troubleshoot issues.

Token Rotation

For WebRTC, use short-lived JWT tokens (1-4 hours) and rotate auth tokens periodically.

Sub-account Isolation

Use sub-accounts to isolate endpoints for different customers or departments.

Delete Unused Endpoints

Remove endpoints that are no longer in use to keep your account organized and secure.

The Endpoint Object

Complete structure and attributes of an Endpoint object.

The Endpoint object represents a SIP endpoint in your account. Each endpoint has a unique identifier and can be registered on SIP clients to make and receive calls. The object structure varies slightly depending on whether the endpoint is currently registered on a SIP client.

Registration Status: When an endpoint is registered on a SIP client, additional fields like sip_contact, sip_expires, and sip_user_agent are included in the response.

Attributes

Core Attributes

Parameter	Type	Description
`endpoint_id` optional	string	Unique identifier for the endpoint. All endpoint API operations are performed using this identifier.
`username` optional	string	SIP username (unique per account). Only alphanumeric characters are accepted.
`alias` optional	string	Friendly name for the endpoint. Accepts alphabets (uppercase and lowercase), numbers (0-9), hyphen (-), and underscore (_) only.
`sip_uri` optional	string	Full SIP URI of the endpoint. External users can call this endpoint on this SIP URI. Format: sip:username@sip.vobiz.ai
`sip_registered` optional	string	Registration status. Set to "true" if the SIP endpoint is registered on a SIP client, "false" otherwise.
`application` optional	object	Associated application details for call routing. Contains app_id, app_name, answer_url, and answer_method. null if no application is attached.
`resource_uri` optional	string	API resource URI for this endpoint.
`sub_account` optional	string	Sub-account auth_id if endpoint belongs to a sub-account. null for main account.
`created_at` optional	string (ISO 8601)	Creation timestamp.
`updated_at` optional	string (ISO 8601)	Last update timestamp.

Permission Attributes

Parameter	Type	Description
`allow_voice` optional	boolean	Voice calls enabled (default: true).
`allow_message` optional	boolean	Messaging enabled (default: true).
`allow_video` optional	boolean	Video calls enabled (default: false).
`allow_same_domain` optional	boolean	Calls to same domain allowed (default: true).
`allow_other_domains` optional	boolean	Calls to other domains allowed (default: false).
`allow_phones` optional	boolean	Calls to phone numbers allowed (default: true).
`allow_apps` optional	boolean	Calls to apps allowed (default: true).

Registration Attributes (when registered)

Parameter	Type	Description
`sip_contact` optional	string	SIP contact address of the registered client. Example: 192.168.1.100:5060
`sip_expires` optional	string (ISO 8601)	Timestamp when the SIP registration expires.
`sip_user_agent` optional	string	User agent string of the SIP client. Example: "Zoiper v5.4.5"
`sip_registration` optional	object	Detailed registration information (retrieve endpoint only). Contains contact, expires, user_agent, received, and path fields.

Examples

Unregistered Endpoint

Response when the endpoint is not currently registered on any SIP client:

Unregistered Endpoint Response

```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "endpoint_id": "87654322",
  "username": "jane_smith",
  "alias": "Jane's Mobile",
```

```
  "sip_uri": "sip:jane_smith@sip.vobiz.ai",
  "sip_registered": "false",
  "sip_contact": null,
  "sip_expires": null,
  "sip_user_agent": null,
  "application": null,
  "allow_voice": true,
  "allow_message": true,
  "allow_video": true,
  "allow_same_domain": true,
  "allow_other_domains": false,
  "allow_phones": true,
  "allow_apps": true,
  "sub_account": null,
  "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654322/",
  "created_at": "2025-10-26T14:20:00Z",
  "updated_at": "2025-10-26T14:20:00Z"
}
```


Registered Endpoint

Response when the endpoint is actively registered on a SIP client:

Registered Endpoint Response


```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "endpoint_id": "87654321",
  "username": "john_doe",
  "alias": "John's Desktop Phone",
  "sip_uri": "sip:john_doe@sip.vobiz.ai",
  "sip_registered": "true",
  "sip_contact": "192.168.1.100:5060",
  "sip_expires": "2025-10-28T11:30:00Z",
  "sip_user_agent": "Zoiper v5.4.5",
  "application": {
    "app_id": "12345678",
    "app_name": "Customer Service App",
    "answer_url": "https://example.com/answer",
    "answer_method": "POST"
  },
  "allow_voice": true,
  "allow_message": true,
  "allow_video": false,
  "allow_same_domain": true,
  "allow_other_domains": false,
  "allow_phones": true,
  "allow_apps": true,
  "sub_account": null,
  "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654321/",
  "created_at": "2025-10-27T10:30:00Z",
```

```
  "updated_at": "2025-10-28T09:15:00Z"
}
```

Note:
The password field is write-only and never returned in API responses for security purposes. Registration timestamps (sip_expires, created_at, updated_at) are in ISO 8601 format (UTC timezone).

Create an Endpoint

Create a new SIP endpoint for making and receiving calls.

This API allows you to create a new SIP endpoint that can be used to make and receive calls through IP phones, softphones, or SIP clients. Each endpoint is assigned a unique SIP URI and endpoint ID.

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

SIP URI: Your endpoint will be assigned a SIP URI in the format `sip:username@sip.vobiz.ai`

HTTP Request

POST `https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/`

Request Parameters

Request Parameters

Parameter	Type	Description
`username` required	string	SIP username (unique per account). Only alphanumeric characters are accepted.
`password` required	string	SIP password. Minimum 8 characters recommended for security.

Parameter	Type	Description
`alias` optional	string	Friendly name for the endpoint. Accepts alphabets, numbers (0-9), hyphen (-), and underscore (_) only.
`application` optional	integer	Application ID for call routing. If null, uses default application.
`allow_voice` optional	boolean	Allow voice calls (default: true).
`allow_message` optional	boolean	Allow messaging (default: true).
`allow_video` optional	boolean	Allow video calls (default: false).
`allow_same_domain` optional	boolean	Allow calls to same domain (default: true).
`allow_other_domains` optional	boolean	Allow calls to other domains (default: false).
`allow_phones` optional	boolean	Allow calls to phone numbers (default: true).
`allow_apps` optional	boolean	Allow calls to apps (default: true).
`sub_account` optional	string	Sub-account auth_id (if creating for sub-account).

Response

If successful, returns "created" in the message field along with the endpoint_id, sip_uri, and resource_uri.

Response - 201 Created

```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "message": "created",
  "endpoint_id": "87654321",
  "sip_uri": "sip:john_doe@sip.vobiz.ai",
  "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654321/"
}
```

Error Response - 400 Bad Request

```
{
  "error": "invalid request parameters",
  "details": {
    "username": "This username already exists",
    "password": "Password must be at least 8 characters"
```

```
  }
}
```

Examples

Basic Endpoint Creation

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "username": "sales_desk",
    "password": "VerySecurePass123!",
    "alias": "Sales Team Desk Phone",
    "allow_voice": true
  }'
```

Create with Application and Permissions

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "username": "john_doe",
    "password": "SecurePassword123!",
    "alias": "John'''s Desktop Phone",
    "application": 12345678,
    "allow_voice": true,
    "allow_message": true,
    "allow_video": false,
    "allow_same_domain": true,
    "allow_other_domains": false,
    "allow_phones": true,
    "allow_apps": true
  }'
```

Best Practices:

- Use strong passwords (minimum 8 characters, mix of letters/numbers/symbols)
- Use descriptive aliases to easily identify endpoints
- Store the endpoint_id and sip_uri securely for future operations

- Only enable permissions your endpoints actually need
- Attach applications for automatic call routing

Delete an Endpoint

Permanently delete an existing SIP endpoint from your account.

This API allows you to permanently delete an endpoint from your Vobiz account. Once deleted, the endpoint's SIP URI will no longer be accessible, and any devices or applications registered with this endpoint will be disconnected.

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token Header:** Your account Auth Token

Warning - Permanent Deletion:

This action is permanent and cannot be undone. Deleting an endpoint will immediately unregister it from all devices and make the SIP URI permanently unavailable. Ensure that no active calls or registrations depend on this endpoint before deletion.

HTTP Request

DELETE `https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/{endpointID}/`

Base URL:

```
https://api.vobiz.ai/api/v1
```

Note: No request parameters are required for this endpoint.

Response

Success Response (204 No Content)

If successful, returns HTTP status code 204 No Content with an empty response body.

Response - 204 No Content

```
HTTP/1.1 204 No Content
```

Error Response (404 Not Found)

If the endpoint does not exist or has already been deleted.

Response - 404 Not Found

```
HTTP/1.1 404 Not Found
```

Examples

cURL

cURL Request

```
curl -X DELETE https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/87654321/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Before Deletion:

- Verify the endpoint is no longer needed
- Check for any active registrations on SIP clients
- Ensure no applications are routing calls to this endpoint
- Consider updating endpoint instead if you need to change credentials

Impact:
Deleting an endpoint will immediately unregister it from all devices and make the SIP URI permanently unavailable. This action cannot be reversed.

Retrieve an Endpoint

Get detailed information about a specific endpoint including registration status.

This API allows you to retrieve the details of an existing endpoint. The

response includes all endpoint attributes and, if the endpoint is currently registered on a SIP client, additional registration details.

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token Header:** Your account Auth Token

HTTP Request

GET `https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/{endpointID}/`

Base URL:

```
https://api.vobiz.ai/api/v1
```

Note: No request parameters are required for this endpoint.

Response

Returns an Endpoint object if valid parameters were provided. Returns an error otherwise.

Success Response (200 OK)

Response - 200 OK

```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "endpoint_id": "87654321",
  "username": "john_doe",
  "alias": "John's Desktop Phone",
  "sip_uri": "sip:john_doe@sip.vobiz.ai",
  "sip_registered": "true",
  "sip_registration": {
    "contact": "192.168.1.100:5060",
    "expires": "2025-10-28T11:30:00Z",
    "user_agent": "Zoiper v5.4.5",
    "received": "203.0.113.42:5060",
    "path": null
  },
  "application": {
    "app_id": "12345678",
    "app_name": "Customer Service App",
    "answer_url": "https://example.com/answer",
```

```
    "answer_method": "POST"
  },
  "allow_voice": true,
  "allow_message": true,
  "allow_video": false,
  "allow_same_domain": true,
  "allow_other_domains": false,
  "allow_phones": true,
  "allow_apps": true,
  "sub_account": null,
  "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654321/",
  "created_at": "2025-10-27T10:30:00Z",
  "updated_at": "2025-10-28T09:15:00Z"
}
```

Registration Details:
The sip_registration object contains detailed information about the endpoint's current SIP registration including contact address, expiration time, user agent, and received address. This object is only present when sip_registered is "true".

Error Response (404 Not Found)

Response - 404 Not Found

```
{
  "error": "Endpoint not found",
  "endpoint_id": "99999999"
}
```

Examples

cURL

cURL Request

```
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/87654321/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Use Cases:

- Verify endpoint registration status before making calls
- Check which application is attached to an endpoint
- Monitor SIP client registration expiration times
- Retrieve SIP URI for sharing with external users

- View detailed permission settings for an endpoint

Update an Endpoint

Update an endpoint's password, alias, or attached application.

This API allows you to update an existing endpoint's configuration. You can change the password for security purposes, update the alias for better identification, or modify the application that handles incoming calls to this endpoint.

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token Header:** Your account Auth Token

Warning - Cannot Update:

The following fields are locked after endpoint creation and cannot be updated: username, endpoint_id, domain, allow_same_domain, allow_other_domains, allow_phones, allow_apps. To change these values, you must create a new endpoint and delete the old one.

HTTP Request

POST `https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/{endpointID}/`

Base URL:

```
https://api.vobiz.ai/api/v1
```

Request Parameters

Request Parameters

Parameter	Type	Description
`password` optional	string	SIP password (minimum 8 characters). Use this to reset or update the endpoint password.
`alias` optional	string	Friendly name for the endpoint.
`application` optional	integer	Application ID for call routing. This application will handle incoming calls to the endpoint.
`allow_voice` optional	boolean	Allow voice calls (default: true).
`allow_message` optional	boolean	Allow messaging (default: true).
`allow_video` optional	boolean	Allow video calls (default: false).

Note: All parameters are optional. You only need to include the fields you want to update. Fields not provided will remain unchanged.

Response

Success Response (202 Accepted)

If successful, returns HTTP status code 202 Accepted with no response body.

Response - 202 Accepted

`HTTP/1.1 202 Accepted`

Error Response (400 Bad Request)

Response - 400 Bad Request

```
{
  "error": "invalid request parameters",
  "details": {
    "password": "Password must be at least 8 characters"
  }
}
```

Error Response (404 Not Found)

Response - 404 Not Found

`HTTP/1.1 404 Not Found`

Examples

Update Alias

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/87654321/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "alias": "John'''s Updated Desktop Phone"
  }'
```

Update Password

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/87654321/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "password": "NewSecurePassword456!"
  }'
```

Update Multiple Fields

cURL Request

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/87654321/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "alias": "John'''s Updated Desktop Phone",
    "password": "NewSecurePassword456!",
    "application": 98765432,
    "allow_voice": true,
    "allow_message": true,
    "allow_video": true
  }'
```

Common Use Cases:

- Reset forgotten endpoint passwords
- Update aliases to reflect role changes
- Switch applications for different call routing logic
- Rotate passwords regularly for security
- Enable or disable video/messaging capabilities

Tip:
After updating a password, SIP clients using this endpoint will need to re-register with the new credentials. Plan updates during maintenance windows to minimize disruption.

List all Endpoints

Retrieve a paginated list of all SIP endpoints in your account.

This API allows you to retrieve a list of all endpoints configured in your account. The response includes complete details for each endpoint, including registration status and attached applications.

Authentication Required:

- **X-Auth-ID Header:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Include your access token in the headers

HTTP Request

GET `https://api.vobiz.ai/api/v1/Account/{authID}/Endpoint/`

Base URL:

```
https://api.vobiz.ai/api/v1
```

Query Parameters

Request Parameters

Parameter	Type	Description
`limit` optional	integer	Number of results per page (max 100, default: 20)
`offset` optional	integer	Number of results to skip (default: 0)
`username__contains` optional	string	Filter by username (partial match)
`username__exact` optional	string	Filter by exact username

Parameter	Type	Description
`username__startswith` optional	string	Filter by username prefix
`alias__contains` optional	string	Filter by alias (partial match)
`alias__exact` optional	string	Filter by exact alias
`application_id__exact` optional	integer	Filter by application ID
`application_id__isnull` optional	boolean	Filter endpoints without application
`sub_account` optional	string	Filter by sub-account auth_id

Response

Returns

a dictionary with an objects property that contains an array of Endpoint objects, along with a meta object containing pagination information.

Response - 200 OK


```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "meta": {
    "limit": 20,
    "offset": 0,
    "total_count": 45
  },
  "objects": [
    {
      "endpoint_id": "87654321",
      "username": "john_doe",
      "alias": "John's Desktop Phone",
      "sip_uri": "sip:john_doe@sip.vobiz.ai",
      "sip_registered": "true",
      "sip_contact": "192.168.1.100:5060",
      "sip_expires": "2025-10-28T11:30:00Z",
      "sip_user_agent": "Zoiper v5.4.5",
      "application": {
        "app_id": "12345678",
        "app_name": "Customer Service App"
      },
      "allow_voice": true,
      "allow_message": true,
      "allow_video": false,
      "allow_same_domain": true,
      "allow_other_domains": false,
      "allow_phones": true,
```

```
      "allow_apps": true,
      "sub_account": null,
      "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654321/",
      "created_at": "2025-10-27T10:30:00Z",
      "updated_at": "2025-10-28T09:15:00Z"
    },
    {
      "endpoint_id": "87654322",
      "username": "jane_smith",
      "alias": "Jane's Mobile",
      "sip_uri": "sip:jane_smith@sip.vobiz.ai",
      "sip_registered": "false",
      "sip_contact": null,
      "sip_expires": null,
      "sip_user_agent": null,
      "application": null,
      "allow_voice": true,
      "allow_message": true,
      "allow_video": true,
      "allow_same_domain": true,
      "allow_other_domains": false,
      "allow_phones": true,
      "allow_apps": true,
      "sub_account": null,
      "resource_uri": "/v1/Account/{Auth_ID}/Endpoint/87654322/",
      "created_at": "2025-10-26T14:20:00Z",
      "updated_at": "2025-10-26T14:20:00Z"
    }
  ]
}
```


Note:
The response includes both registered and unregistered endpoints. Registered endpoints have sip_contact, sip_expires, and sip_user_agent populated, while unregistered endpoints have these fields set to null.

Examples

cURL - List All Endpoints

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/?limit=20&offset=0" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

cURL - Filter by Username

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/?username__contains=john" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Build Endpoint Dashboard

JavaScript Example

```
async function getEndpointDashboard() {
  const response = await fetch(
    'https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Endpoint/',
    {
       headers: {
         'X-Auth-ID': '{Auth_ID}',
         'X-Auth-Token': '{access_token}'
       }
     }
  );

  const data = await response.json();

  const dashboard = {
    total: data.meta.total_count,
    registered: data.objects.filter(ep => ep.sip_registered === 'true').length,
    unregistered: data.objects.filter(ep => ep.sip_registered === 'false').length,
    endpoints: data.objects.map(ep => ({
      id: ep.endpoint_id,
      alias: ep.alias,
      username: ep.username,
      registered: ep.sip_registered === 'true',
      expires: ep.sip_expires || null
    }))
  };

  return dashboard;
}

getEndpointDashboard().then(console.log);
```

Use Cases:

- Build endpoint management dashboards
- Monitor registration status across all endpoints
- Audit endpoint configurations and attached applications
- Identify unregistered endpoints for troubleshooting
- Filter endpoints by username or alias for quick searches