vobiz endpoints 3

Created	@March 17, 2026 1:00 AM
Class	vobiz

Applications

An Application is a set of Answer, Hangup, and Message URLs that help you control your incoming calls and messages.

Key Concepts

Answer URL

Vobiz requests this URL for a valid Vobiz XML element on an incoming call. The XML returned by this URL determines the flow of the call.

Hangup URL

Vobiz will make an HTTP request to this URL when the call is hung up. Useful for call analytics and cleanup operations.

Message URL

Vobiz will send all incoming messages to this URL. We expect to receive an HTTP status code of 200 from this URL.

SIP URI

All Vobiz applications can be called directly without attaching them to a number or an endpoint. When an incoming call is received on this URI, Vobiz follows the same flow as it does with a number or an endpoint.

Application Operations

The Application Object

View the structure and attributes of the Application object including URLs, methods, and default settings.

Create an Application

POST request to create a new application with answer URL, hangup URL, and message URL configuration.

Retrieve an Application

GET request to retrieve all details of a specific application by app_id.

Update an Application

POST request to modify application settings. Unspecified parameters remain unchanged.

Delete an Application

DELETE request to permanently remove an application. Optionally cascade delete associated endpoints.

List All Applications

GET request to retrieve all applications with optional filtering and pagination support.

Link Numbers

Manage associations between phone numbers and voice applications (Attach/Detach).

Webhook Callbacks

Answer URL Callback

When a call is answered, Vobiz makes a request to your `answer_url` with call details.

Request Parameters:

```
POST https://example.com/answer
Content-Type: application/x-www-form-urlencoded

CallUUID=abc123&From=14155551234&To=14155556789&Direction=inb
ound&CallStatus=ringing
```

Expected Response (XML):

```
<?xml version="1.0" encoding="UTF-8"?>
<Response>
  <Speak>Welcome to our service</Speak>
  <Gather numDigits="1" action="https://example.com/gather">
    <Speak>Press 1 for sales, 2 for support</Speak>
  </Gather>
</Response>
```

Hangup URL Callback

When a call ends, Vobiz notifies your `hangup_url` with call details and duration.

Request Parameters:

```
POST https://example.com/hangup
Content-Type: application/x-www-form-urlencoded

CallUUID=abc123&CallStatus=completed&Duration=45&HangupCause=
NORMAL_CLEARING
```

Best Practices

Always Use HTTPS

All webhook URLs (answer_url, hangup_url, etc.) must use HTTPS for security.

Handle Retries

Vobiz retries failed webhook calls up to 3 times. Ensure idempotent operations.

Respond Quickly

Answer URL must respond within 10 seconds to avoid call timeout.

Validate Webhooks

Verify requests are from Vobiz using signature validation.

Use Fallback URLs

Always configure fallback_answer_url for production apps to handle failures.

Test in Development

Use test account before deploying to production environment.

Monitor Usage

Check which numbers/endpoints use each app before deletion.

The Application Object

The Application object contains all configuration for call and message handling, including URL endpoints and HTTP methods.

Attributes

Application Attributes

Parameter	Type	Description
`app_id` optional	string	Unique identifier for the application.
`app_name` optional	string	Name of the application.
`answer_url` optional	string	URL called when call is answered. Vobiz requests this URL for valid Vobiz XML elements to control call flow.
`answer_method` optional	string	HTTP method for answer_url (GET or POST).

Parameter	Type	Description
`hangup_url` optional	string	URL called when call ends. Useful for call analytics and cleanup operations.
`hangup_method` optional	string	HTTP method for hangup_url (GET or POST).
`fallback_answer_url` optional	string	Backup URL if answer_url fails or returns invalid XML.
`fallback_method` optional	string	HTTP method for fallback URL (GET or POST).
`message_url` optional	string	URL for SMS message callbacks. Vobiz expects HTTP 200 status code.
`message_method` optional	string	HTTP method for message_url (GET or POST).
`default_number_app` optional	boolean	Default app for phone numbers. If true, newly created numbers without app_id use this application.
`default_endpoint_app` optional	boolean	Default app for SIP endpoints. If true, newly created endpoints without app_id use this application.
`sub_account` optional	string	Sub-account auth_id (null for main account).
`resource_uri` optional	string	API resource URI.
`application_type` optional	string	The type of application (e.g., "voice", "messaging").
`default_app` optional	boolean	Whether this is the default application for the account.
`enabled` optional	boolean	Whether the application is enabled.
`log_incoming_message` optional	boolean	Whether incoming messages are logged.
`public_uri` optional	boolean	Whether the application has a public URI.
`sip_transfer_method` optional	string	HTTP method used for SIP transfer callbacks.
`sip_transfer_url` optional	string	URL notified during a SIP transfer.

Parameter	Type	Description
`sip_uri` optional	string	SIP URI associated with the application.
`created_at` optional	string (ISO 8601)	Creation timestamp.
`updated_at` optional	string (ISO 8601)	Last update timestamp.

Example Application Object

JSON

```
{
  "api_id": "{api_id}",
  "app_id": "12345678",
  "app_name": "My Voice Application",
  "application_type": "voice",
  "enabled": true,
  "default_app": false,
  "answer_url": "https://example.com/answer",
  "answer_method": "POST",
  "hangup_url": "https://example.com/hangup",
  "hangup_method": "POST",
  "fallback_answer_url": "https://example.com/fallback",
  "fallback_method": "POST",
  "message_url": "https://example.com/message",
  "message_method": "POST",
  "log_incoming_message": true,
  "public_uri": false,
  "sip_transfer_method": "POST",
  "sip_transfer_url": "https://example.com/sip-transfer",
  "sip_uri": "sip:12345678@vobiz.ai",
  "default_number_app": false,
  "default_endpoint_app": false,
  "sub_account": null,
  "resource_uri": "/v1/Account/{auth_id}/Application/12345678/",
  "created_at": "2025-10-28T10:30:00Z",
  "updated_at": "2025-10-28T10:30:00Z"
}
```

Create an Application

POST `https://api.vobiz.ai/api/v1/Account/{authID}/Application/`

Creates
an Application with webhook URLs for call handling. Creating an

application is usually a first step, after which you attach the application to either a number or an endpoint.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Parameters

Request Parameters

Parameter	Type	Description
`answer_url` required	string	The URL fetched when a call executes this application.
`app_name` required	string	The name of your application. Allowed Values: Alphabets (upper case and lower case), Numbers (0-9), Only 2 special characters, i.e. "-" (hyphen) and "_" (underscore)
`answer_method` optional	string	The method used to call the answer_url. Defaults to POST.
`hangup_url` optional	string	The URL notified when the call hangs up. Defaults to answer_url.
`hangup_method` optional	string	The method used to call the hangup_url. Defaults to POST.
`fallback_answer_url` optional	string	Invoked by Vobiz only if answer_url is unavailable or the XML response is invalid. Should contain an XML response.
`fallback_method` optional	string	The method used to call the fallback_answer_url. Defaults to POST.
`message_url` optional	string	The URL notified when an inbound message is received. Defaults not set.
`message_method` optional	string	The method used to call the message_url. Defaults to POST.

Parameter	Type	Description
`default_number_app` optional	boolean	If set to true, this parameter ensures that newly created numbers that don't have an app_id point to this application.
`default_endpoint_app` optional	boolean	If set to true, this parameter ensures that newly created endpoints that don't have an app_id point to this application.
`subaccount` optional	string	ID of the subaccount that this application is associated with.
`application_type` optional	string	The type of application (e.g., "voice", "messaging").
`default_app` optional	boolean	Whether this is the default application for the account.
`enabled` optional	boolean	Whether the application is enabled. Defaults to true.
`log_incoming_messages` optional	boolean	If set to false, the content of incoming messages to Vobiz phone numbers associated with this application are not logged in Vobiz systems. Defaults to true when not specified.
`public_uri` optional	boolean	Whether the application has a public URI.
`sip_transfer_method` optional	string	HTTP method used for SIP transfer callbacks.
`sip_transfer_url` optional	string	URL notified during a SIP transfer.
`sip_uri` optional	string	SIP URI associated with the application.

Request Body

JSON

```
{
  "app_name": "My Voice Application",
```

```
  "answer_url": "https://example.com/answer",
  "answer_method": "POST",
  "hangup_url": "https://example.com/hangup",
  "hangup_method": "POST",
  "fallback_answer_url": "https://example.com/fallback",
  "fallback_method": "POST",
  "message_url": "https://example.com/message",
  "message_method": "POST",
  "default_number_app": false,
  "default_endpoint_app": false,
  "sub_account": null
}
```

Response Examples

Success Response (201 Created)

```
{
  "api_id": "{api_id}",
  "message": "created",
  "app_id": "12345678",
  "application_type": "voice",
  "enabled": true,
  "default_app": false,
  "resource_uri": "/v1/Account/{auth_id}/Application/12345678/"
}
```

Error Response (400 Bad Request)

```
{
  "error": "invalid request parameters",
  "details": {
    "app_name": "This field is required",
    "answer_url": "Enter a valid URL"
  }
}
```

cURL Example

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Application/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "app_name": "My IVR System",
    "answer_url": "https://myapp.com/ivr/answer",
    "answer_method": "POST"
  }'
```

Retrieve an Application

GET `https://api.vobiz.ai/api/v1/Account/{authID}/Application/{appID}/`

Get details of a particular application by passing the app_id. This API returns all the information linked with the application.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Arguments

No request parameters needed.

Response Examples

Success Response (200 OK)

```
{
  "api_id": "{api_id}",
  "app_id": "12345678",
  "app_name": "My Voice Application",
  "application_type": "voice",
  "enabled": true,
  "default_app": false,
  "answer_url": "https://example.com/answer",
  "answer_method": "POST",
  "hangup_url": "https://example.com/hangup",
  "hangup_method": "POST",
  "fallback_answer_url": "https://example.com/fallback",
  "fallback_method": "POST",
  "message_url": "https://example.com/message",
  "message_method": "POST",
  "log_incoming_message": true,
  "public_uri": false,
  "sip_transfer_method": "POST",
  "sip_transfer_url": "https://example.com/sip-transfer",
  "sip_uri": "sip:12345678@vobiz.ai",
  "default_number_app": false,
  "default_endpoint_app": false,
  "sub_account": null,
  "resource_uri": "/v1/Account/{auth_id}/Application/12345678/",
  "created_at": "2025-10-28T10:30:00Z",
  "updated_at": "2025-10-28T10:30:00Z"
}
```

Error Response (404 Not Found)

```
{
  "error": "Application not found",
  "app_id": "99999999"
}
```

cURL Example

cURL

```
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Application/12345678/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Update an Application

POST `https://api.vobiz.ai/api/v1/Account/{authID}/Application/{appID}/`

Modify an application using this API. You can update any subset of fields (partial update).

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Important Notes:

- Fields not provided will remain unchanged
- **sub_account** cannot be changed after creation

Parameters

Request Parameters

Parameter	Type	Description
`answer_url` optional	string	The URL invoked when a call executes this application.
`answer_method` optional	string	The method used to call the answer_url. Defaults to POST.

Parameter	Type	Description
`hangup_url` optional	string	The URL notified when the call hangs up.
`hangup_method` optional	string	The method used to call the hangup_url. Defaults to POST.
`fallback_answer_url` optional	string	Invoked by Vobiz only if answer_url is unavailable or the XML response is invalid.
`fallback_method` optional	string	The method used to call the fallback_answer_url. Defaults to POST.
`message_url` optional	string	The URL that is notified by Vobiz when an inbound message is received.
`message_method` optional	string	The method used to call the message_url. Defaults to POST.
`default_number_app` optional	boolean	If set to true, associates all newly created Vobiz numbers that have not specified an app_id to this application.
`default_endpoint_app` optional	boolean	If set to true, associates all newly created Vobiz endpoints that have not specified an app_id to this application.
`subaccount` optional	string	ID of the subaccount with which this application is associated.
`application_type` optional	string	The type of application (e.g., "voice", "messaging").
`default_app` optional	boolean	Whether this is the default application for the account.
`enabled` optional	boolean	Whether the application is enabled.
`log_incoming_messages` optional	boolean	Controls whether incoming messages to phone numbers associated with the Application are logged in Vobiz systems.
`public_uri` optional	boolean	Whether the application has a public URI.
`sip_transfer_method` optional	string	HTTP method used for SIP transfer

Parameter	Type	Description
		callbacks.
`sip_transfer_url` optional	string	URL notified during a SIP transfer.
`sip_uri` optional	string	SIP URI associated with the application.

Request Body

JSON

```
{
  "app_name": "Updated Application Name",
  "answer_url": "https://example.com/updated-answer",
  "answer_method": "POST",
  "hangup_url": "https://example.com/updated-hangup",
  "hangup_method": "POST",
  "fallback_answer_url": "https://example.com/updated-fallback",
  "fallback_method": "POST",
  "message_url": "https://example.com/updated-message",
  "message_method": "POST",
  "default_number_app": true,
  "default_endpoint_app": false
}
```

Response Examples

Success Response (200 OK)

```
{
  "api_id": "{api_id}",
  "message": "changed",
  "app_id": "12345678",
  "application_type": "voice",
  "enabled": true,
  "default_app": false,
  "resource_uri": "/v1/Account/{auth_id}/Application/12345678/"
}
```

Error Response (400 Bad Request)

```
{
  "error": "invalid request parameters",
  "details": {
    "answer_url": "Enter a valid URL"
  }
}
```

Error Response (404 Not Found)

```
{
  "error": "Application not found",
  "app_id": "99999999"
}
```

cURL Example

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Application/12345678/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "app_name": "Updated IVR System",
    "default_number_app": true
  }'
```

Delete an Application

DELETE `https://api.vobiz.ai/api/v1/Account/{authID}/Application/{appID}/`

This API deletes an Application permanently.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Warning:

Deleting an application is permanent and cannot be undone. If the application is associated with phone numbers, the deletion may be blocked unless those associations are removed first.

Arguments

No request parameters needed.

Response Examples

Success Response (204 No Content)

(No response body)

Error Response (404 Not Found)

```
{
  "error": "Application not found",
  "app_id": "99999999"
}
```

Error Response (409 Conflict)

```
{
  "error": "Cannot delete application",
  "message": "Application is currently in use by 5 phone numbers"
}
```

cURL Example

cURL

```
curl -X DELETE https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Application/12345678/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

List All Applications

GET `https://api.vobiz.ai/api/v1/Account/{authID}/Application/`

This API is used to get details of all the application that have been created under your Vobiz account.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Parameters

Request Parameters

Parameter	Type	Description
`limit` optional	integer	Number of results per page (max 100). Defaults to 20.
`offset` optional	integer	Number of results to skip. Defaults to 0.

Response Example

Success Response (200 OK)


```
{
  "api_id": "550e8400-e29b-41d4-a716-446655440000",
  "meta": {
    "limit": 20,
    "offset": 0,
    "total_count": 45
  },
  "objects": [
    {
      "app_id": "12345678",
      "app_name": "My Voice Application",
      "application_type": "voice",
      "enabled": true,
      "default_app": false,
      "answer_url": "https://example.com/answer",
      "answer_method": "POST",
      "hangup_url": "https://example.com/hangup",
      "hangup_method": "POST",
      "fallback_answer_url": "https://example.com/fallback",
      "fallback_method": "POST",
      "message_url": "https://example.com/message",
      "message_method": "POST",
      "log_incoming_message": true,
      "public_uri": false,
      "sip_transfer_method": "POST",
      "sip_transfer_url": "https://example.com/sip-transfer",
      "sip_uri": "sip:12345678@vobiz.ai",
      "default_number_app": false,
      "default_endpoint_app": false,
      "sub_account": null,
      "resource_uri": "/v1/Account/{auth_id}/Application/12345678/",
      "created_at": "2025-10-28T10:30:00Z",
      "updated_at": "2025-10-28T10:30:00Z"
    },
    {
      "app_id": "87654321",
      "app_name": "Customer Service App",
      "application_type": "voice",
      "enabled": true,
      "default_app": true,
      "answer_url": "https://example.com/cs/answer",
      "answer_method": "GET",
      "hangup_url": null,
      "hangup_method": null,
      "fallback_answer_url": null,
      "fallback_method": null,
      "message_url": null,
      "message_method": null,
      "log_incoming_message": true,
      "public_uri": false,
```

```
      "sip_transfer_method": "POST",
      "sip_transfer_url": null,
      "sip_uri": "sip:87654321@vobiz.ai",
      "default_number_app": true,
      "default_endpoint_app": false,
      "sub_account": null,
      "resource_uri": "/v1/Account/{auth_id}/Application/87654321/",
      "created_at": "2025-10-27T15:20:00Z",
      "updated_at": "2025-10-28T08:15:00Z"
    }
  ]
}
```

cURL Example

cURL

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Application/?limit=20&offset=0" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Link Numbers

Manage
 the association between your phone numbers and voice applications. You can attach a number to an application to handle incoming calls, or detach it to remove the association.

Attach Number to Application

POST `https://api.vobiz.ai/api/v1/account/{authID}/numbers/{number}/application`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Parameters

Request Parameters

Parameter	Type	Description
`number` required	string	The E.164 formatted phone number (URL

Parameter	Type	Description
		encoded, e.g., %2B1234567890)
`application_id` required	string	The ID of the application to link to this number.

Example Request

cURL

```
curl -X POST
"https://api.vobiz.ai/api/v1/account/{Auth_ID}/numbers/%2B1234567890/application" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "application_id": "app_xxxxxxxxxxxx"
  }'
```

Response

Success Response (200 OK)

```
{
  "message": "Number linked successfully",
  "number": "+1234567890",
  "application_id": "app_xxxxxxxxxxxx"
}
```

Detach Number from Application

DELETE `https://api.vobiz.ai/api/v1/account/{authID}/numbers/{number}/application`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token

Parameters

Request Parameters

Parameter	Type	Description
`number` required	string	The E.164 formatted phone number (URL encoded) to detach from its application.

Example Request

cURL

```
curl -X DELETE
"https://api.vobiz.ai/api/v1/account/{Auth_ID}/numbers/%2B1234567890/application" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Response

Success Response (200 OK)

```
{
  "message": "Number detached successfully",
  "number": "+1234567890"
}
```

Recording

Manage call and conference recordings in your account with retrieval and deletion capabilities.

The
 Recording API allows you to manage recordings that are stored in your Vobiz account. You can retrieve recording details including storage duration and billing information, list recordings with advanced filtering options, and delete recordings when they're no longer needed.

Call Recordings

Manage recordings from regular voice calls with detailed metadata.

Conference Recordings

Access recordings from conference calls and multiparty calls.

Storage Management

Track storage duration and associated monthly costs.

File Formats

Recordings are available in MP3 and WAV formats.

Important:
 Recordings are stored securely and accessible via HTTPS URLs. Storage

costs are calculated monthly based on the recording duration and storage time.

API Endpoint

Base URL

https://api.vobiz.ai/api/v1

Recording Base URI

https://api.vobiz.ai/api/v1/Account/{auth_id}/Recording/

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., {Auth_ID})
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Available Operations

OBJECT**The Recording object**
Complete structure and attributes of a Recording object including storage and billing details.View Documentation →GET**Retrieve a recording**
Get details of a specific recording based on its recording ID.View Documentation →GET**List all recordings**
Retrieve a list of all recordings with extensive filtering options.View Documentation →DELETE**Delete a recording**
Permanently delete a specific recording from your account.View Documentation →POST**Export historical recordings**
Export recordings as a downloadable archive sent via email (async operation).View Documentation →DELETE**Bulk delete recordings**
Delete multiple recordings matching filter criteria (async operation).View Documentation →

Note:
Vobiz automatically rounds recording durations to the nearest 60-second interval. Recordings shorter than 60 seconds are rounded up to 60 seconds for billing purposes.

The Recording Object

Complete structure and attributes of a Vobiz Recording object.

The Recording object represents a call or conference recording stored in your Vobiz account. It includes detailed information about the recording file, associated call details, storage duration, and billing information.

Note: All recordings are automatically stored when call or conference recording is enabled. Storage costs are calculated based on duration and time stored, tracked in the `recording_storage_duration` and `monthly_recording_storage_amount` fields.

Attributes

Core Attributes

Parameter	Type	Description
`recording_id` optional	string	Unique identifier for the recording. Used in API operations to identify specific recordings.
`recording_url` optional	string	Direct HTTPS download URL for the audio file. Use this to download or stream the recording.
`recording_format` optional	string	Audio format of the recording file. Allowed values: "mp3", "wav".
`call_uuid` optional	string	UUID of the call or conference that was recorded.
`conference_name` optional	string	Name of the conference that was recorded. Value is null if it was a regular call, not a conference.
`recording_type` optional	string	Type of recording. Values: "call" (regular call), "conference" (conference call).

Parameter	Type	Description
`add_time` optional	timestamp	Timestamp when the recording was created. Format: ISO 8601 (YYYY-MM-DDTHH:MM:SSZ).

Duration & Timing Attributes

Parameter	Type	Description
`recording_start_ms` optional	float	Recording start time in milliseconds since epoch.
`recording_end_ms` optional	float	Recording end time in milliseconds since epoch.
`recording_duration_ms` optional	float	Actual duration of the recording in milliseconds.
`rounded_recording_duration` optional	integer	Rounded duration in seconds used for billing calculations.

Call Details

Parameter	Type	Description
`from_number` optional	string	Caller phone number in E.164 format (e.g., +14155551234).
`to_number` optional	string	Destination phone number in E.164 format.

Storage & Billing Attributes

Parameter	Type	Description
`recording_storage_duration` optional	integer	Number of days since the recording was created. Used to calculate storage costs.
`recording_storage_rate` optional	float	Storage rate per month in USD. This is the unit cost for storing this recording.
`monthly_recording_storage_amount` optional	float	Monthly storage cost in USD for the current billing

Parameter	Type	Description
		cycle.

Example

Complete Recording Object (Conference)

JSON Response


```
{
    "api_id": "668470b7-7a8f-49b6-9011-50075754a50a",
    "meta": {
        "limit": 20,
        "next": null,
        "offset": 0,
        "previous": null,
        "total_count": 1
    },
    "objects": [
        {
            "add_time": "2025-11-06 13:49:10.751756+00:00",
            "call_uuid": "6e558798-499c-4a68-bc77-46f2c53d1f69",
            "conference_name": "",
            "from_number": "+918071387423",
            "monthly_recording_storage_amount": 0,
            "recording_duration_ms": "10080.00000",
            "recording_end_ms": "1762436949502.00000",
            "recording_format": "mp3",
            "recording_id": "d7801b2e-e76d-4dd8-be9c-9e015a7267b8",
            "recording_start_ms": "1762436939422.00000",
            "recording_storage_duration": 1,
            "recording_storage_rate": 0.005,
            "recording_type": "call",
            "recording_url":
"https://media.vobiz.ai/api/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8.mp3",
            "resource_uri": "/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8/",
            "rounded_recording_duration": 60,
            "to_number": "919624705678"
        }
    ]
}
```


Regular Call Recording Example

JSON Response

```
{
    "api_id": "668470b7-7a8f-49b6-9011-50075754a50a",
    "meta": {
        "limit": 20,
        "next": null,
        "offset": 0,
        "previous": null,
        "total_count": 1
    },
    "objects": [
        {
            "add_time": "2025-11-06 13:49:10.751756+00:00",
            "call_uuid": "6e558798-499c-4a68-bc77-46f2c53d1f69",
            "conference_name": null,
            "from_number": "+918071387423",
            "monthly_recording_storage_amount": 0,
            "recording_duration_ms": "10080.00000",
            "recording_end_ms": "1762436949502.00000",
            "recording_format": "mp3",
            "recording_id": "d7801b2e-e76d-4dd8-be9c-9e015a7267b8",
            "recording_start_ms": "1762436939422.00000",
            "recording_storage_duration": 1,
            "recording_storage_rate": 0.005,
            "recording_type": "call",
            "recording_url":
"https://media.vobiz.ai/api/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8.mp3",
            "resource_uri": "/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8/",
            "rounded_recording_duration": 60,
            "to_number": "919624705678"
        }
    ]
}
```


Key Differences:

- **Conference Recording:** `conference_name` contains the conference name, `recording_type` is "conference"
- **Regular Call:** `conference_name` is null, `recording_type` is "call"
- **Duration:** `recording_duration_ms` is actual duration, `rounded_recording_duration` is used for billing
- **Storage Cost:** Calculated from `recording_storage_rate` × `recording_storage_duration`

Important Notes:

- Recording URLs may be temporary - download recordings for permanent storage
- `recording_storage_duration` increments daily and affects monthly costs
- Timestamps (`recording_start_ms`, `recording_end_ms`) are in milliseconds since Unix epoch
- Storage rate and amount are in USD

Retrieve a Recording

Get detailed information about a specific recording using its recording ID.

This API allows you to retrieve the details of a specific recording based on its recording ID. The response includes complete information about the recording file, associated call details, storage duration, and billing information.

Note: You can obtain the recording_id from the List all recordings endpoint or from webhook notifications when recordings are created.

HTTP Request

GET `https://api.vobiz.ai/api/v1/Account/{auth_id}/Recording/{recording_id}/`

Authentication Headers

`X-Auth-ID:` Your account auth_id (e.g., {Auth_ID})

`X-Auth-Token:` Your account auth token

Path Parameters:

- `{auth_id}` - Your account ID
- `{recording_id}` - The unique recording identifier

Response

Returns a complete Recording object with all attributes if the recording ID is valid.

Success Response (200 OK)

Response - 200 OK


```
{
    "api_id": "668470b7-7a8f-49b6-9011-50075754a50a",
    "meta": {
        "limit": 20,
        "next": null,
        "offset": 0,
        "previous": null,
        "total_count": 1
    },
    "objects": [
        {
            "add_time": "2025-11-06 13:49:10.751756+00:00",
            "call_uuid": "6e558798-499c-4a68-bc77-46f2c53d1f69",
            "conference_name": "",
            "from_number": "+918071387423",
            "monthly_recording_storage_amount": 0,
            "recording_duration_ms": "10080.00000",
            "recording_end_ms": "1762436949502.00000",
            "recording_format": "mp3",
            "recording_id": "d7801b2e-e76d-4dd8-be9c-9e015a7267b8",
            "recording_start_ms": "1762436939422.00000",
            "recording_storage_duration": 1,
            "recording_storage_rate": 0.005,
            "recording_type": "call",
            "recording_url":
"https://media.vobiz.ai/api/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8.mp3",
            "resource_uri": "/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-4dd8-be9c-
9e015a7267b8/",
            "rounded_recording_duration": 60,
            "to_number": "919624705678"
        }
    ]
}
```


Error Response (404 Not Found)

Response - 404 Not Found


```
{
    "api_id": "correlation-id-uuid",
    "error": "Recording not found"
}
```


Examples

cURL Request

cURL

```
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Download Recording File

Use the recording_url from the response to download the actual audio file:

Two-Step Process

```
# Step 1: Get the recording details
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"

# Step 2: Extract recording_url from response and download
# Example URL: https://media.vobiz.ai/api/v1/Account/MA_PU0XU668/Recording/d7801b2e-e76d-
4dd8-be9c-9e015a7267b8.mp3
curl -o recording.mp3 "https://media.vobiz.ai/api/v1/Account/MA_PU0XU668/Recording/d7801b2e-
e76d-4dd8-be9c-9e015a7267b8.mp3"
```

Using jq to Extract URL

Bash Script with jq

```
# Get recording URL and download in one command
RECORDING_URL=$(curl -s -X GET
https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  | jq -r '.recording_url')

curl -o recording.mp3 "$RECORDING_URL"
```

Use Cases:

- Verify recording details before downloading
- Check storage duration for billing purposes
- Confirm recording format (MP3 vs WAV)
- Get the download URL for archiving
- Validate recording metadata (call_uuid, phone numbers)

Tip:
The recording_url provides direct access to the audio file and can be used in media players or downloaded programmatically. However, these URLs may be temporary, so download recordings immediately for permanent storage.

Important: Always check the `api_id` field in responses for correlation and debugging purposes. This ID is useful when contacting support about specific requests.

List All Recordings

Retrieve a paginated list of call recordings for your account.

This
API endpoint allows you to fetch a list of call recordings with pagination support. You can filter recordings by type (trunk or extension) and control the number of results returned per request.

Use Cases:
Retrieve recordings for archival, compliance, quality assurance, or to provide playback links to customers. The response includes recording IDs, call IDs for cross-referencing with CDRs, and download URLs.

HTTP Request

GET `https://api.vobiz.ai/api/v1/Account/{ACCOUNT_ID}/Recording/`

Case Sensitivity Notice:

Note that `Account` and `Recording` are capitalized in the URL path. Some APIs are case-sensitive, so ensure the capitalization matches exactly.

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., MA_XXXXXXXX)
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

Query String Parameters

Parameter	Type	Description
`limit` optional	integer	The number of recording records to return in one request (default: 20, max: 100).
`offset` optional	integer	Where to start the list for pagination. Set to 20 to see the next page after the first 20 results (default: 0).
`call_uuid` optional	string	Filter recordings by a specific call UUID. Returns only recordings associated with the given call.
`recording_type` optional	string	Filter by recording type. Common values: "trunk" or "extension".

Response

A successful request returns a `200 OK` status with a JSON array of recording objects.

Success Response - 200 OK


```
{
  "recordings": [
    {
      "recording_id": "REC_abc123def456",
      "call_id": "7f8e9d2c-1a3b-4c5d-6e7f-8g9h0i1j2k3l",
      "recording_type": "trunk",
      "url": "https://recordings.vobiz.ai/files/REC_abc123def456.mp3",
      "download_path": "/v1/Account/MA_XXXXXXXX/Recording/REC_abc123def456/download",
      "duration": 312,
      "created_at": "2026-01-23T10:30:00Z",
      "file_size": 2457600,
      "format": "mp3"
    },
    {
      "recording_id": "REC_xyz789uvw012",
      "call_id": "2a3b4c5d-6e7f-8g9h-0i1j-2k3l4m5n6o7p",
      "recording_type": "trunk",
      "url": "https://recordings.vobiz.ai/files/REC_xyz789uvw012.mp3",
      "download_path": "/v1/Account/MA_XXXXXXXX/Recording/REC_xyz789uvw012/download",
      "duration": 125,
      "created_at": "2026-01-23T09:15:00Z",
```

```
      "file_size": 987600,
      "format": "mp3"
    }
  ],
  "pagination": {
    "limit": 20,
    "offset": 0,
    "total": 150,
    "has_more": true
  }
}
```

Response Fields

- `recording_id` - Unique identifier for the recording (used for download)
- `call_id` - Cross-reference with CDR records
- `url` or `download_path` - Link to the actual audio file (MP3/WAV)
- `created_at` - Timestamp when the recording was made
- `duration` - Recording length in seconds
- `recording_type` - Type of recording (trunk/extension)

Examples

cURL - List Trunk Recordings

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/{ACCOUNT_ID}/Recording/?limit=20&offset=0&recording_type=trunk" \
  -H "X-Auth-ID: {ACCOUNT_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}" \
  -H "Content-Type: application/json"
```

cURL - Filter by Call UUID

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/MA_XXXXXXXX/Recording/?call_uuid=7f8e9d2c-1a3b-4c5d-6e7f-8g9h0i1j2k3l" \
  -H "X-Auth-ID: MA_XXXXXXXX" \
  -H "X-Auth-Token: your_auth_token" \
  -H "Content-Type: application/json"
```

Generic Template (Use Your Own Values)

cURL Template

```
curl -X GET "https://api.vobiz.ai/api/v1/Account/{ACCOUNT_ID}/Recording/?limit=
{LIMIT}&offset={OFFSET}&recording_type={TYPE}" \
  -H "X-Auth-ID: {ACCOUNT_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}" \
  -H "Content-Type: application/json"
```

Parameter Quick Reference

Parameter	Example	Description
`limit`	20	Number of records to return
`offset`	0	Starting position (0 for first page, 20 for second, etc.)
`call_uuid`	7f8e9d2c-1a3b-4c5d-6e7f-8g9h0i1j2k3l	Filter recordings for a specific call
`recording_type`	trunk	Filter by type: "trunk" or "extension"

Quick Tips:

- **Pagination:** Use `offset` to navigate through pages (offset = page × limit)
- **Recording Type:** Filter by "trunk" or "extension" to get specific recording types
- **Case Sensitive:** Ensure "Account" and "Recording" are capitalized in the URL
- **Filter by Call:** Use `call_uuid` to get recordings for a specific call
- **Cross-Reference:** Use `call_id` to match recordings with CDR entries

Next Steps:

- Use the `recording_id` to download specific recordings
- Cross-reference with CDR data using `call_id` for complete call information
- Store recording URLs for playback or archival purposes
- Implement pagination to retrieve all recordings efficiently

Delete a Recording

Permanently delete a specific recording from your account.

This
API allows you to permanently delete a recording from your Vobiz account using the recording ID. Once deleted, the recording file will be permanently removed and cannot be recovered.

⚠️ Warning: This action is permanent and cannot be undone!

- The recording file will be completely removed from storage
- The recording URL will no longer be accessible
- All metadata associated with this recording will be deleted
- This operation cannot be reversed

Best Practice:
Before deleting, consider retrieving the recording details and downloading the audio file if you might need it for compliance or archival purposes.

HTTP Request

DELETE `https://api.vobiz.ai/api/v1/Account/{auth_id}/Recording/{recording_id}/`

Authentication Headers

`X-Auth-ID:` Your account auth_id (e.g., {Auth_ID})

`X-Auth-Token:` Your account auth token

Path Parameters:

- `{auth_id}` - Your account ID
- `{recording_id}` - The unique recording identifier to delete

Response

Success Response (204 No Content)

If the recording was successfully deleted, the API returns HTTP 204 with no response body.

Response - 204 No Content

```
HTTP/1.1 204 No Content
```

Error Response (404 Not Found)

If the recording doesn't exist or has already been deleted:

Response - 404 Not Found

```
{
    "api_id": "correlation-id-uuid",
    "error": "Recording not found"
}
```

Examples

Basic Delete Request

cURL

```
curl -X DELETE https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Safe Delete Workflow: Verify Before Deleting

Best practice: Retrieve recording details before deletion to confirm you're deleting the correct file:

Two-Step Process

```
# Step 1: Get recording details to verify
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"

# Step 2: Review the output, confirm it's the right recording
# Check: call_uuid, conference_name, from_number, to_number, add_time

# Step 3: Delete if confirmed
curl -X DELETE https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Archive Then Delete Workflow

Download the recording before deleting for backup purposes:

Bash Script

```
#!/bin/bash
RECORDING_ID="abc123def456"
ACCOUNT_ID="{Auth_ID}"
AUTH_ID="YOUR_AUTH_ID"
AUTH_TOKEN="YOUR_AUTH_TOKEN"

# Get recording details
RESPONSE=$(curl -s -X GET
https://api.vobiz.ai/api/v1/Account/${ACCOUNT_ID}/Recording/${RECORDING_ID}/ \
  -H "X-Auth-ID: ${AUTH_ID}" \
  -H "X-Auth-Token: ${AUTH_TOKEN}")

# Extract recording URL
RECORDING_URL=$(echo ${RESPONSE} | jq -r '.recording_url')

# Download the recording file
echo "Downloading recording..."
curl -o "${RECORDING_ID}.mp3" "${RECORDING_URL}"

# Verify download was successful
if [ -f "${RECORDING_ID}.mp3" ]; then
  echo "Download successful. File size: $(ls -lh ${RECORDING_ID}.mp3 | awk '{print $5}')"

  # Delete from Vobiz
  echo "Deleting recording from Vobiz..."
  curl -X DELETE https://api.vobiz.ai/api/v1/Account/${ACCOUNT_ID}/Recording/${RECORDING_ID}/
\
    -H "X-Auth-ID: ${AUTH_ID}" \
    -H "X-Auth-Token: ${AUTH_TOKEN}"

  echo "Recording deleted successfully"
else
  echo "Download failed. Recording NOT deleted."
fi
```

Check Deletion Status

Verify the recording was deleted by attempting to retrieve it:

cURL

```
# This should return 404 if deletion was successful
curl -X GET https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/abc123def456/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Before Deleting - Checklist:

- ✓ Download the recording file if you need to archive it
- ✓ Verify you have the correct recording_id

- ✓ Check for any compliance or legal requirements for retention
- ✓ Confirm this isn't an active/recent recording that might be needed
- ✓ Consider storage costs vs. retention needs

Common Use Cases:

- Remove old recordings to reduce storage costs
- Delete recordings after archiving to external storage
- Clean up test recordings from development
- Comply with data retention policies (e.g., GDPR right to deletion)
- Remove recordings that failed quality checks

Tip: For deleting multiple recordings, use the Bulk Delete Recordings endpoint instead of making individual delete requests. This is more efficient and reduces API calls.

Note:
HTTP 204 response means success. If you receive a 404 error and you're certain the recording ID is correct, the recording may have already been deleted by another process or user.

Export Historical Recordings

Export recordings as a downloadable archive sent via email (async operation).

This API allows you to export recordings matching your filter criteria. Recordings are packaged as a downloadable archive and sent via email. This is an asynchronous operation that processes in the background.

🔄 Async Operation Workflow:

1. Request is validated and queued as async task
2. System processes recordings matching your filters
3. Recordings are packaged as downloadable archive
4. Download link is emailed to all recipient addresses

5. Archive typically available within 15-60 minutes depending on volume

Important:
Only one export request can run at a time per account. If an export is already in progress, you must wait for it to complete before starting a new one.

HTTP Request

POST `https://api.vobiz.ai/api/v1/Account/{auth_id}/export/recording/`

Authentication Headers

`X-Auth-ID:` Your account auth_id (e.g., {Auth_ID})

`X-Auth-Token:` Your account auth token

`Content-Type:` application/json

Request Body

Required Parameters

Parameter	Type	Description
`recipient.customer_account` required	array	Array of email addresses to receive the download link. All emails must be in valid format. Example: ["admin@example.com", "user@example.com"]

Date Range Filters (Option 1)

Optional - Date Range

Parameter	Type	Description
`from` optional	string	Start date for export. Format: YYYY-MM-DD HH:MM:SS. Defaults to 7 days ago if not specified.

Parameter	Type	Description
`to` optional	string	End date for export. Format: YYYY-MM-DD HH:MM:SS. Defaults to current time if not specified.

Storage Duration Filters (Option 2 - Alternative to Date Range)

Optional - Storage Duration

Parameter	Type	Description
`recording_storage_duration` optional	string	Export recordings exactly N days old. Example: "7" = recordings from exactly 7 days ago.
`recording_storage_duration__gte` optional	string	Export recordings N days old or older. Example: "7" = recordings 7+ days old.
`recording_storage_duration__gt` optional	string	Export recordings older than N days. Example: "7" = recordings 8+ days old.
`recording_storage_duration__lte` optional	string	Export recordings N days old or newer. Example: "30" = recordings 0-30 days old.
`recording_storage_duration__lt` optional	string	Export recordings newer than N days. Example: "30" = recordings 0-29 days old.

Additional Filters (Only for ranges ≤ 30 days)

Optional - Additional Filters

Parameter	Type	Description
`from_number` optional	string	Filter by caller phone number.
`to_number` optional	string	Filter by destination phone number.
`call_uuid` optional	string	Filter by call UUID (also use for conference_uuid or mpc_uuid).

Parameter	Type	Description
`conference_name` optional	string	Filter by conference name (also use for mpc_name).
`recording_format` optional	string	Filter by format. Values: "mp3", "wav".
`recording_id` optional	string	Filter by specific recording ID.

Note: Additional filters (from_number, to_number, etc.) only work when your date range or storage duration range is 30 days or less.

Constraints & Validation

❌ Cannot combine from/to with storage duration filters

❌ Cannot use __gt and __gte together (choose one)

❌ Cannot use __lt and __lte together (choose one)

⚠️ Maximum date range: 1 year (366 days)

⚠️ Maximum storage duration range: 30 days

⚠️ Filters only apply for ranges ≤ 30 days

⚠️ When using range filters (__gte/__lte), both must be provided

🔒 Only one export can run at a time per account

Response

Success Response (202 Accepted)

The export request has been queued and will be processed in the background:

Response - 202 Accepted

```
{
    "api_id": "correlation-id-uuid",
    "status": "success"
}
```

Error Response (403 Forbidden)

Another export is already in progress:

Response - 403 Forbidden

```
{
    "status": "failure",
    "message": "An Export Historic Recording request is already in process. Please try again
in sometime."
}
```

Error Response (400 Bad Request)

Invalid request parameters:

Response - 400 Bad Request

```
{
    "status": "failure",
    "message": "From/To cannot be used with recording storage duration"
}
```

Examples

Export Last 7 Days (Date Range)

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/export/recording/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "from": "2025-01-23 00:00:00",
    "to": "2025-01-30 23:59:59",
    "recipient": {
      "customer_account": ["admin@example.com"]
    }
  }'
```

Export Using Storage Duration

Export recordings exactly 7 days old:

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/export/recording/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "recording_storage_duration": "7",
    "recipient": {
      "customer_account": ["admin@example.com"]
```

```
    }
  }'
```

Export with Storage Duration Range

Export recordings between 7 and 30 days old:

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/export/recording/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "recording_storage_duration__gte": "7",
    "recording_storage_duration__lte": "30",
    "recipient": {
      "customer_account": ["admin@example.com"]
    }
  }'
```

Export with Filters (Conference Recordings)

Export conference recordings in MP3 format from last 30 days:

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/export/recording/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "from": "2025-01-01 00:00:00",
    "to": "2025-01-30 23:59:59",
    "conference_name": "TeamMeeting",
    "recording_format": "mp3",
    "recipient": {
      "customer_account": ["admin@example.com", "backup@example.com"]
    }
  }'
```

Export with Phone Number Filter

cURL

```
curl -X POST https://api.vobiz.ai/api/v1/Account/{Auth_ID}/export/recording/ \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "from": "2025-01-15 00:00:00",
    "to": "2025-01-30 23:59:59",
```

```
    "from_number": "+14155551234",
    "recipient": {
      "customer_account": ["admin@example.com"]
    }
  }'
```

Use Cases:

- Backup recordings to external storage before deletion
- Archive old recordings for compliance
- Export specific conference recordings for review
- Download recordings for specific phone numbers
- Create monthly recording backups

Tip: For large date ranges (>30 days), don't use additional filters. Export in smaller batches if you need filtered results.

Email Delivery:

- Check spam/junk folders if not received within 1 hour
- Verify email addresses are valid before requesting
- Use multiple recipients for redundancy
- Wait for completion email before starting another export

Bulk Delete Recordings

Delete multiple recordings matching filter criteria (async operation).

This API allows you to delete multiple recordings at once based on filter criteria. This is an asynchronous operation that processes deletions in the background, making it efficient for removing large numbers of recordings.

⚠️ WARNING: This action is permanent and cannot be undone!

- All recordings matching your filters will be permanently deleted
- Recording files will be completely removed from storage

- Recording URLs will no longer be accessible
- All metadata associated with these recordings will be deleted
- This operation cannot be reversed

🔄 Async Operation:

1. Request is validated and queued as async task
2. System identifies all recordings matching your filters
3. Recordings are deleted in batches
4. Operation typically completes within minutes to hours depending on volume

Best Practice: Before bulk deleting, use the List Recordings endpoint with the same filters to verify which recordings will be deleted. Check the `meta.total_count` to see how many recordings match.

HTTP Request

DELETE `https://api.vobiz.ai/api/v1/Account/{auth_id}/Recording/BulkDelete/`

Authentication Headers

`X-Auth-ID:` Your account auth_id (e.g., {Auth_ID})

`X-Auth-Token:` Your account auth token

Query Parameters

Use
query parameters to filter which recordings to delete. At least one filter parameter is recommended to avoid accidentally deleting all recordings.

Filter Parameters

Parameter	Type	Description
`add_time__gte` optional	string	Delete recordings created on or after this date. Format: YYYY-MM-DD HH:MM:SS. Example: 2025-01-01 00:00:00

Parameter	Type	Description
`add_time__lte` optional	string	Delete recordings created on or before this date. Format: YYYY-MM-DD HH:MM:SS.
`call_uuid` optional	string	Delete recordings for a specific call UUID.
`conference_name` optional	string	Delete recordings for a specific conference name (supports partial match).
`from_number` optional	string	Delete recordings from a specific caller number (supports partial match).
`to_number` optional	string	Delete recordings to a specific destination number (supports partial match).
`recording_format` optional	string	Delete recordings with specific format. Values: "mp3", "wav".

Date Format Requirements:

- Format: `YYYY-MM-DD HH:MM:SS`
- Example: `2025-01-15 10:30:45`
- Use 24-hour time format
- Include seconds (even if 00)
- URL encode spaces as %20

Response

Success Response (202 Accepted)

The bulk delete request has been queued and will be processed in the background:

Response - 202 Accepted

```
{
    "api_id": "correlation-id-uuid",
    "status": "successfully queued bulk delete request"
}
```

Note:
A 202 response means the request has been accepted and queued. The actual deletion happens asynchronously in the background. Verify

completion by checking if recordings still exist using the List Recordings endpoint.

Examples

Delete Recordings from January 2025

cURL

```
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?add_time__gte=2025-01-01%2000:00:00&add_time__lte=2025-01-31%2023:59:59" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Delete All Recordings for a Specific Conference

cURL

```
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?conference_name=TeamMeeting" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Delete Recordings from Specific Phone Number

cURL

```
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?from_number=%2B14155551234" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Note: URL encode the + symbol as %2B

Delete WAV Format Recordings

cURL

```
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?recording_format=wav" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Safe Workflow: Verify Before Deleting

Always check what will be deleted before running the bulk delete:

Two-Step Process

```
# Step 1: List recordings that match your filters
curl -X GET "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/?add_time__gte=2025-01-01%2000:00:00&add_time__lte=2025-01-31%2023:59:59" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"

# Check the meta.total_count to see how many will be deleted

# Step 2: Review the output and confirm

# Step 3: Run bulk delete with same filters
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?add_time__gte=2025-01-01%2000:00:00&add_time__lte=2025-01-31%2023:59:59" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Combine Multiple Filters

Delete conference recordings in MP3 format from a specific date range:

cURL

```
curl -X DELETE "https://api.vobiz.ai/api/v1/Account/{Auth_ID}/Recording/BulkDelete/?conference_name=DailyStandup&recording_format=mp3&add_time__gte=2025-01-01%2000:00:00&add_time__lte=2025-01-15%2023:59:59" \
  -H "X-Auth-ID: YOUR_AUTH_ID" \
  -H "X-Auth-Token: YOUR_AUTH_TOKEN"
```

Before Bulk Deleting - Checklist:

- ✓ Use List Recordings endpoint first to verify count
- ✓ Export/download recordings if you need backups
- ✓ Double-check your filter parameters
- ✓ Verify legal/compliance retention requirements
- ✓ Confirm this is intentional (deletions are permanent)
- ✓ Test with a small date range first if unsure

Common Use Cases:

- Clean up old recordings to reduce storage costs
- Delete test recordings from development/staging
- Remove recordings after exporting to external storage
- Comply with data retention policies (e.g., delete after 90 days)

- Remove recordings for specific conferences that ended

Tip:
For automated cleanup policies, combine bulk delete with storage duration filters. For example, delete all recordings older than 90 days on a monthly schedule.

Verify Deletion:

After bulk delete completes, run the List Recordings endpoint with the same filters. If `meta.total_count` is 0, all matching recordings were successfully deleted.

Call Detail Records (CDR)

Retrieve detailed call logs and usage data for your account.

The Call Detail Records (CDR) API endpoint allows you to fetch comprehensive call logs for your account. This includes information about call participants, duration, status, costs, timestamps, and more. CDR data is essential for billing reconciliation, usage analytics, and compliance reporting.

Use Cases:
CDRs are commonly used for billing verification, traffic analysis, fraud detection, and generating usage reports. You can filter records by date range and paginate through large datasets efficiently.

HTTP Request

GET `https://api.vobiz.ai/api/v1/account/{ACCOUNT_ID}/cdr`

Authentication Required:

- **X-Auth-ID:** Your account ID (e.g., MA_BN2MZ1VV)
- **X-Auth-Token:** Your account Auth Token
- **Content-Type:** application/json

Query Parameters

URL Parameters

Parameter	Type	Description
`ACCOUNT_ID` required	string	Your unique Vobiz account identifier (e.g., MA_BN2MZ1VV). Must match your X-Auth-ID header.

Query String Parameters

Parameter	Type	Description
`start_date` required	string (YYYY-MM-DD)	The beginning of the search period in YYYY-MM-DD format (e.g., 2025-12-31).
`end_date` required	string (YYYY-MM-DD)	The end of the search period in YYYY-MM-DD format (e.g., 2026-01-23).
`per_page` optional	integer	Number of records to return per request. Useful for pagination (default: 20, max: 100).
`page` optional	integer	The specific page of results to view. Use for navigating through paginated results (default: 1).
`context` required	string	The underlying engine context. Use "kamailio" for standard CDR queries.

Response

A successful request returns a `200 OK` status with a JSON body containing an array of call objects.

Success Response - 200 OK

```
{
  "data": [
    {
      "call_id": "abc123-def456-ghi789",
      "from_number": "+912271264217",
      "to_number": "+919876543210",
      "direction": "outbound",
      "duration": 125,
      "status": "completed",
      "start_time": "2026-01-23T10:30:00Z",
      "end_time": "2026-01-23T10:32:05Z",
      "cost": 0.05,
      "currency": "USD",
```

```
      "trunk_id": "e3e55a78-1234-5678-90ab-cdef12345678",
      "caller_id": "+912271264217",
      "hangup_cause": "NORMAL_CLEARING"
    },
    {
      "call_id": "xyz789-uvw456-rst123",
      "from_number": "+919876543210",
      "to_number": "+912271264217",
      "direction": "inbound",
      "duration": 45,
      "status": "completed",
      "start_time": "2026-01-23T09:15:00Z",
      "end_time": "2026-01-23T09:15:45Z",
      "cost": 0.02,
      "currency": "USD",
      "trunk_id": "e3e55a78-1234-5678-90ab-cdef12345678",
      "caller_id": "+919876543210",
      "hangup_cause": "NORMAL_CLEARING"
    }
  ],
  "pagination": {
    "current_page": 1,
    "per_page": 20,
    "total_records": 150,
    "total_pages": 8
  }
}
```


Response Fields

- `call_id` - Unique identifier for the call
- `from_number / to_number` - Call participants
- `duration` - Length of the call in seconds
- `status` - Call status (e.g., "completed", "no-answer", "busy", "failed")
- `cost` - Price of the call (if applicable)
- `direction` - "inbound" or "outbound"
- `hangup_cause` - Reason for call termination

Examples

cURL - Fetch CDR for Date Range

cURL Request

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{ACCOUNT_ID}/cdr?start_date=2025-12-31&end_date=2026-01-23&per_page=20&page=1" \
  -H "X-Auth-ID: {ACCOUNT_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}" \
  -H "Content-Type: application/json"
```

Generic Template (Use Your Own Values)

cURL Template

```
curl -X GET "https://api.vobiz.ai/api/v1/account/{ACCOUNT_ID}/cdr?start_date={YYYY-MM-DD}&end_date={YYYY-MM-DD}&per_page={LIMIT}&page={PAGE_NUMBER}" \
  -H "X-Auth-ID: {ACCOUNT_ID}" \
  -H "X-Auth-Token: {AUTH_TOKEN}" \
  -H "Content-Type: application/json"
```

Parameter Quick Reference

Parameter	Example	Description
`start_date`	2025-12-31	Beginning of search period (YYYY-MM-DD)
`end_date`	2026-01-23	End of search period
`per_page`	20	Records per request (pagination)
`page`	1	Page number to view

Quick Tips:

- **Date Format:** Always use YYYY-MM-DD format for dates
- **Pagination:** Use `per_page` and `page` for large datasets
- **Date Range:** Limit your date range to avoid timeouts on large datasets

Common Use Cases:

- **Billing Reconciliation:** Verify call costs against invoices
- **Traffic Analysis:** Analyze call patterns and peak usage times
- **Fraud Detection:** Monitor for unusual calling patterns
- **Compliance Reporting:** Generate call logs for regulatory requirements
- **Usage Reports:** Create detailed usage reports for customers