

Kartavya Mandora_100876605_Final Project_Code_S2

May 3, 2026

```
[1]: import os
import zipfile
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt

from scipy.io import loadmat
```

```
[2]: zip_path = "BCICIV_4_mat.zip"
extract_path = "BCICIV_4_data"

print("Zip path:", zip_path)
print("Extract folder:", extract_path)
```

Zip path: BCICIV_4_mat.zip
Extract folder: BCICIV_4_data

```
[3]: if not os.path.exists(extract_path):
    with zipfile.ZipFile(zip_path, 'r') as zip_ref:
        zip_ref.extractall(extract_path)
    print("Dataset extracted successfully.")
else:
    print("Dataset already extracted.")
```

Dataset already extracted.

```
[4]: for root, dirs, files in os.walk(extract_path):
    print("Folder:", root)
    for file in files:
        print("  ", file)
```

Folder: BCICIV_4_data
sub1_comp.mat
sub2_comp.mat
sub3_comp.mat

```
[5]: file_path = os.path.join(extract_path, "sub2_comp.mat")
data = loadmat(file_path)
```

```
print("Loaded file:", file_path)
```

Loaded file: BCICIV_4_data\sub2_comp.mat

```
[6]: print("Keys in the .mat file:")
      print(data.keys())
```

Keys in the .mat file:

```
dict_keys(['__header__', '__version__', '__globals__', 'train_data',
'test_data', 'train_dg'])
```

```
[7]: train_data = data["train_data"]
      train_dg = data["train_dg"]
      test_data = data["test_data"]

      print("train_data shape:", train_data.shape)
      print("train_dg shape:", train_dg.shape)
      print("test_data shape:", test_data.shape)
```

train_data shape: (400000, 48)

train_dg shape: (400000, 5)

test_data shape: (200000, 48)

```
[8]: n_samples, n_channels = train_data.shape
      n_targets = train_dg.shape[1]

      print(f"Number of training samples: {n_samples}")
      print(f"Number of neural channels: {n_channels}")
      print(f"Number of target outputs (fingers): {n_targets}")
```

Number of training samples: 400000

Number of neural channels: 48

Number of target outputs (fingers): 5

```
[9]: print("First 5 rows of train_data:")
      print(train_data[:5])

      print("\nFirst 5 rows of train_dg:")
      print(train_dg[:5])
```

First 5 rows of train_data:

```
[[ -872    164    609 -4169 -3011 -1713 -1561   -616   -700   3692
  -1077   -48   1891  -753   1489   1141     -8     76    574     93
    2126   1251 -1367   1074   3095   -843   8970 -5569   3564   2428
     494 -11532 -1352   -393   -450 -1551 -1312  -342    961 -1881
  -2825   -113  -495     76   2439 -2776 -7720   -96]
[ -1191   -78    454 -4212 -3018 -1808 -1778   -597   -682   3733
  -1199   -33   1843  -767   1402   1001    -68   -103    457    -1
   1359   1071 -1525    906   3147   -817   8980 -5533   3447   2302
    436 -11469 -1434   -533   -444 -1626 -1368  -387    916 -2019]
```

```

-2935 -249 -700 -9 2380 -2787 -7544 -188]
[ -1507 -395 204 -4429 -3134 -2046 -2065 -630 -826 3654
-1394 -153 1690 -872 1196 735 -207 -243 267 -219
577 782 -1724 737 3134 -862 8840 -5638 3231 2069
277 -11500 -1647 -778 -485 -1819 -1443 -429 750 -2146
-3158 -437 -976 -218 2246 -2871 -7425 -418]
[ -1670 -561 25 -4655 -3214 -2234 -2258 -602 -1037 3572
-1475 -313 1537 -868 1002 487 -301 -273 119 -427
-24 545 -1888 645 3135 -978 8672 -5809 2987 1909
107 -11502 -1913 -1003 -464 -1991 -1486 -449 660 -2241
-3400 -551 -1151 -546 2111 -2931 -7292 -591]
[ -1734 -625 -83 -4839 -3231 -2294 -2355 -535 -1269 3452
-1452 -480 1382 -696 901 239 -389 -256 33 -633
-126 356 -2017 544 3090 -1136 8429 -5997 2684 1822
-46 -11561 -2228 -1169 -428 -2166 -1503 -364 628 -2407
-3681 -645 -1248 -917 1955 -3040 -7180 -679]]

```

First 5 rows of train_dg:

```


[[-0.24004879 -0.17855279 0.21785755 -0.23142546 0.29254389]
 [-0.24004879 -0.17855279 0.21785755 -0.23142546 0.29254389]
 [-0.24004879 -0.17855279 0.21785755 -0.23142546 0.29254389]
 [-0.24004879 -0.17855279 0.21785755 -0.23142546 0.29254389]
 [-0.24004879 -0.17855279 0.21785755 -0.23142546 0.29254389]]

```


```

[10]: plt.figure(figsize=(12, 5))
for i in range(train_dg.shape[1]):
    plt.plot(train_dg[:2000, i], label=f'Finger {i+1}')
plt.title("Example Finger Flexion Signals (First 2000 Samples)")
plt.xlabel("Time")
plt.ylabel("Finger Position")
plt.legend()
plt.show()

```



```
[11]: plt.figure(figsize=(12, 5))
      for i in range(min(5, train_data.shape[1])):
          plt.plot(train_data[:2000, i], label=f'Channel {i+1}')
      plt.title("Example Neural Signal Channels (First 2000 Samples)")
      plt.xlabel("Time")
      plt.ylabel("Signal Value")
      plt.legend()
      plt.show()
```



```
[12]: print("Missing values in train_data:", np.isnan(train_data).sum())
      print("Missing values in train_dg:", np.isnan(train_dg).sum())
      print("Missing values in test_data:", np.isnan(test_data).sum())
```

```
Missing values in train_data: 0
Missing values in train_dg: 0
Missing values in test_data: 0
```

```
[13]: X = train_data
      y = train_dg

      print("Input X shape:", X.shape)
      print("Target y shape:", y.shape)
```

```
Input X shape: (400000, 48)
Target y shape: (400000, 5)
```

```
[14]: from sklearn.model_selection import train_test_split
```

```
X_train, X_val, y_train, y_val = train_test_split(
    X, y, test_size=0.2, random_state=42, shuffle=True
)

print("X_train:", X_train.shape)
print("X_val:", X_val.shape)
```

```
X_train: (320000, 48)
X_val: (80000, 48)
```

```
[15]: from sklearn.preprocessing import StandardScaler

scaler = StandardScaler()

X_train_scaled = scaler.fit_transform(X_train)
X_val_scaled = scaler.transform(X_val)

print("Scaling complete.")
```

Scaling complete.

```
[16]: from sklearn.linear_model import LinearRegression
from sklearn.multioutput import MultiOutputRegressor

baseline_model = MultiOutputRegressor(LinearRegression())
baseline_model.fit(X_train_scaled, y_train)

print("Wiener Filter (Linear Regression) trained.")
```

Wiener Filter (Linear Regression) trained.

```
[17]: from sklearn.metrics import r2_score

y_pred_baseline = baseline_model.predict(X_val_scaled)

baseline_r2 = r2_score(y_val, y_pred_baseline, multioutput='uniform_average')


print("Baseline Wiener Filter R2 score:", baseline_r2)
```

Baseline Wiener Filter R² score: 0.03842790195638783

```
[18]: finger_idx = 0 # choose one finger

plt.figure(figsize=(12, 5))
plt.plot(y_val[:1000, finger_idx], label="True")
plt.plot(y_pred_baseline[:1000, finger_idx], label="Predicted")
plt.title("Baseline (Wiener Filter): True vs Predicted")
plt.xlabel("Time")
plt.ylabel("Finger Position")
```

```
plt.legend()
plt.show()
```



```
[19]: import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, Dropout
from tensorflow.keras.callbacks import EarlyStopping
```

```
[20]: nn_model = Sequential([
    Dense(128, activation='relu', input_shape=(X_train_scaled.shape[1],)),
    Dropout(0.2),

    Dense(64, activation='relu'),
    Dropout(0.2),

    Dense(y_train.shape[1], activation='linear')
])

nn_model.compile(
    optimizer='adam',
    loss='mse'
)

nn_model.summary()
```

C:\Users\karta\anaconda3\Lib\site-packages\keras\src\layers\core\dense.py:95:
 UserWarning: Do not pass an `input\_shape`/`input\_dim` argument to a layer. When
 using Sequential models, prefer using an `Input(shape)` object as the first
 layer in the model instead.

```
super().__init__(activity_regularizer=activity_regularizer, **kwargs)
```

Model: "sequential"

Layer (type) ↳ Param #	Output Shape	
dense (Dense) ↳ 6,272	(None, 128)	↳
dropout (Dropout) ↳ 0	(None, 128)	↳
dense_1 (Dense) ↳ 8,256	(None, 64)	↳
dropout_1 (Dropout) ↳ 0	(None, 64)	↳
dense_2 (Dense) ↳ 325	(None, 5)	↳

Total params: 14,853 (58.02 KB)

Trainable params: 14,853 (58.02 KB)

Non-trainable params: 0 (0.00 B)

```
[21]: early_stop = EarlyStopping(  
        monitor='val_loss',  
        patience=5,  
        restore_best_weights=True  
    )  
  
    history = nn_model.fit(  
        X_train_scaled, y_train,  
        validation_data=(X_val_scaled, y_val),  
        epochs=30,  
        batch_size=256,  
        callbacks=[early_stop],  
        verbose=1  
    )
```

Epoch 1/30

1250/1250

2s 1ms/step -

```

loss: 0.9082 - val_loss: 0.7580
Epoch 2/30
1250/1250          1s 1ms/step -
loss: 0.7406 - val_loss: 0.6169
Epoch 3/30
1250/1250          1s 1ms/step -
loss: 0.6497 - val_loss: 0.5399
Epoch 4/30
1250/1250          1s 1ms/step -
loss: 0.5967 - val_loss: 0.4908
Epoch 5/30
1250/1250          1s 1ms/step -
loss: 0.5636 - val_loss: 0.4635
Epoch 6/30
1250/1250          1s 1ms/step -
loss: 0.5424 - val_loss: 0.4348
Epoch 7/30
1250/1250          1s 1ms/step -
loss: 0.5248 - val_loss: 0.4219
Epoch 8/30
1250/1250          2s 1ms/step -
loss: 0.5094 - val_loss: 0.4106
Epoch 9/30
1250/1250          2s 1ms/step -
loss: 0.5007 - val_loss: 0.3984
Epoch 10/30
1250/1250          2s 1ms/step -
loss: 0.4914 - val_loss: 0.3874
Epoch 11/30
1250/1250          1s 1ms/step -
loss: 0.4844 - val_loss: 0.3730
Epoch 12/30
1250/1250          1s 1ms/step -
loss: 0.4787 - val_loss: 0.3733
Epoch 13/30
1250/1250          1s 1ms/step -
loss: 0.4732 - val_loss: 0.3637
Epoch 14/30
1250/1250          1s 1ms/step -
loss: 0.4677 - val_loss: 0.3630
Epoch 15/30
1250/1250          1s 1ms/step -
loss: 0.4626 - val_loss: 0.3510
Epoch 16/30
1250/1250          1s 1ms/step -
loss: 0.4609 - val_loss: 0.3540
Epoch 17/30
1250/1250          1s 1ms/step -

```



```

loss: 0.4563 - val_loss: 0.3467
Epoch 18/30
1250/1250          1s 1ms/step -
loss: 0.4525 - val_loss: 0.3374
Epoch 19/30
1250/1250          2s 1ms/step -
loss: 0.4506 - val_loss: 0.3452
Epoch 20/30
1250/1250          1s 1ms/step -
loss: 0.4483 - val_loss: 0.3401
Epoch 21/30
1250/1250          2s 1ms/step -
loss: 0.4458 - val_loss: 0.3367
Epoch 22/30
1250/1250          2s 1ms/step -
loss: 0.4446 - val_loss: 0.3314
Epoch 23/30
1250/1250          2s 2ms/step -
loss: 0.4411 - val_loss: 0.3276
Epoch 24/30
1250/1250          2s 1ms/step -
loss: 0.4412 - val_loss: 0.3255
Epoch 25/30
1250/1250          2s 1ms/step -
loss: 0.4386 - val_loss: 0.3266
Epoch 26/30
1250/1250          2s 1ms/step -
loss: 0.4381 - val_loss: 0.3327
Epoch 27/30
1250/1250          2s 1ms/step -
loss: 0.4357 - val_loss: 0.3258
Epoch 28/30
1250/1250          2s 1ms/step -
loss: 0.4339 - val_loss: 0.3180
Epoch 29/30
1250/1250          2s 1ms/step -
loss: 0.4338 - val_loss: 0.3170
Epoch 30/30
1250/1250          2s 1ms/step -
loss: 0.4330 - val_loss: 0.3164

```

```

[22]: y_pred_nn_original = nn_model.predict(X_val_scaled)

nn_r2 = r2_score(y_val, y_pred_nn_original, multioutput='uniform_average')

print("Neural Network R2 score:", nn_r2)

```

```


2500/2500          1s 493us/step

```

Neural Network R^2 score: 0.682314838672229

```
[23]: finger_idx = 0

plt.figure(figsize=(12, 5))
plt.plot(y_val[:1000, finger_idx], label="True")
plt.plot(y_pred_nn_original[:1000, finger_idx], label="Predicted")
plt.title("Neural Network: True vs Predicted")
plt.xlabel("Time")
plt.ylabel("Finger Position")
plt.legend()
plt.show()
```



```
[24]: def apply_channel_dropout(X, drop_fraction=0.3, random_state=42):
    np.random.seed(random_state)
    X_copy = X.copy()
    n_channels = X_copy.shape[1]
    n_drop = int(n_channels * drop_fraction)
    dropped_channels = np.random.choice(n_channels, n_drop, replace=False)
    X_copy[:, dropped_channels] = 0
    return X_copy, dropped_channels
```

```
[25]: X_val_drop30, dropped_channels = apply_channel_dropout(X_val_scaled,
    ↪drop_fraction=0.3)

print("Dropped channel indices:", dropped_channels)
print("Number of dropped channels:", len(dropped_channels))
```

Dropped channel indices: [27 40 26 43 24 37 12 19 4 25 8 3 6 39]

Number of dropped channels: 14

```
[26]: y_pred_baseline_drop = baseline_model.predict(X_val_drop30)
baseline_drop_r2 = r2_score(y_val, y_pred_baseline_drop,
                             multioutput='uniform_average')

print("Wiener Filter R2 with 30% channel dropout:", baseline_drop_r2)
```

Wiener Filter R² with 30% channel dropout: 0.026617965183609326

```
[27]: y_pred_nn_drop = nn_model.predict(X_val_drop30)
nn_drop_r2 = r2_score(y_val, y_pred_nn_drop, multioutput='uniform_average')

print("Neural Network R2 with 30% channel dropout:", nn_drop_r2)
```

2500/2500 1s 501us/step


Neural Network R² with 30% channel dropout: 0.23781916275118914

```
[28]: results = pd.DataFrame({
    "Model": ["Wiener Filter", "Neural Network"],
    "Original R2": [baseline_r2, nn_r2],
    "30% Dropout R2": [baseline_drop_r2, nn_drop_r2]
})

print(results)
```

	Model	Original R2	30% Dropout R2
0	Wiener Filter	0.038428	0.026618
1	Neural Network	0.682315	0.237819

```
[29]: results.set_index("Model").plot(kind="bar", figsize=(8, 5))
plt.title("Model Performance Before and After 30% Channel Dropout")
plt.ylabel("R2 Score")
plt.xticks(rotation=0)
plt.show()
```



```
[30]: dropout_levels = [0.0, 0.1, 0.3, 0.5, 0.7]
```

```
[31]: dropout_results = []

for drop in dropout_levels:
    if drop == 0.0:
        X_test_drop = X_val_scaled
        dropped_channels = []
    else:
        X_test_drop, dropped_channels = apply_channel_dropout(
            X_val_scaled,
            drop_fraction=drop,
            random_state=42
        )

    y_pred_wiener = baseline_model.predict(X_test_drop)
    y_pred_nn_drop_loop = nn_model.predict(X_test_drop)

    wiener_r2 = r2_score(y_val, y_pred_wiener, multioutput='uniform_average')
    nn_r2_loop = r2_score(y_val, y_pred_nn_drop_loop,
        multioutput='uniform_average')

    dropout_results.append({
```

```

        "Dropout Level": f"{int(drop * 100)}%",
        "Wiener Filter R2": wiener_r2,
        "Neural Network R2": nn_r2_loop,
        "Dropped Channels": len(dropped_channels)
    })

```

```

dropout_results_df = pd.DataFrame(dropout_results)
dropout_results_df

```

```

2500/2500          1s 500us/step
2500/2500          1s 509us/step
2500/2500          1s 499us/step
2500/2500          1s 509us/step
2500/2500          1s 498us/step

```

```


[31]:  Dropout Level  Wiener Filter R2  Neural Network R2  Dropped Channels
0           0%         0.038428         0.682315           0
1          10%         0.037010         0.513162           4
2          30%         0.026618         0.237819          14
3          50%         0.013478         0.028574          24
4          70%        -0.000793        -0.276051          33

```

```

[32]: plt.figure(figsize=(8, 5))
plt.plot(dropout_results_df["Dropout Level"], dropout_results_df["Wiener Filter_
↵R2"], marker='o', label="Wiener Filter")
plt.plot(dropout_results_df["Dropout Level"], dropout_results_df["Neural_
↵Network R2"], marker='o', label="Neural Network")
plt.title("Robustness Under Increasing Channel Dropout")
plt.xlabel("Channel Dropout Level")
plt.ylabel("R2 Score")
plt.legend()
plt.grid(True)
plt.show()

```



```
[33]: finger_r2_results = []

for i in range(y_val.shape[1]):
    finger_r2_results.append({
        "Finger": f"Finger {i+1}",
        "Wiener Filter R2": r2_score(y_val[:, i], y_pred_baseline[:, i]),
        "Neural Network R2": r2_score(y_val[:, i], y_pred_nn_original[:, i])
    })

finger_r2_df = pd.DataFrame(finger_r2_results)
finger_r2_df
```

```
[33]:
```

	Finger	Wiener Filter R2	Neural Network R2
0	Finger 1	0.041398	0.681716
1	Finger 2	0.044692	0.655577
2	Finger 3	0.046091	0.751554
3	Finger 4	0.039958	0.644500
4	Finger 5	0.020001	0.678227

```
[34]: finger_r2_df.set_index("Finger").plot(kind="bar", figsize=(9, 5))
plt.title("Per-Finger Decoding Performance")
plt.ylabel("R² Score")
plt.xticks(rotation=0)
```

```
plt.show()
```

