InXiteOut CampaignX API v1.0 - Documentation

1. Introduction

Welcome to the CampaignX API! This high-performance API allows you to programmatically manage your marketing campaigns. You can retrieve customer cohorts, submit new campaigns, and fetch detailed reports.

Our API is built around RESTful principles and returns JSON responses. This document provides all the necessary information to integrate with CampaignX successfully.

Base URL: https://campaignx.inxiteout.ai
API Version: 1.0
Documentation Version: 1.0

2. Getting Started

2.1. Authentication & API Keys

To interact with the CampaignX API, you must authenticate all your requests (except for the signup endpoint) using an API key.

- **How to obtain an API Key:** You will receive your unique API key upon successful registration via the /api/v1/signup endpoint. **Store this key securely, as it is shown only once.**
- **How to use it:** The API key must be included in the X-API-Key header of every request.

Example Header:

X-API-Key: xK8mP3nR7sT9vW2yZ5bN4mQ6jL1hG0fD

2.2. Rate Limiting

To ensure fair usage and system stability, the API enforces rate limits based on your API key.

- **Limit:** 100 requests per day.
- **Scope:** This limit applies to all authenticated endpoints (e.g., getting cohorts, sending campaigns, fetching reports).
- **Monitoring:** Exceeding this limit will result in a 429 Too Many Requests response.

2.3. Making Requests & Handling Responses

- **Request Format:** For POST requests, the request body must be sent in JSON format with the Content-Type: application/json header.
- **Response Format:** All successful responses (2xx status codes) will be in JSON format.
- **Error Handling:** API errors will return appropriate HTTP status codes (e.g., 4xx for client errors, 5xx for server errors) along with a JSON body containing details about the error. Refer to the **Error Handling** section for more information.

3. API Endpoints

This section details all available API endpoints. You can also use the provided examples to test the API.

3.1. Authentication

3.1.1. Signup

Registers a new team and generates a secure API key.

- **Endpoint:** POST /api/v1/signup
- **Description:** This is the only unauthenticated endpoint. It validates team information, ensures uniqueness, creates a team record, generates an API key, and sends a welcome email containing the key.

Request Body:

Parameter	Type	Required	Description
team_name	String	Yes	Team name. Must be alphanumeric and 3-100 characters long.
team_email	String (email)	Yes	A valid team email address. Must be unique in the system.

Example Request:

bash

```bash
curl -X POST https://api.campaignx.com/api/v1/signup \
  -H "Content-Type: application/json" \
  -d '{
    "team_name": "Marketing Team",
    "team_email": "marketing@example.com"
  }'
```

Success Response (201 Created):

json

```json
{
  "api_key": "xK8mP3nR7sT9vW2yZ5bN4mQ6jL1hG0fD",
  "team_name": "Marketing Team",
  "team_email": "marketing@example.com",
  "created_at": "2026-02-17T15:30:00Z",
  "message": "Team registered successfully. API key sent to your email."
}
```

3.2. Customer Data

3.2.1. Get Customer Cohort

Retrieves the list of customers that campaigns can be sent to.

- **Endpoint:** GET /api/v1/get_customer_cohort
- **Description:** Fetches the customer cohort data. This data includes customer identifiers and attributes needed for targeting.
- **Authentication:** Required (API Key via X-API-Key header)
- **Rate Limit:** Yes (100/day)

Success Response (200 OK):

Parameter	Type	Description
data	Array[Object]	An array of customer objects.
total_count	Integer	The total number of customer records in the cohort.
response_code	Integer	The HTTP status code (200).
message	String	A descriptive message about the response.

Example Request:

bash

```bash
curl -X GET https://api.campaignx.com/api/v1/get_customer_cohort \
  -H "X-API-Key: xK8mP3nR7sT9vW2yZ5bN4mQ6jL1hG0fD"
```

Example Response:

json

```json
{
  "data": [
    {
      "customer_id": "CUST001",
      "email": "john@example.com",
      "name": "John Doe"
    },
    {
      "customer_id": "CUST002",
      "email": "jane@example.com",
      "name": "Jane Smith"
    }
  ],
  "total_count": 5000,
  "response_code": 200,
  "message": "Customer cohort retrieved successfully"
}
```

3.3. Campaigns

3.3.1. Send Campaign: Submit a new marketing campaign to a targeted customer cohort.

- **Endpoint:** POST /api/v1/send_campaign
- **Description:** This endpoint Submit a new marketing campaign to a targeted customer cohort. It accepts the message content as subject, body, target customer, and send time. The API validates that all provided customer_ids exist in the cohort and that there are no duplicates.
- **Authentication:** Required (API Key via X-API-Key header)
- **Rate Limit:** Yes (100/day)

Request Body:

Parameter	Type	Required	Description
body	String	Yes	The main content of the campaign message. Supports UTF-8 (e.g., emoji) and URLs. Maximum 5000 characters.
list_customer_ids	Array[String]	Yes	List of unique customer IDs to contact. Customer IDs passed must be present in Customer Cohort.
send_time	String	Yes	The planned send time. Format: DD:MM:YY HH:MM:SS (e.g., 23:02:26 15:30:00).
subject	String or null	No	Email subject (required for Email). Supports text and emojis. Max 200 characters.

Example Request:

bash

```
curl -X POST https://api.campaignx.com/api/v1/send_campaign \
  -H "X-API-Key: xK8mP3nR7sT9vW2yZ5bN4mQ6jL1hG0fD" \
  -H "Content-Type: application/json" \
  -d '{
    "subject": "Special Offer - 20% Off!",
    "body": "Don'\''t miss out on our exclusive offer! 🎉 Visit https://example.com for details.",
    "list_customer_ids": ["CUST001", "CUST002", "CUST003"],
    "send_time": "23:02:26 15:30:00"
  }'
```

Success Response (200 OK):

Parameter	Type	Description
campaign_id	String	The unique identifier for the newly created campaign (UUID).
response_code	Integer	The HTTP status code (200).
invokation_time	String	Timestamp of when the API call was processed. Format: DD:MM:YY HH:MM:SS.
message	String	A success message confirming submission.

json

```
{
  "campaign_id": "123e4567-e89b-12d3-a456-426614174000",
  "response_code": 200,
  "invokation_time": "23:02:26 15:30:00",
  "message": "Campaign submitted successfully"
}
```

3.4. Reports

3.4.1. Get Report

Retrieves the performance report for a specific campaign.

- **Endpoint:** GET /api/v1/get_report
- **Description:** Fetches detailed engagement data for a campaign, such as opens, and clicks.
- **Authentication:** Required (API Key via X-API-Key header)
- **Rate Limit:** Yes (100/day)

Query Parameters:

Parameter	Type	Required	Description
campaign_id	String	Yes	The unique ID of the campaign ID to retrieve report

Example Request:

bash

```
curl -X GET "https://api.campaignx.com/api/v1/get_report?campaign_id=123e4567-e89b-12d3-a456-426614174000" \
  -H "X-API-Key: xK8mP3nR7sT9vW2yZ5bN4mQ6jL1hG0fD"
```

Success Response (200 OK):

Parameter	Type	Description
campaign_id	String	The campaign ID the report belongs to.
data	Array[Object]	An array of objects, each representing a customer's interaction status.
total_rows	Integer	The total number of records in the report (should match the number of customers targeted).
response_code	Integer	The HTTP status code (200).
message	String	A descriptive message.


```
{
  "campaign_id": "123e4567-e89b-12d3-a456-426614174000",
  "data": [
    {
     "invokation_time": "04:31:00",
     "invokation_date": "25:02:26",
    "campaign_id": "b77f9b02-562c-41fb-a262-20c74c8a70cb",
    "customer_id": "CUST0006",
     "send_time": "23:02:26 05:00:00",
    "subject": "Special Offer - 20% Off!",
    "body": "Don't miss out on our exclusive offer! 🎉 Visit https://example.com for details.",
    "EO": "N",
    "EC": "N"
    },
    {
    "invokation_time": "04:31:00",
        "invokation_date": "25:02:26",
        "campaign_id": "b77f9b02-562c-41fb-a262-20c74c8a70cb",
        "customer_id": "CUST0007",
        "send_time": "23:02:26 05:00:00",
        "subject": "Special Offer - 20% Off!",
        "body": "Don't miss out on our exclusive offer! 🎉 Visit https://example.com for details.",
        "EO": "N",
        "EC": "N"
```

}

],

"total_rows": 2,
"response_code": 200,
"message": "Report retrieved successfully"
"campaign_id": "b77f9b02-562c-41fb-a262-20c74c8a70cb"
}

4. Error Handling

The CampaignX API uses conventional HTTP response codes to indicate the success or failure of an API request. In general, codes in the 2xx range indicate success, codes in the 4xx range indicate an error that resulted from the provided information (e.g., a required parameter was missing, a validation failed), and codes in the 5xx range indicate an error with CampaignX's servers.

When a 4xx or 5xx error occurs, the response body will contain a JSON object describing the error, typically a ValidationError or HTTPValidationError.

Common Error Codes:

Status Code	Title	Description
400	Bad Request	The request was malformed or contains invalid parameters.
401	Unauthorized	Missing or invalid API key. Ensure your X-API-Key header is set correctly.
403	Forbidden	The API key is valid but does not have permission to access the resource.
404	Not Found	The requested resource (e.g., a campaign or endpoint) was not found.
422	Unprocessable Entity	The request body or parameters were well-formed but contain semantic errors (e.g., a customer ID in the list does not exist, or a field failed validation). The response body will detail the specific errors.
429	Too Many Requests	You have exceeded your rate limit of 100 requests per day.
5xx	Server Error	An internal server error occurred. Please contact support if the problem persists.

Example 422 Validation Error Response: json


```
{
  "detail": [
    {
      "loc": ["body", "list_customer_ids", 0],
      "msg": "Customer ID 'CUST999' not found in cohort.",
      "type": "value_error"
    },
    {
      "loc": ["body", "send_time"],
      "msg": "Invalid datetime format. Use DD:MM:YY HH:MM:SS",
      "type": "value_error.format"
    }
  ]
}
```