Source trace	**Established statically**
Participant locations	**Recorded**
Pattern hypotheses	4 tentative classifications
Confirmed instances	None
Runtime verification	Not performed

Recommendation for the next investigation: Examine the callback and `super` method-resolution behavior first, then the actual structure of the two lookup approaches. That will help decide whether any recognized pattern is supported or whether this should be documented simply as framework-supported shared behavior.

For now, nothing from this geocoding investigation should be added to `patterns.csv` or its confirmed pattern counts.

Before moving to another part of the repository, I want to close the geocoding investigation properly.
You identified four possible classifications:

1. Template Method
2. Strategy
3. Adapter
4. Observer

None is currently confirmed.
Re-examine these four classifications using the source evidence already traced.
For each one:

1. State the essential mechanism that must exist for that pattern to be defensible.
2. Compare that requirement directly with the DaPlanStan implementation.
3. Identify the actual code evidence that supports the classification.
4. Identify the code evidence that works against it.
5. Decide whether the observed structure is better explained by ordinary Ruby/Rails behavior or third-party integration.
6. Give a final status of either REJECTED or UNCERTAIN. Do not mark anything CONFIRMED unless the source clearly

establishes the defining pattern mechanism.

7. If the result is UNCERTAIN, state exactly what missing source or runtime evidence would be needed to settle it.

At the end, give me one table:
Candidate | Required mechanism | What the source actually does | Final decision | Reason
Then give me the final geocoding conclusion that should be preserved in the candidate-review record.
Do not search for new patterns in this prompt and do not move to another source area yet.

Worked for 1m 36s

Geocoding Investigation — Final Candidate Review

DaPlanStan | Original source snapshot | 23CSE455

Re-examining the four classifications against their defining mechanisms produces the following preliminary decisions:

Template Method	REJECTED
Strategy	REJECTED
Adapter	REJECTED
Observer	UNCERTAIN

These are source-review assessments, not completed human verification decisions. Observer remains uncertain only as a framework-mediated Turbo Streams collaboration, not as a custom observer implementation.

One important detail deserves attention: the source contains both `turbo_stream_from @trip` in the trip view and `Turbo::StreamsChannel.broadcast_refresh_to(trip)` in the geocoding job. Unlike a callback alone, that pair provides concrete evidence of an intended publish-subscribe relationship. It merits further checking before dismissing Observer entirely.

1. Template Method — REJECTED

Essential mechanism: A superclass or inherited implementation defines the fixed structure of an algorithm and delegates selected steps to overridable operations, allowing subclasses or specialized implementations to vary those steps without replacing the algorithm's overall structure.

Supporting source evidence:

`TripItem` includes `Geocodable` at `app/models/trip_item.rb:2` and defines its own `geocode_from_address` method at lines 34–37.