Source provenance: Uploaded ZIP verified for the relevant extracted files; ZIP-to-upstream-commit correspondence remains unverified.

Final conclusion: `Bulk Itinerary Import Coordination` is a defensible GRASP Controller instance because it represents a specific, independently identifiable system-event collaboration. Record it as one source-confirmed instance, while keeping its controller-heavy implementation and potential correctness issues as separate findings.

Now move to the next source area: external integrations and account identity.
Do not begin by assigning pattern names. First trace how DaPlanStan interacts with these external systems and where the application itself makes decisions.
Inspect these files and any directly related callers needed to complete the flows:

1. `app/jobs/fetch_trip_cover_image_job.rb`
2. `app/controllers/sessions_controller.rb`
3. `app/models/user_identity.rb`
4. `app/models/user.rb`
5. `config/initializers/omniauth.rb`
6. `app/mailers/trip_mailer.rb`
7. `app/mailers/invitation_mailer.rb`
8. Relevant routes, authentication callbacks, views and configuration where needed.

Keep the following flows separate.

1. Cover-image retrieval

Trace how the application requests a trip cover image, how the Pexels call is constructed and how the result is stored.
This flow already appeared as a collaborator in Trip Creation Coordination, so do not count the same collaboration again unless there is a genuinely independent pattern inside the integration itself.

2. OAuth sign-in and identity linking

Trace the actual sign-in path for the configured authentication providers.

Identify:

1. how provider data reaches the application
2. how an existing `UserIdentity` is located
3. when a user is found by email
4. when a new user/account/traveler is created
5. how a provider identity is linked to a user
6. how invited travelers are associated with the signed-in user
7. whether different OAuth providers are handled through genuinely interchangeable application-defined behavior or mostly through OmniAuth configuration
8. Outbound mail

Trace how invitation and pending-sender emails are constructed and sent.
Separate application-written mail content and recipient decisions from Rails Action Mailer and Postmark delivery infrastructure.
For each flow:

1. Identify the actual classes and methods involved.
2. Give reliable source paths and line ranges.
3. Trace the control flow.
4. Separate DaPlanStan behavior from Rails, OmniAuth, Pexels and Postmark behavior.
5. Identify where application decisions are made and what is merely configuration.
6. Check whether wrappers around provider APIs actually translate incompatible interfaces or simply invoke dependency APIs directly.
7. Check whether multiple authentication providers really form an application-level Strategy, Adapter, Factory or other pattern before proposing one.
8. Reuse previously established collaborations where appropriate rather than counting them again.

Only after tracing the flows, identify any genuinely new design-pattern candidates.
For each candidate:

1. Give the possible pattern and category.
2. Give a meaningful collaboration name.
3. Identify the actual participants.

4. Explain the behavior supporting the classification.
5. Give the strongest false-positive explanation.
6. State whether it is application-owned, framework-provided or mixed.
7. Leave it UNCONFIRMED.

At the end give me:

1. Cover-image integration trace.
2. OAuth and identity-linking trace.
3. Outbound-mail trace.
4. Participant/source-evidence table.
5. Application/framework/provider responsibility split.
6. New candidate patterns only.
7. Previously confirmed collaborations encountered again but not counted again.
8. Strongest non-pattern explanation.
9. Anything that still requires verification.

Worked for 2m 9s

DaPlanStan — External Integrations and Account Identity

Source Investigation 05 · Original uploaded ZIP · Static source analysis

Pattern classifications unconfirmed

1. Overview of the source findings

The three integration areas have different responsibilities.

- **Cover images:** DaPlanStan constructs its own HTTP request to Pexels, interprets the JSON response and stores the selected image URL on `Trip`.
- **OAuth authentication:** OmniAuth handles provider-specific authentication. DaPlanStan receives normalized authentication information and implements user lookup, identity linking, account provisioning, invitation acceptance and session creation.
- **Outbound email:** DaPlanStan selects recipients and constructs invitation or notification messages. Rails Action Mailer and the configured delivery service handle message processing and transport.

The source also contains an important supporting component that was not in the initial file list: `config/initializers/mail_logger.rb`. It registers an application-defined delivery observer with Action Mailer. That behavior is relevant to candidate discovery, but it must be evaluated separately from ordinary outbound mail delivery.