- **Five rejected classifications excluded.** Their reasons and minimum supporting locations are recorded.
- **Source evidence audited.** Participant roles and line ranges are tied to the uploaded application snapshot, with the `ParseInboxItemJob` location specifically rechecked.
- **Duplicate prevention applied.** One collaboration is counted once even when it spans controllers, models, jobs, views or multiple workflows.

The archive's equivalence to the stated Git commit `da54d9ab8bfc118e99375fdd6c506efb20b66e5b` remains unverified because the supplied ZIP does not establish its Git provenance. Independent human sign-off and runtime behavior are also not established by this source audit. These are provenance and validation limitations, not additional pattern classifications.

Final status: FROZEN SOURCE-SUPPORTED BASELINE PROPOSAL — 9 instances, 3 pattern types.

No `patterns.csv`, `pattern_counts.csv`, UML diagram or evolution analysis has been generated.

The baseline source-supported pattern inventory is now frozen. Do not search for new patterns and do not change any of the nine frozen classifications.
Now prepare the exact contents of `patterns.csv` and `pattern_counts.csv`.
Use `baseline` as the `source_version` value for this original source snapshot. Do not use the stated Git commit as verified provenance because the ZIP-to-commit correspondence is still unverified.
For `patterns.csv`, use exactly these columns:
`source_version,pattern_name,pattern_type,instance_name,participant_roles,source_locations,intent_and_evidence`
Create exactly one row for each of these nine frozen instances:

1. Information Expert (GRASP) — Parsed Email to Trip Record Linking
2. Controller (GRASP) — Inbound Travel Email Intake Coordination
3. Controller (GRASP) — Trip Creation Coordination
4. Controller (GRASP) — Trip Membership Management Coordination
5. Controller (GRASP) — Bulk Itinerary Import Coordination
6. Controller (GRASP) — OAuth Sign-in and Identity Linking Coordination

7. Controller (GRASP) — Account Traveler Enrollment Coordination
8. Observer (GoF) — Outbound Mail Delivery Logging
9. Observer (GoF) — Trip-Scoped Turbo Refresh Notifications

For every `patterns.csv` row:

1. Use only participant roles already verified in the frozen baseline.
2. Include all important participants needed to understand the collaboration.
3. Do not invent GoF-style participant names for GRASP patterns.
4. Keep application participants and framework participants clearly distinguished.
5. Use exact source paths and reliable line ranges from the frozen inventory.
6. Do not count repeated methods or files as separate pattern instances.
7. Keep `intent_and_evidence` concise but specific enough to explain why the pattern classification is supported.
8. Make each field CSV-safe. Quote fields containing commas, semicolons or long participant mappings where necessary.
9. Do not include rejected candidates in `patterns.csv`.

For `pattern_counts.csv`, use exactly these columns:
`source_version,summary,pattern_name,count`
Use only these allowed `summary` values:
`per_pattern`
`total_pattern_types`
`total_pattern_instances`
Generate the following counts:
Controller (GRASP) = 6
Information Expert (GRASP) = 1
Observer (GoF) = 2
Total distinct pattern types = 3
Total pattern instances = 9
For the `per_pattern` rows, put the exact pattern name in `pattern_name`.

For `total_pattern_types` and `total_pattern_instances`, leave `pattern_name` blank.
Before giving the final CSV content, perform a consistency check:

1. `patterns.csv` must contain exactly 9 data rows.
2. Every frozen instance must occur exactly once.
3. `pattern_counts.csv` must agree with the nine inventory rows.
4. No rejected or uncertain candidate may appear.
5. The two Observer instances must remain separate.
6. The Turbo Observer must appear only once despite multiple publishers and subscribers.
7. Trip membership add/remove must remain one instance.
8. Bulk import preview/confirmation must remain one instance.
9. Google and Apple must remain one OAuth Controller instance.

Then output only:

1. Final `patterns.csv` in a CSV code block.
2. Final `pattern_counts.csv` in a second CSV code block.
3. A short validation summary stating row count, pattern-type count and total-instance count.

Do not generate UML, report prose, evolution analysis or any new pattern classifications yet.

1. Final `patterns.csv`

</> csv

```
source_version,pattern_name,pattern_type,instance_name,participant_roles,source_locations,intent_and_evider
baseline,Information Expert (GRASP),GRASP - Responsibility Assignment,Parsed Email to Trip Record Linking,"
baseline,Controller (GRASP),GRASP - Responsibility Assignment,Inbound Travel Email Intake Coordination,"App
baseline,Controller (GRASP),GRASP - Responsibility Assignment,Trip Creation Coordination,"Application: Trip
baseline,Controller (GRASP),GRASP - Responsibility Assignment,Trip Membership Management Coordination,"Appl
baseline,Controller (GRASP),GRASP - Responsibility Assignment,Bulk Itinerary Import Coordination,"Applicati
baseline,Controller (GRASP),GRASP - Responsibility Assignment,OAuth Sign-in and Identity Linking Coordinati
baseline,Controller (GRASP),GRASP - Responsibility Assignment,Account Traveler Enrollment Coordination,"App
baseline,Observer (GoF),GoF - Behavioral (framework-mediated),Outbound Mail Delivery Logging,"Application:
baseline,Observer (GoF),GoF - Behavioral (framework-mediated),Trip-Scoped Turbo Refresh Notifications,"Appl
```