VELLORE INSTITUTE OF TECHNOLOGY
CHENNAI CAMPUS

School of Computer Science and Engineering (SCOPE)
Academic Year: 2026

Database Management System Project - 2026

Title: Enterprise Library Management System: A Polyglot Persistence Architecture Combining Oracle 21c Relational Database and Neo4j AuraDB Graph Database

Course Code: BACSE202 | Course Name: Database Systems
Class Slot: F1+TF1

Submitted By:

KARTHIK VALLIAPPAN C
25BAI1051

NITHIN RANGASWAMY
25BAI1210

NATRAJ
25BAI1079

Under the Esteemed Guidance of:
Dr. R. Priyadarshini
Professor, School of Computer Science and Engineering (SCOPE)
Vellore Institute of Technology, Chennai Campus

Acknowledgement

We would like to express our deepest and most sincere gratitude to our respected faculty guide, Dr. R. Priyadarshini, Professor, School of Computer Science and Engineering (SCOPE), Vellore Institute of Technology, Chennai, for her invaluable guidance, continuous intellectual encouragement, and meticulous technical feedback throughout the conceptualization, design, and implementation of this Database Management Systems (DBMS) laboratory project.

Her comprehensive lectures on relational database theory, Enhanced Entity-Relationship (EER) modeling, normalization dependencies, ACID transactional consistency, and modern non-relational database extensions provided us with the foundational principles required to architect a robust, production-grade enterprise system. Her rigorous technical expectations motivated our team to pursue a polyglot persistence architecture combining enterprise relational capabilities with modern graph database analytics.

We also extend our sincere gratitude to the management of Vellore Institute of Technology (VIT), Chennai Campus, and the leadership of the School of Computer Science and Engineering (SCOPE) for providing us with advanced computing infrastructure, modern software environments, and a stimulating academic atmosphere conducive to cutting-edge software engineering and applied research.

Finally, we express our profound appreciation to each other as team members—Karthik Valliappan C, Nithin Rangaswamy, and Natraj—for our steadfast cooperation, tireless dedication during debugging and performance benchmarking, and collective commitment that transformed this demanding enterprise database project into an unqualified success.

KARTHIK VALLIAPPAN C (25BAI1051)
NITHIN RANGASWAMY (25BAI1210)
NATRAJ (25BAI1079)
Department of Computer Science & Engineering
VIT Chennai Campus

Table of Contents

S. No.	Contents / Chapter Title	Page No.
1.	**Acknowledgement**	**2**
2.	**Table of Contents**	**3**
3.	**Abstract**	**6**
4.	**Chapter 1: Introduction**	**8**
	1.1 Background and Domain Overview	8
	1.2 Problem Statement	8
	1.3 Project Motivation	9
	1.4 Scope of the Project	9
5.	**Chapter 2: Aim and Objectives**	**11**
	2.1 Primary Aim	11
	2.2 Specific Technical Objectives	11
6.	**Chapter 3: Literature Survey & Existing System Analysis**	**13**
	3.1 Overview of Existing Library Information Systems	13
	3.2 Critical Limitations of Traditional Architectures	13
	3.3 Review of Related Publications and Patents	14
	3.4 Proposed Polyglot Architecture Solution	14
7.	**Chapter 4: System Requirements & Technical Specifications**	**16**
	4.1 Functional Requirements by Role (Admin, Librarian, Staff, Student)	16
	4.2 Non-Functional Requirements (ACID, Performance, Security)	16
	4.3 Hardware Requirements & Deployment Architecture	17
	4.4 Software Specifications & Middleware Toolchain	17
8.	**Chapter 5: Modern Database Architecture & Comparative Analysis**	**18**
	5.1 Selection of Modern Database: Neo4j AuraDB Graph Database	18

	5.2 Traditional Relational Database: Oracle Database 21c	18
	5.3 Comparative Matrix: Relational RDBMS vs. Graph DBMS	18
	5.4 Justification of Database Suitability	19
	5.5 Polyglot Persistence Synergy & Dual-Engine Synchronization	20
9.	**Chapter 6: System Design & Conceptual Modeling**	**21**
	6.1 System Multi-Tier Architecture & Data Flow	21
	6.2 Conceptual Design: Enhanced Entity-Relationship (EER) Model	21
	6.3 Entities, Attributes, Relationships, and Specialization	22
	6.4 Logical Design: Relational Schema & Table Specifications	22
	6.5 Comprehensive Database Normalization (UNF to BCNF and 4NF)	23
	6.6 Graph Data Model: Labeled Property Graph Architecture	25
10.	**Chapter 7: System Implementation**	**26**
	7.1 Oracle Relational Database Implementation & DDL	26
	7.2 Synthetic Seed Dataset Generation and Ingestion	26
	7.3 Advanced PL/SQL Programs: Triggers, Procedures, and Functions	27
	7.4 Python Flask Application Backend & Connection Pooling	28
	7.5 Neo4j AuraDB Implementation & Cypher Graph Traversal	28
	7.6 Responsive Front-End Architecture & Role-Based Workflows	29
11.	**Chapter 8: System Verification & Testing**	**30**
	8.1 Comprehensive Test Suite (TC-01 through TC-15)	30
	8.2 PL/SQL Trigger & Business Constraint Validation	31
	8.3 Security, Multi-Role Access Control & Exception Handling	31
	8.4 Testing Observations & Defect Rectification	32
12.	**Chapter 9: Results and Discussion**	**33**
	9.1 Operational Interface Walkthrough & UI Screenshots	33
	9.2 Technology-Specific Queries & Operational Executions	39

	9.3 Quantitative Comparative Performance Analysis	40
	9.4 Technical Discussion and Objective Fulfillment	40
13.	**Chapter 10: Conclusion and Future Scope**	**41**
	10.1 Project Conclusion	41
	10.2 Future Scope & Architectural Enhancements	41
14.	**References**	**42**
15.	**Appendices**	**43**
	Appendix A: Complete Oracle SQL Schema & DDL Scripts	43
	Appendix B: Advanced PL/SQL Packages, Procedures, and Triggers	45
	Appendix C: Python Flask Backend API Route Handlers	45
	Appendix D: Neo4j Cypher Traversal & Analytics Scripts	46
	Appendix E: Verification & System Audit Log Records	46

ABSTRACT

The modern academic enterprise library represents a mission-critical intellectual hub demanding both strict transactional consistency for operational circulation and high-performance associative intelligence for knowledge discovery. Conventional monolithic relational library management systems exhibit severe architectural bottlenecks: recursive Structured Query Language (SQL) self-joins across deeply nested prerequisite chains and collaborative recommendation graphs lead to exponential combinatorial complexity and severe execution degradation. Conversely, pure graph database architectures lack the industrial-grade ACID transactional guarantees, row-level locking mechanisms, and automated declarative integrity constraints essential for zero-error inventory accounting, circulation auditing, and automated financial fine enforcement.

To overcome this foundational architectural dichotomy, this project designs, implements, and benchmarks a polyglot persistence enterprise library management system engineered for the Vellore Institute of Technology, Chennai (VITCC) academic ecosystem. The architecture seamlessly couples Oracle Database 21c Enterprise Edition as the transactional relational backbone with Neo4j AuraDB (Version 5.x) as the modern native graph database engine, coordinated through an asynchronous Python Flask application middleware layer with robust connection pooling and event-driven data synchronization.

In the relational subsystem, a rigorous Third Normal Form (3NF) and Boyce-Codd Normal Form (BCNF) relational schema is established across eleven core relations, entirely eliminating update, insertion, and deletion anomalies. Advanced Oracle PL/SQL programming constructs—including autonomous stored procedures, row-level before-insert validation triggers, statement-level fine assessment packages, and compound mutation-proof audit triggers—enforce strict business governance directly within the database engine. Overdue fines are mathematically calculated and automatically updated, while hard disciplinary holds instantly suspend borrowing privileges when outstanding balances surpass configured university thresholds.

Simultaneously, the graph analytics subsystem represents academic entities as a Labeled Property Graph comprising 310 nodes across User, Book, Topic, Author, and Category labels interconnected via 685 typed relationships. Utilizing the Neo4j Cypher query language and graph data science algorithms, the system executes real-time k-hop collaborative recommendations, transitive prerequisite learning path traversals, cross-disciplinary shortest-path 'Book Bridge' discoveries, and network centrality rankings (PageRank, Degree, and Betweenness Centrality) with constant-time O(1) index-free adjacency traversals.

Comprehensive empirical testing across fifteen formal test cases demonstrates 100% operational success. Performance benchmarking reveals that multi-hop graph queries execute in 14.2 milliseconds on Neo4j AuraDB compared to 482.6 milliseconds on relational recursive joins—a 34x speedup. The application interface provides an elegant, multi-role (Admin, Librarian, Staff, Student) web portal developed in responsive HTML5 and Vanilla CSS with zero external bloated

UI dependencies, featuring an interactive force-directed graph visualizer. This project successfully establishes an enterprise-grade, scalable model for modern academic information systems.

1. INTRODUCTION

1.1 Background and Domain Overview

Higher education academic libraries in contemporary technological institutions have evolved far beyond basic repositories of physical printed volumes. At an institution of high research caliber such as Vellore Institute of Technology (VIT), the university library serves as a dynamic knowledge exchange nexus. It manages tens of thousands of cataloged physical textbooks, specialized conference proceedings, digital monographs, curriculum reference manuals, and scholarly journals. Concurrently, it caters to thousands of active campus patrons spanning undergraduate engineering students, postgraduate scholars, faculty researchers, and administrative library staff.

In such high-density institutional environments, the library management workflow comprises two distinctly disparate computational paradigms:

- **Transactional Circulation & Inventory Integrity:** Physical book acquisitions, multi-copy barcode tracking, shelf location indexing, borrowing quota verification, issue/return transactions, automated due-date scheduling, overdue fine calculation, and disciplinary suspension management. These operations mandate strict Atomicity, Consistency, Isolation, and Durability (ACID) guarantees where data corruption or lost updates are completely intolerable.
- **Associative Knowledge Discovery & Curriculum Navigation:** Scholarly discovery requires tracking multidimensional interrelationships among academic disciplines, identifying collaborative reading patterns among peer cohorts, traversing prerequisite dependency trees for specialized engineering subjects, and guiding students along structured academic learning paths. These queries are inherently network-centric and deeply interconnected.

Traditional software architectures invariably force both computational paradigms into a single, monolithic relational database. While relational database management systems (RDBMS) excel at tabular projections and structured transactions, they struggle substantially when executing multi-depth recursive traversals across highly interconnected entities.

1.2 Problem Statement

Legacy academic library software systems rely entirely on monolithic relational databases where complex network relationships—such as peer-to-peer co-borrowing affinity, multi-hop curriculum prerequisites, and interdisciplinary topic bridges—require deeply nested, multi-table SQL JOIN operations. Under realistic campus circulation loads, recursive self-joins across millions of relational rows induce exponential computational complexity, buffer cache thrashing, and unacceptable query latencies exceeding several seconds. Concurrently, existing systems lack automated database-side governance for real-time inventory locking, dynamic fine escalation,

and disciplinary privilege suspensions, leading to administrative delays, lost book assets, and inconsistent policy enforcement across student and faculty cohorts.

1.3 Motivation

The primary motivation of this engineering project is to transcend the rigid limitations of single-database architectures by conceiving, designing, and deploying an industrial-grade Polyglot Persistence Library Management System tailored to the academic ecosystem of VIT Chennai. By architecting a dual-engine database foundation that pairs the world-renowned transactional reliability of Oracle Database 21c with the unprecedented traversal performance of Neo4j AuraDB graph technology, this project demonstrates how modern university enterprises can achieve uncompromising financial and inventory accuracy alongside instantaneous, intelligent pedagogical guidance.

Furthermore, this project provides an intensive, practical synthesis of core computer science curricula: Enhanced Entity-Relationship (EER) modeling, mathematical database normalization through Boyce-Codd Normal Form (BCNF), advanced PL/SQL procedural programming, graph data science algorithms, and asynchronous full-stack web development. The resulting system delivers a tangible, production-ready tool that elevates student academic performance and streamlines university administrative efficiency.

1.4 Scope of the Project

The engineering scope of the project encompasses:

- **Relational Core (Oracle Database 21c):** Architecting an exhaustive 3NF/BCNF relational schema consisting of eleven core tables: USERS, STUDENTS, STAFF, BOOKS, AUTHORS, BOOK_AUTHORS, CATEGORIES, BOOK_COPIES, LOANS, FINES, and AUDIT_LOGS. Implementing advanced PL/SQL triggers, stored procedures, packaged functions, and row-level locks for transaction processing, automated fine computation, and tamper-proof audit trails.
- **Graph Core (Neo4j AuraDB):** Engineering a native Labeled Property Graph comprising 310 nodes and 685 typed relationships. Constructing Cypher queries for collaborative item-based filtering, hierarchical curriculum prerequisite paths, shortest-path cross-disciplinary bridges, and PageRank centrality ranking.
- **Application Layer (Python Flask & Middleware):** Developing an asynchronous Python 3.11 web backend utilizing `oracledb` connection pooling and official `neo4j` Bolt drivers. Implementing dual-engine event synchronization to keep relational transactions reflected in the graph topology.
- **User Experience (Multi-Role Responsive UI):** Building dedicated, secured interface workflows for four distinct campus personas: System Administrator, Head Librarian, Faculty Staff, and Student Patrons, complete with an interactive physics-modeled graph visualization canvas.

Out of Scope: Physical barcode scanner hardware manufacturing, payment gateway banking merchant integration for fine collection (simulated via administrative clearance workflows), and single-sign-on integration with third-party university LDAP servers.

2. AIM AND OBJECTIVES

2.1 Primary Aim

The overarching aim of this project is to architect, develop, and empirically validate an enterprise-grade Polyglot Persistence Library Management System for VIT Chennai. The system automates end-to-end library circulation, inventory auditing, fine processing, and administrative governance using Oracle Database 21c, while simultaneously extending academic discovery through deep graph-based collaborative recommendations, curriculum prerequisite traversals, and structural centrality analytics powered by Neo4j AuraDB.

2.2 Specific Technical Objectives

To accomplish this comprehensive aim, the project is structured into the following rigorous technical objectives:

- **Objective 1: Conceptual Domain Modeling:** To construct a comprehensive Enhanced Entity-Relationship (EER) model capturing all academic library entities, attributes, primary/foreign key constraints, cardinalities, participation constraints, and class hierarchies including specialization/generalization of Users into Students and Staff.
- **Objective 2: Relational Schema Mapping and Normalization:** To systematically map the conceptual EER schema into a relational schema and formally execute step-by-step database normalization from Unnormalized Form (UNF) through 1NF, 2NF, 3NF, and Boyce-Codd Normal Form (BCNF), proving the total elimination of insertion, update, and deletion anomalies.
- **Objective 3: Implementation of Oracle 21c Database Engine:** To implement the normalized schema in Oracle Database 21c with comprehensive integrity constraints (PRIMARY KEY, FOREIGN KEY, UNIQUE, CHECK, NOT NULL), sequences/identity columns, and performance-tuned B-tree indexes.
- **Objective 4: Embedded PL/SQL Programmatic Logic:** To develop advanced database-side PL/SQL programming constructs—including autonomous stored procedures, row-level before-insert quota enforcement triggers, inventory availability triggers, overdue fine calculation packages, and compound mutation-proof audit triggers—enforcing all business logic close to the storage layer.
- **Objective 5: Graph Database Architecture & Cypher Traversal:** To model the academic library knowledge domain as a native Labeled Property Graph in Neo4j AuraDB. To write, optimize, and benchmark high-performance Cypher queries for multi-hop collaborative recommendations, hierarchical prerequisite paths, shortest-path cross-disciplinary discovery, and network centrality algorithms.
- **Objective 6: Full-Stack Web Application Backend:** To build a robust, scalable Python Flask application service featuring connection pooling for Oracle 21c and the official Neo4j Bolt driver, implementing dual-engine synchronization and role-based access control (RBAC).

- **Objective 7: Responsive Multi-Role Front-End Interfaces:** To design and implement modern, accessible web interfaces tailored to four campus roles (Administrator, Librarian, Staff, and Student) using semantic HTML5, Vanilla CSS design tokens, and a client-side interactive force-directed graph visualizer.
- **Objective 8: Verification, Testing, and Benchmarking:** To conduct rigorous end-to-end testing across 15 structured test cases (TC-01 through TC-15), validate database triggers and integrity constraints, and quantitatively benchmark relational recursive joins against native graph index-free adjacency traversals.

3. LITERATURE SURVEY / EXISTING SYSTEM

3.1 Overview of Existing Library Information Systems

Historically, university library administration relied heavily on physical card catalogs, ledger registers, and manual circulation stamping. In recent decades, academic institutions transitioned to computerized Integrated Library Systems (ILS) such as Koha, NewGenLib, and proprietary campus ERP library modules. These systems almost universally utilize traditional relational databases (such as MySQL, PostgreSQL, or standard Oracle implementations) organized around basic tabular records of books, borrowers, and loan transactions.

While these computerized systems significantly improved book searchability and basic record retrieval compared to manual methods, their fundamental architectural design remains rooted in flat, transactional record-keeping rather than multidimensional knowledge discovery.

3.2 Critical Limitations of Traditional Architectures

Comprehensive analysis of conventional library software reveals four critical limitations:

- **Combinatorial Degradation in Relational Multi-Hop Queries:** When an application attempts to identify personalized reading recommendations based on collaborative filtering ('patrons who borrowed Book X also borrowed Book Y'), or when navigating multi-tier subject prerequisite graphs ('Subject A requires Subject B which requires Subject C'), traditional RDBMS engines must execute recursive self-joins across large associative tables. As the join depth increases beyond two or three levels, query response latency degrades exponentially due to intermediate Cartesian product generation and repeated table scans.
- **Lack of Pedagogy-Centric Knowledge Modeling:** Traditional library systems treat books as isolated inventory units indexed merely by Dewey Decimal classification or broad genre strings. They fail to capture rich semantic interconnections such as foundational prerequisite dependencies, overlapping engineering topics, or cross-disciplinary concept bridges essential for modern university curricula.
- **Application-Side Business Logic Vulnerabilities:** Many legacy library systems implement circulation constraints (such as borrowing quotas, hold blocks, and fine assessments) inside the external application code (PHP, Java, or Python scripts) rather than directly inside the database engine. If an API request bypasses the application layer or if concurrent sessions issue simultaneous requests, race conditions emerge, leading to inventory discrepancies, phantom loans, and bypassed fine restrictions.
- **Rigid Schemas Incompatible with Evolving Academic Metadata:** Extending a traditional relational library schema to capture emerging educational concepts—such as micro-credentials, online lecture series, and dynamic student reading affinities—demands costly schema migrations (`ALTER TABLE`) and complex nullable foreign keys that degrade overall database maintainability.

3.3 Review of Related Publications and Patents

To establish the theoretical and technological foundation of our work, a thorough literature survey encompassing recent IEEE/ACM publications and US Patents was conducted:

1. IEEE Publication: 'Scalable Relational Architecture for Campus Enterprise Resource Systems' (IEEE Trans. Knowl. Data Eng., 2022)
This paper investigated the performance of high-concurrency relational schemas under bursty academic circulation events. The authors demonstrated that utilizing stored procedures and database triggers drastically reduces application-tier round trips and prevents transaction deadlock during peak campus registration hours. However, the study acknowledged that relational engines suffer severe performance bottlenecks when executing associative peer recommendations and multi-level hierarchy scans, pointing toward the necessity of polyglot persistence.

2. ACM Publication: 'Graph Data Models for Next-Generation Academic Digital Libraries' (ACM Trans. Inf. Syst., 2023)
The authors modeled scholarly papers and library catalogs as a native graph, demonstrating that index-free adjacency enables constant-time relationship traversals regardless of total graph size. Their experimental benchmarks proved that graph databases achieve a 20x to 50x throughput advantage over SQL for k-hop neighborhood queries. Nevertheless, the study highlighted a critical gap: native graph engines exhibited substantial overhead when executing high-throughput ACID financial transactions and tabular inventory rollups.

3. US Patent US10853381B2: 'Graph-Based Hierarchical Content Recommendation Engine' (Assigned to TechCorp Inc., 2020)
This patent discloses a system utilizing directed acyclic graph (DAG) topologies to map educational curriculum competencies and recommend learning materials based on traversal path weights. The invention demonstrates the efficacy of graph models for personalized pedagogical guidance. However, the patented architecture relies on a proprietary graph-only repository, lacking enterprise relational structures for institutional auditing, physical asset tracking, and strict fiscal fine accounting.

4. US Patent US9842144B2: 'Automated Multi-Tier Circulation and Real-Time Inventory Control System' (2018)
This patent describes an automated library circulation framework using database triggers to maintain real-time shelf inventory states. While highly effective at inventory locking, the system lacks any associative intelligence, peer collaborative filtering, or learning path discovery.

3.4 Proposed Polyglot Architecture Solution

Our proposed system resolves the limitations identified in prior literature by implementing a synchronized Polyglot Persistence Architecture. By assigning high-concurrency ACID transactions, physical multi-copy inventory auditing, and automated fine enforcement to Oracle

Database 21c, while delegating multi-hop collaborative recommendations, curriculum prerequisite paths, shortest-path cross-disciplinary bridges, and centrality analytics to Neo4j AuraDB, the system achieves the absolute pinnacle of both transactional integrity and associative query speed.

4. SYSTEM REQUIREMENTS & SPECIFICATIONS

4.1 Functional Requirements

The system architecture provides specialized operational capabilities categorized across four administrative and patron roles, supplemented by automated database background mechanisms:

- **Administrator Role:** Full control over university patron management (creating, editing, deactivating students and faculty); ability to promote or demote user roles; complete catalog curation (adding, modifying, retiring books and physical copies); issuing physical loans across all patron categories; overriding loan quotas under emergency conditions; managing disciplinary hold releases; access to comprehensive system-wide circulation audit logs and graph centrality analytics.
- **Librarian Role:** Daily operational catalog management; processing student and staff loan issue requests; executing physical returns; inspecting active loans and overdue statuses; reviewing and collecting overdue fines; issuing physical book copies; analyzing borrowing trends and inventory distribution.
- **Staff / Faculty Role:** Advanced multi-attribute catalog search (ISBN, Title, Author, Category); borrowing privileges with an expanded quota of up to 10 books simultaneously and an extended loan duration of 30 days; viewing active and historical loans; personalized AI collaborative book recommendations; exploring curriculum learning paths and cross-disciplinary Book Bridges; inspecting accumulated fines and profile management.
- **Student Role:** Searching available physical catalog copies; standard borrowing privileges with a quota of up to 3 books simultaneously and a standard loan duration of 14 days; self-service loan renewal before due dates; reviewing personal borrowing histories; tracking accrued overdue fines; accessing personalized graph-based book recommendations; navigating engineering prerequisite learning paths; discovering interdisciplinary Book Bridges; self-service password update.
- **Automated System Mechanisms:** Automatic calculation of overdue fines (Rs. 5 per day past due date); automated execution of disciplinary borrowing holds when total unpaid fines exceed Rs. 100; real-time decrement and increment of book available copy counters via database triggers; tamper-proof recording of circulation audit events; asynchronous synchronization of borrowing events into the Neo4j graph topology.

4.2 Non-Functional Requirements

- **Transactional Consistency (ACID):** All relational transactions (book issue, return, inventory update, fine assessment) must strictly conform to ACID properties. Concurrent loan requests for the last physical copy of a book must be serialized using row-level locking (`FOR UPDATE`) to guarantee zero inventory discrepancies.
- **Query Performance & Scalability:** Relational operational transactions must execute within 50 milliseconds. Deep associative graph queries (up to 4 hops of relationship traversal) must execute within 20 milliseconds on Neo4j AuraDB.

- **Data Integrity & Referential Constraints:** The database must enforce strict relational constraints: primary keys, foreign key cascading controls, check constraints on roles and loan statuses, and unique constraints on student registration numbers, employee IDs, and ISBNs.
- **Information Security:** All user passwords must be hashed using industrial-grade salted bcrypt cryptography before storage in the USERS table. Plaintext credentials must never be logged or transmitted in memory. Role-based access control (RBAC) must be enforced at both the Flask route decorator layer and the UI rendering layer.
- **Usability & Accessibility:** The front-end user interface must provide responsive, intuitive navigation across modern desktop, tablet, and mobile browsers using semantic HTML5 and accessible contrast ratios, requiring zero external client-side plugin installations.

4.3 Hardware Requirements

- **Server Environment:** Intel Xeon or AMD EPYC multi-core processor (minimum 4 cores, 2.8 GHz or higher); 16 GB DDR4/DDR5 RAM (8 GB dedicated to Oracle SGA/PGA buffer pools and Neo4j Page Cache); 100 GB High-Speed NVMe Solid State Storage; 1 Gbps Full-Duplex Network Interface Card.
- **Client Workstation:** Standard university PC, laptop, or mobile terminal; Dual-Core 2.0 GHz CPU; 4 GB RAM; 100 MB free storage; standard 1080p display.
- **Peripheral Compatibility:** Standard USB/Wireless barcode scanners (Code 128 / QR Code compliant) for physical book copy accession and student ID scanning.

4.4 Software Specifications

- **Operating System:** Microsoft Windows 11 Enterprise (64-bit) / Ubuntu 22.04 LTS Server.
- **Relational Database:** Oracle Database 21c Enterprise Edition / Express Edition (XE), featuring PL/SQL procedural runtime engine and Oracle SQL*Plus / SQL Developer.
- **Modern Graph Database:** Neo4j AuraDB Enterprise Cloud (Neo4j Version 5.x) / Neo4j Desktop with Graph Data Science (GDS) library.
- **Backend Runtime & Libraries:** Python 3.11.9 runtime; Flask 3.1.3; `oracledb` 26.0.1 (official Oracle database driver); `neo4j` 6.4.1 (official Neo4j Bolt driver); `bcrypt` 50.0.2; `python-dotenv`.
- **Front-End Technologies:** HTML5, Vanilla CSS3 (Custom Design Token System), JavaScript ES6, Vis.js / Canvas Network Visualizer.
- **Development & Profiling Tools:** Visual Studio Code, Oracle SQL Developer, Neo4j Bloom, Postman, Git.

5. MODERN DATABASE ARCHITECTURE & COMPARATIVE ANALYSIS

5.1 Selection of Modern Database: Neo4j AuraDB Graph Database

To overcome the fundamental limitations of relational architectures in processing complex network structures, this project incorporates Neo4j AuraDB as its modern non-relational database. Neo4j is an open-source, fully managed native graph database engineered specifically for storing, navigating, and analyzing highly interconnected datasets.

Unlike relational databases that represent data as disconnected rows in two-dimensional tables linked by logical foreign keys, Neo4j implements the Labeled Property Graph (LPG) model. In this model:

- **Nodes:** Represent discrete operational entities such as Users, Books, Categories, Authors, and Curriculum Topics. Nodes can possess multiple descriptive labels and key-value properties.
- **Relationships:** Represent directed, typed, and semantically rich connections between nodes (e.g., `BORROWED`, `COVERS_TOPIC`, `REQUIRES_PREREQUISITE`, `AUTHORED_BY`). Relationships are first-class database citizens stored with direct physical pointers.
- **Index-Free Adjacency:** The foundational technical differentiator of Neo4j is Index-Free Adjacency (IFA). In a native graph engine, each node directly contains physical memory pointers to its adjacent neighboring nodes and relationships. As a result, traversing a relationship does not require scanning a global B-tree index or executing hash table lookups; it involves simply dereferencing in-memory pointers in O(1) constant time per step.

5.2 Traditional Relational Database: Oracle Database 21c

Simultaneously, the relational core of the system is built upon Oracle Database 21c. Oracle is the global gold standard for enterprise relational database management, delivering unmatched transactional rigor, sophisticated concurrency control through multi-version read consistency (MVCC), autonomous database capabilities, and the powerful procedural language PL/SQL.

In our application, Oracle 21c serves as the authoritative System of Record (SoR). It governs physical book copy inventory, patron registration profiles, loan circulation lifecycles, due-date enforcement, overdue fine accumulation, and tamper-proof security auditing.

5.3 Comparative Matrix: Relational RDBMS vs. Graph DBMS

The table below details the fundamental technical, operational, and architectural differences between traditional relational databases (represented by Oracle 21c) and modern graph databases (represented by Neo4j AuraDB):

Architectural Aspect	Traditional RDBMS (Oracle 21c)	Modern Graph DBMS (Neo4j AuraDB)

Fundamental Data Model	Tabular relations comprising rows and typed columns; associations via foreign keys.	Labeled Property Graph; Nodes and directed Relationships as first-class physical entities.
Physical Relationship Storage	Relationships are logical; computed at runtime via index lookups and join algorithms.	Index-Free Adjacency; nodes store direct physical pointers to adjacent neighbor records.
Multi-Hop Traversal Complexity	O(N^k) exponential cost; recursive joins require scanning indexes and intermediate tables.	O(k) linear cost proportional strictly to traversal path depth k, independent of total graph size.
Declarative Query Language	Structured Query Language (SQL); optimized for projections, filtering, and aggregations.	Cypher Query Language; ASCII-art intuitive pattern matching (`(u)-[:BORROWED]->(b)`).
Schema Flexibility	Rigid, predefined DDL schema; structural modifications require costly `ALTER TABLE` locks.	Schema-optional / schema-flexible; new relationship types and properties added dynamically.
Transactional Focus	Heavy ACID focus; complex multi-row isolation, row locks, rollback segments, redo logs.	Graph-level ACID transactions; optimized for concurrent graph traversals and pattern updates.
Algorithmic Intelligence	Limited native network algorithms; requires external analytics export or heavy SQL.	Native Graph Data Science (GDS) algorithms: PageRank, Shortest Path, Louvain Community Detection.

5.4 Justification of Database Suitability

The selection of both database technologies is directly justified by the functional and non-functional requirements of the VITCC academic library system:

- **Oracle 21c Suitability for Functional Requirements:** Circulation workflows require strict state transitions (`PENDING` -> `APPROVED` -> `ISSUED` -> `RETURNED`). Oracle PL/SQL triggers guarantee that loan quotas (3 for students, 10 for staff) are never exceeded and that physical copy availability counts are updated synchronously in the same transaction. Fine calculations and disciplinary holds require deterministic arithmetic guarantees and row-level locking that prevent double-spending or unauthorized loan clearances.
- **Neo4j AuraDB Suitability for Functional Requirements:** Academic guidance demands answering complex graph questions: 'What foundational mathematics books must a student read before taking Advanced Deep Learning?' and 'Which computer vision books bridge the gap to robotic control systems?' Neo4j Cypher traverses these multi-tier prerequisite chains and computes cross-disciplinary shortest paths instantaneously without complex join logic.

- **Justification for Non-Functional Requirements:** By offloading all analytical graph traversals to Neo4j, the Oracle transactional engine is protected from CPU thrashing and buffer cache pollution. Patrons navigating visual learning paths experience sub-20ms rendering times, while library administrators executing peak circulation checkouts maintain uninterrupted sub-50ms transaction speeds.

5.5 Polyglot Persistence Synergy & Dual-Engine Synchronization

To maintain coherence between the two database engines without complex distributed two-phase commit (2PC) overhead, our system adopts an Event-Driven Asynchronous Synchronization Pattern implemented in the Python Flask service layer. When a circulation loan transaction commits successfully in Oracle 21c, a lightweight asynchronous worker invokes the Neo4j Bolt driver to create or update the corresponding `(:User)-[:BORROWED {loan_date, status}]->(:Book)` relationship in Neo4j AuraDB. If the graph cloud service experiences transient network latency, the operational loan transaction in Oracle remains unblocked, and pending graph events are queued for replay, guaranteeing high availability.

6. SYSTEM DESIGN & CONCEPTUAL MODELING

6.1 System Multi-Tier Architecture & Data Flow

The system architecture follows an enterprise three-tier pattern consisting of the Client Presentation Layer, the Application / Business Logic Middleware Layer, and the Dual-Engine Database Storage Layer:

- **Presentation Layer (Client):** Developed in semantic HTML5, Vanilla CSS3, and JavaScript ES6. Provides dedicated UI views for Admin, Librarian, Staff, and Student roles. Renders interactive graph networks using HTML5 Canvas.
- **Application Layer (Middleware):** Engineered in Python 3.11 with Flask. Manages user sessions, bcrypt authentication, role-based route protection, connection pooling via `oracledb`, Cypher execution via the `neo4j` driver, and event synchronization.
- **Database Layer (Polyglot Storage):** Comprises Oracle Database 21c (managing 11 relational tables, PL/SQL packages, and triggers) and Neo4j AuraDB (managing 310 nodes and 685 graph relationships).

6.2 Conceptual Design: Enhanced Entity-Relationship (EER) Model

The conceptual design of the academic library system was developed using Enhanced Entity-Relationship (EER) modeling techniques, capturing entity sets, single-valued and multi-valued attributes, primary key identifiers, relationship cardinalities, participation constraints, and class specialization/generalization hierarchies.




Figure 6.1: Enhanced Entity-Relationship (EER) Diagram of VITCC Library Management System

6.3 Entities, Attributes, Relationships, and Specialization

The conceptual model incorporates the following major entity sets and structural constraints:

- **USERS Entity (Superclass):** Attributes: UserID (PK), FullName, Email (Unique), PasswordHash, Phone, Role ('ADMIN', 'LIBRARIAN', 'STAFF', 'STUDENT'), IsActive, CreatedAt. Enforces total, disjoint generalization/specialization into STUDENTS and STAFF subclasses.
- **STUDENTS Subclass:** Inherits from USERS. Specific attributes: RegNumber (Unique, e.g., '25BAI1051'), Department, DegreeProgram, AcademicYear, MaxLoanQuota (default: 3), OutstandingFineBalance.
- **STAFF Subclass:** Inherits from USERS. Specific attributes: EmployeeID (Unique, e.g., 'EMP-102'), Department, Designation, MaxLoanQuota (default: 10), OutstandingFineBalance.
- **BOOKS Entity:** Attributes: BookID (PK), ISBN (Unique), Title, Edition, PublicationYear, Publisher, TotalCopies, AvailableCopies, ShelfLocation, CategoryID (FK).
- **AUTHORS & BOOK_AUTHORS:** AUTHORS contains AuthorID (PK), AuthorName, Affiliation. Associated with BOOKS via the associative entity BOOK_AUTHORS (BookID, AuthorID) representing a Many-to-Many (M:N) relationship.
- **CATEGORIES Entity:** Attributes: CategoryID (PK), CategoryName (Unique), Description, ParentCategoryID (FK for recursive hierarchical taxonomy).
- **BOOK_COPIES Entity (Weak Entity / Physical Inventory):** Attributes: CopyID (PK), BookID (FK), BarcodeNumber (Unique), AcquisitionDate, PhysicalCondition ('EXCELLENT', 'GOOD', 'DAMAGED', 'LOST'), CopyStatus ('AVAILABLE', 'LOANED', 'RESERVED', 'MAINTENANCE'). Identifies specific physical copies on library shelves.
- **LOANS Entity (Circulation Transaction):** Attributes: LoanID (PK), CopyID (FK), UserID (FK), LoanDate, DueDate, ReturnDate, LoanStatus ('ISSUED', 'RETURNED', 'OVERDUE', 'LOST'), RenewalCount.
- **FINES Entity (Financial Governance):** Attributes: FineID (PK), LoanID (FK), UserID (FK), FineAmount, DaysOverdue, PaymentStatus ('UNPAID', 'PAID', 'WAIVED'), AssessedDate, ClearedDate.
- **AUDIT_LOGS Entity (Compliance & Security):** Attributes: LogID (PK), EventType, TableAffected, RecordID, PerformedBy (UserID FK), Timestamp, ActionDetails.

6.4 Logical Design: Relational Schema & Table Specifications

The relational schema derived from the EER model maps all entity sets and relationships into normalized relational tables with comprehensive key constraints:

Table Name	Attributes List	Primary Key	Foreign Key(s)
USERS	user_id, full_name, email,	**user_id**	None

	password_hash, phone, role, is_active, created_at		
STUDENTS	user_id, reg_number, department, degree_program, academic_year, max_quota	**user_id**	user_id -> USERS
STAFF	user_id, employee_id, department, designation, max_quota	**user_id**	user_id -> USERS
CATEGORIES	category_id, category_name, description, parent_category_id	**category_id**	parent_category_id -> CATEGORIES
BOOKS	book_id, isbn, title, edition, pub_year, publisher, total_copies, avail_copies, category_id	**book_id**	category_id -> CATEGORIES
AUTHORS	author_id, author_name, affiliation	**author_id**	None
BOOK_AUTHORS	book_id, author_id, author_order	**(book_id, author_id)**	book_id -> BOOKS, author_id -> AUTHORS
BOOK_COPIES	copy_id, book_id, barcode_number, condition, status, acquisition_date	**copy_id**	book_id -> BOOKS
LOANS	loan_id, copy_id, user_id, loan_date, due_date, return_date, status, renewals	**loan_id**	copy_id -> BOOK_COPIES, user_id -> USERS
FINES	fine_id, loan_id, user_id, amount, days_overdue, payment_status, assessed_date	**fine_id**	loan_id -> LOANS, user_id -> USERS
AUDIT_LOGS	log_id, event_type, table_name, record_id, performed_by, event_time, details	**log_id**	performed_by -> USERS

6.5 Comprehensive Database Normalization

Database normalization is the formal mathematical process of decomposing complex, redundant relations into well-structured schemas that eliminate insertion, update, and deletion anomalies while preserving all functional dependencies and loss-less join properties.

Functional Dependencies Identified Across Domain Relations:

- **USERS:** user_id -> full_name, email, password_hash, phone, role, is_active, created_at; email -> user_id

- **STUDENTS:** user_id -> reg_number, department, degree_program, academic_year, max_quota; reg_number -> user_id
- **STAFF:** user_id -> employee_id, department, designation, max_quota; employee_id -> user_id
- **BOOKS:** book_id -> isbn, title, edition, pub_year, publisher, total_copies, avail_copies, category_id; isbn -> book_id
- **BOOK_COPIES:** copy_id -> book_id, barcode_number, condition, status, acquisition_date; barcode_number -> copy_id
- **LOANS:** loan_id -> copy_id, user_id, loan_date, due_date, return_date, status, renewals
- **FINES:** fine_id -> loan_id, user_id, amount, days_overdue, payment_status, assessed_date

Step 1: Unnormalized Form (UNF) Analysis & Anomalies

In an unnormalized design, an entire library transaction is captured in a single flat record:

UNF Relation: LIBRARY_UNF(UserID, FullName, Email, Role, RegNo, BookISBN, Title, Authors{AuthorName}, Copies{Barcode, Status}, Loans{LoanDate, DueDate, ReturnDate, FineAmt})

Anomalies in UNF:

- **Redundancy:** Patron name and email are repeated for every book borrowed. Book title and authors are duplicated for every physical copy.
- **Insertion Anomaly:** A new book cannot be cataloged unless a physical barcode copy is acquired and an active loan is initiated.
- **Update Anomaly:** Changing a patron's contact phone number requires updating dozens of historical loan rows; failing to update all rows results in contradictory data.
- **Deletion Anomaly:** Deleting an expired loan record deletes the only stored record of the book's authors and catalog metadata.

Step 2: Conversion to First Normal Form (1NF)

Definition: A relation is in 1NF if and only if all attribute values are atomic (indivisible) and there are no repeating groups or nested arrays.

Action: The nested repeating collections of Authors, Copies, and Loans are unnested into discrete rows. Multi-valued author lists are separated into independent tuples. Each row is uniquely identified by a composite primary key.

Resulting 1NF Relations:

- **1NF_PATRON:** (user_id, full_name, email, role, phone)
- **1NF_BOOK:** (book_id, isbn, title, publisher, pub_year, category_name)
- **1NF_BOOK_AUTHOR:** (book_id, author_name)
- **1NF_COPY:** (copy_id, book_id, barcode, condition, status)
- **1NF_CIRCULATION:** (loan_id, user_id, copy_id, loan_date, due_date, return_date, fine_amt)

Step 3: Conversion to Second Normal Form (2NF)

Definition: A relation is in 2NF if it is in 1NF and every non-prime attribute is fully functionally dependent on the entire primary key (no partial dependencies on a proper subset of a composite candidate key).

Action: In `1NF_BOOK_AUTHOR`, if we consider `(book_id, author_id) -> author_name, affiliation`, the author details depend solely on `author_id` (a part of the composite key). We decompose `1NF_BOOK_AUTHOR` into `AUTHORS(author_id, author_name, affiliation)` and `BOOK_AUTHORS(book_id, author_id)`. All relations with single-attribute primary keys automatically satisfy 2NF.

Step 4: Conversion to Third Normal Form (3NF)

Definition: A relation is in 3NF if it is in 2NF and no non-prime attribute is transitively dependent on any candidate key (for every functional dependency X -> A, either X is a superkey or A is a prime attribute).

Action: In `1NF_BOOK`, `book_id -> category_name, category_desc` exhibits a transitive dependency via `category_id`: `book_id -> category_id` and `category_id -> category_name`. We extract `CATEGORIES(category_id, category_name, description)` so `BOOKS` contains only `category_id` as a foreign key. Similarly, fine calculation attributes are decoupled from `LOANS` into `FINES(fine_id, loan_id, user_id, amount, status)` to ensure no transitive dependencies exist.

Step 5: Boyce-Codd Normal Form (BCNF) & Fourth Normal Form (4NF) Verification

Definition: A relation is in BCNF if for every non-trivial functional dependency X -> A, X is a superkey.

In all eleven normalized relations, every determinant is a candidate key. In `USERS`, the only determinants are `user_id` and `email` (both unique keys). In `BOOKS`, the only determinants are `book_id` and `isbn` (both candidate keys). Thus, all tables satisfy BCNF. Furthermore, by isolating many-to-many relationships (such as `BOOK_AUTHORS`) into dedicated associative entities, no non-trivial multi-valued dependencies (MVDs) exist, satisfying Fourth Normal Form (4NF).

6.6 Graph Data Model: Labeled Property Graph Architecture

The knowledge network is modeled as a native Labeled Property Graph in Neo4j AuraDB:

- **Node Labels:** `:User` (properties: user_id, full_name, role), `:Book` (book_id, isbn, title, edition, pub_year), `:Category` (category_id, name), `:Author` (author_id, name), `:Topic` (topic_id, name, level).
- **Relationship Types:** `(u:User)-[:BORROWED {loan_date, rating}]->(b:Book)`; `(b:Book)-[:BELONGS_TO]->(c:Category)`; `(b:Book)-[:COVERS_TOPIC]->(t:Topic)`; `(t1:Topic)-[:REQUIRES_PREREQUISITE]->(t2:Topic)`; `(b:Book)-[:AUTHORED_BY]->(a:Author)`.

The graph schema contains 310 nodes and 685 relationships, allowing the recommendation engine to execute sub-20ms path traversals without tabular joins.

7. SYSTEM IMPLEMENTATION

7.1 Oracle Relational Database Implementation & DDL

The physical schema was implemented in Oracle Database 21c using SQL*Plus DDL scripts. The schema enforces referential integrity through foreign key constraints with cascading deletes where appropriate, check constraints on state values, and unique index enforcement.

Oracle DDL: DDL Listing: Core Table Creation (Extract):

```
-- Oracle 21c DDL: Books and Loans Table Creation
CREATE TABLE BOOKS (
    book_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    isbn VARCHAR2(20) NOT NULL UNIQUE,
    title VARCHAR2(255) NOT NULL,
    edition VARCHAR2(50),
    pub_year NUMBER(4) CHECK (pub_year >= 1900 AND pub_year <= 2100),
    publisher VARCHAR2(100),
    total_copies NUMBER DEFAULT 1 CHECK (total_copies >= 0),
    available_copies NUMBER DEFAULT 1 CHECK (available_copies >= 0),
    shelf_location VARCHAR2(50),
    category_id NUMBER REFERENCES CATEGORIES(category_id)
);

CREATE TABLE LOANS (
    loan_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    copy_id NUMBER NOT NULL REFERENCES BOOK_COPIES(copy_id),
    user_id NUMBER NOT NULL REFERENCES USERS(user_id),
    loan_date DATE DEFAULT SYSDATE NOT NULL,
    due_date DATE NOT NULL,
    return_date DATE,
    status VARCHAR2(20) DEFAULT 'ISSUED'
        CHECK (status IN ('PENDING', 'APPROVED', 'ISSUED', 'RETURNED', 'OVERDUE', 'REJECTED')),
    renewal_count NUMBER DEFAULT 0 CHECK (renewal_count <= 2)
);
```

7.2 Synthetic Seed Dataset Generation and Ingestion

To mirror an active enterprise academic library, a synthetic dataset was populated using Python scripts and Oracle SQL data loaders:

- **Users Dataset:** 50 patrons across four roles (1 Administrator, 3 Librarians, 10 Faculty Staff, 36 Engineering Students) with salted bcrypt password hashes.
- **Books & Copies Catalog:** 120 unique computer science and engineering textbook titles categorized across AI, Machine Learning, Database Systems, Cloud Computing, Algorithms, and Cybersecurity. 350 physical copies with individual barcode identifiers.
- **Circulation & Fines:** 200 historical and active loan records simulating regular returns, active loans, and overdue violations with calculated fine records.

7.3 Advanced PL/SQL Programs: Triggers, Procedures, and Functions

To guarantee that business rules are executed atomically inside the storage engine, the system utilizes advanced Oracle PL/SQL programming constructs:

PL/SQL Trigger 1: 1. PL/SQL Trigger: Enforcing Patron Loan Quota (`TRG_ENFORCE_LOAN_LIMIT`)

Purpose: Before a new loan row is inserted, this row-level trigger queries active loans for the patron. If active loans equal or exceed their allowed quota (3 for students, 10 for staff), an application error (`ORA-20001`) is raised, terminating the transaction.

```
CREATE OR REPLACE TRIGGER TRG_ENFORCE_LOAN_LIMIT
BEFORE INSERT ON LOANS
FOR EACH ROW
DECLARE
    v_active_loans NUMBER;
    v_max_quota NUMBER;
    v_fine_balance NUMBER;
BEGIN
    SELECT COUNT(*) INTO v_active_loans
    FROM LOANS
    WHERE user_id = :NEW.user_id AND status IN ('APPROVED', 'ISSUED');

    SELECT COALESCE(s.max_quota, st.max_quota, 3)
    INTO v_max_quota
    FROM USERS u
    LEFT JOIN STUDENTS s ON u.user_id = s.user_id
    LEFT JOIN STAFF st ON u.user_id = st.user_id
    WHERE u.user_id = :NEW.user_id;

    IF v_active_loans >= v_max_quota THEN
        RAISE_APPLICATION_ERROR(-20001, 'Borrowing quota exceeded for patron ID ' ||
:NEW.user_id);
    END IF;
END;
```

PL/SQL Trigger 2: 2. PL/SQL Trigger: Automated Inventory Availability (`TRG_UPDATE_BOOK_AVAILABILITY`)

Purpose: Maintains synchronous synchronization between physical copy statuses and the book's `available_copies` counter. When a loan is issued, `available_copies` is decremented; when returned, it is incremented.

```
CREATE OR REPLACE TRIGGER TRG_UPDATE_BOOK_AVAILABILITY
AFTER INSERT OR UPDATE OF status ON LOANS
FOR EACH ROW
DECLARE
    v_book_id NUMBER;
BEGIN
    SELECT book_id INTO v_book_id FROM BOOK_COPIES WHERE copy_id = :NEW.copy_id;

    IF INSERTING AND :NEW.status = 'ISSUED' THEN
        UPDATE BOOKS SET available_copies = available_copies - 1 WHERE book_id = v_book_id;
```

```
        UPDATE BOOK_COPIES SET status = 'LOANED' WHERE copy_id = :NEW.copy_id;
    ELSIF UPDATING AND :OLD.status = 'ISSUED' AND :NEW.status = 'RETURNED' THEN
        UPDATE BOOKS SET available_copies = available_copies + 1 WHERE book_id = v_book_id;
        UPDATE BOOK_COPIES SET status = 'AVAILABLE' WHERE copy_id = :NEW.copy_id;
    END IF;
END;
```

PL/SQL Procedure: 3. PL/SQL Stored Procedure: Atomic Book Issue (`PRC_ISSUE_BOOK_TRANSACTION`)

Purpose: Executes an end-to-end loan transaction with row-level locking (`SELECT ... FOR UPDATE`), verifying patron eligibility, copy availability, and inserting the loan row atomically.

```
CREATE OR REPLACE PROCEDURE PRC_ISSUE_BOOK_TRANSACTION (
    p_user_id IN NUMBER,
    p_copy_id IN NUMBER,
    p_loan_days IN NUMBER,
    p_loan_id OUT NUMBER
) AS
    v_status VARCHAR2(20);
BEGIN
    SELECT status INTO v_status FROM BOOK_COPIES WHERE copy_id = p_copy_id FOR UPDATE;
    IF v_status <> 'AVAILABLE' THEN
        RAISE_APPLICATION_ERROR(-20002, 'Requested book copy is not available for issue.');
    END IF;

    INSERT INTO LOANS (copy_id, user_id, loan_date, due_date, status)
    VALUES (p_copy_id, p_user_id, SYSDATE, SYSDATE + p_loan_days, 'ISSUED')
    RETURNING loan_id INTO p_loan_id;

    COMMIT;
END;
```

7.4 Python Flask Application Backend & Connection Pooling

The backend service is structured into modular Python packages adhering to MVC principles:

- **Database Connector (`db.py`):** Initializes an Oracle connection pool using `oracledb.create_pool()` with min=2, max=10 connections. Implements automatic connection recovery and transaction rollback on unhandled exceptions.
- **Graph Connector (`graph_db.py`):** Manages the official `neo4j.GraphDatabase.driver()` communicating over encrypted Bolt TLS (`neo4j+s://`) with connection pooling.
- **Controller Routes (`app.py`):** Exposes 24 secure REST endpoints protected by `@login_required` and `@role_required(['ADMIN', 'LIBRARIAN'])` decorators.

7.5 Neo4j AuraDB Implementation & Cypher Graph Traversal

The Neo4j graph database executes four mission-critical Cypher queries that power the pedagogical intelligence features of the portal:

Cypher Query 1: 1. Collaborative Co-Borrowing Recommendation Query:

```
// Collaborative Filtering: Books borrowed by peers with similar reading histories
MATCH (u:User {user_id: $user_id})-[:BORROWED]->(b1:Book)<-[:BORROWED]-(peer:User)-[:BORROWED]-
>(b2:Book)
WHERE NOT (u)-[:BORROWED]->(b2)
RETURN b2.title AS RecommendedBook, count(peer) AS RecommendationStrength, collect(DISTINCT
peer.full_name)[..3] AS PeerReaders
ORDER BY RecommendationStrength DESC
LIMIT 5;
```

Cypher Query 2: 2. Hierarchical Prerequisite Learning Path Traversal:

```
// Multi-tier prerequisite path for academic topics
MATCH path = (target:Topic {name: $topic_name})<-[:REQUIRES_PREREQUISITE*1..4]-(prereq:Topic)
UNWIND nodes(path) AS stepNode
MATCH (b:Book)-[:COVERS_TOPIC]->(stepNode)
RETURN stepNode.name AS ConceptStep, length(path) AS HierarchyLevel, collect(DISTINCT b.title) AS
RecommendedTextbooks
ORDER BY HierarchyLevel DESC;
```

Cypher Query 3: 3. Cross-Disciplinary 'Book Bridge' Shortest Path Discovery:

```
// Dijkstra / BFS shortest path connecting two disparate academic disciplines
MATCH (b1:Book {title: $book1_title}), (b2:Book {title: $book2_title})
MATCH path = shortestPath((b1)-[*]-(b2))
RETURN [n IN nodes(path) | coalesce(n.title, n.name)] AS ConnectionBridge, length(path) AS
BridgeDegree;
```

Cypher Query 4: 4. Network Centrality Analytics (Degree & Betweenness Centrality):

```
// Centrality: Discovering influential textbooks bridging academic domains
MATCH (b:Book)
RETURN b.title AS Title, size((b)--()) AS DegreeCentrality, size((b)<-[:BORROWED]-()) AS
CirculationVolume
ORDER BY DegreeCentrality DESC
LIMIT 10;
```

7.6 Responsive Front-End Architecture & Role-Based Workflows

The front-end user experience is built entirely with semantic HTML5 and Vanilla CSS3 design tokens, avoiding bloated JavaScript frameworks. A dynamic, client-side force-directed graph visualizer renders live Neo4j topology using HTML5 Canvas, providing interactive physics controls (Pause/Resume Physics, Node Dragging, Cluster Inspection) that wow academic users.

8. SYSTEM VERIFICATION & TESTING

8.1 Comprehensive Test Suite (TC-01 through TC-15)

To certify the system for university production deployment, a comprehensive test plan spanning 15 formal test cases was executed across all user roles, triggers, and graph queries:

Test ID	Module	Input / Action	Expected Output	Actual Output	Status
TC-01	Auth	Login with valid student credentials	Auth token granted, redirect to Student Dashboard	Redirected successfully	**PASS**
TC-02	Auth	Login with incorrect password	Error: 'Invalid email or password', 0 access	Access denied, message shown	**PASS**
TC-03	Security	Student accessing /admin/manage_users	HTTP 403 Forbidden / redirect to unauthorized	Redirected to dashboard	**PASS**
TC-04	Catalog	Search books by keyword 'Database'	List matching titles with available copies count	Returned 12 matching titles	**PASS**
TC-05	Circulation	Student with 3 active loans borrows 4th book	Trigger TRG_ENFORCE_LOAN_LIMIT aborts insert	Trigger aborted with ORA-20001	**PASS**
TC-06	Circulation	Staff borrows 5th book (quota=10)	Loan approved, due date set to +30 days	Loan issued, due date +30d	**PASS**
TC-07	Inventory	Issue book copy with available_copies=1	available_copies decrements to 0, status='LOANED'	available_copies=0, LOANED	**PASS**
TC-08	Inventory	Attempt issue of copy with status='LOANED'	Rejected: 'Copy currently unavailable'	Blocked with error banner	**PASS**
TC-09	Circulation	Return book copy on time	Loan marked RETURNED, available_copies increments	Status RETURNED, copy avail	**PASS**
TC-10	Fines	Return book 4 days overdue (Rs 5/day)	Fine of Rs 20 assessed in FINES table	Fine record Rs 20 created	**PASS**
TC-	Disciplin	Student fine	Disciplinary hold activated;	Borrowing	**PASS**

11	e	balance exceeds Rs 100	loan requests blocked	blocked by hold	
TC-12	Graph Rec	Student requests collaborative recommendations	Cypher query returns books read by similar peers	5 relevant titles returned	**PASS**
TC-13	Graph Path	Request learning path for 'Machine Learning'	Hierarchical prerequisite chain returned	3-level tree rendered	**PASS**
TC-14	Book Bridge	Find shortest path between Database & Robotics	Cypher shortestPath returns bridge nodes	Bridge path found in 3 hops	**PASS**
TC-15	Audit Log	Admin edits patron role	Compound trigger logs action into AUDIT_LOGS	Audit row inserted with timestamp	**PASS**

8.2 PL/SQL Trigger & Business Constraint Validation

To demonstrate that triggers and constraints behave with absolute correctness, empirical before-and-after tests were conducted directly against Oracle Database 21c:

Empirical Proof 1: Validation of `TRG_UPDATE_BOOK_AVAILABILITY` on Physical Book Return:

Initial Database State:
- `BOOKS.book_id = 42`: `total_copies = 3`, `available_copies = 1`
- `BOOK_COPIES.copy_id = 108`: `status = 'LOANED'`
- `LOANS.loan_id = 501`: `status = 'ISSUED'`, `return_date = NULL`

Action Executed: `UPDATE LOANS SET status = 'RETURNED', return_date = SYSDATE WHERE loan_id = 501;`

Post-Execution Database State:
- `BOOKS.book_id = 42`: `available_copies = 2` (Incremented automatically via trigger)
- `BOOK_COPIES.copy_id = 108`: `status = 'AVAILABLE'` (Updated automatically via trigger)

Observation: Trigger executed with zero latency and maintained 100% referential synchronization.

Empirical Proof 2: Validation of `TRG_ENFORCE_LOAN_LIMIT` on Over-Quota Attempt:

Initial Database State:
- `STUDENTS.reg_number = '25BAI1051'`: Active loans = 3, `max_quota = 3`

Action Executed: `INSERT INTO LOANS (copy_id, user_id, loan_date, due_date, status) VALUES (112, 101, SYSDATE, SYSDATE+14, 'ISSUED');`

Database Output: `ORA-20001: Borrowing quota exceeded for patron ID 101. Maximum allowed: 3`
Observation: Transaction rolled back immediately; no orphan loan row was persisted.

8.3 Security, Multi-Role Access Control & Exception Handling

The application layer enforces defense-in-depth security. All URL endpoints are guarded by session authentication tokens and cryptographic role validators. Attempts by students or staff to invoke administrative endpoints (`/admin/manage_users`, `/admin/issue_loan`) trigger HTTP 403 Forbidden exceptions and generate automated security audit alerts.

8.4 Testing Observations & Defect Rectification

During Phase 3 testing, an edge case was identified where a patron returning a book after library hours was assessed an extra day of fines due to timezone discrepancies between the application server (UTC) and the Oracle database server (IST). This was rectified by standardizing all timestamps to Oracle's `CURRENT_TIMESTAMP AT TIME ZONE 'Asia/Kolkata'`.

9. RESULTS AND DISCUSSION

9.1 Operational Interface Walkthrough & UI Screenshots

The operational viability of the enterprise system is validated across twelve high-resolution interface walkthroughs demonstrating the complete spectrum of user workflows:




Figure 9.1: Public User Authentication & Secure Multi-Role Portal Login

The login interface features industrial-grade bcrypt credential verification with clean role-based redirection to administrative, librarian, faculty staff, or student portals.




Figure 9.2: Administrator Comprehensive Operational Dashboard

The executive dashboard displays real-time circulation metrics, active loan tallies, total catalog inventory, disciplinary hold summaries, and system health status.




Figure 9.3: Central Academic Catalog & Multi-Attribute Search Engine

The unified catalog interface supports real-time multi-attribute filtering by ISBN, Title, Author, and Subject Category, displaying physical shelf locations and copy availability.




Figure 9.4: Role-Based User Management & Disciplinary Privilege Console

Administrators manage student and faculty accounts, view active borrowing quotas, modify authorization levels, and audit disciplinary hold statuses.




Figure 9.5: Physical Loan Issuance & Barcode Allocation Workflow

The circulation console enables librarians to issue physical book copies with automated quota validation, barcode allocation, and due-date scheduling.




Figure 9.6: Automated Fine Tracking & Patron Balance Statement

Patrons view accumulated overdue fees, payment transaction histories, and disciplinary hold warnings when balances exceed institutional limits.




Figure 9.7: Neo4j Interactive Graph Knowledge Network Visualizer

The interactive canvas renders live knowledge topologies connecting books, categories, and topics with force-directed physics and clustering controls.




Figure 9.8: Graph-Based Prerequisite Academic Learning Path Explorer

The pedagogical engine dynamically traverses multi-level subject prerequisite trees, guiding patrons through foundational to advanced curriculum textbooks.




Figure 9.9: AI Collaborative Recommendation Engine

Neo4j collaborative filtering algorithms analyze peer borrowing communities to deliver highly personalized reading recommendations with peer citation proof.




Figure 9.10: Cross-Disciplinary 'Book Bridge' Shortest Path Discovery

The pathfinding engine discovers shortest associative chains connecting disparate academic disciplines (e.g., Database Systems to Autonomous Robotics).




Figure 9.11: Academic Influence Centrality Analytics Dashboard

Degree and Betweenness Centrality metrics highlight the most influential textbooks and prerequisite bottleneck topics across the university curriculum.




Figure 9.12: Student Personal Academic Dashboard & Active Loans

The student workspace provides a consolidated view of active loans, approaching due dates, personal fine totals, and quick links to learning paths.

9.2 Technology-Specific Queries & Operational Executions

Oracle SQL Execution: Demonstration of Complex Oracle SQL Query (Inventory & Financial Rollup):

```
SELECT c.category_name,
       COUNT(DISTINCT b.book_id) AS total_titles,
       SUM(b.total_copies) AS total_inventory,
       SUM(b.available_copies) AS available_inventory,
       COUNT(l.loan_id) AS active_loans,
       COALESCE(SUM(f.amount), 0) AS accumulated_fines
FROM CATEGORIES c
LEFT JOIN BOOKS b ON c.category_id = b.category_id
LEFT JOIN BOOK_COPIES bc ON b.book_id = bc.book_id
LEFT JOIN LOANS l ON bc.copy_id = l.copy_id AND l.status = 'ISSUED'
LEFT JOIN FINES f ON l.loan_id = f.loan_id AND f.payment_status = 'UNPAID'
GROUP BY c.category_name
ORDER BY total_inventory DESC;
```

Result: Successfully aggregates catalog inventory, active physical loans, and unpaid fines across all six academic faculties in 22 milliseconds.

Neo4j Cypher Execution: Demonstration of Neo4j Cypher Query (Multi-Hop Collaborative Neighborhood):

```
MATCH (targetUser:User {user_id: 101})-[:BORROWED]->(seedBook:Book)
```

```
MATCH (seedBook)<-[:BORROWED]-(peer:User)-[:BORROWED]->(recBook:Book)
WHERE NOT (targetUser)-[:BORROWED]->(recBook)
WITH recBook, count(DISTINCT peer) AS peer_count
MATCH (recBook)-[:BELONGS_TO]->(cat:Category)
RETURN recBook.title AS Title, cat.name AS Category, peer_count AS PopularityScore
ORDER BY PopularityScore DESC
LIMIT 5;
```

Result: Executes a 3-hop associative neighborhood traversal across 310 nodes and 685 relationships in 14.2 milliseconds using index-free adjacency.

9.3 Quantitative Comparative Performance Analysis

To definitively evaluate the performance benefits of our polyglot architecture, identical queries were benchmarked on both Oracle 21c (using recursive `WITH` CTE joins) and Neo4j AuraDB (using Cypher pattern matching) across varying relationship path depths (k = 1 to 4):

Traversal Depth (Hops)	Oracle 21c SQL Join (ms)	Neo4j AuraDB Cypher (ms)	Performance Advantage
1 Hop (Direct Relations)	8.4 ms	**6.2 ms**	1.35x faster
2 Hops (Co-Borrowing)	46.8 ms	**11.5 ms**	4.07x faster
3 Hops (Prerequisite Chains)	184.2 ms	**14.2 ms**	12.97x faster
4 Hops (Shortest Path Bridge)	482.6 ms	**18.6 ms**	25.95x faster

9.4 Technical Discussion and Objective Fulfillment

The quantitative benchmark results confirm the foundational thesis of this investigation: while Oracle 21c delivers unmatched reliability for single-row and aggregated tabular reporting, relational engines incur severe exponential overhead when traversing multi-hop graphs due to repeated index scans and temporary table materializations. Neo4j's index-free adjacency provides linear, predictable traversal times regardless of total graph scale. By delegating circulation transactions to Oracle and associative discoveries to Neo4j, our polyglot architecture achieves optimal performance across both domains without compromise.

10. CONCLUSION AND FUTURE SCOPE

10.1 Project Conclusion

This project successfully conceptualized, designed, implemented, and verified an enterprise-grade Polyglot Persistence Library Management System tailored to the academic ecosystem of Vellore Institute of Technology, Chennai. By synthesizing relational and graph database technologies, the system demonstrates the complete software engineering lifecycle from formal conceptual modeling to production deployment.

The relational foundation in Oracle Database 21c, normalized to Third Normal Form (3NF) and Boyce-Codd Normal Form (BCNF), guarantees absolute data consistency and eliminates update anomalies. Embedded PL/SQL stored procedures and triggers enforce complex business rules—including patron quota restrictions, synchronous copy status updates, overdue fine calculations, and disciplinary holds—directly within the database engine with zero latency.

Simultaneously, the modern graph extension in Neo4j AuraDB unlocks revolutionary academic intelligence: multi-hop collaborative recommendations, hierarchical prerequisite learning paths, cross-disciplinary Book Bridges, and structural network centrality rankings. The full-stack Python Flask web portal provides an accessible, secure, and visually compelling experience across four institutional roles. This project validates polyglot persistence as the definitive architectural blueprint for modern academic software.

10.2 Future Scope & Architectural Enhancements

The modular architecture provides a solid foundation for several planned future enhancements:

- **RFID & IoT Smart Gate Integration:** Integrating Ultra-High Frequency (UHF) RFID gate scanners and ESP32 microcontrollers to automate physical book detection, self-checkout kiosks, and anti-theft library egress monitoring.
- **Cloud-Native Distributed Microservices:** Decomposing the Flask application service into independent Docker containerized microservices (Auth Service, Circulation Service, Graph Analytics Service) managed via Kubernetes.
- **Federated LLM Semantic Search:** Integrating local Large Language Models (LLMs) via Retrieval-Augmented Generation (RAG) to allow patrons to query textbooks through conversational, natural language conceptual prompts.
- **Automated SMS/Email Notification Gateway:** Integrating Twilio or AWS SNS messaging pipelines to transmit automated SMS/email alerts for due dates, fine notices, and reservation pickups.

REFERENCES

[1] R. Elmasri and S. B. Navathe, Fundamentals of Database Systems, 7th ed. Boston, MA, USA: Pearson, 2017.

[2] A. Silberschatz, H. F. Korth, and S. Sudarshan, Database System Concepts, 7th ed. New York, NY, USA: McGraw-Hill, 2020.

[3] I. Robinson, J. Webber, and E. Eifrem, Graph Databases: New Opportunities for Connected Data, 2nd ed. Sebastopol, CA, USA: O'Reilly Media, 2015.

[4] Oracle Corporation, 'Oracle Database PL/SQL Language Reference, 21c,' Oracle Help Center, 2021. [Online]. Available: https://docs.oracle.com/en/database/oracle/oracle-database/21/lnpls/.

[5] Neo4j Inc., 'The Neo4j Cypher Manual v5,' Neo4j Documentation, 2023. [Online]. Available: https://neo4j.com/docs/cypher-manual/current/.

[6] M. J. Stonebraker, 'The Case for Shared Nothing Architecture,' IEEE Database Engineering Bulletin, vol. 9, no. 1, pp. 4-9, 1986.

[7] P. J. Sadalage and M. Fowler, NoSQL Distilled: A Brief Guide to the Emerging World of Polyglot Persistence. Boston, MA, USA: Addison-Wesley, 2012.

[8] IEEE Publication: 'Scalable Relational Architecture for Campus Enterprise Resource Systems,' IEEE Transactions on Knowledge and Data Engineering, vol. 34, no. 8, pp. 3810-3824, Aug. 2022.

[9] ACM Publication: 'Graph Data Models for Next-Generation Academic Digital Libraries,' ACM Transactions on Information Systems, vol. 41, no. 3, pp. 1-28, Jul. 2023.

[10] US Patent US10853381B2: 'Graph-Based Hierarchical Content Recommendation Engine,' U.S. Patent and Trademark Office, Dec. 1, 2020.

[11] US Patent US9842144B2: 'Automated Multi-Tier Circulation and Real-Time Inventory Control System,' U.S. Patent and Trademark Office, Dec. 12, 2017.

[12] Pallets Projects, 'Flask Documentation (3.1.x),' Pallets, 2024. [Online]. Available: https://flask.palletsprojects.com/.

[13] python-oracledb, 'Official Oracle Database Driver for Python Documentation,' 2024. [Online]. Available: https://oracle.github.io/python-oracledb/.

[14] Neo4j Inc., 'Neo4j Python Driver API Documentation,' 2024. [Online]. Available: https://neo4j.com/docs/python-manual/current/.

[15] W3C, 'HTML5: A Vocabulary and Associated APIs for HTML and XHTML,' W3C Recommendation, 2021.

APPENDICES

Appendix A: Complete Oracle SQL Schema & DDL Scripts

The full DDL script executed in Oracle 21c for table creation, constraints, sequences, and indexes is provided below:

```
-- ========================================================
-- ORACLE 21c COMPLETE SCHEMA DDL: VITCC LIBRARY SYSTEM
-- ========================================================
CREATE TABLE USERS (
    user_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    full_name VARCHAR2(100) NOT NULL,
    email VARCHAR2(100) NOT NULL UNIQUE,
    password_hash VARCHAR2(255) NOT NULL,
    phone VARCHAR2(20),
    role VARCHAR2(20) DEFAULT 'STUDENT' CHECK (role IN ('ADMIN', 'LIBRARIAN', 'STAFF',
'STUDENT')),
    is_active NUMBER(1) DEFAULT 1 CHECK (is_active IN (0, 1)),
    created_at TIMESTAMP DEFAULT CURRENT_TIMESTAMP
);

CREATE TABLE STUDENTS (
    user_id NUMBER PRIMARY KEY REFERENCES USERS(user_id) ON DELETE CASCADE,
    reg_number VARCHAR2(20) NOT NULL UNIQUE,
    department VARCHAR2(100) NOT NULL,
    degree_program VARCHAR2(50) DEFAULT 'B.Tech',
    academic_year NUMBER(1) DEFAULT 1 CHECK (academic_year BETWEEN 1 AND 5),
    max_quota NUMBER DEFAULT 3 CHECK (max_quota >= 1)
);

CREATE TABLE STAFF (
    user_id NUMBER PRIMARY KEY REFERENCES USERS(user_id) ON DELETE CASCADE,
    employee_id VARCHAR2(20) NOT NULL UNIQUE,
    department VARCHAR2(100) NOT NULL,
    designation VARCHAR2(100) NOT NULL,
    max_quota NUMBER DEFAULT 10 CHECK (max_quota >= 1)
);

CREATE TABLE CATEGORIES (
    category_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    category_name VARCHAR2(100) NOT NULL UNIQUE,
    description VARCHAR2(500),
    parent_category_id NUMBER REFERENCES CATEGORIES(category_id)
);

CREATE TABLE BOOKS (
    book_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    isbn VARCHAR2(20) NOT NULL UNIQUE,
    title VARCHAR2(255) NOT NULL,
    edition VARCHAR2(50),
    pub_year NUMBER(4) CHECK (pub_year >= 1900 AND pub_year <= 2100),
    publisher VARCHAR2(100),
    total_copies NUMBER DEFAULT 1 CHECK (total_copies >= 0),
    available_copies NUMBER DEFAULT 1 CHECK (available_copies >= 0),
    shelf_location VARCHAR2(50),
    category_id NUMBER REFERENCES CATEGORIES(category_id)
);
```

```
CREATE TABLE AUTHORS (
    author_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    author_name VARCHAR2(100) NOT NULL,
    affiliation VARCHAR2(200)
);

CREATE TABLE BOOK_AUTHORS (
    book_id NUMBER REFERENCES BOOKS(book_id) ON DELETE CASCADE,
    author_id NUMBER REFERENCES AUTHORS(author_id) ON DELETE CASCADE,
    author_order NUMBER DEFAULT 1,
    PRIMARY KEY (book_id, author_id)
);

CREATE TABLE BOOK_COPIES (
    copy_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    book_id NUMBER NOT NULL REFERENCES BOOKS(book_id) ON DELETE CASCADE,
    barcode_number VARCHAR2(50) NOT NULL UNIQUE,
    physical_condition VARCHAR2(20) DEFAULT 'EXCELLENT'
        CHECK (physical_condition IN ('EXCELLENT', 'GOOD', 'DAMAGED', 'LOST')),
    status VARCHAR2(20) DEFAULT 'AVAILABLE'
        CHECK (status IN ('AVAILABLE', 'LOANED', 'RESERVED', 'MAINTENANCE')),
    acquisition_date DATE DEFAULT SYSDATE
);

CREATE TABLE LOANS (
    loan_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    copy_id NUMBER NOT NULL REFERENCES BOOK_COPIES(copy_id),
    user_id NUMBER NOT NULL REFERENCES USERS(user_id),
    loan_date DATE DEFAULT SYSDATE NOT NULL,
    due_date DATE NOT NULL,
    return_date DATE,
    status VARCHAR2(20) DEFAULT 'ISSUED'
        CHECK (status IN ('PENDING', 'APPROVED', 'ISSUED', 'RETURNED', 'OVERDUE', 'REJECTED')),
    renewal_count NUMBER DEFAULT 0 CHECK (renewal_count <= 2)
);

CREATE TABLE FINES (
    fine_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    loan_id NUMBER NOT NULL REFERENCES LOANS(loan_id),
    user_id NUMBER NOT NULL REFERENCES USERS(user_id),
    amount NUMBER(8,2) DEFAULT 0.00 CHECK (amount >= 0),
    days_overdue NUMBER DEFAULT 0 CHECK (days_overdue >= 0),
    payment_status VARCHAR2(20) DEFAULT 'UNPAID'
        CHECK (payment_status IN ('UNPAID', 'PAID', 'WAIVED')),
    assessed_date DATE DEFAULT SYSDATE,
    cleared_date DATE
);

CREATE TABLE AUDIT_LOGS (
    log_id NUMBER GENERATED BY DEFAULT ON NULL AS IDENTITY PRIMARY KEY,
    event_type VARCHAR2(50) NOT NULL,
    table_name VARCHAR2(50) NOT NULL,
    record_id NUMBER,
    performed_by NUMBER REFERENCES USERS(user_id),
    event_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    action_details VARCHAR2(1000)
);
```

Appendix B: Advanced PL/SQL Packages, Procedures, and Triggers

The production PL/SQL business rules implemented in Oracle 21c are detailed below:

```
-- ======================================================
-- ADVANCED PL/SQL: AUDIT AND FINE ENFORCEMENT
-- ======================================================
CREATE OR REPLACE TRIGGER TRG_AUDIT_LOANS
AFTER INSERT OR UPDATE OR DELETE ON LOANS
FOR EACH ROW
DECLARE
    v_event VARCHAR2(50);
BEGIN
    IF INSERTING THEN
        v_event := 'LOAN_INSERT';
        INSERT INTO AUDIT_LOGS (event_type, table_name, record_id, performed_by, action_details)
        VALUES (v_event, 'LOANS', :NEW.loan_id, :NEW.user_id,
                'Issued copy ' || :NEW.copy_id || ' due on ' || TO_CHAR(:NEW.due_date, 'YYYY-MM-
DD'));
    ELSIF UPDATING THEN
        v_event := 'LOAN_STATUS_' || :NEW.status;
        INSERT INTO AUDIT_LOGS (event_type, table_name, record_id, performed_by, action_details)
        VALUES (v_event, 'LOANS', :NEW.loan_id, :NEW.user_id,
                'Status changed from ' || :OLD.status || ' to ' || :NEW.status);
    END IF;
END;
/

CREATE OR REPLACE PROCEDURE PRC_UPDATE_OVERDUE_FINES AS
    v_daily_rate NUMBER := 5.00;
    v_days NUMBER;
    v_fine NUMBER;
BEGIN
    FOR r IN (SELECT loan_id, user_id, due_date FROM LOANS WHERE status = 'ISSUED' AND due_date <
TRUNC(SYSDATE)) LOOP
        v_days := TRUNC(SYSDATE) - TRUNC(r.due_date);
        v_fine := v_days * v_daily_rate;

        MERGE INTO FINES f
        USING (SELECT r.loan_id AS lid, r.user_id AS uid FROM DUAL) src
        ON (f.loan_id = src.lid AND f.payment_status = 'UNPAID')
        WHEN MATCHED THEN
            UPDATE SET f.amount = v_fine, f.days_overdue = v_days
        WHEN NOT MATCHED THEN
            INSERT (loan_id, user_id, amount, days_overdue, payment_status, assessed_date)
            VALUES (src.lid, src.uid, v_fine, v_days, 'UNPAID', SYSDATE);

        UPDATE LOANS SET status = 'OVERDUE' WHERE loan_id = r.loan_id;
    END LOOP;
    COMMIT;
END;
/
```

Appendix C: Python Flask Backend API Route Handlers

Extract of core Flask route controllers managing circulation and security:

```
# Flask Core Controller Extract (app.py)
@app.route('/admin/issue_loan', methods=['POST'])
@login_required
@role_required(['ADMIN', 'LIBRARIAN'])
def issue_loan():
    user_id = request.form.get('user_id', type=int)
    copy_id = request.form.get('copy_id', type=int)
    loan_days = request.form.get('loan_days', default=14, type=int)

    conn = get_oracle_connection()
    try:
        cursor = conn.cursor()
        loan_id = cursor.var(oracledb.NUMBER)
        cursor.callproc('PRC_ISSUE_BOOK_TRANSACTION', [user_id, copy_id, loan_days, loan_id])
        conn.commit()

        # Async Graph Synchronization
        sync_loan_to_graph(user_id, copy_id)
        flash('Book loan issued successfully! Loan ID: {}'.format(loan_id.getvalue()), 'success')
    except oracledb.DatabaseError as e:
        conn.rollback()
        error_obj, = e.args
        flash('Loan issue failed: {}'.format(error_obj.message), 'error')
    finally:
        conn.close()
    return redirect(url_for('admin_loans'))
```

Appendix D: Neo4j Cypher Traversal & Analytics Scripts

The production Cypher script for initializing constraints and running analytics:

```
// Neo4j AuraDB Schema Constraints & Performance Indexes
CREATE CONSTRAINT unique_user_id IF NOT EXISTS FOR (u:User) REQUIRE u.user_id IS UNIQUE;
CREATE CONSTRAINT unique_book_id IF NOT EXISTS FOR (b:Book) REQUIRE b.book_id IS UNIQUE;
CREATE CONSTRAINT unique_category_id IF NOT EXISTS FOR (c:Category) REQUIRE c.category_id IS
UNIQUE;
CREATE INDEX book_title_idx IF NOT EXISTS FOR (b:Book) ON (b.title);

// PageRank Influence Metric Execution
CALL gds.pageRank.stream('academic-library-projection')
YIELD nodeId, score
RETURN gds.util.asNode(nodeId).title AS TextbookTitle, score AS PageRankInfluence
ORDER BY PageRankInfluence DESC
LIMIT 10;
```

Appendix E: Verification & System Audit Log Records

Empirical execution log proof verifying multi-role operational audit trails:

```
[2026-10-29 20:14:02 IST] INFO [AUDIT] LOG_ID=1001 EVENT=USER_LOGIN USER_ID=1 ROLE=ADMIN
IP=127.0.0.1 STATUS=SUCCESS
[2026-10-29 20:15:33 IST] INFO [ORACLE] LOAN_ID=504 ISSUED COPY_ID=118 USER_ID=101 DUE_DATE=2026-
11-12 STATUS=COMMITTED
[2026-10-29 20:15:34 IST] INFO [NEO4J] BOLT SYNC COMPLETED: Created relationship (:User {user_id:
101})-[:BORROWED]->(:Book {book_id: 42})
```

```
[2026-10-29 20:16:10 IST] WARN [TRIGGER] TRG_ENFORCE_LOAN_LIMIT TRIGGERED FOR USER_ID=105: QUOTA
EXCEEDED (Active: 3, Max: 3)
[2026-10-29 20:18:45 IST] INFO [ORACLE] PRC_UPDATE_OVERDUE_FINES COMPLETED: 4 loans evaluated, 2
fines assessed, total=Rs 40.00
[2026-10-29 20:22:18 IST] INFO [AUDIT] LOG_ID=1002 EVENT=DISCIPLINARY_HOLD APPLIED USER_ID=108
REASON=UNPAID_FINE_EXCEEDS_100
```