Exp No: 11 Date:

# HADOOP IMPLEMENT THE MAX TEMPERATURE MAPREDUCE PROGRAM TO IDENTIFY THE YEAR WISE MAXIMUM TEMPERATURE FROM SENSORDATA

## <u>AIM</u>

To implement the Max temperature MapReduce program to identify the year-wise maximum temperature from the sensor data.

# Description

Sensors senses weather data in big text format containing station ID, year, date, time, temperature, quality etc. from each sensor and store it in a single line. Suppose thousands of data sensors are there, then we have thousands of records with no particular order. We require only a year and maximum temperature of particular quality in that year.

# For example:

Input string from sensor:

0029029070999991902010720004+64333+023450

FM-12+

000599999V0202501N02781999999N0000001N9-00331+

99999098351ADDGF10299199999999999999999

Here: 1902 is year 0033 is temperature

1 is measurement quality (Range between 0 or 1 or 4 or 5 or 9)

Here each mapper takes the input key as "byte offset of line" and value as "one weather sensor read i.e one line". and parse each line and produce an intermediate key "year" and intermediate value as "temperature of certain measurement qualities" for that year.

The combiner will form set values of temperature. Year and set of values of temperatures is given as input <key, value> to reducer and Reducer will produce year and maximum temperature for that year from the set of temperature values.

#### **PROGRAM**

```
*/
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Job;
import org.apache.hadoop.mapreduce.lib.input.FileInputFormat;
import org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
importorg.apache.hadoop.io.Text;
import org.apache.hadoop.mapreduce.Mapper;
importorg.apache.hadoop.mapreduce.Reducer;
//Mapper class
class MaxTemperatureMapper
extends Mapper<LongWritable, Text, Text, IntWritable> { private static final int MISSING
= 9999:
@Override
public void map(LongWritable key, Text value, Context context) throws IOException,
InterruptedException {
String line = value.toString(); String year = line.substring(15, 19); int airTemperature;
if (line.charAt(87) == '+') { // parseInt doesn't like leading plus signs airTemperature =
Integer.parseInt(line.substring(88, 92));
} else {
airTemperature = Integer.parseInt(line.substring(87, 92));
String quality = line.substring(92, 93);
if (airTemperature != MISSING && quality.matches("[01459]")) { context.write(new
Text(year), new IntWritable(airTemperature));
//Reducer class
class MaxTemperatureReducer
extends Reducer<Text, IntWritable, Text, IntWritable> {
@Override
```

```
public void reduce(Text key, Iterable<IntWritable> values, Context context)
throws IOException, InterruptedException {
int maxValue = Integer.MIN VALUE; for (IntWritable value : values)
{ maxValue = Math.max(maxValue, value.get());
context.write(key, new IntWritable(maxValue));
//Driver Class
public class MaxTemperature {
public static void main(String[] args) throws Exception { if (args.length != 2)
{ System.err.println("Usage: MaxTemperature <input path=""> <output path>"); System.exit(-
1);
Job job = Job.getInstance(new Configuration()); job.setJarByClass(MaxTemperature.class);
job.setJobName("Max temperature");
FileInputFormat.addInputPath(job, new Path(args[0])); FileOutputFormat.setOutputPath(job,
new Path(args[1]));
job.setMapperClass(MaxTemperatureMapper.class);
job.setReducerClass(MaxTemperatureReducer.class);
job.setOutputKeyClass(Text.class); job.setOutputValueClass(IntWritable.class);
job.submit();
```

### **OUTPUT:**

Input for String:

002902907099999<u>1</u>902010720004+64333+023450FM-12+ 000599999V0202501N02781999999N0000001N9-00331+ 

```
File Actions Edit View Help
     (hadoop⊕kali)-[~]
start-all.sh
L=Start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting maemodes on [localhost]
Starting datagade.
```

```
·(hadoop⊗kali)-[~/hadoop/bin]
-rw-r--r-- 1 hadoop supergroup 79205 2024-08-29 10:50 /exp3/dataset.txt drwxr-xr-x - hadoop supergroup 0 2024-08-29 10:52 /exp3/new_output drwxr-xr-x - hadoop supergroup 0 2024-09-13 01:00 /exp3/output
Found 3 items
```



## **RESULT**

Thus a java program has been implemented to identify the year-wise maximum temperature from the sensor data.