

**EXP NO: 8     IMPLEMENT SVM/DECISION TREE CLASSIFICATION TECHNIQUES****a) SVM**

```

# Install and load the e1071 package (if not already installed)
install.packages("e1071")
library(e1071)
# Load the iris dataset
data(iris)
# Inspect the first few rows of the dataset
head(iris)
# Split the data into training (70%) and testing (30%) sets
set.seed(123) # For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
train_data <- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]
# Fit the SVM model
svm_model <- svm(Species ~ ., data = train_data, kernel = "radial")
# Print the summary of the model
summary(svm_model)
# Predict the test set
predictions <- predict(svm_model, newdata = test_data)
# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)
# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
cat("Accuracy:", accuracy * 100, "%\n")

```

**OUTPUT:**

The screenshot shows the RGui interface with the R Console and R Editor. The R Console displays the output of the code, including the number of classes, levels, confusion matrix, and accuracy. The R Editor shows the code being executed.

```

( 7 18 20 )

Number of Classes: 3

Levels:
setosa versicolor virginica

> # Predict the test set
> predictions <- predict(svm_model, newdata = test_data)
> # Evaluate the model's performance
> confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
> print(confusion_matrix)
      Actual
Predicted setosa versicolor virginica
setosa      14         0         0
versicolor  0         17         0
virginica   0          1        13

> # Calculate accuracy
> accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
> cat("Accuracy:", accuracy * 100, "%\n")
Accuracy: 97.77778 %
>

```

**b) DECISION TREE**

```

# Install and load the rpart package (if not already installed)
install.packages("rpart")
library(rpart)
# Load the iris dataset
data(iris)
# Split the data into training (70%) and testing (30%) sets
set.seed(123) # For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
train_data <- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]
# Fit the Decision Tree model
tree_model <- rpart(Species ~ ., data = train_data, method = "class")
# Print the summary of the model
summary(tree_model)
# Plot the Decision Tree
plot(tree_model)
text(tree_model, pretty = 0)
# Predict the test set
predictions <- predict(tree_model, newdata = test_data, type = "class")
# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)
# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
cat("Accuracy:", accuracy * 100, "%\n")

```

**OUTPUT:**