

# Rajalakshmi Engineering College

Name: Karthick Raja R  
Email: 240801147@rajalakshmi.edu.in  
Roll no: 2116240801147  
Phone: 6380349066  
Branch: REC  
Department: I ECE FB  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are tasked with implementing basic operations on a queue data structure using a linked list.

You need to write a program that performs the following operations on a queue:

Enqueue Operation: Implement a function that inserts an integer element at the rear end of the queue. Print Front and Rear: Implement a function that prints the front and rear elements of the queue. Dequeue Operation: Implement a function that removes the front element from the queue.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements to be inserted into the queue.

The second line consists of N space-separated integers, representing the queue elements.

### **Output Format**

The first line prints "Front: X, Rear: Y" where X is the front and Y is the rear elements of the queue.

The second line prints the message indicating that the dequeue operation (front element removed) is performed: "Performing Dequeue Operation:".

The last line prints "Front: M, Rear: N" where M is the front and N is the rear elements after the dequeue operation.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

12 56 87 23 45

Output: Front: 12, Rear: 45

Performing Dequeue Operation:

Front: 56, Rear: 45

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
};
```

```
struct Node* front = NULL;
struct Node* rear = NULL;
```

```
// You are using GCC
```

```
void enqueue(int d) {
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));
    if(newnode==NULL){
```

```

        printf("Queue is full\n");
        return;
    }
    newnode->data=d;
    newnode->next=NULL;
    if(rear==NULL){
        front=rear=newnode;
        return;
    }
    rear->next=newnode;
    rear=newnode;
}

void printFrontRear() {
    if(front==NULL){
        printf("Front: -1,Rear: -1\n");
        return;
    }
    printf("Front: %d, Rear: %d\n",front->data,rear->data);
}

void dequeue() {
    if(front==NULL){
        printf("Queue is empty\n");
        return;
    }
    struct Node* temp=front;
    front=front->next;
    if(front==NULL){
        rear=NULL;
    }
    free(temp);
}

int main() {
    int n, data;
    scanf("%d", &n);
    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        enqueue(data);
    }
    printFrontRear();
}

```

```
printf("Performing Dequeue Operation:\n");  
dequeue();  
printFrontRear();  
return 0;  
}
```

**Status :** Correct

**Marks : 10/10**