

Rajalakshmi Engineering College

Name: Karthick Raja R
Email: 240801147@rajalakshmi.edu.in
Roll no: 2116240801147
Phone: 6380349066
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string k, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next n - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next n lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {
    strcpy(dict->pairs[dict->size].key, key);
    strcpy(dict->pairs[dict->size].value, value);
    dict->size++;
}

void removeKeyValuePair(Dictionary *dict, const char *key) {
```

```

        for(int i=0;i<dict->size;i++){
            if(strcmp(dict->pairs[i].key,key)==0){
                for(int j=i;j<dict->size-1;j++){
                    strcpy(dict->pairs[i].key,dict->pairs[j+1].key);
                    strcpy(dict->pairs[j].value,dict->pairs[j+1].value);
                }
                dict->size--;
                return;
            }
        }
    }
}

int doesKeyExist(Dictionary *dict, const char *key) {
    for(int i=0;i<dict->size;i++){
        if(strcmp(dict->pairs[i].key,key)==0)
            return 1;
        return 0;
    }
}

void printDictionary(Dictionary *dict) {
    for(int i=0;i<dict->size;i++){
        printf("Key: %s; Value: %s\n",dict->pairs[i].key,dict->pairs[i].value);
    }
}

```

Status : Wrong

Marks : 0/10