

Ex. No.: 10

Date: 10/11/24

A PYTHON PROGRAM TO IMPLEMENT DIMENSIONALITY REDUCTION
USING PCA

Aim:

To implement Dimensionality Reduction using PCA in a python program.

Algorithm:

Step 1: Import Libraries

Import necessary libraries, including pandas, numpy, matplotlib.pyplot, and sklearn.decomposition.PCA.

Step 2: Load the Dataset (iris dataset)

Load your dataset into a pandas DataFrame.

Step 3: Standardize the Data

Standardize the features of the dataset using StandardScaler from sklearn.preprocessing.

Step 4: Apply PCA

- Create an instance of PCA with the desired number of components.
- Fit PCA to the standardized data.
- Transform the data to its principal components using transform.

Step 5: Explained Variance Ratio

- Calculate the explained variance ratio for each principal component.
- Plot a scree plot to visualize the explained variance ratio.

Step 6: Choose the Number of Components

Based on the scree plot, choose the number of principal components that explain a significant amount of variance.

Step 7: Apply PCA with Chosen Components

Apply PCA again with the chosen number of components.

Step 8: Visualize the Reduced Data

- Transform the original data to the reduced dimension using the fitted PCA.

- Visualize the reduced data using a scatter plot.

Step 9: Interpretation

Interpret the results, considering the trade-offs between dimensionality reduction and information loss.

PROGRAM:


```
from sklearn import datasets
import pandas as pd
from sklearn.preprocessing import StandardScaler
from sklearn.decomposition import PCA
import seaborn as sns

iris = datasets.load_iris()
df = pd.DataFrame(iris['data'], columns = iris['feature_names'])
df.head()
```

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)
0	5.1	3.5	1.4	0.2
1	4.9	3.0	1.4	0.2
2	4.7	3.2	1.3	0.2
3	4.6	3.1	1.5	0.2
4	5.0	3.6	1.4	0.2

```
scalar = StandardScaler()
scaled_data = pd.DataFrame(scalar.fit_transform(df)) #scaling the data
sns.heatmap(scaled_data.corr())
```


	0	1	2	3
0	-0.900681	1.019004	-1.340227	-1.315444
1	-1.143017	-0.131979	-1.340227	-1.315444
2	-1.385353	0.328414	-1.397064	-1.315444
3	-1.506521	0.098217	-1.283389	-1.315444
4	-1.021849	1.249201	-1.340227	-1.315444
...
145	1.038005	-0.131979	0.819596	1.448832
146	0.553333	-1.282963	0.705921	0.922303
147	0.795669	-0.131979	0.819596	1.053935
148	0.432165	0.788808	0.933271	1.448832
149	0.068662	-0.131979	0.762758	0.790671



```
pca = PCA(n_components = 3)
pca.fit(scaled_data)
data_pca = pca.transform(scaled_data)
data_pca = pd.DataFrame(data_pca, columns=['PC1', 'PC2', 'PC3'])
data_pca.head()
```

	PC1	PC2	PC3
0	-2.264703	0.480027	-0.127706
1	-2.080961	-0.674134	-0.234609
2	-2.364229	-0.341908	0.044201
3	-2.299384	-0.597395	0.091290
4	-2.389842	0.646835	0.015738

```
sns.heatmap(data_pca.corr())
```



RESULT:-

Thus Dimensionality Reduction has been implemented using PCA in a python program successfully and the results have been analyzed.