
36118 / APPLIED NATURAL LANGUAGE PROCESSING

SPRING 2026 · ASSESSMENT TASK 2, PART B

FormBridge

Evidence-linked dialogue state tracking for restaurant booking briefs

GROUP TECHNICAL REPORT



The conversation and the reviewed booking brief in the live application.

---

11 October 2026

Application https://formbridge-nlp-at2.vercel.app/

Source repository https://github.com/KarthikRamesh9149/NLP-AT2

Abstract

A restaurant enquiry rarely arrives as a finished form. A customer may change the number of guests, offer a time range or accept a staff suggestion several messages later. FormBridge turns this conversation into an editable booking brief while keeping unresolved details visible. The web application tracks restaurant, city, date, time and party size, links model-derived details to their source messages, records revisions and requires staff approval before handoff.

The project compares a rule-based extractor, direct contextual extraction and FormBridge's contextual extraction with evidence checks and state reconciliation. Evaluation uses a documented restaurant subset of Google's Schema-Guided Dialogue dataset. The final production configuration achieved 100/100 field checks on an inspected 20-dialogue regression sample and 96/100 on a repeatedly used 20-dialogue development selection. In a separate same-model comparison, direct extraction and FormBridge both achieved 92/100 canonical field checks on development data and 62/65 on 13 previously unselected test dialogues. FormBridge produced more consistent representations under the stricter matcher, but also used more tokens and longer replay times.

The application supports review and handoff of a booking brief; it does not reserve a table. Recorded browser checks cover 20 ordinary enquiries and 15 edge cases; native text and JSON downloads were verified. No recruited-user study was conducted. The results show that the application supports the tested workflow. Broader extraction accuracy and benefits for restaurant staff require further evaluation.

Contents

Section	Page
1. Problem, objectives and scope	3
2. Application features and user journey	4
3. System architecture and state design	5
4. NLP methods and technical choices	6–7
5. Data sources and preparation	8
6. Evaluation design and reproducibility	9
7. Results	10
8. Findings, errors and challenges	11
9. Interaction design and verification	12
10. Ethics, limitations and next steps	13
11. Project phases, contributions and conclusion	14
References	15
Appendices A–B: reproduction and supporting results	16–18

1. Problem, objectives and scope

1.1 The problem and intended users

Consider a customer who asks for four people at seven, then changes the request to five people sometime after eight. Copying the first message into a form gives the wrong brief. Copying the final message alone loses the restaurant, date and city. Choosing 8:30 pm would invent a decision the customer has not made. The task therefore needs both an understanding of language and a record of how the request develops.

FormBridge is intended for small restaurant service teams, particularly staff preparing or handing over enquiries. It places the conversation beside the current booking details so staff can check them together. The workflow was designed from restaurant enquiry scenarios; interviews and adoption testing were outside the project evaluation.

The application addresses dialogue state tracking: maintaining the current set of requested slot values as a conversation progresses. Earlier work such as TRADE models this as generating a dialogue state from utterances, including values outside a fixed ontology (Wu et al., 2019). The Schema-Guided Dialogue dataset provides a relevant task-oriented corpus with service schemas and state annotations (Rastogi et al., 2020). FormBridge builds on this problem formulation and public data, using hosted contextual extraction rather than retraining those research models.

1.2 Objectives and research question

The primary objective was to build a web application that gathers five booking details, tracks revisions and lets staff inspect the current request. The technical objectives were to compare rules with contextual extraction, check supporting evidence and dates, and retain the configuration and outputs needed to reproduce the experiments.

Research question: How does contextual extraction with evidence checking and state reconciliation compare with rules and direct contextual extraction when maintaining restaurant booking information, and what does that additional structure contribute to staff review?

The question separates value accuracy from interaction quality. A field can match a dataset label while still needing clarification before staff can approve it. Likewise, a visually complete form can be inaccurate. The system therefore measures automatic value agreement separately from the user-facing review workflow.

1.3 Scope and success conditions

Included	Boundary
Restaurant, city, date, time and guest count	One restaurant reservation enquiry per brief
Pasted transcripts and incremental messages	English-language text; up to 30 messages
Corrections, uncertainty, source links and history	Exact details stay unresolved when evidence is insufficient
Manual review, approval and downloads	Approval prepares information for staff
Public web application and local reproduction	No availability search, restaurant contact, payment or table reservation

Success means that staff can enter an enquiry, inspect the values and their sources, resolve uncertainty and export a reviewed brief. Evaluation covers these functions and automatic extraction within the stated scope. Effects on restaurant operations were not measured.

2. Application features and user journey

The application starts with an empty workspace. Examples are available through an explicit button, while the main route supports the user's own conversation. A transcript can be pasted with Customer: and Staff: labels, or entered one message at a time. Unlabelled short text is treated as a customer enquiry. Speaker labels matter because a staff offer is not automatically the customer's choice.




Figure 1. Live application captured on 11 October 2026. The example request is Juniper, Sydney, 18 October 2026, 8:30 pm and five guests. Source: original product capture using a fictional enquiry.

2.1 From enquiry to reviewed brief

1. **Gather:** Enter “A table for four at Juniper in Sydney on 18 October 2026 at 7 pm.”
2. **Revise:** Add “Actually, make that five guests, and sometime after 8 pm instead.” Five guests becomes the current value; the exact time remains open.
3. **Clarify:** The application suggests a question asking for the exact time. Staff can copy it and add the customer's reply.
4. **Check:** A staff offer of 8:30 pm becomes ready after the customer accepts. Selecting Time displays both source messages.
5. **Hand over:** Staff review or edit the details, approve the current revision and download text or JSON.

2.2 Features that support review

Each field shows a status: Needed, Ask customer, Ready or Reviewed. These combine text and icons, so colour is not the only signal. A source link opens the relevant messages; change history preserves earlier values. Manual edits are labelled as staff input and retained during subsequent analysis. If the conversation later conflicts with an edit, the interface asks staff to review that detail.

Approval requires five resolved, non-empty fields and no unfinished analysis. A semantic change clears prior approval. The approved state says that the brief is ready for handoff, while the interface explicitly states that no table has been reserved. Drafts survive refresh in the current browser tab, and New brief starts the next enquiry.

3. System architecture and state design

FormBridge uses Next.js 16.3.6, React 19.3.0 and TypeScript 5.9.3, with a Node.js server route on Vercel. OpenAI SDK 7.23.0 supplies contextual extraction, and Zod 4.6.5 defines request and output contracts. The dependency lockfile fixes the installed package versions for reproduction.




Figure 2. Implemented flow. The model predicts a candidate state; deterministic application code checks evidence and reconciles the brief. A validation-directed repair is limited to one additional model request.

3.1 Separation of responsibilities

The browser owns the transcript, current draft and review controls. POST /api/analyze validates the incoming request before calling the selected analysis method. In the live product, the interface selects FormBridge; rules and direct extraction are available in the technical evaluation runner rather than presented as extra staff-facing modes.

The model receives the ordered, visible conversation and an optional reference date. It returns a candidate for each of the five fields. Application code checks supporting quotations, admissible values, acceptance and recency before updating authoritative state. Clarification questions are generated from deterministic templates, making their relationship to the unresolved field inspectable.

This separation allows the interface, extraction provider and reconciliation code to be changed independently. It also gives tests a stable target: approval, cancellation, evidence checking and manual overrides can be checked without calling a paid model.

3.2 State and persistence

A field stores its value, status, constraint, evidence message IDs, source and explanatory note. A brief also stores revision history, its current revision and the revision that was approved. This distinguishes an unanswered field from a stated preference such as “after 8 pm”, and distinguishes an extracted detail from an intentional staff edit.

The draft uses browser session storage and can be downloaded as a local file. The application has no accounts or customer database, so it supports individual review sessions rather than shared inboxes, long-term case histories or cross-device collaboration. External model processing is discussed in Section 10.

The server imposes request-size and schema limits. Its local production rate limiter allows up to 60 requests per minute per observed address within one process. Because serverless instances do not share this map, it is a basic protection rather than a durable global quota. A shared limiter would be necessary for broader operational use.

4. NLP methods and technical choices

4.1 Three approaches to the same task

Method	Implementation	Reason for including it
Rules	Regular expressions, number-word conversion, explicit correction patterns and simple acceptance of the preceding staff offer	An interpretable, model-free baseline for explicit booking language
Direct contextual extraction	A structured five-field prediction from the complete visible prefix	Tests the benefit of contextual language understanding without FormBridge's evidence reconciliation
FormBridge	Contextual candidates with quotations and message IDs, followed by deterministic checks, bounded repair and revision-aware reconciliation	Tests a more inspectable state flow suitable for staff review

The rules recognise common party-size phrases, full calendar dates, explicit times, after-time constraints and named restaurants or cities in restricted patterns. They process messages in order and use a simple acceptance pattern to connect a customer reply with the preceding staff message. Its restricted vocabulary limits coverage of varied dialogue. It uses no learned parameters or API tokens.

The direct baseline reconstructs the five-field state at every customer turn. Its structured output contains value, status and constraint, but no evidence citations. Its prompt instructs the model to avoid invented values and unaccepted staff offers. Both contextual methods therefore target the same booking-state task.

FormBridge reconstructs candidate values from the same visible prefix. Previous browser state supplies staff overrides and history; supporting utterances determine whether a candidate is accepted. Corrections update the brief without changing model weights.

4.2 Why a hosted LLM and structured output?

Contextual extraction was selected because acceptance, correction and omitted context extend beyond a small set of regular expressions. A hosted model allowed the project to spend effort on state integrity, review controls and comparison, without assembling a new training corpus or serving a fine-tuned model. This choice brings network dependency, variable latency, external data processing and limited control over model weights.

The Responses API parses a Zod-derived output schema. OpenAI distinguishes schema adherence from factual correctness: structured output can still contain mistakes (OpenAI, n.d.-b). FormBridge therefore validates what a candidate is supported by, in addition to whether it is shaped correctly.

The deployed configuration uses GPT-6 Luna for extraction and at most one GPT-6.1 Sol repair, with low reasoning effort. The controlled comparison uses GPT-6 Luna for both approaches and repairs. Primary requests have a 12-second timeout; repairs have a 10-second timeout. SDK retries are disabled. Output budgets are 2,400 tokens for FormBridge and 900 for direct extraction. These model names are provider aliases, so a future rerun may use an updated model.

4.3 Scope of the model implementation

Retrieval-augmented generation was unnecessary for this task because all required evidence is in the conversation. Fine-tuning, multilingual support and booking integrations were outside scope. The implementation combines an existing language model with evidence checks, uncertainty handling and a staff review workflow.

4. NLP methods and technical choices, continued

4.4 Evidence checking and state reconciliation

For each candidate, the system verifies that cited message IDs exist, quotations occur within those messages and at least one cited message comes from the customer. A value must be supported by a customer statement or by a staff statement with a later customer acceptance. Dates composed across messages receive additional checks. These mechanisms make sources inspectable, but their pattern-based acceptance checks do not establish a perfect understanding of intent.

Check	Implemented behaviour
Quote integrity	Reject unknown IDs, duplicate citations, empty quotes and quotations absent from their source messages
Value admissibility	Enforce guest counts of 1–30 and bounded field lengths; check calendar dates and exact times
Temporal uncertainty	Preserve missing years, alternatives and ambiguous expressions; anchor today/tomorrow only when a valid reference date exists
Evidence recency	Prevent older customer evidence from reversing a later semantic correction
Explicit clearing	Give cancellation or removal precedence over repeated older predictions
Staff control	Retain manual values, flag conflicts and clear approval when review is needed

If validation finds a repairable inconsistency, the model receives targeted feedback and may return one revised candidate state. It does not receive dataset labels or benchmark answers. A failed repair produces a review warning; the first candidate remains subject to the same checks. If the initial request fails, the last valid brief is preserved and the unfinished update can be retried.




Figure 3. Time correction and acceptance in the live application. Left: “after 8 pm” leaves the exact time unresolved. Right: accepting 8:30 pm links the staff offer and customer reply. Source: original product captures.

4.5 Distinguishing value agreement from readiness

A historical dataset may label a date as “March 10th” without a year. FormBridge can retain that stated value while asking which year is intended. A correct field under the benchmark can therefore be unready for approval. Inventing a year would improve apparent completeness while reducing trustworthiness.

Evidence checking can miss implicit acceptance or reject a valid correction. A quotation may also be present but misinterpreted. Prompt instructions and pattern filters provide limited protection against adversarial input. Staff review is therefore necessary, and an unsupported-value rate was not independently measured.

5. Data sources and preparation

5.1 Public data and application input

The benchmark source is Google's Schema-Guided Dialogue (SGD) dataset at revision e852981ae34990f4358979625854259302feaa78. Its annotated task-oriented conversations and service schemas make it suitable for evaluating booking state (Google Research, n.d.; Rastogi et al., 2020). The project uses a restaurant subset, not the full multi-domain benchmark.

A reproducible audit identified the following single-service restaurant reservation dialogues. These audited subset counts are distinct from the counts of all dialogues in each upstream split.

Split	Restaurant service	Audited reservation dialogues	Reservation user turns
Train	Restaurants_1	367	1,870
Development	Restaurants_2	73	385
Test	Restaurants_2	73	342

The train split is described in the audit but was not used to fit model weights. Development and test use a different restaurant schema. The loader maps city to location and party_size to number_of_seats for Restaurants_2. Restaurant name, date and time retain their corresponding names. This mapping prevents a schema difference from being mistaken for a missing prediction.

Live application input is user-supplied text, while the browser scenarios and report screenshots use authored examples. Neither represents collected restaurant customer traffic. No customer personal data was required for the project.

5.2 Preparation procedure

1. Read the split's dialogue files in stable filename order.
2. Retain conversations containing only the selected restaurant service and at least one ReserveRestaurant user frame.
3. Stop the input prefix at the final reservation user turn, excluding later conversation.
4. Convert USER and SYSTEM speakers to customer and staff, and assign stable message IDs.
5. Map the final annotated slot values to the five application fields. Preserve multiple acceptable label variants.
6. For evaluation, retain prefixes within the 30-message application limit, apply the exclusion list and select the recorded dialogue IDs.

The extractor receives utterances, speakers and message IDs. The annotated reference states are kept outside its input. Historical reference dates are null, so a phrase such as “today” is not silently interpreted using the execution date. Dataset schema defaults are not passed into the model as customer statements.

5.3 Fitness, licensing and limitations

SGD is useful for controlled comparison, but its annotations are not a complete ground truth for evidence accuracy, clarification quality or approval readiness. Some slot values carry across revised staff summaries or reflect service conventions. Real staff may reasonably ask for clarification where a dataset retains a value. Section 8 examines this mismatch.

The upstream dataset uses Creative Commons Attribution-ShareAlike 4.0 International. Dataset-derived excerpts require attribution and the applicable licence; the repository retains a copy of the licence. Public availability also means that inclusion in a hosted model's pretraining cannot be ruled out. “Previously unselected” describes this project's evaluation history, not guaranteed absence from provider training.

6. Evaluation design and reproducibility

6.1 Comparing the methods

Rules, direct extraction and FormBridge process the same ordered conversation, with analysis after every customer message. Each method is scored on its final five-field state after the same message. Staff edits are excluded from automatic scoring. The evaluation runs the application analysis code directly, avoiding differences caused by changes to the deployed website.

Two experiments answer different questions. The production-configuration runs check the selected deployable system on the inspected 20-dialogue regression sample and a repeatedly used 20-dialogue development selection. The controlled comparison fixes model identity: both AI systems, including FormBridge's repair, use GPT-6 Luna with low reasoning. The prompts, evidence generation and number of calls differ, so the comparison measures complete systems rather than the isolated effect of validation.

A further controlled run evaluated all 13 eligible test dialogues remaining after excluding 60 previously selected IDs, including interrupted selections. IDs and exclusions were fixed before calls, and prompts and matching rules remained unchanged throughout the runs. These cases had not been selected in earlier project experiments; subsequent reuse would be a regression check.

6.2 Metrics and interpretation

For N attempted dialogues, field accuracy is the number of matching final values divided by 5N. Complete-brief accuracy is the number of dialogues in which all five values match divided by N. Failed dialogues remain in both denominators. An absent reference slot matches only a null prediction.

Strict matching retains the original text-normalisation rules. **Canonical matching** additionally recognises equivalent supported calendar and clock formats, such as “March 3rd” and “3rd of March”. It does not invent missing years or AM/PM to obtain a match. Both results are reported. This remains a limited value matcher, not human semantic adjudication or the official full-SGD joint-goal metric.

Operational measures include analysis requests, provider attempts, returned input/output tokens, complete-dialogue replay time and repair warnings. Replay time sums requests across several customer turns; it is not the latency of one live message. Concurrent provider use and unreported usage from failed calls limit cost and timing interpretations.

No independent aggregate score was produced for evidence correctness, unsupported values, clarification accuracy or real-user task completion. These require additional annotation or participants. The functional checks assess selected behaviours rather than replace those missing measurements.

6.3 Reproduction and verification

Selections, predictions, per-prefix usage and warnings are saved as versioned JSON, with a summary CSV. SHA-256 fingerprints record the extractor and runner used for each experiment. Exact commands and dataset acquisition steps appear in Appendix A.

The final source was checked from a clean archive with fresh locked dependencies: 53 tests, TypeScript checking and a production build passed. GitHub Actions also passed these gates for release 0b6bc90. Saved model predictions support result auditing without another paid run, although provider aliases and stochastic inference limit identical regeneration.

7. Results

7.1 Controlled comparison: same primary and repair model

Selection and method	Strict fields	Canonical fields	Strict complete briefs	Canonical complete briefs
Development, rules	35/100	35/100	0/20	0/20
Development, direct model	86/100	92/100	9/20	14/20
Development, FormBridge	92/100	92/100	14/20	14/20
Previously unselected, rules	25/65	25/65	0/13	0/13
Previously unselected, direct model	56/65	62/65	6/13	12/13
Previously unselected, FormBridge	62/65	62/65	12/13	12/13

Table 1. Final five-field value agreement. Both AI approaches use GPT-6 Luna in these controlled runs. Development uses 20 dialogues; the previously unselected selection contains 13.




Figure 4. Canonical field accuracy calculated from the saved comparison reports. Different sample sizes are labelled. The two AI methods tie within each sample.

Both contextual systems outperform the rule baseline on these selections, reaching 92% canonical field accuracy on development data and 95.4% on the smaller test remainder. FormBridge's advantage under strict matching disappears when equivalent formats are accepted. The difference concerns how values are represented; canonical value accuracy is equal.

7.2 Final production configuration

Selection	Correct fields, strict and canonical	Complete briefs	Terminal dialogue failures
Inspected regression sample	100/100	20/20	0/20
Repeated development selection	96/100	17/20	0/20

Table 2. Production configuration: GPT-6 Luna extraction and at most one GPT-6.1 Sol repair. These are separate runs from Table 1.

The production development run recorded two failed repair calls and retained the checked first-pass state; no dialogue failed completely. The inspected regression score describes performance on known cases. The small samples do not establish general accuracy or a statistically significant advantage over direct extraction.

8. Findings, errors and challenges

8.1 What the results establish

The same-model comparison suggests that contextual understanding is the main source of value accuracy over the rule patterns. On development data, the direct model correctly matched all 20 restaurant names and 15 dates; FormBridge matched 19 names and 16 dates. The aggregate tie therefore conceals different errors. Both achieved 20 city values, 19 times and 18 party sizes.

FormBridge adds evidence links, revision history and explicit review states. Their operational benefit is demonstrated as implemented behaviour, but reduced staff workload or fewer real booking mistakes has not been measured. The additional processing also has a cost.

Controlled run	Provider attempts	Input / output tokens	Mean whole-dialogue replay
Development, direct	166	93,947 / 22,893	23.835 s
Development, FormBridge	170	295,908 / 57,475	31.852 s
Test remainder, direct	98	55,253 / 11,989	20.576 s
Test remainder, FormBridge	101	176,247 / 37,395	30.754 s

Table 3. Returned API usage and mean replay time. Replay time covers multiple customer turns; token totals are observed usage rather than invoiced cost.

8.2 Error review and practical solutions

Observed issue	Evidence and response
Implicit carryover	Production development dialogues 1_00005 and 1_00017 omit an annotated date or party size carried from earlier staff summaries. Explicit acceptance and multi-message evidence were added, but carryover remains a weakness.
Rejected summaries	Development 1_00006 loses date and party size after a customer rejects one summary and accepts a shorter revision. Test 1_00027 omits three reference slots after repeated corrections; both AI systems make those omissions in the controlled run.
Residual scoring sensitivity	Controlled development 4_00069 predicts “the 5th of this month” against “5th of this month”. The matching rule still marks this wording difference wrong; the reported score was not changed.
Failed second checks	Two production development repair calls fail. Recovery preserves checked first-pass information and exposes a warning instead of applying unchecked output.

The four production development mismatches are omissions across three dialogues: two dates labelled “today” and two party-size values of two. These are benchmark mismatches even when preserving uncertainty is sensible for staff. In the test failure, later accepted text states time and city but omits venue, date and size, illustrating the difficulty of interpreting which parts of a rejected summary carry forward.

The original conversations show these carryover patterns, but the saved traces do not retain every intermediate candidate and rejection decision. They therefore cannot establish whether extraction, repair or reconciliation caused each omission. Future evaluation needs both detailed decision traces and annotations that distinguish a supported carryover from an unresolved request.

9. Interaction design and verification

9.1 A review desk designed around the task

On desktop, the conversation appears beside a booking slip. Mobile tabs switch between the two views without discarding the draft. Familiar restaurant terms, cream surfaces and green accents organise the five details, while text and icons identify their status.

Status labels, familiar terms and editable values follow Nielsen's usability principles (Nielsen, 1994). Source links and explanations of uncertainty also support checking and correcting model output, as recommended by Amershi et al. (2019). These principles guided the interface design; its usability has not been tested with recruited participants.

9.2 Verification performed

The recorded browser run passed all 20 ordinary enquiry cases and 15 edge cases. The authored cases exercised custom input, corrections, uncertain dates and times, staff acceptance, cancellation, manual overrides, refresh and mobile switching. Each pass refers to the case's specified functional checks, rather than general extraction accuracy.

Four downloads were saved and opened: draft text, approved text, approved JSON and revised unresolved draft JSON. Checks covered values, transcript, source IDs, revision history and review status. A correction cleared approval in the revised export. Native file inspection verified delivery where browser automation had not returned a download event.

The interface includes labelled inputs and edit controls, a skip link, modal keyboard focus handling and reduced-motion support. The code and recorded interaction checks support these implementation claims. No formal accessibility conformance audit has been completed.

9.3 What remains unmeasured

The functional checks did not measure satisfaction, task completion time or adoption by restaurant staff. A usability study should compare matched transcript-to-brief tasks with and without FormBridge, vary task order and record completion time, remaining errors and source checks. Restaurant staff would be the preferred participants; classmates would provide proxy feedback. The study should also test whether analysis delays disrupt the workflow.




Figure 5. Mobile view of the same live enquiry captured on 11 October 2026. The detail statuses, source controls and approval boundary remain visible.

10. Ethics, limitations and next steps

10.1 Privacy, accountability and appropriate use

FormBridge's narrow five-field task does not require names, contact details, payment information or dietary and medical information. The live interface warns users to avoid sensitive personal information. However, users can paste arbitrary text, so unnecessary personal information can still be transmitted. Clear instructions alone do not prevent that exposure.

The API key stays on the server. Analysis requests use store: false and do not create a FormBridge customer database. This does not establish zero provider retention. OpenAI documents separate abuse-monitoring and application-state controls, including possible retention and caching (OpenAI, n.d.-a). Browser-local storage therefore does not make model processing local or establish zero retention.

Human approval is a review step; the application has no restaurant availability or reservation connection. Sources are evidence pointers, not a proof of intent. A plausible quotation can still be misinterpreted, and staff may over-trust a complete-looking slip. Explicit uncertainty, manual review and the “no table is reserved” boundary reduce that risk without eliminating it.

10.2 Limits of the evidence

The samples are small and domain-restricted. Development cases were repeatedly used; the regression selection was inspected. The 13-case remainder provides some separation from this project's earlier selections, but one dialogue changes its complete-brief percentage by 7.7 points. Its public provenance also prevents claims of guaranteed absence from model pretraining.

The controlled experiment fixes model identity, but evidence prompts and repair budgets differ. It cannot isolate validation as the causal source of improvement. Values are scored at the final turn; intermediate-turn accuracy, unsupported-value rates, evidence correctness and clarification quality were not independently quantified. The canonical scorer still misses some harmless wording differences. API aliases, concurrent provider use and incomplete failed-call token reporting limit exact regeneration and cost conclusions.

English-only patterns, a 30-message cap and party sizes of 1–30 limit applicability. Tab-local storage and a process-local limiter suit the current demonstration but do not establish production-scale reliability. A complete security or legal compliance assessment was outside the project evaluation.

10.3 Prioritised next steps

1. **Evaluate the review workflow with people.** Measure task errors, time and how often sources are checked; recruit restaurant staff where feasible.
2. **Improve diagnostic evidence.** Log redacted candidate/check decisions for research, label carryover and rejection scope, and add independent evidence and clarification annotations.
3. **Run a stronger controlled experiment.** Freeze a new dataset or collection before tuning; compare prompts and repair budgets, then ablate evidence validation separately.
4. **Reduce operational overhead.** Test compact context and repair policies, measuring quality alongside per-message latency and observed usage.
5. **Prepare for shared use.** Add consent-aware persistence, a durable shared rate limiter and suitable access controls only when a real staff workflow requires them.

These priorities address the observed extraction errors, unmeasured user benefits and limits of individual browser sessions.

11. Project phases, contributions and conclusion

11.1 Phases and delivered work

Phase	Recorded period	Delivered evidence
Scope and initial implementation	29 September	Five-field state model, rule baseline, contextual extraction and initial web interface
Public workflow and product communication	30 September	Public access, custom enquiries, empty initial workspace and separation of internal evaluation
Extraction and interaction refinement	1 October	Grounding and temporal checks, cancellation handling, retained staff edits, focus handling and restaurant desk design
Final evaluation and reproduction	1 October	Fixed evaluation settings, same-model comparison, result files, clean-checkout checks and verified exports
Product media and report preparation	4–11 October	Updated launch/walkthrough films, real product captures and the technical report

Table 4. Project phases and deliverables recorded in the repository.

11.2 Individual contributions

Karthik Ramesh was responsible for technical implementation. The delivered technical work includes the web application, analysis pipeline, evaluation runner, deployment and supporting product media.

11.3 Conclusion

FormBridge demonstrates an end-to-end NLP application for a specific task: converting changing restaurant enquiries into reviewable booking briefs. It combines contextual state extraction with source checking, revision handling and human approval in a working web interface. The main contribution is making extracted information inspectable and actionable within that review task.

Both contextual approaches exceeded the rule baseline, and their canonical value accuracy was equal on the controlled selections. FormBridge added source links, uncertainty handling and review controls at the cost of more tokens and longer replay times. Testing whether those controls reduce staff errors is the next step. The project demonstrates how dialogue state tracking can support a restaurant booking handoff while leaving the final decision with staff.

References

Amershi, S., Weld, D., Vorvoreanu, M., Fourney, A., Nushi, B., Collisson, P., Suh, J., Iqbal, S., Bennett, P. N., Inkpen, K., Teevan, J., Kikin-Gil, R., & Horvitz, E. (2019). Guidelines for human-AI interaction. In *Proceedings of the 2019 CHI Conference on Human Factors in Computing Systems* (pp. 1–13). Association for Computing Machinery. https://doi.org/10.1145/3290605.3300233

Google Research. (n.d.). *Schema-Guided Dialogue dataset* [Data set; revision e852981ae34990f4358979625854259302feaa78]. GitHub. https://github.com/google-research-datasets/dstc8-schema-guided-dialogue/tree/e852981ae34990f4358979625854259302feaa78

Nielsen, J. (1994, April 24). *10 usability heuristics for user interface design*. Nielsen Norman Group. https://www.nngroup.com/articles/ten-usability-heuristics/

OpenAI. (n.d.-a). *Data controls in the OpenAI platform*. Retrieved October 11, 2026, from https://developers.openai.com/api/docs/guides/your-data

OpenAI. (n.d.-b). *Structured model outputs*. Retrieved October 11, 2026, from https://developers.openai.com/api/docs/guides/structured-outputs

Rastogi, A., Zang, X., Sunkara, S., Gupta, R., & Khaitan, P. (2020). Towards scalable multi-domain conversational agents: The Schema-Guided Dialogue dataset. *Proceedings of the AAAI Conference on Artificial Intelligence, 34*(5), 8689–8696. https://doi.org/10.1609/aaai.v34i05.6394

Wu, C.-S., Madotto, A., Hosseini-Asl, E., Xiong, C., Socher, R., & Fung, P. (2019). Transferable multi-domain state generator for task-oriented dialogue systems. In A. Korhonen, D. Traum, & L. Màrquez (Eds.), *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics* (pp. 808–819). Association for Computational Linguistics. https://doi.org/10.18653/v1/P19-1078

Appendix A. Reproducing the application and evaluation

A.1 Application and source

Prerequisites are Node.js 24, pnpm 11.24.0, Git, repository access and an OpenAI API project with access to the configured models. Installation and build do not require an API key; model analysis does.

```
git clone https://github.com/KarthikRamesh9149/NLP-AT2.git
cd NLP-AT2
git checkout 0b6bc901363b34472173ff7a05d5366f7bd5549c
pnpm install --frozen-lockfile
cp .env.example .env.local
pnpm test
pnpm typecheck
pnpm build
pnpm start
```

The server reads OPENAI_API_KEY from the private environment file. The application runs at http://localhost:3000. The evaluation used source commit 32af459b6a1cd20ede9b08c2b73c20a0c385301e; the application release above has unchanged extractor and runner fingerprints.

A.2 Dataset and same-model development comparison

```
git clone https://github.com/google-research-datasets/dstc8-schema-guided-dialogue.git ../formbridge-sgd
git -C ../formbridge-sgd checkout e852981ae34990f4358979625854259302feaa78
pnpm data:audit ../formbridge-sgd

OPENAI_MODEL=gpt-6-luna \
FORMBRIDGE_MODEL=gpt-6-luna \
FORMBRIDGE_REPAIR_MODEL=gpt-6-luna \
node --env-file=.env.local --import tsx scripts/evaluate.ts ../formbridge-sgd \
  --transport=in-process --replay=all-user-turns \
  --split=dev --sample=20 --modes=rules,model,formbridge \
  --selection=evaluation/results/selection-grounded-v6-release-heldout-development.json \
  --tag=report-reproduce-equal-development
```

Each run needs a unique tag because completed results and selection manifests refuse overwrites. All systems receive identical customer prefixes, and the extractor receives no reference values. A repeat uses previously evaluated data and constitutes a reproduction attempt.

A.3 Reading outputs

The runner writes a selection manifest before inference and a completed result file containing values, strict/canonical matches, brief states, prefix usage, latency and warnings. The manifest and source fingerprints identify the configuration associated with each completed result.

Provider alias updates and inference variability may change a rerun's outputs. The saved JSON and CSV permit inspection of the reported findings without new API requests.

Appendix A. Reproduction, continued

A.4 Previously unselected test comparison

```
OPENAI_MODEL=gpt-6-luna \
FORMBRIDGE_MODEL=gpt-6-luna \
FORMBRIDGE_REPAIR_MODEL=gpt-6-luna \
node --env-file=.env.local --import tsx scripts/evaluate.ts ../formbridge-sgd \
  --transport=in-process --replay=all-user-turns \
  --split=test --sample=13 --modes=rules,model,formbridge \
  --exclude=evaluation/research/exclude-prior-test-20261001.json \
  --seed=assessment-unselected-20261001 \
  --tag=report-reproduce-equal-test
```

The exclusion file contains 60 previously selected test IDs, including interrupted runs. The remaining 13 were selected before the final comparison. Subsequent runs reuse that same selection.

A.5 Production-configuration checks

For the two production checks, use GPT-6.1 Sol as the repair model. The two commands below reuse the original sample selections.

```
OPENAI_MODEL=gpt-6-luna \
FORMBRIDGE_MODEL=gpt-6-luna \
FORMBRIDGE_REPAIR_MODEL=gpt-6.1-sol \
node --env-file=.env.local --import tsx scripts/evaluate.ts ../formbridge-sgd \
  --transport=in-process --replay=all-user-turns \
  --split=test --sample=20 --modes=formbridge \
  --selection=evaluation/results/selection-grounded-v6-release-regression.json \
  --tag=report-reproduce-production-regression

OPENAI_MODEL=gpt-6-luna \
FORMBRIDGE_MODEL=gpt-6-luna \
FORMBRIDGE_REPAIR_MODEL=gpt-6.1-sol \
node --env-file=.env.local --import tsx scripts/evaluate.ts ../formbridge-sgd \
  --transport=in-process --replay=all-user-turns \
  --split=dev --sample=20 --modes=formbridge \
  --selection=evaluation/results/selection-grounded-v6-release-heldout-development.json \
  --tag=report-reproduce-production-development
```

A.6 Interface and download reproduction

Start with a new brief; enter the four-message enquiry from Section 2 with a valid future date. Confirm four guests and 7 pm, then five guests and an unresolved after-8 preference, then accepted 8:30 pm. Inspect both time sources. Approve the resolved brief and download text and JSON; open the files and check the values and reviewed status. Add a further correction and confirm that approval clears. Refresh and inspect the restored draft. Downloads can be checked directly from the saved files.

Appendix B. Evidence index

B.1 Where to verify the findings

Paths below are relative to the application repository.

Evidence	File or location
Evaluation settings and sample selection	evaluation/research/assessment-final-protocol.md
Verified results and accounting	evaluation/research/assessment-final-verification.md
Aggregate tables	evaluation/results/assessment-summary.csv and assessment-summary.json
Production regression	evaluation/results/sgd-test-20-assessment-final-regression.json
Production development	evaluation/results/sgd-dev-20-assessment-final-development.json
Same-model development	evaluation/results/sgd-dev-20-assessment-equal-model-development.json
Same-model test remainder	evaluation/results/sgd-test-13-assessment-equal-model-unselected.json
Dataset audit and licence	evaluation/results/sgd-audit.json; evaluation/DATA_LICENSE.txt
Authored browser cases	evaluation/browser-cases-35.json
Recorded 35-case browser run	evaluation/results/browser-use-35-final.json
Native exports and file checks	evaluation/results/download-verification-20261001.json; evaluation/results/downloads/
Full reproduction instructions	evaluation/REPRODUCIBILITY.md
Automated release checks	GitHub Actions run 37173880400, release 0b6bc90

Source fingerprints are recorded in the completed evaluation files. The browser-case record covers an earlier product release; the later evaluation runner change did not alter the interface.

B.2 Evidence provenance

Error analysis used development dialogues 1_00005, 1_00006 and 1_00017, and test dialogue 1_00027 from the pinned SGD revision. The original labels and final run scores were retained. Figure 4 uses the saved summary CSV; field-level observations use the saved predictions. Dataset-derived material is attributed to Google Research and is subject to the dataset's Creative Commons Attribution-ShareAlike 4.0 International licence.

Figures 1, 3 and 5 are original captures of the live application on 11 October 2026 using a fictional restaurant enquiry. They illustrate the interface without including customer records. Figure 2 describes the implemented processing flow.