Dashboard / My courses / CS23331-DAA-2023-CSE / Greedy Algorithms / 1-G-Coin Problem

Started on	Sunday, 25 August 2024, 5:58 PM
State	Finished
Completed on	Sunday, 25 August 2024, 6:03 PM
Time taken	4 mins 32 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```
1   #include<stdio.h>
2   int Coins[] = { 1, 2, 5, 10, 20, 50, 100, 500, 1000};
3   int G_coin(int coin){
4       int size = sizeof(Coins)/sizeof(Coins[0]);
5       int count = 0;
6       int i=size-1;
7       while(coin){
8           if(coin>=Coins[i]){
9               count+=coin /Coins[i];
10              coin %= Coins[i];
11          }
12          else{
13              i--;
14          }
15      }
16      return count;
17  }
18
19  int main(){
20      int coin;
21      scanf("%d",&coin);
22      int totalCoins = G_coin(coin);
23      printf("%d",totalCoins);
24      return 0;
25
26  }
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

◄ Problem 5: Finding Complexity using counter method

Jump to...

2-G-Cookies Problem ►