


PRACTICAL: 02

Aim: To implement and find the time analysis of Linear Search and Binary Search algorithm.

A) Linear Search:

Algorithm:



Program / Code:

```
#include <iostream>

using namespace std;

int main() {
    int arr[100], i, n, key;
```



```
cout<<"enter number of array elements:"<<endl;
cin>>n;
cout<<"enter array elements:"<<endl;
for(i=0;i<n;i++){
    cin>>arr[i];
}
cout<<"enter element to serach:"<<endl;
cin>>key;
for(i=0;i<n;i++){
    if(arr[i]==key)
    {
        cout<<"element found at index of:"<<i;
    }
}
return 0;
}
```

Output:

Time Complexity:

Time Complexity:

```

for (i=0; i<n; i++) {
    if (A[i] == Key) {
        cout << "Element found";
        break;
    }
}
    
```

$T(n) = 1 + 1 + 1 + n$

$T(n) = O(n)$

In worst case

Best case $\rightarrow O(1)$

Average case $\rightarrow O(1)$

B) Binary Search:

Algorithm:

Binary Search:-

Algorithm:

1. Start
2. Read array A , n and Key .
3. Set $low = 0$ & $high = n-1$.
4. Find the middle element.
 $mid = \frac{low + high}{2}$
5. Compare $A[mid]$ with Key .
6. If $A[mid] == Key$, print the position.
7. If $Key < A[mid]$, search in the left half.
8. If $Key > A[mid]$, search in the right half.
9. Repeat the above steps until the Key is found or $low = high$.
10. If Key is not found, print "Element not found".
11. End.

Program / Code:

```
#include <iostream>

using namespace std;

void bubblesort(int arr[], int n) {
    for(int i=0; i<n-1; i++) {
        for(int j=0; j<n-i-1; j++) {
            if(arr[j] > arr[j+1]) {
                int temp = arr[j];
                arr[j] = arr[j+1];
                arr[j+1] = temp;
            }
        }
    }
}


int binarySearch(int arr[], int n, int key) {
    int low = 0, high = n-1;
    while(low <= high) {
        int mid = (low + high) / 2;
        if(arr[mid] == key) return mid;
        else if(arr[mid] < key) low = mid+1;
        else high = mid-1;
    }
    return -1;
}

int main() {
    int arr[100], n, key;
    cout << "Enter number of array elements: ";
```

```
cin >> n;

cout << "Enter array elements: ";
for(int i=0; i<n; i++) {
    cin >> arr[i];
}
bubblesort(arr, n);
cout << "Sorted elements: ";
for(int i=0; i<n; i++) {
    cout << arr[i] << " ";
}
cout << endl;
cout << "Enter element to search: ";
cin >> key;
int result = binarySearch(arr, n, key);
if(result != -1)
    cout << "Element found at index " << result << endl;
else
    cout << "Element not found" << endl;
return 0;
}
```

Output:



```
Enter number of array elements: 4
Enter array elements: 9
5
1
7
Sorted elements: 1 5 7 9
Enter element to search: 7
Element found at index 2
Process returned 0 (0x0) execution time : 16.577 s
Press any key to continue.
```




$$\begin{aligned} T(n) &= T(n/2^k) + 3 \\ &= T\left(\frac{n}{2^k}\right) + k \rightarrow T\left(\frac{n}{n}\right) + \log_2 n \\ &= T(1) + \log_2 n \\ &= 1 + \log_2 n \end{aligned}$$
$$\begin{aligned} n &= 1 \\ \frac{n}{2^k} &= 1 \\ n &= 2^k \\ \log n &= \log 2^k \\ \log n &= k \log 2 \\ k &= \frac{\log n}{\log 2} \\ k &= \log_2 n \end{aligned}$$
$$\begin{aligned} T(n) &= O(\log n) \rightarrow \text{in worst case} \\ O(1) &\rightarrow \text{in Best case.} \\ O(\log n) &\rightarrow \text{in Average case.} \end{aligned}$$

Conclusion:

In this practical, we studied and implemented two searching algorithms: Linear Search checks each element one by one, so it takes more time as the list size grows. Binary Search is much faster because it works only on sorted lists and cuts the list in half every time, making it a better choice for large data.