

Assignment

Karthikeya hanu prakash kanithi (EE22BTECH11026)

Question : Consider communication over a memoryless binary symmetric channel using a (7, 4) Hamming code. Each transmitted bit is received correctly with probability $(1 - \epsilon)$, and flipped with probability ϵ . For each codeword transmission, the receiver performs minimum Hamming distance decoding, and correctly decodes the message bits if and only if the channel introduces at most one bit error.

For $\epsilon = 0.1$, the probability that a transmitted codeword is decoded correctly is _____ (rounded off to two decimal places). (rounded off to two decimal places).

Solution: Given that, Let X be a random variable defined in the Table I;

| RV | Value | Description |
|--------------|-------------------|--|
| n (or) p | 7 | The total number of bits |
| ϵ | 0.1 | Probability of error in transimitted bit |
| X | $0 \leq X \leq 7$ | The number of bit errors in transmission |

TABLE I
RANDOM VARIABLE X DECLARATION

Then, $X \sim \text{Bin}(n, p)$ where

$$n = 7 \quad p = \epsilon = 0.1 \quad (1)$$

the pmf of X is given by

$$p_X(k) = {}^7C_k(\epsilon)^k(1 - \epsilon)^{7-k} \quad (2)$$

the cdf of X is given by

$$F_X(k) = \sum_{i=0}^k {}^7C_i(\epsilon)^i(1 - \epsilon)^{7-i} \quad (3)$$

From equation (3), the probability of getting one or less error is given by

$$F_X(1) = \sum_{i=0}^1 {}^7C_i(\epsilon)^i(1 - \epsilon)^{7-i} \quad (4)$$

$$= {}^7C_0(\epsilon)^0(1 - \epsilon)^7 + {}^7C_1(\epsilon)^1(1 - \epsilon)^6 \quad (5)$$

$$= (1 - \epsilon)^7 + 7(\epsilon)^1(1 - \epsilon)^6 \quad (6)$$

From (1) and (6),

$$F_X(1) = (1 - 0.1)^7 + 7(0.1)^1(1 - 0.1)^6 \quad (7)$$

$$= 0.85 \quad (8)$$

\therefore the probability that a transmitted codeword is decoded correctly is 0.85.

Gaussian

Let parameters be defined in the Table II;

| RV | Value | Description |
|------------------|-------|-----------------------------------|
| $\mu = np$ | 0.7 | Mean of Binomial distribution |
| $\sigma^2 = npq$ | 0.63 | Variance of Binomial distribution |

TABLE II
PARAMETERS

Let Y is the Gaussian obtained by approximating binomial with parameters n, p then by Central limit theroem the gaussian random variable Y approximates X . Then let Z be a random variable

$$Z \approx \frac{Y - \mu}{\sigma} \quad (9)$$

Z converges to normal distribution for large value of n

$$f(x) = \frac{1}{\sqrt{2\pi}} e^{-\frac{x^2}{2}} \quad (10)$$

Q function is defined

$$Q(x) = \int_x^\infty f(x) dx \quad (11)$$

then CDF of X is:

$$F_Y(k) = \int_{-\infty}^x f(x) dx \quad (12)$$

$$= 1 - \int_x^\infty f(x) dx \quad (13)$$

$$= 1 - Q(x) \quad (14)$$

From (1) and (14),

$$F_Y(1) = 1 - Q(1) \quad (15)$$

$$= 0.84134 \quad (16)$$

\therefore the probability that a transmitted codeword is decoded correctly is 0.84134. The CDF plot is given in fig1




Fig. 1. CDF plot