PRODUCT SPACE AI HACKATHON · SUBMISSION

Differential

An adaptive exam-prep tutor with a learner model.
It knows the answer was wrong, and it knows *why*.

Problem statement	**Adaptive exam-prep tutor with a learner model**
Team name	**Works Locally**
Syllabus	Class 10 Computer Science, with Python Programming fully assessed
Runs on	One PC, with a local LLM (`qwen3.5:9b` on Ollama). No cloud, and no student data leaves the machine
Repository	github.com/Karthikeyan-2001/agentic-ai-hackathon
Demo video	Link to be added

Team member
Karthikeyan

Team member
Nandini

Contents

1 The problem and our idea
2 Requirements and how we met them
3 System architecture
4 What happens on every answer
5 The learner model
6 Misconception detection
7 Choosing and generating questions
8 Spaced repetition
9 Student experience
10 Teacher dashboard
11 Evaluation and testing
12 Guided demo walkthrough
13 Running the project
14 Limits and next steps

1. The problem and our idea

Generic AI tutors answer questions, but they don't track what a student actually understands. Most quiz tools also look only at the final answer. Yet the same wrong answer can come from completely different misunderstandings, and a right answer can hide a wrong belief that will break on the next problem.

Differential is a Class 10 Python Programming tutor that reads the student's **reasoning**, not just the answer. Its name comes from a doctor's *differential diagnosis*: when a student makes a mistake, it forms competing explanations, then asks the question that best separates them.

One question, three students, three different problems

Every student is asked: *"How many times does the body of* `for i in range(1, 5):` *run?"* (Correct answer: 4 times.)

Student	Answer	Their reasoning	Differential's diagnosis	Mastery	Next question tests
A	5 times Wrong	"It counts up to and including 5"	Thinks `range` includes its stop value	Falls	The last number printed by `range(3, 7)`
B	5 times Wrong	"The 5 says how many times"	Thinks the stop value is the number of repeats	Falls	How many times `range(4, 6)` runs
C	4 times Right	"It is always one less than the stop number"	Right answer, wrong reason	Unchanged	How many times `range(3, 8)` runs

An answer-only tutor treats A and B the same and gives C full marks. Differential gives A and B different diagnoses and different follow-up questions, and it gives C no credit until the reasoning holds up on a loop that doesn't start at 1.




Figure 1. Student A's diagnosis, recorded from a real run on the local model. Student A answered 5 times (the correct answer is 4) and explained "It counts up to and including 5". The tutor names the false belief behind that sentence, lowers A's mastery of the concept from 30% to 5%, and keeps two possible explanations open: 72% that A thinks range includes its stop value, and 24% that A thinks the stop value is the number of repeats. It then asks about range(3, 7): only the leading belief leads to the answer 7, so A's next answer confirms or weakens it.

Our main design rule: the LLM interprets and the code decides. The language model only reads the student's reasoning and returns structured data. Tested, deterministic code marks every answer, changes every score and chooses every question. Code written by the LLM is never run. This makes every number on screen explainable and testable.

2. Requirements and how we met them

The brief asked for seven things. All seven work in the running app and appear in the guided demo (section 12).

#	Requirement	What we built	Where in the code
1	**Diagnostic test**	An 8-question **adaptive** diagnostic. Each question goes to the concept the tutor is least certain about (mastery closest to 50%), with ties going to the concept the most other concepts depend on. Every answer needs written reasoning and a "Sure" / "Not sure" confidence tap.	`engine/selection.py`
2	**Concept graph for one syllabus**	29 concepts across Class 10 Computer Science, linked by prerequisites: Python Programming (12), Computer Networks (6), Web Pages with HTML (6) and Cyber Ethics (5). A test makes sure the graph has no cycles. Python is assessed; other chapters show as "not assessed".	`content/concepts.json` `engine/graph.py`
3	**Learner model updated after every answer**	Bayesian Knowledge Tracing per concept, with slip and guess values that depend on the *diagnosis*, not just correctness. Changes spread to prerequisites up to two links away. Each misconception has its own probability and status.	`engine/mastery.py` `engine/misconceptions.py`
4	**Question generation targeted at weak concepts, with difficulty calibration**	Code picks the target (suspected misconception, due review, or weakest ready concept), then the question closest to a 60% chance of success. Generated questions use fixed program templates: the LLM writes only the wording and options, code computes the answer and rejects bad questions. Elo ratings for students and questions update after every answer.	`engine/selection.py` `engine/elo.py` `agent/generate.py` `agent/solvers.py`
5	**Misconception detection from reasoning**	The LLM classifies the written reasoning into an error type and matches it against a catalogue of 8 Python misconceptions. It must quote the student's own words; code checks that the quote really appears in the text.	`agent/diagnose.py` `content/misconceptions.json`
6	**Spaced-repetition scheduling**	A forgetting curve for each concept and each cleared misconception. A review comes due when predicted recall drops below 85%. A **Jump 7 days** button moves the app clock for the demo.	`engine/scheduling.py`

#	Requirement	What we built	Where in the code
7	**Teacher dashboard of class-wide gaps**	Class summary, biggest gaps, reviews due, shared misconceptions, root causes, a student-by-concept heatmap, difficulty surprises from Elo and an AI-drafted Monday lesson plan. Always labelled "Simulated class".	`engine/class_summary.py` `agent/plan.py` `web/src/pages/TeacherPage.tsx`

Beyond the brief

- **Separating explanations:** when two misconceptions are both possible, code picks the question whose options split them apart, like a doctor ordering the test that rules one out.
- **"Right answer, wrong reason":** a correct answer with flawed reasoning earns no mastery.
- **Thinking panel:** the student sees the explanations the tutor is weighing and why it chose the next question.
- **Root causes:** the dashboard traces low scores back to the earliest weak prerequisite behind them.
- **Fully local and private:** the model runs on the team's own PC, so the tutor works offline.
- **Measured accuracy** on held-out test cases, reported honestly (section 11).

3. System architecture

Differential is one Python service. FastAPI serves both the API and the built React app, so there is a single process to start. The LLM is reached through one file, `agent/llm.py`, so changing provider changes one file.




Figure 2. System architecture. Only `agent/llm.py` talks to the model. The engine is pure, so every formula is unit-tested and time is passed in, which also powers the "Jump 7 days" demo clock.

Folder ownership

Folder	Owns
`content/`	Concept graph, misconception catalogue, 12 hand-checked seed questions, 20 pre-generated questions, 40 evaluation samples, demo script
`engine/`	Mastery, misconceptions, scheduling, Elo, graph, selection, class summary. Pure code with no LLM, database, network or system clock
`agent/`	LLM client, diagnosis, question generation, solvers, lesson plan, the agent loop
`api/`	Database tables, persistence, routes, mock sign-in and role checks
`scripts/`	Seeding the simulated class, pre-generating questions, evaluation, demo warm-up
`web/`	React app: landing page, sign-in, student app, teacher dashboard, guided demo

Technology

Layer	Choice
Backend	Python 3.12+, FastAPI, Uvicorn, SQLModel on SQLite, Pydantic
LLM	Ollama with `qwen3.5:9b`: thinking off, temperature 0, 8192-token context, kept loaded, 30-second timeout, up to two retries, every reply validated against a schema and cached
Frontend	React 19, Vite, TypeScript, Tailwind CSS, React Flow with Dagre for the concept graph
Tests	pytest and httpx, with a fake LLM for fast deterministic tests and a separate live-model test run

4. What happens on every answer

This is the core flow of the product. Each time a student submits an answer, the agent loop runs six steps. Only one of them uses the LLM.




Figure 3. The agent loop for one answer. Teal steps are deterministic code; the amber step is the only LLM call.

Step by step

1. **Check.** Each option in the question bank has an `is_correct` flag. Code compares the student's option. The LLM never marks answers.
2. **Diagnose.** The local LLM receives the question, the chosen option, whether it was correct, the student's reasoning and the misconception catalogue. It returns JSON matching a fixed schema: `error_type`, `misconception_id`, `first_wrong_step`, `evidence_quote` and `confidence`.
3. **Validate.** Code rejects anything it can't verify: the quote must appear in the student's text, the misconception ID must be in the catalogue, and diagnoses below 60% confidence are treated as "unclear".
4. **Update.** The engine updates concept mastery (section 5), spreads the change to prerequisites, updates each misconception's probability, reschedules reviews (section 8) and updates Elo ratings for the student and the question.
5. **Decide.** The engine chooses the next question with fixed priority rules (section 7).
6. **Explain.** The response carries a trace: the explanations being weighed, their probabilities and why the next question was chosen. The student sees this in the "What the agent is thinking" panel.

Answer response (from `POST /api/students/{id}/answers`)

Field	Meaning
`correct`	Whether the chosen option was right (set by code)
`diagnosis`	The validated error type, misconception and quoted evidence
`diagnosis_status`	`ok`, `cached` or `failed`, so the UI is honest about where the diagnosis came from
`mastery_changes`, `misconception_changes`	Before and after values, shown on the result card
`trace`	The reasoning behind the next question, shown in the thinking panel

5. The learner model

For each student, the learner model holds a **mastery** value for every concept and a **probability** for every misconception. Both update after every answer. All functions are pure and take the current time as an argument.

5.1 Mastery: Bayesian Knowledge Tracing that listens to the reasoning

Each concept starts at mastery 0.30 and stays between 0.01 and 0.99. The update uses standard Bayesian Knowledge Tracing:

```
Correct:  p' = p(1-s) / ( p(1-s) + (1-p)g )
Wrong:    p' = p·s   / ( p·s    + (1-p)(1-g) )
Learning: p'' = p' + (1-p')·T
```

The key idea is that the **slip (s)**, **guess (g)** and **learn (T)** values depend on the diagnosis, not just on right or wrong:

Answer	Diagnosis (`error_type`)	s	g	T	Starting from 0.5	Meaning
Correct	`none` (sound reasoning)	0.1	0.2	0.1	0.836	Real understanding: mastery rises
Correct	`misconception` , `gap`	0.1	0.9	0	0.500	Right for the wrong reason: no credit
Correct	`slip` , `unclear`	0.1	0.5	0	0.643	Partial credit
Wrong	`misconception` , `gap` , `none` , `unclear`	0.1	0.2	0	0.111	Mastery falls
Wrong	`slip` (careless error)	0.6	0.2	0	0.429	Barely lowered

5.2 Spreading along the concept graph

A mastery change of *d* also moves the concept's prerequisites, up to two links back: by *d* × *0.3* per link when it rises, and *d* × *0.1* per link when it falls. Failing "Nested loops" is mild evidence of weakness in "for loops with range", but succeeding at it is stronger evidence of strength.




Figure 4. The Python Programming part of the concept graph (simplified), coloured for one example student. Arrows run from a prerequisite to the concept that needs it. The full graph has 29 concepts across four chapters.

5.3 Misconception probabilities

Each misconception starts at probability 0.05. The confidence tap sets a multiplier *k*: 1.0 for "Sure", 0.6 for "Not sure".

Event	Update
Diagnosis names misconception *m* with confidence *c* ≥ 0.6	`p += (1-p) × 0.7 × c × k`
The chosen option maps to *m*, but the diagnosis didn't name it	`p += (1-p) × 0.2 × k`
Correct answer with sound reasoning on a question that has an option for *m*	`p × 0.5`

Status follows the probability: `inactive` below 0.2 → `candidate` 0.2–0.5 → `active` 0.5 and above → `resolved` when an active one falls below 0.2. A resolved misconception that climbs back to 0.5 becomes active again.

5.4 Difficulty calibration with Elo

Each student starts at 1500 Elo. Each question starts from its difficulty prior (1 → 1200, 2 → 1350, 3 → 1500, 4 → 1650, 5 → 1800). Expected success is `E = 1 / (1 + 10^((d - a)/400))`, and after each answer both ratings move by `32 × (actual - E)`. The dashboard flags a question when its rating has moved 150 or more from its prior after at least 10 attempts, so teachers can see questions that are harder or easier than expected.

6. Misconception detection from reasoning

The brief asked for misconceptions to be detected from the **reasoning** in wrong answers, not just the wrong final answer. Differential does this in two layers: the local LLM reads the explanation, and code checks the LLM's work.

6.1 The misconception catalogue (Python Programming)

ID	The student believes...
`range_includes_stop`	`range(start, stop)` includes the stop value, so the loop reaches that number
`range_stop_is_count`	The stop value says how many times the loop runs, whatever the start value is
`range_one_less_than_stop`	A loop always runs one less time than its stop value, ignoring the start value
`assignment_links_variables`	`b = a` links the two variables, so changing `a` later also changes `b`
`integer_division_rounds`	`//` rounds to the nearest whole number instead of dropping the part after the decimal point
`string_plus_adds`	`+` adds digits as numbers even when they are strings in quotes
`while_exits_mid_body`	A `while` loop stops the moment its condition becomes false, skipping the rest of the body
`index_starts_at_one`	List indexes start at 1, so index 1 is the first item

Each question option is mapped to the misconceptions that would lead a student to pick it. One option can map to several misconceptions, which is exactly why reading the reasoning matters: Students A and B pick the same option for different reasons.

6.2 Error types

`error_type`	Meaning
`none`	The reasoning is sound
`misconception`	The reasoning shows a catalogued false belief (must name which one)
`slip`	The reasoning is sound, with a careless or calculation error
`gap`	The student doesn't know, or guessed
`unclear`	The reasoning can't be judged from the text

6.3 How code keeps the LLM honest

Evidence must be real

The LLM must quote the student's own words. If the quote doesn't appear in the student's text, code removes it and caps the confidence at 0.5.

Uncertain means ask again

A diagnosis below 0.6 confidence is treated as "unclear". The tutor then asks another question instead of asserting a misconception.

Fixed vocabulary

The reply must match a Pydantic JSON schema, and the misconception ID must come from the catalogue. Invalid replies are retried up to two times.

Student text is untrusted

Reasoning is wrapped in clear delimiters and the prompt treats it only as data, so a student can't instruct the model. Empty reasoning skips the LLM.

7. Choosing and generating questions

After every answer, code applies the first rule in this list that returns a question. The student's three most recent questions are always excluded.




Figure 5. Next-question priority rules (`engine/selection.py`). Within a rule, the question whose expected success (from Elo) is closest to 60% wins, then question ID, so results are repeatable.

7.1 Separating explanations

When two misconceptions are both plausible, every available question gets a score:

```
score = sum of p(m) for each of the top-two misconceptions that has an option in the
question
        + 0.5 if both have options and those options are different
```

The highest score wins. A question where the two beliefs lead to *different* wrong answers tells them apart in one step. When no such question is available, the question that tests the leading belief scores highest. For Student A, the leading belief is "range includes the stop" (72%), so the tutor asks "What is the last number printed by `range(3, 7)` ?". Only that belief leads to the answer 7, so the reply confirms or weakens it.

7.2 Generating questions safely

When a weak concept runs out of unseen questions, the agent can generate a new one. To avoid wrong answer keys, **the LLM never writes the code or the answer**:

1. Code chooses a template from a fixed list in `agent/solvers.py` : floor division, modulo, powers, running totals with `range` , nested-loop counts and list totals.
2. Code writes the Python program from that template and works out the correct result itself.
3. The LLM writes only the question wording and the answer options, naming the misconception behind each wrong option.
4. Code rejects the question unless exactly one option matches the computed answer, all options differ, every misconception ID is in the catalogue and the wording matches the numbers used. Rejected questions are retried up to two times.

`scripts/pregenerate.py` builds a pool of 20 checked questions ahead of time, so the demo doesn't wait on generation. LLM-written code is never run.

8. Spaced repetition

Knowledge fades. Differential models this with a forgetting curve for every concept and for every misconception the student has cleared.

```
Recall R = exp( −days since last practice / S )        review due when R < 0.85
Displayed mastery = mastery × (0.5 + 0.5·R)
```

Concept stability S

- Starts at 2 days
- Correct with sound reasoning: **doubles**
- Slip or unclear: unchanged
- Anything else: **halves** (minimum 1 day)

Cleared misconceptions

- Start with S = 3 days once resolved
- Rechecked when recall drops below 85%
- A sound answer on the recheck doubles S
- A failed recheck raises the probability again





Figure 6. Illustrative forgetting curves. Sound answers raise stability, so reviews of well-understood concepts come due later.

- Reviews always use a question the student hasn't seen recently, never the same question again.
- All time-based calculations use an app clock with an offset. The teacher's **Jump 7 days** button adds a week, so the demo can show reviews coming due without waiting.

9. Student experience

9.1 The student's flow






Figure 7. The question screen. Every answer needs the student's own reasoning ("How did you work it out?") and a confidence tap. The right panel shows what the agent is thinking, and "Reviews due" lists spaced reviews.




Figure 8. The student's concept map, drawn from the concept graph. Each node is coloured by displayed mastery (red, amber, green), or grey when not yet assessed. Arrows run from a prerequisite to the concept that needs it.

9.2 What the student sees after answering

- **Right or wrong**, decided by code.
- **The diagnosis** in plain words, with the student's own words quoted back ("You wrote...").
- **Mastery before and after** for the concept, such as "30% → 5%".
- **The explanations still open** and their probabilities, such as "72% range includes the stop".
- **Why the next question was chosen**, such as "This question best tests the current explanations".

A "Right answer, wrong reason" result explains that the answer was correct but the reasoning wouldn't hold for other cases, so mastery doesn't move.

9.3 Accounts and roles

The app has mock sign-in with one teacher and four demo students. The server checks the role on every API request: students can only see and answer their own questions, only the teacher can see the class dashboard or use the demo controls, and the teacher can read a student's progress but can't answer for them.




Figure 9. Sign-in page, with one-click demo accounts.

10. Teacher dashboard

The dashboard turns every student's learner model into a view of class-wide gaps. To show how it works at scale, it uses a **simulated class of 30 made-up students**, and it says so in a banner at the top of the page.




Figure 10. Top of the dashboard: the "Simulated class" banner, demo controls (Jump 7 days, Reset demo), the four live demo students, class totals, the biggest class gaps and reviews due per concept.




Figure 11. Shared misconceptions (students grouped by the false belief they share), root causes (the earliest weak prerequisite behind low scores), "What to teach on Monday", and the mastery heatmap by student and concept.




Figure 12. Difficulty surprises: questions whose Elo rating has moved away from the predicted difficulty, based on class results.

What each panel tells the teacher

Panel	What it shows	How it's computed
Class totals	Students, average mastery, how many hold an active misconception, reviews due	Aggregated from each student's learner model
Biggest class gaps	Python concepts ranked weakest first, with how many students are below 40%	Average displayed mastery per concept
Reviews due	How many students need a review on each concept	Forgetting curve, recall below 85%
Shared misconceptions	Each active false belief and the students who share it	Misconception status = active
Root causes	The prerequisite that holds the most students back, and what it blocks	For each weak score, the deepest prerequisite also below 50%
Mastery heatmap	Every student against every concept, weakest first	Displayed mastery, coloured red, amber or green
Difficulty surprises	Questions harder or easier than predicted	Elo moved 150+ points after 10+ attempts
What to teach on Monday	A short draft lesson plan: a title, a board demonstration and a check question from the bank	LLM draft for the most common misconception; the teacher reviews it

How the simulated class is built

`scripts/seed_class.py` creates 30 students with a fixed random seed. Each has up to two hidden misconceptions and gets 12 to 15 scripted answers. When a question has an option for a hidden misconception, the student picks it 80% of the time; otherwise they answer correctly with the probability Elo predicts. Every answer goes through the real engine, without LLM calls. This data shows how the dashboard works. It isn't evidence that diagnosis works; that comes from the evaluation in section 11.

11. Evaluation and testing

11.1 Diagnosis accuracy

We wrote **40 labelled reasoning samples** as test cases. We used 10 to tune the prompt and **held out 30**, which were used only for the reported result. `scripts/evaluate.py` runs them against the local model and saves results to `eval/results.json`.

Measure (30 held-out cases)	Thinking off (used)	Thinking on
Error type correct	**30 of 30 (100%)**	30 of 30 (100%)
Misconception identified, where one was expected	**18 of 18 (100%)**	18 of 18 (100%)
Average time per diagnosis	**0.84 seconds**	3.84 seconds

Turning the model's thinking mode on gave the same accuracy at about 4.5 times the time, so we kept it off. All 8 misconceptions were covered in the held-out set.

> **Being honest about this result.** These are written test cases, not real student data. The same AI assistant that helped write the misconception catalogue also wrote the test cases, in fairly clear wording. Real students will be harder to read, so we treat this as a check that the system works, not as evidence of accuracy with real students.

11.2 Automated tests

The project has **302 automated tests, all passing**, plus a separate live-model suite (`pytest -m llm`) that runs the demo cases against the real model.

Level	What is covered
Engine unit tests	Every formula value in section 5, clamping, misconception statuses, recall, Elo
Graph and content tests	No cycles, valid references, exactly one correct option per question, solver accuracy
Selection tests	Each priority rule and repeatable tie-breaks
Agent tests (fake LLM)	Quote validation, retries, failure handling, rejected generated questions
Demo tests (fake LLM)	Students A, B and C get the expected mastery outcomes and next questions
API and sign-in tests	Answering changes state; role checks block the wrong accounts
Live LLM tests	The demo cases against `qwen3.5:9b`

11.3 Reliability for the demo

- Every LLM reply is cached by a hash of the model, prompt and schema. `scripts/warm_demo.py` runs the scripted demo answers through the real model beforehand, so the demo keeps working even if Ollama stops. It fails loudly if the tutor stops following the script.
- The UI shows the diagnosis status (`ok`, `cached` or `failed`), so it never hides where a result came from.

12. Guided demo walkthrough

Clicking **Start guided demo** on the landing page resets the four demo students and opens a step bar at the bottom of the page. It switches accounts automatically and fills in answers from `content/demo_script.json`. Each answer still goes through the same diagnosis and scoring as a typed one. The whole demo takes about 4 minutes.

Step	Account	What happens	Requirement shown
1	Student A	Answers "5 times... up to and including 5". Diagnosed with `range_includes_stop`; mastery 30% → 5%. The next question tests that belief; A gets it right and the probability falls from 72% to 36%.	Misconception from reasoning, learner model
2	Student B	Same wrong answer, different reason ("the 5 says how many times"). Gets a different diagnosis and a different next question.	Misconception from reasoning
3	Student C	Right answer, wrong reason: mastery stays at 30%. When the reasoning holds on a different start value, mastery rises to 69%.	Learner model
4	Student D	Takes the 8-question diagnostic ("question N of 8"), then the concept map shows a red weak spot.	Diagnostic test, concept graph
5	Student D	Gets a "Generated question" on the weakest concept, picked for about 60% expected success.	Targeted generation, calibration
6	Teacher	Clicks **Jump 7 days**; reviews due rise across the class.	Spaced repetition
7	Student C	"for loops with range" has faded to 3% recall, so the tutor brings it back as a review; mastery 69% → 92%.	Spaced repetition
8	Teacher	Shows the biggest gaps, shared misconceptions and root causes, drafts the Monday plan, and shows Elo difficulty moves (e.g. 1350 → 1476).	Teacher dashboard, calibration
9	Close	Shows the accuracy result and how it was measured.	Evaluation

The generated question in step 5 was created ahead of time by `scripts/pregenerate.py` and is served to any student who needs it; it isn't written live for Student D.




Figure 13. The landing page, with **Start guided demo**. The concept graph on the right shows mastery across prerequisites for one example student.

13. Running the project

You need Python 3.12 or later, Node 20 or later, and **Ollama** running locally. The commands below are for Windows; on macOS or Linux use `.venv/bin` instead of `.venv/Scripts`.

Set up once

```
ollama pull qwen3.5:9b
python -m venv .venv
.venv/Scripts/pip install -r requirements.txt
npm --prefix web install
npm --prefix web run build
```

Run

```
.venv/Scripts/python -m scripts.seed_class      # creates the simulated class of 30
.venv/Scripts/python -m scripts.warm_demo       # caches the demo answers
.venv/Scripts/python -m uvicorn api.main:app --port 8000
```

Then open **http://localhost:8000** and click **Start guided demo**, or sign in with a demo account.

Demo accounts (mock, local only)

Role	Username	Password
Teacher	`teacher`	`Teacher-Demo-2026`
Student A	`student.a`	`Student-A-2026`
Student B	`student.b`	`Student-B-2026`
Student C	`student.c`	`Student-C-2026`
Student D (takes the diagnostic)	`student.d`	`Student-D-2026`

Tests

```
.venv/Scripts/python -m pytest          # 302 tests, fake LLM
.venv/Scripts/python -m pytest -m llm   # demo cases against the real model
```

Main API routes

Route	Purpose
`GET /api/students/{id}/next`	Next question with the trace, or "all caught up"
`POST /api/students/{id}/answers`	Submit option, reasoning and confidence; runs the agent loop
`POST /api/clock/advance` / `reset`	Move the demo clock (teacher only)
`GET /api/class/summary`	Dashboard data (teacher only)
`POST /api/class/plan`	Draft the Monday lesson plan (teacher only)
`POST /api/demo/reset`	Restore the demo students and clock (teacher only)

14. Limits and next steps

Current limits

- Questions cover **Python Programming only**. Computer Networks, Web Pages with HTML and Cyber Ethics appear in the graph as "not assessed".
- Comparison and logic, if and else, and functions have no questions yet.
- New questions can be generated for arithmetic, running totals, nested loops and list traversal only. Other concepts cycle through their existing questions.
- Sign-in is mock (passwords in code, sessions in memory). This is a local demo and shouldn't be exposed to the internet as it is.
- No real student has used it yet, and the accuracy figure comes from written test cases.
- The AI-written lesson plan is a draft for a teacher to review.

Next steps

1. **Real classroom pilot:** test with Class 10 students and teachers, and measure diagnosis accuracy on real reasoning.
2. **Wider content:** questions and misconceptions for the remaining Python concepts, then the other chapters and other subjects such as Class 10 physics.
3. **More templates** so more concepts can get safely generated questions.
4. **Real accounts** with several classes and teachers.
5. **Teaching impact:** let teachers record "I taught this" and see the class before and after.
6. **Handwritten working:** let students upload a photo of their reasoning.

Summary

Differential meets all seven requirements of the brief in one running app. What sets it apart is that it diagnoses *why* a student is wrong from their own words, treats a right answer with wrong reasoning as no evidence of mastery, and chooses the question that best separates competing explanations. Throughout, the LLM only interprets and tested code makes every decision, and everything runs locally on one PC.

Team Works Locally

Karthikeyan · Nandini

Product Space AI Hackathon · Adaptive exam-prep tutor with a learner model