Ex No: 6

Date:

RECOGNIZE A VALID VARIABLE WITH LETTERS AND DIGITS USING LEX AND YACC

AIM:

To recognize a valid variable which starts with a letter followed by any number of letters or digits.

ALGORITHM:

Lex (exp6.l):

- 1. Recognizes letters, digits, any single character, and newline.
- 2. Returns tokens for letters, digits, and single characters.
- 3. Indicates the end of input with yywrap().

Yacc (exp6.y):

- 1. Includes headers and defines global variables.
- 2. Declares tokens digit and letter.
- 3. Defines grammar rules for identifiers.
- 4. Handles syntax errors with yyerror().
- 5. The main function, obtain the input, parses it, and prints if it's recognized as an identifier.

PROGRAM:

exp6.l:

Roll Number: 210701112 Name: N.Karthikeyan

```
}
exp6.y:
% {
  #include<stdio.h>
  int yylex();
  int yyerror();
  int valid=1;
%}
%token digit letter
%%
start : letter s
s:
     letter s
   | digit s
%%
int yyerror(){
  printf("\nIts not a identifier!\n");
  valid=0;
  return 0;
}
Roll Number: 210701112
Name: N.Karthikeyan
```

```
int main() {
  printf("\nEnter a name to test for an identifier: ");
  yyparse();
  if(valid) {
     printf("\nIt is a identifier!\n");
  } }
OUTPUT:
```

```
-(kali⊗kali)-[~/Documents/cdlab]
vi exp6.y
  -(kali®kali)-[~/Documents/cdlab]
s yacc -d exp6.y
  -(kali®kali)-[~/Documents/cdlab]
└$ vi exp6.l
(kali@ kali)-[~/Documents/cdlab]
$ lex exp6.l
(kali@ kali)-[~/Documents/cdlab]
$ cc lex.yy.c y.tab.c
  -(kali@kali)-[~/Documents/cdlab]
 -$ ./a.out
Enter a name to test for an identifier: 1variable
Its not a identifier!
  -(kali@kali)-[~/Documents/cdlab]
Enter a name to test for an identifier: variable1
It is a identifier!
```

RESULT:

Thus, a program using lex and yacc tool is implemented to recognize a valid variable which starts with a letter followed by any number of letters or digits.

Roll Number: 210701112 Name: N.Karthikeyan