

Deep Freezer (-40°C)

Scope of Application:

Deep Freezer (-40°C) are designed for Critical Scientific, Pharmaceutical, or Blood-Plasma Storage.

Control System:

- *Temperature Range: Standard ranges from -10°C to -40°C.*
- *Temperature Accuracy: $\pm 0.1^{\circ}\text{C}/1.0^{\circ}\text{C}$.*
- *Audio Visual Alarm for Temperature Deviation.*
- *Microprocessor-based digital temperature controller with LED display and alarms.*
- **Features:** *USB port for data logging, backup batteries, and audio-visual alarms for power failure or temperature fluctuations.*
- *Suitable Automatic Voltage stabilizer with time delay restart.*
- *Power source 220/240V, 50 Hz, Single phase.*

Refrigeration System:

- *Heavy duty hermetically sealed air-cooled compressors.*
- *Air cooled condenser aided by continuous rated fan motor.*
- *Compressor Running time is <60% to 70%.*
- *Temperature sensors PT100 / NTC.*
- *Power supply: 210-240V 50 Hz*

Construction:

- **Construction:** *Stainless Steel (SS 304) interior with heavy-duty PUF insulation and solid independent inner foamed doors to minimize frost.*
- **Refrigerant:** *Eco-friendly, CFC-free hydrocarbon refrigerants.*
- *Heavy duty casters with brakes for easy movement.*
- *Durable latch with pad lock.*
- *Heavy duty casters with brakes for easy movement.*
- *Hot condenser line around the mouth of the cabinet prevents moisture condensation.*



Deep Freezer Model:

Model	Capacity	Outer Dimension
<i>RS-DF-100</i>	<i>100 Ltrs</i>	<i>500 x 700 x 1150mm (W x D x H)</i>
<i>RS-DF-200</i>	<i>200 Ltrs</i>	<i>660 x 700 x 1400mm (W x D x H)</i>
<i>RS-DF-300</i>	<i>300 Ltrs</i>	<i>820 x 700 x 1500mm (W x D x H)</i>
<i>RS-DF-400</i>	<i>400 Ltrs</i>	<i>820 x 700 x 1750mm (W x D x H)</i>
<i>RS-DF-500</i>	<i>500 Ltrs</i>	<i>820 x 875 x 1750mm (W x D x H)</i>
<i>RS-DF-700</i>	<i>700 Ltrs</i>	<i>855 x 975 x 1950mm (W x D x H)</i>

Optional Accessories:

- *Cryo Gloves*
- *Cryo Racks and Boxes*
- *Chart Recorder*
- *Data Logger*
- *PlasmaTrays*

Ethernet Communication:

- *Offers high-speed data transfer, surpassing serial (RS-485) communication, and adheres to a global standard for communication protocol, enabling data operations from any PC over the LAN without requiring a separate PC interface.*