

APPLICATIONS:

RS Equipments Industrial Hot Air Ovens are designed to meet various applications in research, medical, industrial, agricultural, and educational institutions for drying, sterilizing, baking etc. which can work up to 350°C. The offered range of Hot Air Oven is broadly acknowledged for high strength, ability to withstand adverse conditions, low running cost, distort free operation and longer service life. These models have double walled chamber.

HEATING ELEMENT

Heating is accomplished by the aid of strip heaters, made out of imported Nichrome wires which are fixed in between the two interior walls of the vertical sides facilities will be provided for easy replacement of heaters.

AIR CIRCULATION:

This is accomplished by a centrifugal fan driven by a powerful motor, which will circulate uniform temperature inside chamber.

CONTROL SYSTEMS:

Consists of one no. digital temp. controller for automatic temperature control, One no. heat control switch, 3 no's ammeters, one no volmeter with selector switch indicating lamps, Air break magnetic contactor, ON/OFF Switch for fan motor, fuses, etc. Which will be mounted on a sheet steel cubicle and fitted on to one side of the oven itself.



FEATURES

- Temperature Range: 5°C above ambient to 250°C. / 350°C.
- Temperature controlled by Microprocessor based digital temperature controller with digital display with an accuracy of $\pm 1^\circ\text{C}$.
- High quality heating elements ensures longer life and uniform temperature on shelves.
- Exterior Body Power Coated Mild Steel.
- Interior Body: AISI SS304 stainless Steel.

- *Shelve/trays: Removable perforated stainless steel shelves /trays.*
- *Ovens are provided with Silicone door gasket.*
- *Insulation: Thick Glass/Mineral/ceramic /Wool insulation to reduce the heat loss.*
- *Forced air circulation/Gravity convection.*



POWER SUPPLY

- *Power: 220-240VAC, 50-60Hz.*

CERTIFICATIONS

- *Quality Certificate: ISO 9001:2015*
- *CE Certified*

Model	Internal Dimensions (WDH) in mm	No. of Shelves	Approx. Liter Capacity	Watts
RS - HAO - 42	350 x 350 x 350	2	42	1000
RS - HAO - 90	450 x 450 x 450	2	90	1200
RS - HAO - 170	600 x 600 x 498	3	170	1200
RS - HAO - 216	600 x 600 x 600	3	216	1500
RS - HAO - 330	600 x 700 x 786	3	330	1800

Note: And also available as per the customer required size.

No.5/13, Karunanidhi Street, West Mambalam, Chennai-600033

E-Mail: rs4equipments@gmail.com, rsequipments.marketing@gmail.com

Mobile No: 9840168240 /7358078463