

APPLICATIONS:

RS Equipments Industrial Hot Air Ovens are designed to meet various applications in research, medical, industrial, agricultural, and educational institutions for drying, sterilizing, baking etc. which can work up to 350°C. The offered range of Hot Air Oven is broadly acknowledged for high strength, ability to withstand adverse conditions, low running cost, distort free operation and longer service life. These models have double walled chamber.



HEATING ELEMENT

Industrial hot air ovens use heating elements primarily composed of high-performance resistance alloys like Nichrome or Kanthal (Iron-Chromium-Aluminium).

FEATURES

- Industrial hot air ovens are heavy-duty thermal processing units designed for large-scale drying, curing, sterilizing, and heat-treating.
 - Essential features include rugged construction (stainless steel interiors and powder-coated steel exteriors), precise microprocessor PID temperature controllers, forced-air circulation systems, and high-grade fiberglass insulation to minimize heat loss and maximize energy efficiency

AIR CIRCULATION:

- Air circulation in an industrial hot air oven uses heavy-duty blowers and motors for forced convection
- This system pushes heated air horizontally or vertically across the chamber. It eliminates cold spots, ensures uniform temperature distribution, and accelerates drying or curing processes.

CONTROL SYSTEMS:

The air control system of an industrial hot air oven regulates airflow, temperature, and exhaust to maintain uniform heat distribution. It typically consists of a motorized blower, adjustable intake/exhaust dampers, a digital PID controller, and a duct system that ensures steady convective heat transfer.

Technical Specifications

- *Temperature Range: 5°C above ambient to 250°C. / 350°C.*
- *Temperature controlled by Microprocessor based digital temperature controller with digital display with an accuracy of $\pm 1^\circ\text{C}$.*
- *High quality heating elements ensures longer life and uniform temperature on shelves.*
- *Exterior Body Powder Coated Mild Steel.*
- *Interior Body: AISI SS304 stainless Steel.*
- *Shelve/trays: Removable perforated stainless steel shelves /trays.*
- *Ovens are provided with Silicone door gasket.*
- *Insulation: Thick Glass/Mineral/ceramic /Wool insulation to reduce the heat loss.*
- *Power: 220-240VAC, 50-60Hz.*
- *Forced air circulation/Gravity convection.*

Certifications

- *CE Certified*
- *Quality Certificate: ISO 9001:2015*

Model	Internal Dimensions (WDH) in mm	No. of Trays	Approx. Liter Capacity	Watts
RS - HAO - 500	710 x 710 x 1000	10	500	1000
RS - HAO - 1000	1000 x 1000 x 1000	20	1000	1200
RS - HAO - 2000	1200 x 1200 x 1200	30	2000	1200

Note: And also available as per the customer required size.