

Laboratory Refrigerator

Scope of Application:

Laboratory refrigerators are designed for the strict preservation of samples, reagents, and pharmaceuticals. A temperature range of 2°C to 8°C, microprocessor PID controllers, forced-air circulation, and alarms for temperature deviations.

Technical Specifications:

- Corrosion-free Exterior and interior.
- Inner made up of Epoxy powder coated/Stainless Steel.
- Outer made up of corrosion resistant Powder-Coated.
- Temperature Accuracy: $\pm 1^{\circ}\text{C}$.
- Temperature Range: $+2^{\circ}\text{C}$ to $+8^{\circ}\text{C}$
- Designed for long storage of products.
- Refrigerant: 404A HFC Free.
- Height Adjustable shelves.
- Environment-friendly CFC-free cooling.
- Microprocessor-based Digital LED display temperature controller.
- Audio-visual alarm for high and low temperatures.
- PUF insulation.
- Reliable Energy Efficient. Sturdy Construction.
- Low Maintenance.
- Thick insulation ensures temperature stability
- Access Port for Validation Purpose.
- Smooth Castor Wheels
- Power supply: 210-240V 50 Hz
- CE & ISO Certified Product.



Optional Accessories:

- ❖ Datta Logger
- ❖ Chart Recorder
- ❖ Plasma Trays
- ❖ IQ, OQ, PQ Documentation and online calibration with traceability.

Ethernet Communication:

- Offers high-speed data transfer, surpassing serial (RS-485) communication, and adheres to a global standard for communication protocol, enabling data operations from any PC over the LAN without requiring a separate PC interface.

Lab Refrigerator Model:

Model	Capacity	Dimension
<i>RS-LR-100</i>	<i>100 Ltrs</i>	<i>508 x 584 x 864mm (W x D x H)</i>
<i>RS-LR-200</i>	<i>200 Ltrs</i>	<i>500 x 655 x 1447mm (W x D x H)</i>
<i>RS-LR-300</i>	<i>300 Ltrs</i>	<i>583 x 710 x 1790mm (W x D x H)</i>
<i>RS-LR-400</i>	<i>400 Ltrs</i>	<i>583 x 710 x 2050mm (W x D x H)</i>
<i>RS-LR-500</i>	<i>500 Ltrs</i>	<i>640 x 710 x 2050mm (W x D x H)</i>
<i>RS-LR-1000</i>	<i>1000 Ltrs</i>	<i>1152 x 785 x 2188mm (W x D x H)</i>