

Re-Circulating Chiller

Scope of Application:

Recirculating chillers are cooling systems designed to maintain stable temperatures in laboratories, industrial settings, and medical applications. The Re-circulating Chiller pressure to remove waste heat from sensitive equipment. Chiller used in hospitals to cool medical equipment, such as MRI machines and CT scanners, as well as to maintain a comfortable temperature in patient rooms and other areas.

Data centers: *Water cooled chillers are used in data centers to cool servers, storage devices, and other equipment that generates heat.*

Food and beverage production: *Water cooled chillers are used in the food and beverage industry to cool products during processing and storage, such as wine, beer, and dairy products.*

Commercial buildings: *Water cooled chillers are used in commercial buildings, such as office buildings, hotels, and shopping centers, to provide air conditioning and maintain a comfortable temperature for occupants.*

Technical Specifications:

- *Eco friendly R134A/R407C Refrigerant*
- *High efficiency Reciprocating / Scroll compressors*
- *High efficiency shell & tube Condenser*
- *Low noise level to suit indoor installation*
- *Insulated SS 304 reservoir*
- *All wetted parts are SS 304*
- *Highly reliable global brand pumps*
- *Highly efficient SS 316 plate type brazed heat exchanger*
- *Microprocessor based intelligent controller*



Cost Efficiency: How Re-circulating Chillers Save Energy and Reduce Costs:

Re-circulating chillers help minimize energy consumption and operational costs by utilizing advanced cooling technologies that enhance efficiency. They incorporate closed-loop systems that significantly reduce water waste and improve long-term savings. The high search interest in cost-effective cooling solutions highlights the importance of energy-efficient models in reducing expenses while maintaining performance.

Safety, Standards, and Best Practices for Recirculating Chillers:

Overheat protection:

- **Built in systems prevent excessive temperatures.**

Low coolant Alarms:

- **Warn users when fluid levels drop.**

Leak Detection Systems:

- **Ensure the safe operation**



Re-Circulating Chiller Model:

Model	Capacity
RS-CH-0.5TR	0.5 TR
RS-CH-1TR	1 TR
RS-CH-2TR	2 TR
RS-CH-3TR	3 TR
RS-CH-4TR	4 TR
RS-CH-5TR	5 TR

Note : Maximum of 100 TR.