

CONSTRUCTION

Double walled construction with rigid frame work and heavily insulated with glass wool, Fresh air inlet and suitable exhaust will be provided. The interior will be finished with heat resistant aluminum and outside with hemmer tone and black borders.

HEATING ELEMENT

Heating is accomplished totally enclosed strip heaters made out of imported BDH nichrome wire provided of the sides of the inner chamber to obtain maximum temperature. Hot Air Generators are fitted with our Fully Automatic Oil/Gas Burners. Electrically Heated models are provided with bank of specially designed MS/SS Tube, MS Strip Heater with fins. Steam Heated or Thermic Fluid Heated with temperature range of 150°C models are fitted with High Efficiency Fine Tube type Heat Exchangers.



AIR CIRCULATION

In order obtain uniform temperature, especially designed air Circulation fans are fitted on the sides of the unit, The designs of the fans are such that the unit will suck the hot air to pass over the trays and throw it on the sides where they will be recirculate to continue the cycle. A part of the air is come out to throw out the moisture.

CONTROL

The fan motor is controlled by a starter and the working of the fan indicated by lamp. The temperature inside the chamber is controlled by digital temp. controller and an indicating pilot lamp is also provided to signal working of the drier. The heater circuit will be interlocked with the circulation fan, so that the heaters are not energized without the circulation fan being 'ON' which in turn will protect the heaters.

*Size of trays will be 32"*16"*1/4", material of construction may be aluminum or stainless steel wire mesh trays of size 32"*16" can also be supplied, Trays could be supplied at the extra cost noted under accessories.*

INSULATION

The cavity formed in between double wall is heavily insulated with Ceramic Fibers / Glass Wool on all the sides to prevent heat losses from the Dryer.

CERTIFICATIONS

- CE Certified
- ISO Certified: ISO 9001:2015

POWER SUPPLY

- AC, 3 Phase, 415V & 50 Hz

MODEL	RS-TD-6	RS-TD-8	RS-TD-10
CAPACITY	6 TRAYS (50 kg)	8 TRAYS (70 kg)	10 TRAYS (80 kg)
NO OF FANS	10" x 1	12" x 1	12" x 1
NO. OF MOTOR/H.P	0.5 H.P	0.5 H.P	0.5 H.P
HEATING LOAD (Kw)	3-4KW+0.75 kw (motor)	3 -4 KW + 0.75 kw (motor)	6 kw + 0.75 kw (motor)
NO OF RACKS	6	8	10
INTERNAL DIMENSIONS IN MM (LxWxH)	750 x 450 x 600mm	750 x 450 x 650mm	750 x 450 x 700mm