

Ultra Low Temperature Freezer(-80°C)

Scope of Application:

Ultra Low Temperature are designed for biological samples, Research Laboratories, blood banks, clinical and clinical Research labs, Pharma Labs and Universities.



Cabinet Design:

- Vacuum Insulation Pannel.
- Manual Defrost.
- Inner cabinet made up of Stainless Steel 304.
- Outer cabinet made up of CRCA
- Features 3 to 5 inner adjustable stainless steel shelves with independent, insulated inner doors to prevent massive cold air loss when the outer door is opened
- Thick (usually 130 mm) polyurethane or vacuum-insulated panels (VIP) to minimize thermal loss and frost buildup
- Designed for long storage of products.
- Reliable Energy Efficient. Sturdy Construction.
- Low Maintenance.
- Thick insulation ensures temperature stability
- Access Port for Validation Purpose.
- Heavy Duty Castor Wheels
- ISO 9001:2015 Certified & CE marked product.

Control System:

- Temperature Range: -40°C to -86°C
- Microprocessor-based Digital LED display temperature controller.
- Audio-visual alarm for high and low temperatures.
- Temperature Accuracy: $\pm 1^{\circ}\text{C}$.
- Power supply: 210-240V 50 Hz

Refrigeration:

- Refrigerant: 404A HFC Free.
- Environment-friendly CFC-free cooling.

Ultra Low Freezer Model:

Model	Capacity	Outer Dimension
RS-ULF-340	340 Ltrs	488 x 607 x 1140mm (W x D x H)
RS-ULF-410	410 Ltrs	606 x 575 x 1180mm (W x D x H)
RS-ULF-590	590 Ltrs	606 x 738 x 1310mm (W x D x H)
RS-ULF-730	730 Ltrs	963 x 571 x 1350mm (W x D x H)
RS-ULF-840	840 Ltrs	894 x 718 x 1310mm (W x D x H)

Optional Accessories:

- Cryo Rack
- Cryo Box
- Battery Backup
- Data Logger
- Chart Recorder
- IQ, OQ, PQ Documentation and online calibration with traceability.

Ethernet Communication:

Offers high-speed data transfer, surpassing serial (RS-485) communication, and adheres to a global standard for communication protocol, enabling data operations from any PC over the LAN without requiring a separate PC interface.