

DUC-10

Low-Temperature Cooling Circulator Series

NEW

Applications

Designed for cooling support of life science instruments, analytical equipment, laser systems, and small industrial devices, including AAS, ICP-OES, ICP-MS, SEM, TEM, vacuum coating systems, Kjeldahl analyzers, Soxhlet extractors, diffusion pumps, molecular pumps, and PIPS systems.

Features

- **LCD Touchscreen Control:** Fast and intuitive temperature and hysteresis setting.
- **Auto Circulation Start:** Circulation begins automatically at power-on.
- **Overflow Protection & Level Window:** Front viewing window for easy liquid monitoring.
- **Built-in Pre-Filter:** Visible filter design for quick inspection and replacement.
- **Hot Gas Bypass + PID Control:** High precision temperature stability up to $\pm 0.1^\circ\text{C}$.
- **Proportional Cooling System:** Optimized compressor output for energy-efficient operation.
- **Adjustable Flow Control:** Stable constant temperature, flow, and pressure circulation.
- **Low Noise Design:** Imported compressor with ultra-quiet fan, ideal for laboratories.
- **High-Performance Pump:** Ensures uniform coolant circulation and stable cooling.
- **Multi-Level Safety Protection:** Over-temperature, over-pressure, overheat, and overload protection.
- **Eco-Friendly Refrigerant:** Environmentally compliant and non-toxic.



Specifications	DUC-10*
Working temperature range	5-35 °C
Temperature stability	$\pm 0.1^\circ\text{C}$
Temperature display	3.5-inch LCD touch screen
Display resolution	0.1 °C
Temperature control method	Intelligent PID
Temperature sensor	PT 100
Cooling capacity @20°C	1000 W
Refrigerant	R404a
Max pump pressure	1.3 bar
Pump flow rate	2-20 L/min (Adjustable)
Reservoir volume	7 L
Installation type	Floor standing
Continuous operation	100 %
Ambient temperature	5-40 °C
Relative humidity	$\leq 80\%$
External tubing inner diameter	10 mm
Dimensions (W×D×H)	310×650×530 mm
Power supply	220V/50Hz
Power consumption	650 W Max.
Current	3.5 A Max.

Note: "*" indicates product coming soon