

# OS20-S/OS40-S

## LED Overhead Stirrer

## Features

- High reliability and outstanding performance
- Wide range of speed from 50 to 2200rpm
- Brushless DC motor for long life, maintenance free and explosion proof
- LED screen for monitoring actual speed
- Safety circuits allow for safe stop function in anti-stall or overload conditions
- Large chuck diameter for many shaft types



### Set of Overhead Stirrer tools

Cat.No. 18900743



Contains one vertical rod, six stirring blades, Such as Propeller stirrer, Paddle stirrer, Centrifugal stirrer, Flat-blade stirrer, Radial-flow stirrer, Anchor stirrer and Disassembling tool

## Plate Stands

### Universal Plate Stand

Cat. No.18900605



Dimension [W x D x H] :  
20x31x78cm  
Material: cast iron

### Grand Plate Stand (for OS70)

Cat. No.18900497



Dimension [W x D x H] :  
33.5x46.3x78cm  
Material: cast iron

### Universal H-shaped stand (for OS70 & T400)

Cat. No. 18205388



Dimension [W x D x H] :  
26.5 to 49.6x50.5x78 cm  
adjustable width:  
(W: 265 to 496 mm)

| Specifications                               | OS20-S             | OS40-S             |
|----------------------------------------------|--------------------|--------------------|
| Max. stirring quantity[H <sub>2</sub> O]     | 20L                | 40L                |
| Speed range                                  | 50~2200rpm         | 50~2200rpm         |
| Max. torque                                  | 40N·cm             | 60N·cm             |
| Viscosity max.                               | 10000mPa·s         | 50000mPa·s         |
| Motor type                                   | Brushless DC motor | Brushless DC motor |
| Speed display                                | LED                | LED                |
| Overload protection display                  | LED                | LED                |
| Chuck range diameter                         | 2-10mm             | 2-10mm             |
| Motor input power                            | 60W                | 120W               |
| Motor output power                           | 50W                | 100W               |
| Power                                        | 70W                | 130W               |
| Voltage, Frequency                           | 100~240V, 50/60 Hz | 100~240V, 50/60 Hz |
| Dimension[WxHxD]                             | 83 x 220 x 186mm   | 83 x 220 x 186mm   |
| Protection class                             | IP21               | IP21               |
| Weight                                       | 2.8kg              | 2.8kg              |
| Permissible ambient temperature and humidity | 5~40°C, 80%RH      | 5~40°C, 80%RH      |

**DLAB Overhead Stirrer provides a variety of stirring tools, such as impellers, paddles and blades:**

|                                                                                                                                                                                                                                                                                       |                                                                                                                 |                                                                                                                                                                                                                                                                                                   |                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>Propeller stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 5cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Standard stirring applications<br>at medium and high speed                                                                                       | <b>Cat. No.18900071</b><br>    | <b>Paddle stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 6.8cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>For gentle mixing at low and medium speeds                                                                                                                    | <b>Cat. No.18900073</b><br>    |
| <b>Straight stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 6cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>For low viscosity media at medium and high speeds                                                                                                 | <b>Cat. No.18900072</b><br>    | <b>Centrifugal stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 9cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Blades open while speeding.<br>For narrow neck vessels at medium to high speed.                                                                            | <b>Cat. No.18900074</b><br>    |
| <b>Propeller stirrer</b><br>Shaft length: 35cm<br>Stirrer diameter: 6.5cm<br>Shaft diameter: Ø8mm<br>Material: PTFE coated<br>Standard stirring applications<br>at medium and high speed                                                                                              | <b>Cat. No.18900075</b><br>    | <b>Paddle stirrer</b><br>Shaft length: 35cm<br>Stirrer diameter: 6.8cm<br>Shaft diameter: Ø8mm<br>Material: PTFE coated<br>For gentle mixing at low and medium speeds                                                                                                                             | <b>Cat. No.18900077</b><br>    |
| <b>Straight stirrer</b><br>Shaft length: 35cm<br>Stirrer diameter: 7cm<br>Shaft diameter: Ø8mm<br>Material: PTFE coated<br>For low viscosity media at medium and high speeds                                                                                                          | <b>Cat. No.18900076</b><br>    | <b>Centrifugal stirrer</b><br>Shaft length: 35cm<br>Stirrer diameter: 8.5cm<br>Shaft diameter: Ø8mm<br>Material: PTFE coated<br>Blades open while speeding.<br>For narrow neck vessels at medium to high speed.                                                                                   | <b>Cat. No.18900078</b><br>    |
| <b>Grand propeller stirrer</b><br>Shaft length: 60cm<br>Stirrer diameter: 10cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Standard stirring                                                                                                                         | <b>Cat. No. 18900478</b><br>   | <b>Grand paddle stirrer</b><br>Shaft length: 60cm<br>Stirrer diameter: 10cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Gentle mixing for those stratify easily or sensitive to shear                                                                                            | <b>Cat. No.18900499</b><br>    |
| <b>Grand anchor stirrer</b><br>Shaft length: 60cm<br>Stirrer diameter: 10cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Standard stirring or for those easily precipitate                                                                                            | <b>Cat. No. 18900498</b><br> | <b>Grand dissolving stirrer</b><br>Shaft length: 60cm<br>Stirrer diameter: 10cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Breaking down granules in the mixture with strong shear                                                                                              | <b>Cat. No.18900500</b><br>  |
| <b>Flat-blade stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 6cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Suitable for medium speed stirring, low viscosity and medium viscosity materials                                                                | <b>Cat. No. 18900625</b><br> | <b>Anchor stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 6cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Suitable for low speed stirring, medium viscosity and high viscosity materials                                                                                  | <b>Cat. No.18900627</b><br>  |
| <b>Radial-flow stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 5cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Suitable for medium speed or high speed agitation, low viscosity or medium viscosity materials, recommended for the treatment of gas in liquid | <b>Cat. No. 18900626</b><br> | <b>Spiral stirrer</b><br>Shaft length: 40cm<br>Stirrer diameter: 5cm<br>Shaft diameter: Ø8mm<br>Material: 316L stainless steel<br>Suitable for medium speed or high speed agitation, medium viscosity and high viscosity materials, recommended for liquid homogenization or suspension treatment | <b>Cat. No. 18900628</b><br> |