



RECHARGE LINK FOR GLOBE

TECHNICAL SPECIFICATTIONS - DC CCS2 CHARGERS

Parameter	Characteristic	DC Charger CCS2
Charger	Design	
Power	Rated Power	120 kW
	Input Voltage	3-Phase, 415V (+6% and -10%)
	Number of Output	Single or Dual Gun
	Output Current	200A Max
	Output Charging Outlet	Combined Charging System Combo 2 (CCS2)
	Output Voltage	200-1000 Vdc
	Efficiency	≥95%
	Power Factor	≥0.98
	Battery Backup	Battery Backup for controlling unit > 60 mins
User Interface and Controls	Display	7" TFT LCD Display Touchscreen (Optional 10" size)
	LEDs	LEDs for charging/fault modes
	User Authentication	RFID + OCPPv1.6
Environment	Ambient Temperature	-20°C to 55°C
	Storage Temperature	-40°C to 70°C
	Altitude	<2000 m
	Humidity	<95%, Non condensing
Communication	External	WiFi, RS485, LAN/4G + OCPPv1.6
	Metering and Billing	Class 1 Energy Metering
	Charging Operation	Autocharge / RFID Card / QR Code / Mobile CMS App (OCPPv1.6)
Protections / Safety	Input/ Output Protections	Over/Under Voltage, Overload, Short Circuit, Current Leakage, Grounding, Surge protection, Over Temperature
	Mechanical Protections	Enclosure Mechanical Strength IK-10, IP55 for Outdoor use, Flame Retardant Grade UL94 V-0, Safety Lock
	Mounting	Floor Mount
	Push Button	Mushroom Push Button for Emergency Stop
	Cooling	Forced Air Cooling
Certifications	As per	IEC 61851 / AIS 138 Part-2 / IS-17017
	Certifications	ARAI, CE