


PocketBeagle P1 and P2 (sockets)







I2C1 pull-ups




BME280 (0x76)



LIS3DH (0x18)




APDS-9306-065 (0x52)



Qwiic (I2C1)




Cape EEPROM on I2C2 (0x57)




AIN5: NTC (PocketBeagle halves it: 0–1.65 V)




AIN6: trimmer




Buttons



LEDs on PWM0A / PWM1A



Power nets





Mounting holes



EoS Sense Cape for PocketBeagle, rev A. Designed by Kartikeydheer Srivastava.
Copyright (c) 2026 Kartikeydheer Srivastava. All rights reserved; see LICENSE.txt.
Socket positions from BeagleBoard.org's PocketBeagle board file (CC BY 4.0).
Analog inputs: AIN5 and AIN6 only: PocketBeagle's 10k/10k divider keeps them under 1.8 V.
No pull-ups on PocketBeagle's I2C1/I2C2: R1, R2, R4, R5 provide them.

PocketBeagle outline and P1/P2 header positions taken from BeagleBoard.org PocketBeagle (github.com
Generated by tools/eos_boards from the board's design file
Copyright (c) 2026 Kartikeydheer Srivastava. Licence: All rights reserved
Kartikeydheer Srivastava

Sheet: /
File: eos-sense-cape.kicad_sch

Title: EoS Sense Cape for PocketBeagle

Size: A2	Date: 2026-10-11	**Rev: A**
KiCad E.D.A. 10.0.6		Id: 1/1